Started on	Tuesday, 31 March 2026, 1:03 PM
State	Finished
Completed on	Tuesday, 31 March 2026, 1:22 PM
Time taken	18 mins 53 secs
Marks	16.00/25.00
Grade	**64.00** out of 100.00

Question 1

Complete

Mark 1.00 out of 1.00

What does the following output?

```
1: public class InitOrder {
2: public String first = "instance";
3: public InitOrder() {
4: first = "constructor";
5: }
6: { first = "block"; }
7: public void print() {
8: System.out.println(first);
9: }
10: public static void main(String... args) {
11: new InitOrder().print();
12: }
13: }
```

- a. instance
- b. The code does not compile.
- c. constructor
- d. block

Question 2

Complete

Mark 0.00 out of 1.00

How many objects are eligible for garbage collection right before the end of the main method?

```
1: public class Person {
2: public Person youngestChild;
3:
4: public static void main(String... args) {
5: Person elena = new Person();
6: Person diana = new Person();
7: elena.youngestChild = diana;
8: diana = null;
9: Person zoe = new Person();
10: elena.youngestChild = zoe;
11: zoe = null;
12: }
13: }
```

- a. Two
- b. Three
- c. One
- d. None of these

Question 3

Complete

Mark 1.00 out of 1.00

```
What is the output of the following?

package beach;
public class Sand {
public Sand() {
System.out.print("a");
}
public void Sand() {
System.out.print("b");
}
public void run() {
new Sand();
Sand();
}
public static void main(String... args) {
new Sand().run();
}
}
```

- a. aab
- b. None of these
- c. ab
- d. a

Question 4

Complete

Mark 1.00 out of 1.00

Which of the following variable types is not permitted in a switch statement?

- a. double
- b. int
- c. String
- d. char

Question 5

Complete

Mark 1.00 out of 1.00

What is the output of the following application?

```
package registration;
public class NameCheck {
public static void main(String... data) {
String john = "john";
String jon = new String(john);
System.out.print((john==jon)+" "+(john.equals(jon)));
}
}
```

- a. true false
- b. false true
- c. true true
- d. false false

Question 6

Complete

Mark 1.00 out of 1.00

What is the output of the following application?

```
package planning;
public class ThePlan {
public static void main(String[] input) {
int plan = 1;
plan = plan++ + --plan;
if(plan==1) {
System.out.print("Plan A");
} else { if(plan==2) System.out.print("Plan B");
} else System.out.print("Plan C");
}
}
```

- a. None of these
- b. Plan C
- c. Plan A
- d. Plan B

Question 7

Complete

Mark 1.00 out of 1.00

What is the value of **thatNumber** after the execution of the following code snippet?

```
long thatNumber = 5 >= 5 ? 1+2 : 1*1;
if(++thatNumber < 4)
thatNumber += 1;
```

- a. The answer cannot be determined until runtime.
- b. 3
- c. 5
- d. 4

Question 8

Complete

Mark 0.00 out of 1.00

```
What is the output of the following application?

package dinosaur;
public class Park {
public final static void main(String... arguments) {
int pterodactyl = 6;
long triceratops = 3;
if(pterodactyl % 3 >= 1)
triceratops++;
triceratops--;
System.out.print(triceratops);
}
}
```

- a. The code does not compile.
- b. 2
- c. 3
- d. 4

Question 9

Complete

Mark 1.00 out of 1.00

Fill in the blanks: The _____ operator increases the value of a variable by 1 and returns the new value, while the _____ operator decreases the value of a variable by 1 and returns the original value.

- a. post-increment [v++], post-decrement [v--]
- b. post-increment [v++], pre-decrement [--v]
- c. pre-increment [++v], post-decrement [v--]
- d. pre-increment [++v], pre-decrement [--v]

Question 10

Complete

Mark 1.00 out of 1.00

```
What is the output of the following application?

package jungle;
public class TheBigRace {
public static void main(String[] in) {
int tiger = 2;
short lion = 3;
long winner = lion+2*(tiger + lion);
System.out.print(winner);
}
}
```

- a. 25
- b. 11
- c. None of these
- d. 13

Question 11

Complete

Mark 0.00 out of 1.00

```
Given the following code snippet, assuming dayOfWeek is an int, what variable type of
saturday is not permitted?

final _________ saturday = 6;
switch(dayOfWeek) {
default:
System.out.print("Another Weekday");
break;
case saturday:
System.out.print("Weekend!");
}
```

- a. long
- b. int
- c. byte
- d. None of these

Question 12

Complete

Mark 1.00 out of 1.00

Fill in the blanks: Given two non-null String objects with reference names apples_____ and oranges, if apples oranges evaluates to true, then apples_____ oranges must also evaluate to true.

- a. !=, equals()
- b. ==, equals()
- c. equals(), ==
- d. equals(), =!

Question 13

Complete

Mark 1.00 out of 1.00

For a given non-null **String myTestVariable**, what is the resulting value of executing the statement **myTestVariable.equals(null)?**

- a. true
- b. The statement does not compile.
- c. The statement compiles but will produce an exception when used at runtime.
- d. false

Question 14

Complete

Mark 0.00 out of 1.00

```
What is the output of the following code snippet?

int x = 10, y = 5;
boolean w = true, z = false;
x = w ? y++ : y--;
w = !z;
System.out.print((x+y)+" "+(w ? 5 : 10));
```

- a. 12 5
- b. 10 10
- c. The code does not compile.
- d. 11 5

Question 15

Complete

Mark 0.00 out of 1.00

```
What is the output of the following application?

package yoyo;
public class TestGame {
public String runTest(boolean spinner, boolean roller) {
if(spinner = roller) return "up";
else return roller ? "down" : "middle";
}
public static final void main(String pieces[]) {
final TestGame tester = new TestGame();
System.out.println(tester.runTest(false,true));
}
}
```

- a. middle
- b. down
- c. up
- d. The code does not compile.

Question 16

Complete

Mark 0.00 out of 1.00

```
Which of the following are primitives?

int[] lowercase = new int[0];
Integer[] uppercase = new Integer[0];
```

- a. Only uppercase
- b. Bother lowercase and uppercase
- c. Neither lowercase nor uppercase
- d. Only lowercase

Question 17

Complete

Mark 0.00 out of 1.00

```
Given the following two methods, which method call will not compile?

public void printStormName(String... names) {
System.out.println(Arrays.toString(names));
}
public void printStormNames(String[] names) {
System.out.println(Arrays.toString(names));
}
```

- a. printStormNames("Cindy");
- b. printStormName("Arlene");
- c. printStormName(new String[] { "Bret" });
- d. printStormNames(new String[] { "Don" });

Question 18

Complete

Mark 1.00 out of 1.00

```
What does this code output?

String[] nums = new String[] { "1", "9", "10" };
Arrays.sort(nums);
System.out.println(Arrays.toString(nums));
```

- a. [1, 9, 10]
- b. None of these
- c. [10, 1, 9]
- d. [1, 10, 9]

Question 19

Complete

Mark 1.00 out of 1.00

Which line of code causes an ArrayIndexOutOfBoundsException? String[][] matrix = new String[1][2]; matrix[0][0] = "Don't think you are, know you are."; // m1 matrix[0][1] = "I'm trying to free your mind Neo"; // m2 matrix[1][0] = "Is all around you "; // m3 matrix[1][1] = "Why oh why didn't I take the BLUE pill?"; // m4

- a. m2
- b. m4
- c. m1
- d. m3

Question 20

Complete

Mark 1.00 out of 1.00

```
How many of the following are legal declarations?

[][] String alpha;
[] String beta;
String[][] gamma;
String[] delta[];
String epsilon[][];
```

- a. Three
- b. Two
- c. Four
- d. Five

Question 21

Complete

Mark 1.00 out of 1.00

```
What is the result of running the following program?

1: package fun;
2: public class Sudoku {
3: static int[][] game = new int[6][6];
4:
5: public static void main(String[] args) {
6: game[3][3] = 6;
7: Object[] obj = game;
8: obj[3] = "X";
9: System.out.println(game[3][3]);
10: }
11: }
```

- a. The code compiles but throws a different exception at runtime.
- b. X
- c. The code does not compile.
- d. The code compiles but throws a NullPointerException at runtime.

Question 22

Complete

Mark 0.00 out of 1.00

```
What is the output of the following when run as java Count "1 2"?

public class Count {
public static void main(String target[]) {
System.out.println(target.length);
}
}
```

- a. 2
- b. 0
- c. The code does not compile.
- d. 1

Question 23

Complete

Mark 0.00 out of 1.00

```
Which of the following statements are true?

I. You can always change a method signature from call(String[] arg) to
call(String... arg) without causing a compiler error in the calling code.

II. You can always change a method signature from call(String... arg) to
call(String[] arg) without causing a compiler error in the existing code.
```

- a. II
- b. I
- c. Neither I nor II
- d. Both I and II

Question 24

Complete

Mark 1.00 out of 1.00

```
What does the following code output?

public static void main(String[] args) {
List bottles = Arrays.asList("glass", "plastic");
for (int type = 0; type < bottles.size();) {
System.out.print(bottles.get(type) + ",");
break;
}
System.out.print("end");
}
```

- a. glass,plastic,end
- b. None of these
- c. glass,end
- d. The code does not compile.

Question 25

Complete

Mark 1.00 out of 1.00

```
What is the output of the following code?

package chicago;
public class Loop {
private static int count;
private static String[] stops = new String[] { "Washington",
"Monroe", "Jackson", "LaSalle" };
public static void main(String[] args) {
while (count < stops.length) {
if (stops[count++].length() < 8) {
break;
}
}
System.out.println(count);
}
}
```

- a. 4
- b. 2
- c. 1
- d. The code does not compile.