



Classes in Dart

- Non-nullable members have to be initialized
- Private members
- Getters, setters, encapsulation
- Constructors with “initializing formal parameters” or with “initializer list”
- Named constructors
- `const` constructors
- Optional: List as generic type



Reminder: Classes and constructors in Java

```
package com.journaldev.constructor;

public class Data {

    private String name;
    private int id;

    //no-args constructor
    public Data() {
        this.name = "Default Name";
    }
    //one parameter constructor
    public Data(String n) {
        this.name = n;
    }
    //two parameter constructor
    public Data(String n, int i) {
        this.name = n;
        this.id = i;
    }

    public String getName() {
        return name;
    }
}
```

```
    public int getId() {
        return id;
    }

    @Override
    public String toString() {
        return "ID="+id+", Name="+name;
    }
    public static void main(String[] args) {
        Data d = new Data();
        System.out.println(d);

        d = new Data("Java");
        System.out.println(d);

        d = new Data("Pankaj", 25);
        System.out.println(d);
    }
}
```



Reminder: Inheritance in Java

```
package com.journaldev.constructor;

public class Person {

    private int age;

    public Person() {
        System.out.println("Person Created");
    }

    public Person(int i) {
        this.age = i;
        System.out.println("Person Created with Age = " + i);
    }
}
```

```
public class Student extends Person {

    private String name;

    public Student() {
        System.out.println("Student Created");
    }

    public Student(int i, String n) {
        super(i); // super class constructor called
        this.name = n;
        System.out.println("Student Created with name = " + n);
    }
}
```



Classes in Dart

Class names in Dart should start with capital letters (exceptions: num, int, double).

Non-nullable fields have to be initialized:

```
class User {  
  String firstName;  
  String lastName;  
}
```



```
Non-nullable instance field 'firstName' must be initialized.  
Try adding an initializer expression, or a generative constructor that initializes it.
```

```
void main() {  
  User u1 = new User();    // new is not needed in Dart !  
  User u2 = User();        // class name on left side can be replaced by 'var'  
  var u3 = User();  
  
  print(u3.firstName);     // prints empty line  
  u3.firstName = "Franz";  
  print(u3.firstName);     // prints "Franz"  
  print(u3);               // prints "Instance of 'User'"  
}  
  
class User {  
  String firstName = "";  
  String lastName = "";  
}
```



Class methods

```
void main() {  
    var u = User();  
    u.firstName = "Fritz";  
    u.lastName = "Fischer";  
    print (u.getFullName());    // prints "Fritz Fischer"  
}  
  
class User {  
    String firstName = "";  
    String lastName = "";  
  
    String getFullName() {  
        return firstName + " " + lastName;  
    }  
}
```

Same method with “arrow syntax”:

```
String getFullName2() => firstName + " " + lastName;
```



Getter

```
void main() {  
  var u = User();  
  u.firstName = "Fritz";  
  u.lastName = "Fischer";  
  print(u.getFullName()); // prints "Fritz Fischer"  
  print(u.fullName);      // prints the same  
}  
  
class User {  
  String firstName = "";  
  String lastName = "";  
  
  String getFullName() {  
    return firstName + " " + lastName;  
  }  
  
  String get fullName {  
    return firstName + " " + lastName;  
  }  
}
```

Usage in Flutter (sample from scaffold.dart):

```
/// Whether this scaffold has a non-null [Scaffold.appBar].  
bool get hasAppBar => widget.appBar != null;
```

Same with “arrow syntax”:

```
String get fullName => firstName + " " + lastName;
```



Setter

```
void main() {
    var u = User();
    u.SetFullName("Olaf Scholz");
    print(u.firstName);    // prints Olaf
}

class User {
    String firstName = "";
    String lastName = "";

    void setFullName(String fullName) {
        var names = fullName.split(" ");
        if (names.length == 2) {
            firstName = names[0];
            lastName = names[1];
        }
    }

    String get fullName => firstName + " " + lastName;
}
```

```
Run | Debug
void main() {
    var u = User();
    u.fullName = "Olaf Scholz";
    print(u.firstName);    // prints Olaf
}

class User {
    String firstName = "";
    String lastName = "";

    set fullName(String fullName) {
        var names = fullName.split(" ");
        if (names.length == 2) {
            firstName = names[0];
            lastName = names[1];
        }
    }

    String get fullName => firstName + " " + lastName;
}
```



Put classes in their own files

It is a good practice to put class “Abc” into a file “abc.dart”:

```
lib > main.dart > ...  
1  
2 import 'user.dart';  
3  
4 void main() {  
5   var u = User();  
6   u.fullName = "Olaf Scholz";  
7   print(u.firstName); // prints Olaf  
8 }  
9
```

```
lib > user.dart > ...  
1  
2 class User {  
3   String firstName = "";  
4   String lastName = "";  
5  
6   set fullName(String fullName) {  
7     var names = fullName.split(" ");  
8     if (names.length == 2) {  
9       firstName = names[0];  
10      lastName = names[1];  
11    }  
12  }  
13  
14  String get fullName => firstName + " " + lastName;  
15 }  
16
```




Private members

Members, whose names start with “_” are private.

They can only be accessed inside the file, where the class is defined:

```
user.dart > ...  
  
class User {  
  String _firstName = "";  
  String lastName = "";  
  
  set fullName(String fullName) {  
    var names = fullName.split(" ");  
    if (names.length == 2) {  
      _firstName = names[0];  
      lastName = names[1];  
    }  
  }  
  
  String get fullName => _firstName + " " + lastName;  
}  
  
String getFirstNameOfUser(User u) {  
  return u._firstName;  
}
```

```
main.dart > ...  
  
import 'user.dart';  
  
Run | Debug  
void main() {  
  var u = User();  
  u.fullName = "Olaf Scholz";  
  print(u._firstName); // prints Olaf  
}  
  
String getFirstNameOfUser(User u) {  
  return u._firstName;  
}
```



Encapsulation made easy with IntelliSense

```
class User {  
  String firstName = "";  
  String lastName = "";  
}
```

Set cursor on "firstName", press right mouse button and select:

```
Format Document With...  
Refactor... Ctrl+Shift+R  
Source Action
```

```
class User {  
  String firstName = "";  
  String  
  set full  
  v
```

More Actions...

- Remove type annotation
- Encapsulate field

```
class User {  
  String _firstName = "";  
  
  String get firstName => _firstName;  
  
  set firstName(String value) {  
    _firstName = value;  
  }  
  
  String lastName = "";
```

main.dart is unchanged:

```
void main() {  
  var u = User();  
  u.fullName = "Olaf Scholz";  
  print(u.firstName);  
}
```

Advantages of a setter:

- it can check if the value makes sense (e.g. in our case if value has at least 2 characters)
- you can set a breakpoint in it



Sample of encapsulation in Flutter sources

```
basic.dart x
C: > FlutterSDK > flutter_windows_3.3.10-stable > flutter > packages > flutter > lib > src > widgets > basic.dart > _RenderColoredBox

7727
7728 class _RenderColoredBox extends RenderProxyBoxWithHitTestBehavior {
7729   _RenderColoredBox({ required Color color })
7730     : _color = color,
7731       super(behavior: HitTestBehavior.opaque);
7732
7733   /// The fill color for this render object.
7734   ///
7735   /// This parameter must not be null.
7736   Color get color => _color;
7737   Color _color;
7738   set color(Color value) {
7739     if (value == _color) {
7740       return;
7741     }
7742     _color = value;
7743     markNeedsPaint();
7744   }
7745
```



Classes: constructors (part 1)

Remember the issue we had at the beginning:

```
class User {  
    String firstName;  
    String lastName = "";
```

```
Non-nullable instance field 'firstName' must be initialized.  
Try adding an initializer expression, or a generative constructor that initializes it.
```

We solved it with an initializer expression:

```
String firstName = "";
```

As mentioned in the error text above, an alternative is to define a constructor (in short: c-tor):

```
class User {  
    String firstName;  
    String lastName;  
  
    User (this.firstName, this.lastName);  
}
```

```
void main() {  
    //var u = User();    // error: 2 positional arguments expected  
    var u = User("Fritz", "Fischer");  
    print(u.firstName);    // prints Fritz  
}
```



Classes: constructors (part 2)

The constructor and other class methods have several significant differences.

1. The constructor has the same name as the class name.
2. The constructor does not have a return type.
3. When an object is created, the constructor is automatically invoked.
4. If no constructor is specified, the default no-argument constructor is used.

There are 2 types of constructors:

```
class User {  
  String firstName;  
  String lastName;  
  
  // c-tor with "initializing formal parameters"  
  User (this.firstName, this.lastName);  
}
```

Most frequently used

```
class User {  
  String firstName;  
  String lastName;  
  
  // c-tor with "initializer list"  
  User(String fName, String lName) : firstName = fName, lastName = lName;  
}
```

More seldom used



C-tors can have bodies

```
int numberOfUsers = 0;

class User {
    String firstName;
    String lastName;

    User(this.firstName, this.lastName) {
        numberOfUsers++;
    }
}
```

Better than above with a global variable: use a static variable in the class.
Static class variables exist only once for all class objects !

```
class User {
    static int numberOfUsers = 0;

    String firstName;
    String lastName;

    User(this.firstName, this.lastName) {
        numberOfUsers++;
    }
}
```

```
void main() {
    var u = User("Fritz", "Fischer");
    var u2 = User("Olaf", "Scholz");
    print(User.numberOfUsers);    // prints 2
}
```



Beside the default c-tor, classes can have “named c-tors”

```
class User {  
    String firstName;  
    String lastName;  
  
    User(this.firstName, this.lastName);  
  
    User.withFullName(String fullName) : firstName = "", lastName = "" {  
        this.fullName = fullName;  
    }  
}
```

```
void main() {  
    var u = User("Fritz", "Fischer");  
    var u2 = User.withFullName("Olaf Scholz");  
    print("${u2.lastName} ${u2.firstName}");  
}
```

Remark: in C# a class can have several c-tors with the same name, as long as their argument-list is different.



Strange: Initializing fields in the body is not enough

```
User.withFullName(String fullName) {  
  firstName = "";  
  lastName = "";  
  this.fullName = fullName;  
}
```

Non-nullable instance field 'firstName' must be initialized.

Try adding an initializer expression, or add a field initializer in this constructor, or mark it 'late'. dart([not_initialized_non_nullable_instance_field](#))

Non-nullable instance field 'lastName' must be initialized.

Try adding an initializer expression, or add a field initializer in this constructor, or mark it 'late'. dart([not_initialized_non_nullable_instance_field](#))



Samples of using named c-tors in Flutter

Taken from our hello_world app:

```
Image.network(  
  "https://fdg-ab.de/wp-content/uploads/2021/03/logo_fdg_neu_freigestellt.png",  
  width: 150), // Image.network  
  
ClipRRect(  
  borderRadius: BorderRadius.all(Radius.circular(30)),  
  // next 2 lines would round only top-left and bottom-right corners  
  // borderRadius: BorderRadius.only(  
  //   topLeft: Radius.circular(30), bottomRight: Radius.circular(30)),  
  child: Image.asset("assets/images/snoopy_christmas.jpg",  
    width: 250)), // Image.asset // ClipRRect
```




Sample of a definition of named c-tors in Flutter

```
/// A radius for either circular or elliptical shapes.
class Radius {
  /// Constructs a circular radius. [x] and [y] will have the same radius value.
  ///
  /// 
  /// 
  const Radius.circular(double radius) : this.elliptical(radius, radius);

  /// Constructs an elliptical radius with the given radii.
  ///
  /// 
  /// 
  const Radius.elliptical(this.x, this.y);

  /// The radius value on the horizontal axis.
  final double x;

  /// The radius value on the vertical axis.
  final double y;
}
```



The keywords “final” and “const” inside classes are explained in the next slides !



Exercise

Create a class Rectangle in an own file rectangle.dart inside directoy lib.

Create the class in such a way that you can use it in main.dart in the following way:

```
(new) Rectangle Rectangle(double width, double height)
lib/rectangle.dart
var rect = Rectangle(200, 50);
print("calling method getArea: ${rect.getArea()}");
print("calling setter area: ${rect.area}");
```

Possible solution:

```
class Rectangle {
  Rectangle(this.width, this.height);
  double width;
  double height;

  double getArea() {
    return width * height;
  }

  double get area => width * height ;
}
```