

## Practical No. 5. HANDLING MULTIPLE WINDOWS & FRAMES USING SELENIUM

**Date:** \_\_\_\_\_

**Aim:**

To learn how to handle multiple windows, frames and modals using selenium.

**Theory:**

### How to handle Selenium multiple window using Webdriver

In automation, when we have multiple windows in any web application, the activity may need to switch control among several windows from one to other in order to complete the operation.

After completion of the operation, it has to return to the main window i.e. parent window in Selenium.

**WindowHandle:**

*It is a unique identifier that holds the address of all the windows.* Think of it as a pointer to a window, which returns the string value. It is assumed that each browser will have a unique window handle. This window handle function helps to retrieve the handles of all windows.

In Selenium web driver there are methods through which we can handle multiple windows.

**Driver.getWindowHandles();**

To handle all opened windows by web driver, we can use “Driver.getWindowHandles()”. This method helps to get the handles of all the windows opened and then we can switch window from one window to another in a web application. Its return type is Iterator<String>.

**Driver.getWindowHandle();**

When the site opens, we need to handle the main window by driver.getWindowHandle(). This method helps to get the window handle of the current window. Its return type is String.

**set:**

This method helps to set the window handles in the form of a string.

set<string>            set=            driver.get.windowhandles()

**driver.switchTo()**

This method helps to switch between the windows **action:**

This method helps to perform certain actions on the windows

**How to handle frames in Selenium Webdriver**

Frames in HTML can be used to divide a web-page vertically or horizontally. iFrames is mainly used for displaying external content on a target web page, for example, an advertisement for any online programming course on a web page. An iframe is also known as the inline frame. It is a tag used in HTML5 to embed an HTML document within a parent HTML document. An iframe tag is defined using `<iframe></iframe>` tags.

It is possible to identify the iframes on a web page in two ways:

- Right-click on the specific element and check all the options. If you find an option like This Frame, view Frame source or Reload Frame, it means the page includes frames.
- Similar to the first step, right-click on the page and click on View Page Source. On the page source, search for “iframe-tags”. If you find any iframe tags, it means the page includes iframes.

To interact with any web element present within any frame, one needs to switch to that particular frame. This allows the user to identify elements present on that page and write tests accordingly.

QAs can switch between frames using the **Switch.frame()** function. The switch function can be implemented using three different locators: By.index, By.id, By WebElement. Refer to the commands below:

By Index

```
driver.switchTo().frame(1);
```

Switches to the frame with index number 1

By	Id	or	Name
----	----	----	------

```
driver.switchTo().frame("resultframe");
```

Switches the frame where the value of id attribute is resultframe

## By Web Element

```
WebElement    iframeElement    =    driver.findElement(By.id("resultframe"));
driver.switchTo().frame(iframeElement);
```

The `WebElement` command above identifies the web element and then passes it through the `iframe` element object.

### How to handle modals in Selenium WebDriver?

A Modal Dialog Box (also referred to as Bootstrap Modal Window) is built in Bootstrap Framework, due to which it gets displayed on top of your current page. Due to this, modal boxes need to be interacted with first before moving to the current webpage. Switching is not necessary for modals.

### Implementation

1. Open “flight\_reservation.html” and write a script to handle frames and print heading of page in each frame.


#### Program:

```
package seleniumScriptsA1;
import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.firefox.FirefoxDriver;
public class IFrames {
    public static void main(String[] args) {
        //setting path
        System.setProperty("webdriver.gecko.driver","C:\\Selenium_Drivers\\geckodriver.exe");
        //creating instance of web driver
        WebDriver driver=new FirefoxDriver();
        //navigate to web page
        driver.get("file:///C:/Users/parth/OneDrive/Desktop/SQA_HTML%20FILES/flight_reservation.html");
        //switch to frame1 using Index
        driver.switchTo().frame(0); //switch focus from main window to 1
        //locate and print heading in iframe1
        WebElement heading_frame1 = driver.findElement(By.id("heading1"));
        System.out.println("The heading inside the iframe1 is: "+heading_frame1.getText());
        driver.switchTo().defaultContent(); //switch to main menu
        //switching to iframe2 using id
        driver.switchTo().frame("IF2");
        //locate and print the heading in iframe2
        WebElement heading_frame2 = driver.findElement(By.id("heading2"));
        System.out.println("The heading inside the iframe2 is: "+heading_frame2.getText());
        driver.switchTo().frame(0);
        //locate and print heading inside the child iframe of iframe2
        WebElement heading_childframe1 = driver.findElement(By.id("heading3"));
        System.out.println("The heading inside the child iframe of iframe 2 is: "+heading_childframe1.getText());
```

```

        driver.switchTo().defaultContent();
        System.out.println("Title of main window is: "+driver.getTitle());
    }
}

```

**Output:**


```

<terminated> IFrames [Java Application] C:\Program Files\eclipse_EE\eclipse\plugins\org.eclipse.justj.openjdk.hotspot.jre.full.win32.x86_64
The heading inside the iframe1 is: This is iFrame-1
The heading inside the iframe2 is: This is iFrame-2
The heading inside the child iframe of iframe 2 is: This is iFrame inside iFrame 2
Title of main window is: Ratnagiri Tours

```


2. Open <https://demoqa.com/browser-windows> and write a script to handle multiple windows that opens after clicking button “New Window” and print the heading on that new window.

**Program:**

```

package webDriver;
import java.util.Set;
import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.chrome.ChromeDriver;
import org.openqa.selenium.firefox.FirefoxDriver;
public class Question_02 {
    public static void main(String[] args) throws InterruptedException {
        System.setProperty("webdriver.chrome.driver",
"E:\\selenium_setup\\chromedriver.exe");
        WebDriver driver = new ChromeDriver();
        driver.get("https://demoqa.com/browser-windows");
        String mainWindow = driver.getWindowHandle();
        WebElement newWindow = driver.findElement(By.id("windowButton"));
        newWindow.click();
        Set<String> handles = driver.getWindowHandles();
        for (String windowHandle : handles) {
            if (!windowHandle.equals(mainWindow)) {
                driver.switchTo().window(windowHandle);
                WebElement heading = driver.findElement(By.id("sampleHeading"));
                System.out.println(heading.getText());
            }
        }
    }
}

```

**Output:**

3. Write a selenium script to login to <http://demo.guru99.com/test/login.html> .

Use name and ID locator strategy to locate elements.


**Program:**

```
package seleniumScriptsA1;
import java.util.Set;
import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.chrome.ChromeDriver;
import org.openqa.selenium.chrome.ChromeOptions;
import org.openqa.selenium.firefox.FirefoxDriver;
import org.openqa.selenium.firefox.FirefoxOptions;
public class PopupDemo {
    public static void main(String[] args) throws InterruptedException {
        System.setProperty("webdriver.gecko.driver",
"C:\\Selenium_Drivers\\geckodriver.exe");
        //setting the options for google chrome browser
        FirefoxOptions options = new FirefoxOptions();
        options.addArguments("--remote-allow-origins=*");
        //creating instance of web driver
        WebDriver driver=new FirefoxDriver();
        //navigate to web page
        driver.get("file:///C:/Users/parth/OneDrive/Desktop/SQA_HTML%20FILES/flight_reservation.html");
    }
}
```

```

System.out.println("Title of the main window: "+driver.getTitle());
//print windows ID or windows handle
String mainWindow = driver.getWindowHandle();          System.out.println(mainWindow);
//locate and click on the hotels link
WebElement hotel_link = driver.findElement(By.linkText("Hotels"));
hotel_link.click();
Set<String> handles = driver.getWindowHandles();
for (String windowHandle : handles)
{
    if(!windowHandle.equals(mainWindow))
    {
        driver.switchTo().window(windowHandle);
        System.out.println("Title of ChildWindow is "+driver.getTitle());
        System.out.println("Id of Child Window is "+driver.getWindowHandle());
        //locate and print heading in the child window
        WebElement heading = driver.findElement(By.id("sampleHeading"));
        System.out.println("heading inside child window is "+heading.getText());
        Thread.sleep(5000);
        driver.close();          }          }          }          }

```

**Output:**


```

<terminated> PopupDemo [Java Application] C:\Program Files\eclipse_EE\eclipse\plugins\org.eclipse.justj.op
Title of the main window: Ratnagiri Tours
986d8931-20fc-4969-a79e-6079b1f87af4
Title of ChildWindow is Ad
Id of Child Window is c56d6074-aba4-4474-8933-334c0398b09b

```

**4. Open “hotel\_search.html” page and handle modals that appear after clicking on buttons on that webpage.**


**Program:**

```

package seleniumScriptsA1;
import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.firefox.FirefoxDriver;
public class ModelsDemo {
    public static void main(String[] args) throws InterruptedException {
        //setting path
        System.setProperty("webdriver.gecko.driver",
"C:\\Selenium_Drivers\\geckodriver.exe");
        //creating instance of web driver

```

```
WebDriver driver=new FirefoxDriver();
//navigate to web page
driver.get("file:///C:/Users/parth/OneDrive/Desktop/SQA_HTML%20FILES/hotel_search.html
");
WebElement hotels = driver.findElement(By.cssSelector("button[data-
target='#myModal']"));
hotels.click();
//locate modal header and print it
WebElement modal_header_1 = driver.findElement(By.className("modal-title"));
System.out.println(modal_header_1.getText());
Thread.sleep(5000);
WebElement btn_ok = driver.findElement(By.xpath("//button[text()='Ok']"));
btn_ok.click();
Thread.sleep(2000);
WebElement room = driver.findElement(By.id("myBtn1"));
room.click();
//locate and type in text box a modal
WebElement hotel_name= driver.findElement(By.id("htlname"));
hotel_name.sendKeys("Saptagiri");
Thread.sleep(3000);
WebElement cancel_button=
driver.findElement(By.xpath("//button[@type='submit']//following::button"));
cancel_button.click();    }    }
```

**Output:**

```
Console x
<terminated> ModelsDemo [Java Application] C:\Program Files\eclipse_EE\eclipse\plugins\org.eclipse.justj.openjdk.hotspot.jre.f
SLF4J: No SLF4J providers were found.
SLF4J: Defaulting to no-operation (NOP) logger implementation
SLF4J: See https://www.slf4j.org/codes.html#noProviders for further details.
5 Star Hotels in Ratnagiri
```

**Conclusion:** Learnt to handle multiple windows, frames and modals in Selenium.