

Name: Gufraan Nisar Shaikh

PRN: 202501040073

Class: CS1/C14

Practical 1

Practical lab Assignment

1.1.1 Calculate Momentum

Write a program that accepts the mass of an object (in kilograms) and its velocity (in meters per second), then calculates and displays the momentum of the object. The momentum is calculated using the formula: $p = mv$

where:

m is the mass of the object (in kilograms).

v is the velocity of the object (in meters per second).

Input Format:

- A single floating-point number representing the mass of the object in kilograms.
- A single floating-point number representing the velocity of the object in meters per second.

Output Format:

- The output will display calculated momentum with appropriate units (kgm/s) (rounded up to 2 decimal places).

Code:

```
mass = float(input())  
velocity = float(input())  
momentum = mass * velocity  
print(f"{momentum:.2f}kgm/s")
```

Output:

The screenshot displays a code editor interface with a file explorer on the left and a debugger on the right. The code in the editor is as follows:

```
1  
2 mass = float(input())  
3 velocity = float(input())  
4 momentum = mass * velocity
```

Below the code editor, the performance metrics are shown:

Average time	Maximum time
0.010 s 9.75 ms	0.018 s 18.00 ms

Test results summary:

- 2 out of 2 shown test case(s) passed
- 2 out of 2 hidden test case(s) passed

Test case details:

Test case	Time	Expected output	Actual output
Test case 1	18 ms	5.0 10.0 50.00kgm/s	5.0 10.0 50.00kgm/s
Test case 2	6 ms	2.3 4.8 11.04kgm/s	2.3 4.8 11.04kgm/s

The interface also includes a 'Submit' button at the top right and a 'Terminal' tab at the bottom.

1.1.2 Conditional Calculation Based on the Digits

Write a Python program that accepts an integer as input. Depending on the number of digits in .

Constraints:

$$1 \leq \leq 999$$

Input Format:

- The input consists of a single integer .

Output Format:

- If is a single-digit number, print its square.
- If is a two-digit number, print its square root (rounded to two decimal places).
- If is a three-digit number, print its cube root (rounded to two decimal places).
- Else print "Invalid".

Code:

```
import math
num=int(input(""))
if(num>0 and num<10):
    square=num*num
    print(square)
```

```

elif(num>9 and num<100):
    root=math.sqrt(num)
    print(f"{root:0.2f}")
elif(num>99 and num<1000):
    croot=math.pow(num,1/3)
    print(f"{croot:0.2f}")
else:
    print("Invalid")

```

Output:

Average time: 0.004 s (4.14 ms) | Maximum time: 0.006 s (6.00 ms) | 4 out of 4 shown test case(s) passed | 3 out of 3 hidden test case(s) passed

Test Case	Expected output	Actual output
Test case 1 (6 ms)	9 81	9 81
Test case 2 (4 ms)	166 5.50	166 5.50
Test case 3 (4 ms)	24 4.90	24 4.90
Test case 4 (3 ms)	3456 Invalid	3456 Invalid

1.1.3 Days between two Dates

Write a Python program to calculate number of days between two dates.

Input Format:

- The first line contains the first date in the format .
- The second line contains the second date in the format .

Output Format:

- An integer representing the number of days between the given dates.

Note:

- The first date should always be considered earlier than the second date.

Code:

```
from datetime import date
from datetime import datetime
date1 = input().strip()
date2 = input().strip()
d1 = datetime.strptime(date1, "%Y-%m-%d")
d2 = datetime.strptime(date2, "%Y-%m-%d")
difference = d2-d1
print(difference.days)
```

Output:

Average time

0.011 s

11.50 ms

Maximum time

0.029 s

29.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 29 ms Debug

Expected output

Actual output

2014-07-02

2014-07-02

2014-11-02

2014-11-02

123

123

✓ Test case 2 6 ms Debug

Expected output

Actual output

2014-07-02

2014-07-02

2014-07-11

2014-07-11

9

9

Terminal

Test cases

1.1.4 Reverse a Number

Write a Python program to reverse the digits of the number and print the reversed number.

Input Format:

- The input is a single integer.

Output Format:

- The output prints a single integer, which is the reversed number.

Code:

```
n = int(input())
```

```
n=str(n)
print(int(n[::-1]))
```

Output:

The screenshot displays a code execution environment with the following details:

- Performance Metrics:**
 - Average time: 0.005 s (4.80 ms)
 - Maximum time: 0.010 s (10.00 ms)
- Test Results Summary:**
 - 2 out of 2 shown test case(s) passed
 - 3 out of 3 hidden test case(s) passed
- Test Case Details:**
 - Test case 1 (10 ms):** Expected output: 5367, Actual output: 5367. Input: 7635.
 - Test case 2 (4 ms):** Expected output: 0132, Actual output: 0132. Input: 231.
- Interface Elements:** Includes 'Terminal' and 'Test cases' tabs at the bottom, and 'Debug' buttons for each test case.

1.1.5 Multiplication Table

Write a Python program that takes an integer as input and prints the multiplication table for that integer from 1 to 10.

Input Format:

- The first line of input contains an integer that represents the number for which the multiplication table is to be printed.

Output Format:

- Print the multiplication table for the given number in the format:

<number> x <multiplier> = <result>

Note:

- The character "x" is used in the output to represent multiplication.
- Refer to the visible test-cases for more clarity.

Code:

```
num=int(input())
```

```
for i in range(1,11):
```

```
    table=num*i
```

```
    print(num,"x",i,"=",num*i)
```


Output:

Average time
0.004 s
3.50 ms

Maximum time
0.005 s
5.00 ms

✓ 2 out of 2 shown test case(s) passed
✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 5 ms Debug

Expected output	Actual output
8	8
8 · x · 1 = · 8	8 · x · 1 = · 8
8 · x · 2 = · 16	8 · x · 2 = · 16
8 · x · 3 = · 24	8 · x · 3 = · 24
8 · x · 4 = · 32	8 · x · 4 = · 32
8 · x · 5 = · 40	8 · x · 5 = · 40
8 · x · 6 = · 48	8 · x · 6 = · 48
8 · x · 7 = · 56	8 · x · 7 = · 56
8 · x · 8 = · 64	8 · x · 8 = · 64
8 · x · 9 = · 72	8 · x · 9 = · 72
8 · x · 10 = · 80	8 · x · 10 = · 80

✓ Test case 2 3 ms Debug

Expected output	Actual output
5	5
5 · x · 1 = · 5	5 · x · 1 = · 5
5 · x · 2 = · 10	5 · x · 2 = · 10
5 · x · 3 = · 15	5 · x · 3 = · 15
5 · x · 4 = · 20	5 · x · 4 = · 20
5 · x · 5 = · 25	5 · x · 5 = · 25
5 · x · 6 = · 30	5 · x · 6 = · 30
5 · x · 7 = · 35	5 · x · 7 = · 35
5 · x · 8 = · 40	5 · x · 8 = · 40
5 · x · 9 = · 45	5 · x · 9 = · 45
5 · x · 10 = · 50	5 · x · 10 = · 50

Terminal

Test cases

Lab Assignment

1.2.1 Pass or Fail

Write a Python program that accepts the number of courses and the marks of a student in those courses.

The grade is determined based on the aggregate percentage:

- If the aggregate percentage is greater than 75, the grade is Distinction.
- If the aggregate percentage is greater than or equal to 60 but less than 75, the grade is First Division.
- If the aggregate percentage is greater than or equal to 50 but less than 60, the grade is Second Division.
- If the aggregate percentage is greater than or equal to 40 but less than 50, the grade is Third Division.

Input Format:

- The first input will be an integer , the number of courses.
- The second input will be integers representing the marks of the student in each of the courses, separated by a space.

Output Format:

If the student passes all courses:

- Print the aggregate percentage (formatted to two decimal places).
- Print the grade based on the aggregate percentage.

If the student fails any course (marks < 40 in any course), print:

- "Fail".

Note:

- Aggregate Percentage: Average performance across all courses, calculated by summing all marks and dividing by the number of courses.

Code:

```
n = int(input())
marks=list(map(int, input().split()))
failed = False
for m in marks:
    if (m<40):
        failed=True
        break

if failed:
    print("Fail")
else:
    total=sum(marks)
    agg=total/n
    print("Aggregate Percentage: "f"{agg:.2f}")
    if agg>75:
        print("Grade: Distinction")
    elif(agg>=60):
        print("Grade: First Division")
    elif(agg>=50):
        print("Grade: Second Division")
    elif(agg>=40):
        print("Grade: Third Division")
```

Output:

Average time
0.006 s
6.00 ms

Maximum time
0.009 s
9.00 ms

5 out of 5 shown test case(s) passed

5 out of 5 hidden test case(s) passed

Test case 10 ms Debug

Expected output

4

55 65 78 89

Aggregate Percentage: 71.75

Grade: First Division

Actual output

4

55 65 78 89

Aggregate Percentage: 71.75

Grade: First Division

Test case 20 ms Debug

Expected output

5

56 78 97 86 93

Aggregate Percentage: 82.00

Grade: Distinction

Actual output

5

56 78 97 86 93

Aggregate Percentage: 82.00

Grade: Distinction

Test case 37 ms Debug

Expected output

5

99 85 43 97 34

Fail

Actual output

5

99 85 43 97 34

Fail

Test case 45 ms Debug

Expected output

3

55 54 53

Aggregate Percentage: 54.00

Grade: Second Division

Actual output

3

55 54 53

Aggregate Percentage: 54.00

Grade: Second Division

Test case 56 ms Debug

Expected output

5

40 45 42 48 41

Aggregate Percentage: 43.20

Grade: Third Division

Actual output

5

40 45 42 48 41

Aggregate Percentage: 43.20

Grade: Third Division

1.2.2 Fibonacci Series

Write a Python program that uses recursion to print the first terms of the Fibonacci series.

Input Format:

- A single integer representing the number of terms to generate.

Output Format:

- A single line containing the first terms of the Fibonacci sequence, separated by spaces.

Code:

```
def fibonacci(n):  
    if n==1:  
        return 0  
    elif n==2:  
        return 1  
    else:  
        return fibonacci(n-1)+fibonacci(n-2)
```

```
n = int(input())  
for i in range(1, n + 1):  
    print(fibonacci(i), end=" ")
```

Output:

Average time
0.009 s
9.50 ms

Maximum time
0.025 s
25.00 ms

✓ 2 out of 2 shown test case(s) passed
✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 4 ms Debug

Expected output
5
0 1 1 2 3

Actual output
5
0 1 1 2 3

✓ Test case 2 3 ms Debug

Expected output
15
0 1 1 2 3 5 8 13 21 34 55 89 144 233 377

Actual output
15
0 1 1 2 3 5 8 13 21 34 55 89 144 233 377

Terminal Test cases

1.2.3 Pattern-1

Write a Python program to print a pattern of asterisks in the form of a right-angled triangle.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format

- The output should display the pattern of asterisks (*), with each row containing an increasing number of asterisks.

Note: Refer to the displayed test cases for the sample pattern.

Code:

#Type Content here...

```
n=int(input())
```

```
for i in range(1,n+1):
```

```
    for j in range(i):
```

```
        print("* ",end="")
```

```
    print()
```

Output:

The screenshot displays a code execution environment with the following components:

- Performance Metrics:**
 - Average time: 0.004 s (3.83 ms)
 - Maximum time: 0.004 s (4.00 ms)
- Test Results Summary:**
 - 2 out of 2 shown test case(s) passed
 - 4 out of 4 hidden test case(s) passed
- Test Case Details:**
 - Test case 1 (4 ms):** Expected output is 5. The actual output is a right-angled triangle of asterisks:

```
5
* 
* * 
* * * 
* * * * 
* * * * * 
```
 - Test case 2 (3 ms):** Expected output is 4. The actual output is a right-angled triangle of asterisks:

```
4
* 
* * 
* * * 
* * * * 
```
- Navigation:** Buttons for 'Terminal' and 'Test cases' are at the bottom.

1.2.4 Pattern-2

Write a Python program to print a right-angled triangle pattern of numbers.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format:

- The output should display the pattern of numbers separated by space, with each row containing increasing numbers starting from 1 up to the row number.

Note:

- Refer to the displayed test cases for the sample pattern.

Code:

```
n=int(input())
for i in range(1,n+1):
    for j in range(1,i+1):
        print(j,end=" ")
    print()
```


Output:

Average time
0.004 s
4.50 ms

Maximum time
0.005 s
5.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 5 ms Debug

Expected output

Actual output

5

1 · 1

1 · 2 · 1

1 · 2 · 3 · 1

1 · 2 · 3 · 4 · 1

1 · 2 · 3 · 4 · 5 · 1

1 · 2 · 3 · 4 · 5

1 · 2 · 3 · 4 · 5

✓ Test case 2 5 ms Debug

Expected output

Actual output

8

1 · 1

1 · 2 · 1

1 · 2 · 3 · 1

1 · 2 · 3 · 4 · 1

1 · 2 · 3 · 4 · 5 · 1

1 · 2 · 3 · 4 · 5 · 6 · 1

1 · 2 · 3 · 4 · 5 · 6 · 7 · 1

1 · 2 · 3 · 4 · 5 · 6 · 7 · 8 · 1

1 · 2 · 3 · 4 · 5 · 6 · 7 · 8

Terminal

Test cases