Proceedings of the

International Conference on Innovations in Intelligent Computing and Biological Sciences

IICBS -2025

24th January 2025

Organized by

SRI RAMAKRISHNA

COLLEGE OF ARTS & SCIENCE FOR WOMEN

An Autonomous Institution | Reaccredited by NAAC with A+ Grade

Affiliated to Bharathiar University | ISO 9001:2015 Certified

Coimbatore – 641044

In collaboration with

A · P · U

ASIA PACIFIC UNIVERSITY OF TECHNOLOGY & INNOVATION

Proceedings of the

International Conference
on
Innovations in Intelligent Computing and Biological Sciences,

IICBS - 2025

24th January 2025

ISBN Number: 978-93-341-9627-6

33	IICBS 2025- CS33	Review on Gait Analysis for Early Detection of Huntington's Disease Using Machine Learning Classifiers *N. Karthick, M. K. Darun, V. S. Guhan and M. Dharineesh*	127
34	IICBS 2025- CS34	Analyzing and Classifying Colored Sound Signals with Supervised Learning *Dr. M. Arun Prasad*	133
35	IICBS 2025- CS35	Review on AI in Smart Healthcare *N. Karthick, S. Dharshana, K. Nandana and A. Aswitha*	138
36	IICBS 2025- CS36	Review on Artificial Intelligence on Automobiles *Dr. Joselin, T. Kavin, P. Hari Prasath and J. M. Kavivarmaa*	142
37	IICBS 2025- CS37	Review on Paddy Disease Prediction using Machine Learning Techniques *Dr. Anuja Beatrice, C. Harini, A. Vanisree and S. Janani*	146
38	IICBS 2025- CS38	Revolutionizing Brain Tumor Detection: The Role of Deep Learning in Advancing Medical Imaging and Diagnosis *A. M. Aishwarya*	151
39	IICBS 2025- CS39	Review of Identifying and Preventing Mulberry Leave Diseases *N. Karthick, M. Susendhiran, S. Pranesh and S. S. Balaji*	155
40	IICBS 2025- CS40	Review on Thyroid Disease Using Machine Learning *N. Karthick, S. Vaishnavi, P. S. Rathiarasi and R. Priyadharshini*	160
41	IICBS 2025- CS41	Review on Alzheimer's Dissease Detection and Diagnosis *N. Karthick, J. B. Bavadarishika, M. Jaya Sree and V. S. Varshini*	167
42	IICBS 2025- CS42	Generative AI as a Catalyst for Future Learning Innovations *M. A. Dhivyavarshan, Keren Kaitilin Alisa, G. Gracy Jasmine, Dr. C. Thangamani and Dr P. Kavitha*	174
43	IICBS 2025- CS43	Data Science and Big Data Analytics *A.Shobana, T. Anushri and R. Vishnupriya*	178
44	IICBS 2025- CS44	Study On: Artificial Intelligence in Genomics - Revolutionizing Biological Sciences *Anagha M Krishna and K. Pranathi*	181
45	IICBS 2025- CS45	Combinational Approach of Neural Networks and Ensemble Methods for Brain Tumor Classification *D. Shree Purvaja and Dr. B. Meena Preeti*	184
46	IICBS 2025- CS46	Smart IoT-Based Evapotranspiration Monitoring System for Precision Agriculture *D. Antony Pradeesh*	188
47	IICBS 2025- CS47	A Novel Dicepn-Clun-Based Pitting/Crusting Ratio Estimation and Multiclass Skin Cancer Classification Using Dermoscopy Images *N. Jasmine and Dr. S. Preetha*	194
48	IICBS 2025- CS48	Impact of Social Media among Youngsters: A Data Analytics Approach *J. Bharath Kanna and Dr. V. Vijayakumar*	200
49	IICBS 2025- CS49	Review on Advanced Deep Learning Design for Early-Stage Breast Image Cancer Detection *K. B. Sreeji and Dr. R. Khanchana*	204

Review on Gait Analysis for Early Detection of Huntington's Disease Using Machine Learning Classifiers

N. Karthick[1], M. K. Darun[2], V. S. Guhan[3] and M. Dharineesh[4]

[1]*Assistant Professor,* [2,3,4]*Student*
[2,3,4]*Department of Computer Applications, Sri Krishna Arts and Science College, Coimbatore.*
E-Mail: [1]*karthickn@skasc.ac.in,* [2]*darunmk24bca105@skasc.ac.in*

***Abstract*—**This review underscores the transformative potential of gait analysis as a cutting-edge tool for the early detection and ongoing monitoring of Huntington's Disease (HD), a debilitating neurodegenerative disorder characterized by progressive motor impairments[1]. By meticulously examining nuanced gait abnormalities in HD patients, this research integrates advanced machine learning algorithms—including Support Vector Machines (SVM), Random Forest (RF), K-Nearest Neighbors (KNN), and Decision Tree (DT)—to achieve superior diagnostic accuracy and clinical relevance. These algorithms demonstrated exceptional efficacy, with high precision in differentiating HD patients from healthy controls based on gait metrics[3].

This innovative approach offers a compelling combination of advantages: it is non-invasive, cost-efficient, and readily scalable, making it a practical option for widespread clinical implementation. Beyond its role in early diagnosis, which is critical for timely therapeutic interventions, this methodology also establishes a robust framework for longitudinal monitoring of disease progression. Such advancements promise to significantly enhance patient management strategies, optimize treatment outcomes, and contribute to the broader understanding of HD's impact on motor function [5].

***Keywords*—**Component, Huntington's Disease, Gait Analysis, Machine Learning, Support Vector Machines, Random Forest, K-Nearest Neighbors, Decision Tree, Early Detection, Biomarkers.

I INTRODUCTION

HUNTINGTON'S Disease (HD) is a devastating progressive neurodegenerative disorder characterized by motor dysfunction, cognitive decline, and psychiatric disturbances[6]. Early diagnosis is paramount to slowing disease progression, improving treatment outcomes, and enhancing the quality of life for affected individuals. Among the earliest and most sensitive biomarkers of HD are subtle gait abnormalities, which often precede overt motor symptoms. Identifying these early changes in gait offers a unique window for timely intervention, potentially delaying disease onset and optimizing patient care strategies[7].

This study explores the application of advanced machine learning classifiers—*Support Vector Machines (SVM), Random Forest (RF), K-Nearest Neighbors (KNN), and Decision Tree (DT)*—to effectively classify individuals based on detailed gait features[4]. By analyzing gait data from both healthy controls and HD patients, the research assesses the performance of these algorithms in terms of accuracy, precision, and reliability. The results underscore the ability of these models to detect early-stage motor impairments with high efficacy, offering a promising foundation for non-invasive, cost-effective diagnostic tools[8].

This work not only advances early detection capabilities but also sets the stage for integrating machine learning in clinical settings, where scalable and robust methodologies can transform the diagnosis and management of Huntington's Disease. Such innovations hold immense potential for enhancing patient outcomes and contributing to the broader understanding of neurodegenerative disorders[13].




Fig 1. Difference Between Normal and HD affected Brain

II LITERATURE REVIEW

2. Methodology

A. Dataset

Gait data were meticulously collected from Huntington's Disease (HD) patients and healthy controls using state-of-the-art motion capture systems, wearable sensors, and high-definition video analysis techniques. This multi-modal approach ensured the acquisition of comprehensive, high-resolution data, capturing even the most subtle nuances of gait dynamics[2]. Key gait parameters analyzed include stride length, step time, gait velocity, joint angles, and postural sway—critical indicators of motor function, coordination, and balance that are highly sensitive to the motor deficits characteristic of HD[3].




Fig 2. Dataset for Gait

To ensure a holistic understanding of HD's impact, data were gathered from individuals at various stages of the disease, from pre-symptomatic to advanced phases. This diverse dataset enabled a granular analysis of disease progression, uncovering stage-specific gait abnormalities and providing insights into how motor impairments evolve over time. Such a robust and diverse dataset forms a solid foundation for the application of advanced machine learning classifiers, facilitating the detection of subtle motor impairments with precision. By leveraging these sophisticated techniques, this research offers a transformative approach to diagnosing HD, with the potential to enhance early detection, track disease progression, and improve clinical outcomes[5]

.




Fig 3. How Data is extracted from Every Patient.

B. *Preprocessing and Feature Extraction*

Gait sequences underwent meticulous preprocessing to ensure temporal alignment, eliminate artifacts, and reduce noise, thereby enhancing the reliability and accuracy of the subsequent analysis. From these refined data, key features were extracted, providing valuable insights into motor dysfunctions associated with Huntington's Disease (HD):

- ✓ Stride length: Markedly reduced in HD patients, signaling compromised motor control and diminished stride efficiency.
- ✓ Step symmetry: Often disrupted in HD, revealing coordination deficits and asymmetrical gait patterns.
- ✓ Postural stability: Progressively declines with disease severity, serving as a critical marker of balance impairments and fall risk.
- ✓ Gait velocity, cadence, joint movements, and body sway: Comprehensive indicators of motor dysfunction, reflecting the multi-faceted impact of HD on gait dynamics.

To optimize the performance of machine learning classifiers and mitigate computational complexity, dimensionality reduction techniques such as Principal Component Analysis (PCA) were employed. This approach effectively isolated the most informative features, ensuring that the analysis concentrated on critical patterns while preserving the variability essential for early detection and nuanced insights. This refined framework not only strengthens the model's diagnostic capabilities but also enhances its clinical applicability for identifying HD-related motor impairments with precision [5].




Fig 4. Flowchart of PCA

C. *Machine Learning Classifiers*

Each machine learning classifier was meticulously trained on the extracted gait features to rigorously evaluate its effectiveness in detecting Huntington's Disease (HD) by identifying subtle motor impairments. The training process involved fine-tuning hyperparameters, optimizing decision boundaries, and employing cross-validation techniques to ensure robust and unbiased performance.

By leveraging high-resolution gait data, the classifiers were designed to capture intricate patterns and deviations in motor function associated with HD. This thorough approach not only maximized the models' diagnostic precision but also highlighted their potential to distinguish HD patients from healthy individuals with remarkable accuracy. The analysis further validated the classifiers' ability to detect early-stage motor impairments, demonstrating their transformative utility in clinical diagnostics and disease monitoring[1].

1) *Support Vector Machine (SVM)*

Support Vector Machine (SVM) is a powerful supervised learning algorithm used for classification and regression tasks. It works by finding the optimal hyperplane that maximally separates data points of different classes. By leveraging a Radial Basis Function (RBF) kernel, SVM extends its capability to handle non-linear separability in complex datasets. The RBF kernel maps data into a higher-dimensional space, enabling the SVM to accurately capture intricate patterns, making it particularly effective for tasks like precise classification of gait anomalies[1].




Fig 5. SVM - RBF Kernel

2) Random Forest (RF)

Random Forest (RF) is a highly versatile and powerful ensemble learning algorithm widely employed for classification and regression tasks. It operates by constructing an ensemble of decision trees during the training process and aggregating their outputs—via majority voting for classification or averaging for regression—to deliver robust and reliable predictions. By leveraging the diversity of individual trees, Random Forest excels in modeling intricate, non-linear relationships within complex datasets.

This ensemble approach offers several advantages, including enhanced predictive accuracy, reduced susceptibility to overfitting, and strong generalization capabilities for unseen data. These strengths make Random Forest particularly well-suited for analyzing high-dimensional and complex datasets, such as gait data, where subtle patterns and variations must be identified to detect early motor impairments. Its ability to handle feature interactions and accommodate variability further underscores its utility in extracting meaningful insights from challenging datasets, enabling precise and actionable predictive performance[2].




Fig 5. RF Flowchart

3) K-Nearest Neighbors (KNN)

K-Nearest Neighbors (KNN) is a simple yet powerful non-parametric, instance-based machine learning algorithm widely used for both classification and regression tasks. It functions by identifying the k closest data points (neighbors) to a given query point, using a predefined distance metric such as Euclidean, Manhattan, or Minkowski distance. For classification, KNN assigns a class label based on majority voting among the neighbors, while for regression, it computes an average of the neighbors' values.

What sets KNN apart is its ability to effectively capture localized feature similarities, making it highly adaptable to complex and diverse datasets. In the context of gait analysis, KNN excels at identifying proximity-based relationships within gait feature patterns, such as stride length, step symmetry, and joint movements. These relationships are crucial for accurate classification of subtle motor impairments, particularly in cases like Huntington's Disease (HD). Its simplicity, flexibility, and effectiveness in recognizing nuanced patterns make KNN a valuable tool for pattern recognition and predictive modeling in clinical and real-world applications[1].




Fig 6. KNN Flowchart

4) Decision Tree (DT)

A Decision Tree is a versatile and interpretable supervised learning algorithm employed for both classification and regression tasks. It operates by recursively partitioning the dataset into subsets based on the most significant features, forming a tree-like structure where each internal node represents a decision rule, each branch corresponds to an outcome of the rule, and each leaf node denotes a final prediction or outcome.

This structured approach enables the model to pinpoint key decision points within the data, such as critical gait features (e.g., stride length, symmetry, or postural stability), making it highly effective for capturing complex patterns. Decision Trees are particularly valued for their interpretability, as the hierarchical decision-making process is easy to visualize and understand, even by non-experts. Additionally, they provide insights into feature importance, highlighting the most influential factors driving predictions. These qualities make Decision Trees an excellent choice for constructing transparent, actionable predictive models, especially in domains like gait analysis where interpretability is essential for clinical and diagnostic applications [12].




Fig 7. DT Flowchart

The classifiers underwent rigorous evaluation using k-fold cross-validation, a robust method for assessing model generalizability and mitigating overfitting. This process involved dividing the dataset into k subsets, training the model on k-1 folds, and validating it on the remaining fold, iteratively covering all subsets. This systematic approach ensured reliable performance estimates across diverse data splits.

To comprehensively assess the classifiers' effectiveness in detecting early-stage Huntington's Disease (HD), multiple performance metrics were employed:

- ✓ **Accuracy:** Measured the overall correctness of predictions across all classes.
- ✓ **Precision:** Evaluated the proportion of correctly identified positive cases out of all predicted positives, crucial for minimizing false positives.
- ✓ **Recall (Sensitivity):** Assessed the ability to correctly identify true positives, vital for early detection of HD.
- ✓ **F1-Score:** Harmonized precision and recall to provide a balanced evaluation metric, especially useful in cases with imbalanced datasets.

This rigorous evaluation framework ensured that the classifiers were not only highly reliable in detecting subtle motor impairments but also capable of delivering consistent and clinically relevant predictions for early-stage HD.

III RESULTS

A. Accuracy and Sensitivity

The paper presents a comprehensive analysis of the performance metrics for the machine learning classifiers evaluated for the diagnosis of Huntington's Disease (HD) based on gait features. The reported metrics provide a detailed assessment of each classifier's ability to accurately identify HD patients from healthy controls, with a focus on detecting subtle motor impairments associated with the early stages of the disease.

1) Support Vector Machine (SVM)

The model achieved an impressive accuracy of 86.9%, showcasing its exceptional capability in distinguishing neurodegenerative disorders, including Huntington's Disease (HD). This high level of accuracy underscores the effectiveness of leveraging advanced gait analysis techniques to capture subtle, disease-specific movement patterns. By identifying nuanced motor impairments with precision, the model demonstrates significant potential for aiding early diagnosis and enhancing clinical decision-making in neurodegenerative disease management [1].

2) Random Forest (RF)

The model achieved an accuracy of 85%, highlighting its robust capability to effectively identify critical gait features such as step length variation and postural sway. These features are pivotal in capturing nuanced movement patterns, enabling precise analysis and accurate classification of Huntington's Disease (HD). This performance underscores the model's potential as a reliable diagnostic tool for detecting subtle motor impairments associated with HD and other neurodegenerative disorders[2].

3) K-Nearest Neighbors (KNN)

The model reported an accuracy of 80%, demonstrating its effectiveness in detecting motor abnormalities associated with Huntington's Disease (HD). The performance was strongly influenced by the choice of the parameter K, emphasizing the model's sensitivity to the number of nearest neighbors selected for optimal classification. This result underscores the importance of fine-tuning hyperparameters to enhance the model's ability to accurately capture and classify subtle gait abnormalities, making it a valuable tool for early diagnosis and disease monitoring[1].

4) Decision Tree (DT)

The model achieved an accuracy of 81.8%, demonstrating exceptional proficiency in identifying critical gait features such as gait velocity. This feature proved pivotal in accurately analyzing movement patterns and distinguishing between Huntington's Disease (HD) and other conditions with high precision. The model's performance highlights its capability to capture nuanced motor impairments, underscoring its potential as a reliable diagnostic tool for early detection and precise classification in clinical applications.

The results underscore the models' significant potential in distinguishing Huntington's Disease (HD) patients from healthy controls. Among the classifiers evaluated, Support Vector Machines (SVM) and Random Forest (RF) emerged as top performers, demonstrating superior accuracy. Their ability to effectively capture complex gait patterns and subtle motor impairments reinforces their promise as powerful tools for early diagnosis and precise classification of HD in clinical settings[12].

B. Feature Importance

The most critical gait features identified by the machine learning classifiers for distinguishing Huntington's Disease (HD) from healthy controls are as follows:

- ✓ Support Vector Machines (SVM) and Random Forest (RF): Emphasized features such as step length variation, gait velocity, and postural sway, demonstrating their importance in accurately detecting HD-related motor impairments.
- ✓ K-Nearest Neighbors (KNN): Highlighted stride length and gait velocity as key indicators, enabling the model to capture subtle gait abnormalities associated with early stages of HD.
- ✓ Decision Tree (DT): Identified gait velocity, stride length variation, and step width as significant contributors to classification, reflecting their critical role in distinguishing HD patients.

These findings align with existing research on machine learning applications for HD diagnosis, further validating the relevance of these gait features in identifying disease-specific motor impairments. Their consistent importance across classifiers underscores their value in developing reliable and precise diagnostic models [3].

C. Early History

All classifiers demonstrated strong effectiveness in detecting early-stage Huntington's Disease (HD) by accurately identifying key gait abnormalities, including decreased gait velocity, increased step width, and reduced stride length. These subtle changes are among the earliest motor symptoms of HD, serving as crucial biomarkers for early diagnosis. Detecting such indicators at the initial stages is vital, as it facilitates timely clinical interventions that can significantly improve symptom management and potentially delay disease progression.

By leveraging advanced machine learning models, clinicians can achieve higher accuracy and sensitivity in pinpointing these early motor impairments. This enhanced diagnostic capability not only supports earlier and more precise identification of HD but also contributes to better patient outcomes, improved quality of life, and a more effective allocation of healthcare resources[5].

IV DISCUSSIONS

A. Clinical Relevance

Gait analysis powered by advanced machine learning classifiers presents a transformative, non-invasive, automated, and cost-efficient approach for the early detection of Huntington's Disease (HD). By utilizing sophisticated algorithms, this method identifies subtle gait abnormalities—such as reduced stride length and increased step width—that are often undetected through traditional clinical assessments. These early markers of motor impairment provide critical insights for timely diagnosis[2].

Early detection through gait analysis enables proactive clinical interventions that can significantly enhance symptom management, improve patient quality of life, and potentially slow the progression of HD. Furthermore, this approach complements existing diagnostic tools, serving as an efficient and scalable screening technique for at-risk individuals. By reducing the dependency on more invasive or resource-intensive procedures, gait analysis advances the accessibility and effectiveness of HD diagnosis, paving the way for improved patient care and management[4].

B. Challenges and Limitations

1) Variability in Gait Patterns:

Gait patterns exhibit significant variability across individuals, influenced by factors such as age, physical fitness, and the progression stage of Huntington's Disease (HD). This variability presents a major challenge in achieving consistent classification accuracy. To address this, robust feature selection techniques and adaptive model architectures are essential for accounting for inter-individual differences, ensuring reliable performance across diverse patient demographics and disease stages.

2) Overfitting in Classifiers:

Classifiers like Decision Trees are particularly prone to overfitting, especially when they become overly complex by fitting noise in the training data. Overfitting compromises the model's generalizability to new, unseen data. Pruning techniques were employed to streamline the model by removing redundant branches and reducing complexity, thereby enhancing its ability to deliver accurate predictions on test datasets and improving its robustness in clinical applications[7].

3) Impact of Parameter Selection:

Classifiers such as K-Nearest Neighbors (KNN) are highly sensitive to parameter tuning, particularly the choice of K. Selecting an inappropriate value for K can significantly impact classification accuracy, potentially limiting the model's effectiveness in detecting subtle gait abnormalities. To overcome this, rigorous optimization through cross-validation was applied, enabling the identification of the optimal parameter values and ensuring reliable and precise model performance.

These challenges underscore the importance of a thoughtful and systematic approach to model design, feature selection, and parameter tuning. By addressing these obstacles, machine learning-based gait analysis can achieve higher reliability, scalability, and effectiveness as a diagnostic tool for early

detection and monitoring of Huntington's Disease, ultimately improving patient care and outcomes[4].

C. Comparison

Model	Accuracy	Key strengths	Features
SVM	86.9%	Exceptional at distinguishing between neurodegenerative diseases like HD using gait analysis.	Handles non-linear separability with RBF kernel for complex datasets.
RF	85%	Effectively identifies key gait features, such as step length variation and postural sway, enhancing accuracy.	Combines multiple decision trees to reduce overfitting and improve generalization.
KNN	80%	Sensitive to selected K, but effective in detecting motor abnormalities in HD patients.	Classifies based on proximity and similarity using distance metrics like Euclidean distance.
DT	81.8%	Excels at identifying critical gait features like gait velocity, aiding in precise classification.	Provides transparency and interpretability with a clear decision structure.

This comparison highlights each model's strengths, showing that while SVM achieves the highest accuracy, Random Forest, KNN, and Decision Tree also provide valuable insights into gait analysis, each with unique advantages.

V Conclusion

Machine learning classifiers, including Support Vector Machine (SVM), Random Forest (RF), K-Nearest Neighbors (KNN), and Decision Tree (DT), demonstrate significant potential for the early detection of Huntington's Disease (HD) through advanced gait analysis. These models effectively leverage subtle gait abnormalities—such as reduced stride length and increased step width—as key indicators of motor impairments, often identifying these changes before clinical symptoms become apparent[5].

The non-invasive nature, coupled with the high reliability of these methods, makes them invaluable tools for early diagnosis and timely intervention. Decision Trees, in particular, stand out due to their interpretability, which enhances their clinical applicability by providing clear insights into the decision-making process, vital for healthcare providers[6].

To fully realize the impact of these machine learning techniques, future efforts should focus on refining model accuracy, incorporating comprehensive data from wearable sensors or motion capture systems, and developing real-time diagnostic solutions. This integrated approach has the potential to revolutionize early HD screening, offering a more efficient, scalable, and accessible diagnostic pathway that could significantly improve patient outcomes and overall quality of care[13].

References

[1] Sowmiyalakshmi Ganesh, Thillai Chithambaram, Nadesh Ramu Krishnan, Durai Raj Vincent, Jayakumar Kaliappan, and Kathiravan Srinivasan. Exploring Huntington's Disease Diagnosis via Artificial Intelligence Models: A Comprehensive Review.

[2] Neel Parekh, Anjali Bhagat, Binith Raj, Raunak Singh Chhabra, Harpal Singh Buttar, Ginpreet Kaur, Seema Ramniwas, and Hardeep Singh Tuli. Artificial Intelligence in Diagnosis and Management of Huntington's Disease.

[3] Andrius Lauraitis, Rytis Maskeliūnas, and Robertas Damaševičius. ANN and Fuzzy Logic-Based Model to Evaluate Huntington Disease Symptoms.

[4] Andrew Jiang, Renee R. Handley, Klaus Lehnert, and Russell G. Snell. From Pathogenesis to Therapeutics: A Review of 150 Years of Huntington's Disease Research.

[5] Bhachawat, S.; Shriram, E.; Srinivasan, K.; Hu, Y.C. Leveraging Computational Intelligence Techniques for Diagnosing Degenerative Nerve Diseases: A Comprehensive Review, Open Challenges, and Future Research Directions.

[6] Walker, F.O. Huntington's Disease.

[7] McColgan, P.; Tabrizi, S.J. Huntington's Disease: A Clinical Review.

[8] Ghosh, R.; Tabrizi, S.J. Clinical Features of Huntington's Disease. In Polyglutamine Disorders.

[9] Mahendran, N.; PM, D.R.V. Deep Belief Network-Based Approach for Detecting Alzheimer's Disease Using the Multi-Omics Data.

[10] Mahendran, N.; PM, D.R.V. A Deep Learning Framework with an Embedded-Based Feature Selection Approach for the Early Detection of Alzheimer's Disease.

[11] Mahendran, N.; Vincent, P.D.R.; Srinivasan, K.; Chang, C.Y. Improving the Classification of Alzheimer's Disease Using Hybrid Gene Selection Pipeline and Deep Learning.

[12] Dixit, S.; Bohre, K.; Singh, Y.; Himeur, Y.; Mansoor, W.; Atalla, S.; Srinivasan, K. A Comprehensive Review on AI-Enabled Models for Parkinson's Disease Diagnosis.

[13] Medina, A.; Mahjoub, Y.; Shaver, L.; Pringsheim, T. Prevalence and Incidence of Huntington's Disease: An Updated Systematic Review and Meta-Analysis.

[14] Rusz, J.; Tykalova, T. Reader Response: Motor Speech Patterns in Huntington Disease.

Analyzing and Classifying Colored Sound Signals with Supervised Learning

Dr. M. Arun Prasad

Assistant Professor, Department of Electronics and Communication Systems
KG College of Arts and Science, Coimbatore, India. E-Mail: arunprasad@kgcas.com

***Abstract*---**This research proposes a supervised learning technique to analyze and classify six distinct types of colored noisy additive signals. The approach involves preprocessing predefined source audio signals to extract their unique characteristics in both time and time-frequency domains. By leveraging these features, the method categorizes input datasets into corresponding recognized classes. The classification model is trained using labeled datasets, where each audio signal is analyzed to identify its distinguishing characteristics. Various machine learning techniques are employed to ensure the reliability and predictability of the classification results. During the testing phase, the system is presented with a new, unidentified dataset to estimate the corresponding category of each incoming signal. The validation process includes evaluating the model's accuracy, robustness, and generalization capabilities using diverse testing approaches. The outcomes highlight the potential of this supervised learning method in accurately distinguishing between different types of colored noise. This study contributes to noise categorization, offering insights into signal processing and supervised machine learning applications. It can serve as a foundational approach for further research and practical implementations in audio signal analysis, environmental monitoring, and communication systems.

***Keywords*---**Noise, Machine Learning, Supervised Learning, Classification, Signal Characteristics.

I INTRODUCTION

TO anticipate and categorize audio signals, a supervised learning approach might be utilized. The supervised training method's learning is characterized by the presence of an instructor. When input data set and related output answers are recognized the supervised learning approach may be used. Most information processing algorithms may be broken down into multiple processes, including detection, segment, image segmentation, categorization, and post-processing. We may create more reasonable predictions about the training dataset by implementing the information of the source examples, and the resultant classifier is being used to categorize the unidentified occurrences. The goal of the learning experience is to offer information about the nature of the objective idea rather than to achieve optimum prediction and categorization of information. Preparing summary statistics is the first stage in deep classification. All supervised learning methods begin with a data matrix as input. Every number in the sequence takes a unique variable or data. For each row of the data input, the data collected is a column vector containing the output of the observable relation. Online reviews, accelerometers and Gaussian processes have all used supervised machine learning categorization algorithms. Various classification techniques, such as Decision tree, Discriminant analysis, and Closest Neighbor, had been used to evaluate and develop the supervised learning method.

II LITERATURE SURVEY

Acoustics is a waveform that contains both pleasant and unpleasant atmospheric disruptions. Whenever the particles of air move, the hearing interprets those atmospheric oscillations as noise and transforms them to kinetic motion, which even the mind may then understand via the intermediate and internal ear, and this is how humans detect sound. This study will look at how machines can differentiate among different noises. The noise signal is an undesired, strong noise and has the same properties as sound. Any type of processed random noise is referred to as" hued noise," which indicates impure white noise. Due to the obvious wavelength of the noise, noise colors are classified by coloring type. Self-organizing feature vectors are a machine learning approach that is utilized in various applications. MATLAB Simulink was used to produce colored noise signals. In this research, the essential characteristics retrieved from the time and frequency domains for each produced noise signal are used to construct a model, and a supervised learning technique is used to distinguish between the different specimen colors of noisy sound.

III PROPOSED SYSTEM

A. Data Preprocessing

Optimization has been created at the pre-processing stage to extract features in the time domain and frequency domain from both development and technical datasets. We looked at eight core features in the time and frequency domains. The standard deviation of the random noise was determined in time series using Equations (1) and (2):

$$\alpha = \frac{1}{X}\sum_{x=1}^{X} Y_x$$

$$W = \frac{1}{X-1}\sum_{x=1}^{X} |Y_x - \alpha|^2$$

Where Y = noise signal, X = scalar observation and W = variance noise signal. PSD estimation is the Transform of the skewed auto-correlation time series prediction. For the input