



Review Supported Technologies

Copyright Page

This document supports Pentaho Business Analytics Suite 5.1 GA and Pentaho Data Integration 5.1 GA, documentation revision June 10, 2014, copyright © 2014 Pentaho Corporation. No part may be reprinted without written permission from Pentaho Corporation. All trademarks are the property of their respective owners.

Help and Support Resources

To view the most up-to-date help content, visit <https://help.pentaho.com>.

If you do not find answers to your questions here, please contact your Pentaho technical support representative.

Support-related questions should be submitted through the Pentaho Customer Support Portal at <http://support.pentaho.com>.

For information about how to purchase support or enable an additional named support contact, please contact your sales representative, or send an email to sales@pentaho.com.

For information about instructor-led training, visit <http://www.pentaho.com/training>.

Liability Limits and Warranty Disclaimer

The author(s) of this document have used their best efforts in preparing the content and the programs contained in it. These efforts include the development, research, and testing of the theories and programs to determine their effectiveness. The author and publisher make no warranty of any kind, express or implied, with regard to these programs or the documentation contained in this book.

The author(s) and Pentaho shall not be liable in the event of incidental or consequential damages in connection with, or arising out of, the furnishing, performance, or use of the programs, associated instructions, and/or claims.

Trademarks

The trademarks, logos, and service marks ("Marks") displayed on this website are the property of Pentaho Corporation or third party owners of such Marks. You are not permitted to use, copy, or imitate the Mark, in whole or in part, without the prior written consent of Pentaho Corporation or such third party. Trademarks of Pentaho Corporation include, but are not limited, to "Pentaho", its products, services and the Pentaho logo.

Trademarked names may appear throughout this website. Rather than list the names and entities that own the trademarks or inserting a trademark symbol with each mention of the trademarked name, Pentaho Corporation states that it is using the names for editorial purposes only and to the benefit of the trademark owner, with no intention of infringing upon that trademark.

Third-Party Open Source Software

For a listing of open source software used by each Pentaho component, navigate to the folder that contains the Pentaho component. Within that folder, locate a folder named licenses. The licenses folder contains HTML files that list the names of open source software, their licenses, and required attributions.

Contact Us

Global Headquarters Pentaho Corporation Citadel International, Suite 340

5950 Hazeltine National Drive Orlando, FL 32822

Phone: +1 407 812-OPEN (6736)

Fax: +1 407 517-4575

<http://www.pentaho.com>

Sales Inquiries: sales@pentaho.com

Components Reference

Pentaho aims to accommodate diverse computing environments. This list provides details about the environment components and versions we support. If you have questions about your particular computing environment, please contact Pentaho support.

Server

Pentaho server software is hardware-independent and runs on server-class computers that comply with these specifications for minimum hardware and required operation systems.

- Pentaho Business Analysis Server
- Pentaho Data Integration Server

Hardware—64 bit	Operating System—64 bit
<p>Processor:</p> <ul style="list-style-type: none">• Apple Macintosh Pro Quad-Core or Macintosh Mini Quad-Core• Intel EM64T or AMD64 Dual-Core <p>RAM: 8 GB with 4 GB dedicated to Pentaho servers</p> <p>Disk Space: 20 GB free after installation</p>	<ul style="list-style-type: none">• Apple Macintosh OS X Server 10.8 & 10.9• CentOS Linux 5 & 6• Microsoft Windows 2008 Server R2, 2012 Server• Red Hat Enterprise Linux 5 & 6• Solaris 10• Ubuntu Server 10.x & 12.x

Workstation

These Pentaho design tools are hardware-independent and run on client-class computers that comply with these specifications for minimum hardware and required operation systems.

- Pentaho Aggregation Designer
- Pentaho Data Integration
- Pentaho Metadata Editor
- Pentaho Report Designer
- Pentaho Schema Workbench

Hardware—32 or 64 bit	Operating System—32 or 64 bit
Processors: <ul style="list-style-type: none"> • Apple Macintosh Dual-Core, 64 bit only • Intel EM64T or AMD64 Dual-Core RAM: 2 GB RAM for most of the design tools, PDI requires 2 GB dedicated Disk Space: 2 GB free after installation Minimum Screen Size: 1280 x 960	<ul style="list-style-type: none"> • Apple Macintosh OS 10.8 & 10.9, 64 bit only • Microsoft Windows 7 & 8 • Ubuntu Desktop 12.x

Embedded Software

When embedding Pentaho software into other applications, the computing environment should comply with these specifications for minimum hardware and required operation systems.

- Embedded Pentaho Reporting
- Embedded Pentaho Analysis
- Embedded Pentaho Data Integration

Hardware—64 bit	Operating System—64 bit
Processors: <ul style="list-style-type: none"> • Apple Macintosh Pro Quad-Core or Macintosh Mini Quad-Core • Intel EM64T or AMD64 Dual-Core RAM: 8 GB with 4 GB dedicated to Pentaho servers Disk Space: 20 GB free after installation	<ul style="list-style-type: none"> • Apple Macintosh OS X Server 10.7 & 10.8 • CentOS Linux 5 & 6 • Microsoft Windows 2008 Server R2 • Microsoft Windows 7 • Red Hat Enterprise Linux 5 & 6 • Solaris 10 • Ubuntu Server 10.x & 12.x

Application Servers

Servers to which you deploy Pentaho software must run one of these application servers.

Pentaho Software	Application Server
Pentaho Business Analysis Server Pentaho Data Integration Server	<ul style="list-style-type: none"> • JBoss 7.x (EAP 6.x.x) • Tomcat 7.0.x

Solution Database Repositories

Pentaho software stores processing artifacts in these solution database repositories.

Pentaho Software	Database Repository
Pentaho Business Analysis Server Pentaho Data Integration Server	<ul style="list-style-type: none">• MySQL 5.x• Oracle 10g/11i• PostgreSQL 8.4 & 9.1.x*

*Default installed solution database

Data Sources

Pentaho software connects to these relational and non-relational data sources.

Pentaho Software	Data Source
Pentaho Reporting	<ul style="list-style-type: none">• JDBC 3**• ODBC• OLAP4J• XML• MongoDB 2.6• Pentaho Analysis• Pentaho Data Integration• Pentaho Metadata• Scriptable
Pentaho Business Analysis Server, Action Sequences	<ul style="list-style-type: none">• Relational (JDBC)• Hibernate• Javascript• Metadata (MQL)• Mondrian (MDX)• XML (XQuery)• Security User/Role List Provider• Data Integration Steps (PDI)• Other Action Sequences• Web Services• XMLA
Pentaho Data Integration	<ul style="list-style-type: none">• JDBC 3**

Pentaho Software	Data Source
	<ul style="list-style-type: none"> • OLAP4J • Salesforce • XML • CSV • Microsoft Excel • Pentaho Analysis • Hadoop distributions, click here for versions <ul style="list-style-type: none"> • Cloudera • Intel • Hortonworks • MapR • Cassandra <ul style="list-style-type: none"> • Apache 2.0.x • DataStax DSE 4.0, includes Cassandra 2.0.x • MongoDB 2.6

**Use a JDBC 3.x compliant driver that is compatible with SQL-92 standards when communicating with relational data sources. For your convenience, we provide a [list of drivers](#) used to get data from relational JDBC databases.

SQL Dialect-Specific

Pentaho software generates dialect-specific SQL when communicating with these data sources.

Pentaho Software	Data Source
Pentaho Analysis	<ul style="list-style-type: none"> • Access • Amazon Redshift • DB2 • Derby • Firebird • Greenplum • Hsqldb • Impala*** • Infobright • Informix • Ingres • Interbase • LucidDb • MicrosoftSqlServer

Pentaho Software	Data Source
	<ul style="list-style-type: none"> • MonetDB • MySql • Neoview • Netezza • Oracle • PostgreSQL • SqlStream • Sybase • Teradata • Vectorwise • Vertica • Other SQL-89 compliant****
Pentaho Metadata	<ul style="list-style-type: none"> • Amazon Redshift • DB2 • Firebird • H2 • Hive 2 • Hypersonic • Impala • Ingres • MS Access • ASSQL • MSSQLNative • MySQL • Netezza • Oracle • PostgresSQL • Sybase • Vertica • Other SQL-92 compliant****
Pentaho Data Integration	<ul style="list-style-type: none"> • Apache Derby • AS/400 • InfiniDB • Exasol 4 • Firebird SQL • Greenplum • H2 • Hive

Pentaho Software	Data Source
	<ul style="list-style-type: none"> • Hive 2 • Hypersonic • IBM DB2 • Impala • Infobright • Informix • Ingres • Ingres VectorWise • LucidDB • MaxDB (SAP DB) • MonetDB • MySQL • MS SQL Server • Neoview • Netezza • Oracle • Oracle RDB • PostgreSQL • SQLite • Teradata • UniVerse database • Vertica • Other SQL-92 compliant****

***Current capability supports only a single table and does not support star or snowflake schemas

****If your data source is not in this list and is compatible with SQL-92, Pentaho software uses a generic SQL dialect.

Security

Pentaho software integrates with these third-party security authentication systems.

Pentaho Software	Authentication System
Pentaho Business Analysis Server Pentaho Data Integration Server	<ul style="list-style-type: none"> • Active Directory • CAS • Integrated Microsoft Windows Authentication • LDAP • RDBMS

Java Virtual Machine

All Pentaho software, except the Pentaho Mobile App, requires the Sun/Oracle version 1.7 distribution of the Java Runtime Environment (JRE) or Java Development Kit (JDK).

Web Browsers

Pentaho supports these major versions of Web browsers that are publicly available six weeks prior to when Pentaho begins to finalize a release. We also support the preceding major version.

Pentaho Software	Web Browser
Pentaho User Console Pentaho Report Designer*****	<ul style="list-style-type: none">• Apple Safari 5.x, 6.x, & 7.x on OSX only• Google Chrome 32 & 33• Microsoft Internet Explorer 8 - 11• Mozilla Firefox 26 & 27

*****Requires a web browser to preview exported HTML reports.

Mobile Apps

The Pentaho mobile app runs on the Apple iPad 2 and later, with iOS 6.x & 7.x using Safari mobile.

JDBC Drivers Reference

This reference is a continuous work in progress. If you are viewing it in the Pentaho InfoCenter and see something that is not correct, know of a driver that is not listed here, or have a tip you want to share, please let us know by using the comments fields found in the bottom right corner.

Database	Vendor	URL
Apache Derby	IBM	http://db.apache.org/derby/derby_downloads.html
Cache'	InterSystems	http://www.cachemonitor.de/interSystems-documentation/cache-jdbc-driver
CUBRID	CUBRID	http://www.cubrid.org/?mid=downloadsitem=jdbc_driver
Daffodil DB	Daffodil Software	http://sourceforge.net/projects/daffodildb/
DB2 AS/400	IBM	http://www-03.ibm.com/systems/i/software/toolbox/
DB2 Universal Database	IBM	http://www-306.ibm.com/software/data/db2/java
Firebird	Firebird Foundation	http://www.firebirdsql.org/en/jdbc-driver/
FrontBase	FrontBase	http://www.frontbase.com/cgi-bin/WebObjects/FBWebSite
Greenplum	EMC2	http://jdbc.postgresql.org/download.html
H2 Database	H2	http://www.h2database.com
Hive	Apache	http://hive.apache.org/
Hive2	Apache	
HSQLDB	HyperSQL	http://sourceforge.net/projects/hsqldb/
Impala	Cloudera	http://www.cloudera.com/content/cloudera-content/

Database	Vendor	URL
		cloudera-docs/Impala/latest/Installing-and-Using-Impala/ciiu_impala_jdbc.html
Informix	IBM	http://www-01.ibm.com/software/
Ingres	Action	http://esd.action.com/product/drivers/JDBC/java
InterBase	Embarcadero	http://edn.embarcadero.com
jTDS Free MS Sybase	jTDS	http://jtds.sourceforge.net/
LucidDB	LucidDB	http://sourceforge.net/projects/luciddb
MaxDB	SAP	http://maxdb.sap.com
Mckoi	Mckoi SQL Database	http://www.mckoi.com/originalmckoisql/index.html
Mimer	Mimer Information Technology	http://www.mimer.com
MonetDB	MonetDB	http://www.monetdb.org/
MySQL	Oracle	http://dev.mysql.com/downloads/connector/j/
Neoview	HP	https://h20392.www2.hp.com/portal/swdepot/displayProductInfo.do?productNumber=NEO10
Netezza	IBM	http://www.netezza.com
OpenBase SQL	OpenBase International	http://www.openbase.com/index.php/products/downloads
Oracle	Oracle	http://www.oracle.com/technetwork/database/features/jdbc/index.html
Pervasive	Pervasive	http://www.pervasivedb.com/download/Pages/PDBDownloads.aspx
PostgreSQL	PostgreSQL Global Development Group	http://jdbc.postgresql.org/
SAP DB	SAP DB	http://www.sapdb.org/sap_db_jdbc.htm
SQLite	Xerial	http://www.xerial.org/trac/Xerial/wiki/SQLiteJDBC
SQL Server	Microsoft	http://msdn.microsoft.com/en-us/sqlserver/aa937724.aspx

Database	Vendor	URL
Sybase ASE	SAP	http://www.sybase.com/products/allproductsa-z/softwaredeveloperkit/jconnect
Sybase SQL Anywhere	SAP	http://www.sybase.com/products/allproductsa-z/softwaredeveloperkit/jconnect
SmallSQL	SmallSQL	http://www.smallsql.de/download.html
Teradata	Teradata	http://downloads.teradata.com/download/connectivity/jdbc-driver
Vertica	HP	http://www.vertica.com

Apache Derby

Vendor Name	Details	
Recommended Native Driver		
IBM	Company URL http://www.ibm.com	
	Driver URL http://db.apache.org/derby/derby_downloads.html	
	JDBC URL Syntax by Type Server—jdbc:derby://<server>[:<port>]<databaseName>[;<URL attribute>=>value>] Embedded—jdbc:derby:<databaseName>[;create=true]	Default Port 1527
	JDBC Class org.apache.derby.jdbc.ClientDriver org.apache.derby.jdbc.EmbeddedDriver	JDBC JAR File Name derby.jar
	Shipped with Pentaho Products Pentaho Data Integration	

Vendor Name	Details
	Comments Open source database

Caché

Vendor Name	Details	
Recommended Native Driver		
InterSystems	Company URL http://www.cachemonitor.de	
	Driver URL http://www.cachemonitor.de/intersystems-documentation/cache-jdbc-driver	
	JDBC URL Syntax by Type Server—jdbc:Cache://<server>[:<port>]<namespace>	Default Port 1972
	JDBC Class com.intersys.jdbc.CacheDriver	JDBC JAR File Name cachedb.jar

CUBRID

Vendor Name	Details
Recommended Native Driver	
CUBRID	Company URL http://www.cubrid.org
	Driver URL http://www.cubrid.org/?mid=downloads&item=jdbc_driver

Vendor Name	Details	
	JDBC URL Syntax by Type Server—jdbc:cubrid:<server>:<port>:33000 <databaseName>:<username>: <password> :[?<URL attribute>=<value> [&<URL attribute>=<value>] ...]	Default Port 33000
	JDBC Class cubrid.jdbc.driver.CUBRIDDriver	JDBC JAR File Name N/A
	Comments Open source database highly optimized for Web applications.	

Daffodil DB

Vendor Name	Details	
Recommended Native Driver		
Daffodil Software	Company URL http://db.daffodilsw.com	
	Driver URL http://sourceforge.net/projects/daffodildb/	
	JDBC URL Syntax by Type Server—jdbc:daffodilDB://<server>[:<port>]/<databaseName> Embedded—jdbc:daffodilDB_embedded:<databaseName>	Default Port 3456 N/A
	JDBC Class in.co.daffodil.db.rmi.RmiDaffodilDBDriver in.co.daffodil.db.jdbc.DaffodilDBDriver	JDBC JAR File Name DaffodilDB_client.jar DaffodilDB_Embedded.jar,

Vendor Name	Details	
		DaffodilDB_Common.jar
	Comments Open source database	

DB2 AS/400

Vendor Name	Details	
Recommended Native Driver		
IBM	Company URL http://www.ibm.com	
	Driver URL http://www-03.ibm.com/systems/i/software/toolbox/	
	JDBC URL Syntax by Type Server—jdbc:as400://<server>naming=sql;errors=full	Default Port N/A
	JDBC Class com.ibm.as400.access.AS400JDBCDriver	JDBC JAR File Name jdbc400.jar
	Shipped with Pentaho Products Pentaho Data Integration	

DB2 Universal Database

Vendor Name	Details
Recommended Native Driver	
IBM	Company URL

Vendor Name	Details	
	http://www.ibm.com	
	Driver URL http://www-306.ibm.com/software/data/db2/java	
	JDBC URL Syntax by Type Server—jdbc:db2://<server>[:<port>] <databaseName>[:<URL attribute>=<value>]	Default Port 50000
	JDBC Class com.frontbase.jdbc.FBJDriver	JDBC JAR File Name frontbasejdbc.jar

Firebird

Vendor Name	Details	
Recommended Native Driver		
Firebird Foundation	Company URL http://www.firebirdsql.org	
	Driver URL http://www.firebirdsql.org/en/jdbc-driver/	
	JDBC URL Syntax by Type Server—jdbc:firebirdsql:<server>[/<port>]:/<database-file> (JDBC Type 4, official format) Server—jdbc:firebirdsql://<server>[:<port>]/<database-file> (JDBC Type 4, compatibility format)	Default Port 3050 3050 3050 3050 N/A

Vendor Name	Details	
	<p>Server—jdbc:firebirdsql:native://<server>[/<port>]:/<database-file></p> <p>(JDBC Type 2, compatibility format)</p> <p>Server—jdbc:firebirdsql:native://<server>[:<port>]/<database-file></p> <p>JDBC Type 2, compatibility format. Requires libraries)</p> <p>Embedded—jdbc:firebirdsql:embedded:/<local-database-file></p> <p>(JDBC Type 2, compatibility format. Requires libraries)</p>	
	<p>JDBC Class</p> <p>org.firebirdsql.jdbc.FBDriver</p>	<p>JDBC JAR File Name</p> <p>jaybird-full-xxx.jar</p>
	<p>Shipped with Pentaho Products</p> <p>Pentaho Data Integration</p>	

FrontBase

Vendor Name	Details	
Recommended Native Driver		
FrontBase	Company URL http://www.frontbase.com	
	Driver URL http://www.frontbase.com/cgi-bin/WebObjects/FBWebSite	
	JDBC URL Syntax by Type Server—	Default Port

Vendor Name	Details	
	jdbc:FrontBase://<host>[:<port>]/<databaseName>	N/A
	JDBC Class com.frontbase.jdbc.FBDriver	JDBC JAR File Name frontbasejdbc.jar

Greenplum

Vendor Name	Details	
Recommended Native Driver		
Greenplum	Company URL http://www.greenplum.com	
	Driver URL http://jdbc.postgresql.org/download.html	
	JDBC URL Syntax by Type Server—jdbc:postgresql://<server>[:<port>]/<databaseName>	Default Port 5342
	JDBC Class org.postgresql.Driver	JDBC JAR File Name postgresql-8.x-xxx.jdbc4.jar
	Comments Greenplum uses the Postgresql JDBC driver	

H2 Database

Vendor Name	Details
Recommended Native Driver	

Vendor Name	Details	
H2	Company URL http://www.h2database.com	
	Driver URL http://www.h2database.com	
	JDBC URL Syntax by Type Server—jdbc:h2: tcp://server [:port]/file-path Embedded—jdbc:h2:file-name	Default Port 9092 N/A
	JDBC Class jdbc:h2: tcp://server [:port]/file-path org.h2.Driver	JDBC JAR File Name h2-x.x.xxx.jar
	Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Business Analysis Server • Pentaho Data Integration • Pentaho Metadata-Editor Pentaho Report-Designer	
	Comments Open source Java SQL database	

Hive

Vendor Name	Details
Recommended Native Driver	
Apache	Company URL

Vendor Name	Details	
	http://hive.apache.org/	
	Driver URL Built in	
	JDBC URL Syntax by Type Server—jdbc:hive://<server>[:<port>] default	Default Port 10000
	JDBC Class org.apache.hadoop.hive.jdbc. HiveDriver	JDBC JAR File Name pentaho-hadoop-hive-jdbc-shim- x.x.x.jar
	Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Business Analysis Server • Pentaho Data Integration • Pentaho Metadata-Editor • Pentaho Report-Designer 	
	Comments The pentaho-hadoop-hive-jdbc-shim-xxx.jar library is a proxy driver. The actual Hive JDBC implementation for the specific distribution and version of Hadoop is located in the Pentaho Configuration (shim) for that distro. See Hadoop Configuraiton for more information. Hive does not support the full SQL capabilities. It uses a subset and is more accurately referred to as HiveQL.	

Hive2

Vendor Name	Details
Recommended Native Driver	
Apache	Company URL

Vendor Name	Details	
	http://hive.apache.org/	
	Driver URL Built in	
	JDBC URL Syntax by Type Server—jdbc:hive2://<server>[:<port>]0000<db>	Default Port
	JDBC Class org.apache.hive.jdbc. HiveDriver	JDBC JAR File Name pentaho-hadoop-hive-jdbc-shim-x.x.x.jar
	Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Business Analysis Server • Pentaho Data Integration • Pentaho Metadata-Editor • Pentaho Report-Designer 	
	Comments The pentaho-hadoop-hive-jdbc-shim-xxx.jar library is a proxy driver. The actual Hive JDBC implementation for the specific distribution and version of Hadoop is located in the Pentaho Configuration (shim) for that distro. See Hadoop Configuraiton for more information. Hive2 does not support the full SQL capabilities. It uses a subset and is more accurately referred to as HiveQL.	

HSQLDB

Vendor Name	Details
Recommended Native Driver	
HyperSQL	Company URL

Vendor Name	Details	
	http://www.hsqldb.org	
	Driver URL http://sourceforge.net/projects/hsqldb/	
	JDBC URL Syntax by Type Server—jdbc:hsqldb:hsqldb://<server>[:<port>]/<databaseName> Embedded Memory—jdbc:hsqldb:mem:<databaseName> Embedded File —jdbc:hsqldb:file:<database-file>	Default Port 9001 N/A N/A
	JDBC Class org.hsqldb.jdbcDriver	JDBC JAR File Name hsqldb.jar
	Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Enterprise-Console • Pentaho Business Analysis Server • Pentaho Aggregation-Designer • Pentaho Data Integration • Pentaho Metadata-Editor • Pentaho Report-Designer 	

Impala

Vendor Name	Details
Recommended Native Driver	
Cloudera	Company URL http://cloudera.com
	Driver URL Built in

Vendor Name	Details	
	JDBC URL Syntax by Type jdbc:hive2://<server>[<port>]/ ;auth=noSasl	Default Port 21050
	JDBC Class org.apache.hadoop.hive.jdbc. HiveDriver	JDBC JAR File Name pentaho-hadoop-hive-jdbc-shim- x.x.x.jar
	Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Business Analysis Server • Pentaho Data Integration • Pentaho Metadata-Editor • Pentaho Report-Designer 	
	Comments <p>The pentaho-hadoop-hive-jdbc-shim-xxx.jar library is a proxy driver. The actual Hive JDBC implementation for the specific distribution and version of Hadoop is located in the Pentaho Configuration (shim) for that distro. See Hadoop Configuraiton for more information.</p> <p>Hive does not support the full SQL capabilities. It uses a subset and is more accurately referred to as HiveQL.</p>	

Informix

Vendor Name	Details
Recommended Native Driver	
IBM	Company URL http://www.ibm.com
	Driver URL

Vendor Name	Details	
	http://www14.software.ibm.com/webapp/download/search.jsp?go=y&rs=ifxjdbc	
	JDBC URL Syntax by Type Server—jdbc:informix-sqli://<server>[:<port>]/<databaseName>:informixserver=<dbservername>	Default Port 1533
	JDBC Class com.informix.jdbc.IfxDriver	JDBC JAR File Name ifxjdbc.jar
	Shipped with Pentaho Products Pentaho Data Integration	

Ingres

Vendor Name	Details	
Recommended Native Driver		
Actian	Company URL http://www.actian.com/	
	Driver URL http://esd.actian.com/product/drivers/JDBC/java	
	JDBC URL Syntax by Type Server—jdbc:ingres://<server>[:<port>]/<databaseName>	Default Port 21071
	JDBC Class com.ingres.jdbc.IngresDriver	JDBC JAR File Name iijdbc.jar
	Comments	

Vendor Name	Details
	Open source relational database management system

InterBase

Vendor Name	Details	
Recommended Native Driver		
Embarcadero	Company URL http://edn.embarcadero.com	
	Driver URL N/A	
	JDBC URL Syntax by Type Server—jdbc:interbase://<server>/<full_db_path>	Default Port N/A
	JDBC Class interbase.interclient.Driver	JDBC JAR File Name interclient.jar
	Shipped with Pentaho Products Pentaho Data Integration	

jTDS Free MS SQL Sybase

Vendor Name	Details
Recommended Native Driver	
jTDS	Company URL http://jtds.sourceforge.net/
	Driver URL

Vendor Name	Details	
	N/A	
	JDBC URL Syntax by Type	Default Port
	SQL Server—jdbc:jtds:<server_type>//<server>[:<port>][/ <database>][;<property>=<value>[:...]]	1433
	Sybase—jdbc:jtds:<server_type>//<server>[:<port>][/ <database>]	7100
	JDBC Class interbase.interclient.Driver	JDBC JAR File Name jtds-x.x.x.jar
Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Enterprise-Console • Pentaho Business Analysis Server • Pentaho Aggregation-Designer • Pentaho Data Integration • Pentaho Metadata-Editor • Pentaho Report-Designer 		

LucidDB

Vendor Name	Details	
Recommended Native Driver		
DynamoDB	Company URL http://www.luciddb.com	
	Driver URL http://sourceforge.net/projects/luciddb/	
	JDBC URL Syntax by Type Server—jdbc:luciddb:http://<server>[:<port>]	Default Port 8034

Vendor Name	Details	
	JDBC Class org.luciddb.jdbc.LucidDbClientDriver	JDBC JAR File Name LucidDbClient-x.x.x.jar
	Shipped with Pentaho Products Pentaho Data Integration	
	Comments Open source BI solution for Big Data	

MaxDB

Vendor Name	Details	
Recommended Native Driver		
SAP	Company URL http://www.sap.com	
	Driver URL http://maxdb.sap.com	
	JDBC URL Syntax by Type Server—jdbc:sapdb://<server>[:<port>]@<databaseName>	Default Port 3710
	JDBC Class com.sap.dbtech.jdbc.DriverSapDB	JDBC JAR File Name sapdbc.jar
	Comments Database management system developed and supported by SAP AG	

Mckoi SQL Database

Vendor Name	Details	
Recommended Native Driver		
Mckoi	Company URL http://www.mckoi.com	
	Driver URL http://www.mckoi.com/originalmckoisql/index.html	
	JDBC URL Syntax by Type Server—jdbc:mckoi://<server>[:<port>][/<schema>]/	Default Port 9157
	JDBC Class com.mckoi.JDBCDriver	JDBC JAR File Name mckoidb.jar
	Comments Open source SQL database written in Java	

Mimer

Vendor Name	Details	
Recommended Native Driver		
Mimer Information Technology	Company URL http://www.mimer.com	
	Driver URL N/A	
	JDBC URL Syntax by Type Server—jdbc:mimer:<protocol>://<server>[:<port>]/<database>	Default Port 1260

Vendor Name	Details	
	JDBC Class com.mimer.jdbc.Driver	JDBC JAR File Name mimer.jar

MonetDB

Vendor Name	Details	
Recommended Native Driver		
MonetDB	Company URL http://www.monetdb.org	
	Driver URL N/A	
	JDBC URL Syntax by Type Server—jdbc:monetdb://<server>[:<port>]<database>	Default Port 50000
	JDBC Class nl.cwi.monetdb.jdbc.MonetDriver	JDBC JAR File Name monetdb-jdbc-x.x.jar
	Shipped with Pentaho Products Pentaho Data Integration	
	Comments An open source database system	

MY SQL

Vendor Name	Details
Recommended Native Driver	

Vendor Name	Details	
Oracle	Company URL http://www.mysql.com	
	Driver URL http://dev.mysql.com/downloads/connector/j/	
	JDBC URL Syntax by Type Server—jdbc:mysql://<hostname>[,<failoverhost>][:<port>] /<dbname>[?<URL attribute>=<value>[&<URL attribute>=<value>] ...]	Default Port 3306
	JDBC Class com.mysql.jdbc.Driver (official class name) org.gjt.mm.mysql.Driver (older class name)	JDBC JAR File Name mysql-connector-java-5.x.xx- bin.jar
	Shipped with Pentaho Product <ul style="list-style-type: none"> • Pentaho Enterprise-Console • Pentaho Business Analysis Server • Pentaho Aggregation-Designer • Pentaho Metadata-Editor • Pentaho Report-Designer 	

Neoview

Vendor Name	Details
Recommended Native Driver	
HP	Company URL

Vendor Name	Details	
	http://www.hp.com	
	Driver URL https://h20392.www2.hp.com/portal/swdepot/displayProductInfo.do?productNumber=NEO10	
	JDBC URL Syntax by Type Server—jdbc:hpt4jdbc://<system>[:<port>][:][<URL attribute>=<value>[:<URL attribute>=<value>...]]	Default Port 18650
	JDBC Class com.hp.t4jdbc.HPT4Driver	JDBC JAR File Name N/A

Netezza

Vendor Name	Details	
Recommended Native Driver		
IBM	Company URL http://www.netezza.com	
	Driver URL N/A	
	JDBC URL Syntax by Type jdbc:netezza://<server>[:<port>]/<database>	Default Port 5480
	JDBC Class org.netezza.Driver	JDBC JAR File Name N/A

OpenBase SQL

Vendor Name	Details	
Recommended Native Driver		
OpenBase International	Company URL http://www.openbase.com	
	Driver URL http://www.openbase.com/index.php/products/downloads	
	JDBC URL Syntax by Type Server—jdbc:openbase://<server>/<databaseName>	Default Port N/A
	JDBC Class com.openbase.jdbc.ObDriver	JDBC JAR File Name OpenBaseJDBC.jar

Oracle

Vendor Name	Details	
Recommended Native Driver		
Oracle	Company URL http://www.oracle.com	
	Driver URL http://www.oracle.com/technetwork/database/features/jdbc/index.html	
	JDBC URL Syntax by Type Thin Server—jdbc:oracle:thin:@<server>[:<port>]:<sid>	Default Port 1521

Vendor Name	Details	
	OCI Server —jdbc:oracle:oci:@<server>[:<port>]:<sid>	
	JDBC Class oracle.jdbc.driver.OracleDriver oracle.jdbc.OracleDriver	JDBC JAR File Name ojdbcx.jar, ora18n.jar
	Comments The OCI server requires OCI libraries	

Pervasive

Vendor Name	Details	
Recommended Native Driver		
Pervasive	Company URL http://www.pervasivedb.com/Pages/default.aspx	
	Driver URL http://www.pervasivedb.com/download/Pages/PDBDownloads.aspx	
	JDBC URL Syntax by Type Server—jdbc:pervasive://<server>[:<port>]/<datasource>	Default Port 1583
	JDBC Class com.pervasive.jdbc.v2.Driver	JDBC JAR File Name N/A
	Shipped with Pentaho Products <ul style="list-style-type: none">• Pentaho Data Integration• Pentaho Report-Designer	

Vendor Name	Details
	Comments The data source is the ODBC DSN

PostgreSQL

Vendor Name	Details
Recommended Native Driver	
PostgreSQL Global Development Group	Company URL http://www.postgresql.org/
	Driver URL http://jdbc.postgresql.org/
	JDBC URL Syntax by Type Server—jdbc:postgresql://<server>[:<port>]/<databaseName>
	Default Port 5342
	JDBC Class org.postgresql.Driver
	JDBC JAR File Name postgresql-8.x-xxx.jdbc4.jar
	Shipped with Pentaho Products <ul style="list-style-type: none"> • Pentaho Data Integration • Pentaho Report-Designer

SAP DB

Vendor Name	Details
Recommended Native Driver	
SAP DB	Company URL N/A

Vendor Name	Details	
	Driver URL http://www.sapdb.org/sap_db_jdbc.htm	
	JDBC URL Syntax by Type Server—jdbc:sapdb://<server>/<database_name>	Default Port N/A
	JDBC Class com.sap.dbtech.jdbc.DriverSapDB	JDBC JAR File Name sapdbc-x.x.x.jar
	Shipped with Pentaho Products Pentaho Data Integration	
	Comments FREE Enterprise Open Source Database	

SQLite

Vendor Name	Details	
Recommended Native Driver		
Xerial	Company URL N/A	
	Driver URL http://www.xerial.org/trac/Xerial/wiki/SQLiteJDBC	
	JDBC URL Syntax by Type Server—jdbc:sqlite:<filename.db>	Default Port N/A
	JDBC Class org.sqlite.JDBC	JDBC JAR File Name sqlite-jdbc-x.x.x.jar

Vendor Name	Details
	Shipped with Pentaho Products Pentaho Data Integration

SQL Server

Vendor Name	Details	
Recommended Native Driver		
Microsoft	Company URL http://www.microsoft.com	
	Driver URL http://msdn.microsoft.com/en-us/sqlserver/aa937724.aspx	
	JDBC URL Syntax by Type Server—jdbc:sqlserver://<server>[:<port>];DatabaseName=<databaseName>	Default Port 1433
	JDBC Class com.microsoft.sqlserver.jdbc. SQLServerDriver	JDBC JAR File Name sqljdbc4.jar
	Comments The open source jtds driver also works with MSSQL	

Sybase ASE

Vendor Name	Details
Recommended Native Driver	
SAP	Company URL

Vendor Name	Details	
	http://www.sybase.com	
	Driver URL http://www.sybase.com/products/allproductsa-z/softwaredeveloperkit/jconnect	
	JDBC URL Syntax by Type Server—jdbc:sybase:Tds:<server>[:<port>]/<databaseName>	Default Port 5000
	JDBC Class com.sybase.jdbc4.jdbc.SybDriver	JDBC JAR File Name N/A
	Comments The open source jTDS driver works with Sybase as well. Note that although you can use jTDS open source JDBC driver, we recommend that you use the Sybase-supplied JDBC driver instead. Connections might not work reliably if you use the jTDS JDBC driver.	

Sybase SQL Anywhere

Vendor Name	Details	
Recommended Native Driver		
SAP	Company URL http://www.sybase.com	
	Driver URL http://www.sybase.com/products/allproductsa-z/softwaredeveloperkit/jconnect	
	JDBC URL Syntax by Type	Default Port 2638

Vendor Name	Details	
	Server—jdbc:sybase:Tds:<server>[:<port>]/<databaseName>	
	JDBC Class com.sybase.jdbc4.jdbc.SybDriver	JDBC JAR File Name N/A
	Comments This open source jTDS driver works with Sybase as well. Note that although you can use jTDS open source JDBC driver, we recommend that you use the Sybase-supplied JDBC driver instead. Connections might not work reliably if you use the jTDS JDBC driver.	

SmallSQL

Vendor Name	Details	
Recommended Native Driver		
SmallSQL	Company URL http://www.smallsql.de/	
	Driver URL http://www.smallsql.de/download.html	
	JDBC URL Syntax by Type Embedded—jdbc:smallsql:databaseName[?URL attribute=value[URLattribute=value]...]	Default Port N/A
	JDBC Class smallsql.database.SSDriver	JDBC JAR File Name smallsql.jar
	Comments Java desktop SQL database engine	

Vendor Name	Details

Teradata

Vendor Name	Details	
Please see the Teradata JDBC Driver Reference for information about required drivers.		
Teradata	Company URL http://www.teradata.com	
	Driver URL http://downloads.teradata.com/download/connectivity/jdbc-driver	
	JDBC URL Syntax by Type Server—jdbc:teradata://<dbshost>[/<URL attribute>[:<URL attribute>]...]	Default Port N/A
	JDBC Class com.teradata.jdbc.TeraDriver	JDBC JAR File Name terajdbc4.jar tdgssconfig.jar

Vertica

Vendor Name	Details
Recommended Native Driver	
HP	Company URL http://www.vertica.com
	Driver URL

Vendor Name	Details	
	TBD	
	JDBC URL Syntax by Type Server—jdbc:vertica://<server>[:<port>] <databaseName>	Default Port 5433
	JDBC Class com.vertica.Driver	JDBC JAR File Name N/A