

# Write a docker-compose.yml file to define a multi-container application

---

## Table of Contents

---

- [Description](#)
- [Problem Statement](#)
- [Prerequisites](#)
  - [Software Requirement](#)
  - [Hardware Requirement](#)
- [Implementation Steps](#)
  - [Step-1 :: Create Standard Folder Structure](#)
  - [Step-2 :: Create docker-compose.yml](#)
- [References](#)

## Description

---

This guide demonstrates how to use Docker Compose to define a multi-container application. We'll set up two containers: one for a Java-based TodoApp and another for a MySQL database. Using Docker Compose simplifies managing multiple containers and their communication.

## Problem Statement

---

You need to run a Java-based TodoApp that requires a MySQL database. Instead of manually configuring and linking containers, you want to automate this process using a **docker-compose.yml** file.

## Prerequisites

---

Completion of all previous lab guides (up to Lab Guide-05) is required before proceeding with Lab Guide-06.

## Software Required

- **Docker Desktop:** Ensure Docker and Docker Compose are installed on your Windows machine.
- **Java SDK:** If you're working with Java.
- **Maven/Gradle:** For building your Java app.
- **MySQL Database:** To store todo application data.
- **TodoAPP\_MYSQL:** To download the source folder [click here](#)

## Hardware Requirement

- Minimum of 4 GB RAM
- At least 2 cores in the processor
- 5 GB of free storage space for Docker images and containers

# Implementation Steps

---

## Step-1 :: Create Standard Folder Structure

1. Create a project folder:

```
todoapp-docker
├── docker-compose.yml
├── todoapp/
│   ├── Dockerfile
│   ├── src/
│   └── target/
└── db/
```

2. **Dockerfile** for your Java-based TodoApp:

Inside the `app/` directory, create a **Dockerfile** to build the Java TodoApp.

```
FROM openjdk:11.0.15-jre
ADD target/*.jar app.jar
ENTRYPOINT ["java", "-jar", "app.jar"]
```

## Step-2 :: Create docker-compose.yml

In the root directory of your project, create a **docker-compose.yml** file:

```
services:
  # MySQL Database Service
  db:
    image: mysql
    container_name: mysql_db
    environment:
      MYSQL_ROOT_PASSWORD: P@ssw0rd
      MYSQL_DATABASE: tododb
      MYSQL_PASSWORD: P@ssw0rd
    ports:
      - "3306:3306"
    networks:
      - todoapp_network
    volumes:
      - db_data:/var/lib/mysql

  # Java TodoApp Service
  todoapp:
    build:
      context: ./todoapp
```

```

    container_name: todoapp_container
    ports:
      - "8081:8081"
    depends_on:
      - db
    environment:
      SPRING_DATASOURCE_URL: jdbc:mysql://db:3306/tododb
      SPRING_DATASOURCE_USERNAME: root
      SPRING_DATASOURCE_PASSWORD: P@ssw0rd
    networks:
      - todoapp_network
    entrypoint: sh -c "sleep 30 && java -jar /app.jar"
  networks:
    todoapp_network:
      driver: bridge

volumes:
  db_data:

```

- **Services Section:** This section defines the different containers (services) that will be run as part of the Docker Compose setup.
- **image: mysql:** This specifies the Docker image to use. In this case, it uses the official MySQL image from Docker Hub.
- **container\_name: mysql\_db:** This gives the container a specific name (**mysql\_db**).
- **depends\_on:** Ensures that the **todoapp** service starts after the **db** service (MySQL) is up and running. However, this does not wait for the database to be fully initialized.
- **environment:** Defines the environment variables to configure MySQL:
  - **MYSQL\_ROOT\_PASSWORD:** Sets the root user password (**P@ssw0rd**).
  - **MYSQL\_DATABASE:** Creates a database named **tododb**.
  - **MYSQL\_PASSWORD:** Sets the password for the default MySQL user (root).
  - **SPRING\_DATASOURCE\_URL:** Defines the JDBC connection URL to the MySQL database (**db** is the hostname for the database within the Docker network).
  - **SPRING\_DATASOURCE\_USERNAME:** Sets the username to connect to the MySQL database (**root**).
  - **SPRING\_DATASOURCE\_PASSWORD:** Defines the password to connect to the MySQL database.
- **ports:** Exposes port **3306** (MySQL's default port) on the host system, allowing external connections to the MySQL database.
  - **"3306:3306":** The format is **host\_port:container\_port**.
- **entrypoint: sh -c "sleep 30 && java -jar /app.jar":** This introduces a delay of 30 seconds before starting the application, allowing MySQL to be ready.
- **networks:** Adds this service to the custom network **todoapp\_network** so that the other services can communicate with it.

- **volumes:** Uses a Docker volume (**db\_data**) to persist the database data so that it won't be lost when the container is restarted. The database files are stored in **/var/lib/mysql** inside the container.

## References

---

1. Docker documentation: <https://docs.docker.com/>
2. MySQL container setup: [https://hub.docker.com/\\_/mysql](https://hub.docker.com/_/mysql)
3. Spring Boot with MySQL example: [Spring Boot MySQL](#)