Use Docker commands to build, tag, and push Docker images to a registry

Table of Contents

- Description
- Problem Statement
- Prerequisites
 - Software Requirement
 - Hardware Requirement
- Implementation Steps
 - Step-1: Build the Docker Image
 - Step-2: Tag the Docker Image
 - Step-3: Push the Docker Image to a Registry
- References

Description

This guide explains how to build, tag, and push Docker images for your **TodoApp** using Docker commands. After creating a Dockerfile for the web application, you'll need to build the image, assign a tag, and push it to a remote registry (such as Docker Hub or a private registry).

Problem Statement

To deploy your **TodoApp** in different environments or share it with others, you must publish the Docker image to a registry. This requires:

- Building a Docker image from the application code.
- Tagging the image with a unique identifier (such as a version number).
- Pushing the image to a Docker registry for distribution.

Prerequisites

Completion of all previous lab guides (up to Lab Guide-01) is required before proceeding with Lab Guide-02.

Software Requirement

- **Docker Desktop**: Installed on your Windows machine.
- **Docker Hub Account** (or any other Docker-compatible registry).
- TodoAPP_MYSQI: To download the source folder click here

Hardware Requirement

• Minimum of 4 GB RAM.

• At least 2 cores in the processor.

Implementation Steps

Step-1: Build the Docker Image

1. **Create a Dockerfile** for your TodoApp (if not done already). Here is an example Dockerfile for a simple Java-based web application:

```
FROM openjdk:11.0.15-jre

ADD target/*.jar app.jar

ENTRYPOINT ["java","-jar","app.jar"]
```

2. Build the Docker image:

```
docker build -t todoapp .
```

In this example:

- todoapp:latest is the tag you are assigning to the image. The latest tag indicates that this is the most current version.
- The . specifies that Docker should look for the Dockerfile in the current directory.

3. Verify that the image was built successfully:

```
docker images
```

This command will list all available Docker images. You should see todoapp in the list.

```
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>docker images
REPOSITORY \ TAG IMAGE ID CREATED SIZE
todoapp latest 24fc48428bd3 29 hours ago 557MB
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>_
```

Step-2: Tag the Docker Image

Next, assign a tag to the image so that it can be pushed to a registry. Tags generally include the registry URL, the repository name, and a version number.

```
docker tag todoapp:latest <your-dockerhub-username>/todoapp:v1.0
```

In this example:

- <your-dockerhub-username> is your Docker Hub username.
- todoapp:v1.0 assigns a version (v1.0) to the image.

Now, when you list images using docker images, you should see the newly tagged image.

```
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>docker tag todoapp sooryav/todoapp:v1.0
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>_
```

```
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>docker images
REPOSITORY TAG IMAGE ID CREATED SIZE
sooryav/todoapp v1.0 24fc48428bd3 29 hours ago 557MB
todoapp latest 24fc48428bd3 29 hours ago 557MB

C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>_
```

Step-3: Push the Docker Image to a Registry

To make the image accessible to others, push it to a Docker registry. For this example, we will use Docker Hub, but you can push to any compatible registry.

1. Login to Docker Hub:

```
docker login
```

```
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>docker login

USING WEB BASED LOGIN

To sign in with credentials on the command line, use 'docker login -u <username>'


Your one-time device confirmation code is: BNNF-RZFB

Press ENTER to open your browser or submit your device code here: <a href="https://login.docker.com/activate">https://login.docker.com/activate</a>


Waiting for authentication in the browser...

-
```

• Copy the device confirmation code and submit the device code here: https://login.docker.com/activate



• You'll be prompted to enter your Docker Hub username and password.



• Once the device is connected, you should should an output like this:



Congratulations, you're all set!

Your device is now connected.

```
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>docker login

USING WEB BASED LOGIN

To sign in with credentials on the command line, use 'docker login -u <username>'

Your one-time device confirmation code is: PZMV-DWFD

Press ENTER to open your browser or submit your device code here: <a href="https://login.docker.com/activate">https://login.docker.com/activate</a>

Waiting for authentication in the browser...

Login Succeeded
```

2. **Push the tagged image** to Docker Hub:


docker push <your-dockerhub-username>/todoapp:v1.0

Docker will upload the image to your Docker Hub repository.

```
C:\Users\Administrator\Documents\TodoApp_MySQL-main\todoapp>docker push sooryav/todoapp:v1.0
The push refers to repository [docker.io/sooryav/todoapp]
d1989b6e74cf: Pushed
19babefbed06: Pushed
529e95713a10: Pushed
72f9b148e5a2: Pushed
66a9e63c657a: Pushed
66a9e63c657a: Pushed
d836772a1c1f: Pushed
09bd66433199: Pushed
cc8fcf8b61a2: Pushed
v1.0: digest: sha256:24fc48428bd35ce6595a2f597daf2c05730ee5c8cdc42052fd2d3dd0ba4b8e7e size: 856
C:\User\s\s\Administrator\Documents\TodoApp_MySQL-main\todoapp>__
```

3. Verify the image:

Once the push is complete, visit Docker Hub and verify that your image is available in your repository.



References

- Docker Hub Documentation: https://docs.docker.com/docker-hub/
- Docker Build and Push: https://docs.docker.com/engine/reference/commandline/push/
- Tagging Docker Images: https://docs.docker.com/engine/reference/commandline/tag/