

How-To Guide: DT Import (DIF) Doc for EAM Work Center

Applies to

MDG EAM Solutions by Utopia

Summary

MDG for EAM include standard implementations of the Data Import Framework (DIF) that read the data from file which captured from other system. The data in the file can be saved to “Active Area” directly or “Staging Area” based on the options chosen in the Import Framework screen. The standard implementations support Key Mapping and value mapping.

This guide describes the necessary configuration steps for implementing DIF. This guide explains the Data Import Framework for Work Center. Same steps can be followed for other EAM objects.

You can perform most configuration tasks in Customizing for Master Data Governance under SAP Reference IMG -> Cross Application Components -> Processes and Tools for Enterprise Applications -> Master Data Governance.

Additionally, you can use the following transactions:

- MDGIMG: IMG Master Data Governance
- FILE : Logical File Path Definition
- IDMIMG : IMG Key Mapping

Author: Pradeep Haridas

Company: Prometheus Group

Created On: September 05, 2018

Version: 1.0

Table of Contents

Introduction.....	3
Steps for ALE Scenario Configuration	3
Define Logical Systems	3
Define a RFC Connection.....	3
Define an XML Port	4
Define Partner Profiles	5
Define Object Types.....	5
File Source and Archive directories	7
Defining Source and Logical Directories.....	8
Define the Technical Settings for Business Systems	10
Test Scenario for DIF	11
Data Import.....	12

Introduction

Data transfer represents a collection of functions and features that you can use to move master data and mapping information between systems and clients. Examples of these systems include existing ERP systems and your Master Data Governance hub system.

Steps for ALE Scenario Configuration


Note: The following configuration is required only when you want to generate XML file from IDOC.

This guide uses the system S17 and its client 100 as sample data. When you configure this scenario for your landscape, ensure you replace system ID and client ID with your own system data.

Define Logical Systems

Use the following to define a logical system:

1. Enter transaction code (t-code) BD54.
2. Click New entries to create a Logical System.
3. Enter a name for the Logical System and a description.
The Logical System names used throughout this example is MDG System S17 CLNT 100 as the source and S17 CLNT 200 as the target.



The screenshot shows the SAP 'Display View "Logical Systems": Overview'. It features a table with two columns: 'Log.System' and 'Name'. The table lists four logical systems: FS4CLNT100 (CLIENT 100 FS4), M9LCLNT100 (M9LCLNT100), S17CLNT100 (S17 100), and S17CLNT200 (S17 200). The last two rows are highlighted in yellow. A red box highlights the first two rows.


Log.System	Name
FS4CLNT100	CLIENT 100 FS4
M9LCLNT100	M9LCLNT100
S17CLNT100	S17 100
S17CLNT200	S17 200


Define a RFC Connection

Use the following steps to define the RFC connection:

1. Run the t-code SALE. Navigate to tree menu Communication -> Create RFC Connections or Run the transaction SM59 to create an RFC Connection.
2. Create a RFC connection using Connection Type T (Start External Program Using TCP/IP) into the same client:

RFC Destination LOCAL_EXEC

Connection Test Unicode Test 

RFC Destination 

Connection Type TCP/IP Connection Description

Description

Description 1

Description 2

Description 3

Administration **Technical Settings** Logon & Security Unicode Special Options

Activation Type

☒ Start on Application Server ☐ Registered Server Program

☐ Start on Explicit Host

☐ Start on Front-End Work Station

Start on Application Server

Program

Start Type of External Program

☒ Default Gateway Value

☐ Remote Execution

☐ Remote Shell

☐ Secure Shell

Define an XML Port

Use the following steps to define an XML Port:

1. Run the t-code WE21 > Create an XML File type port and enter the name of the port and relevant description. For example, WC_XML.
2. Enter the name of the Directory created using t-code AL11 and enter the Function module as displayed in the following screen.

Port


Description

XML format

☐ SAP Release 46

☒ Unicode

Outbound file **Outbound: Trigger**

☐ Logical directory 

☒ physical directory

Directory

Function module

Description

Outbound file

Define Partner Profiles

Run the t-code WE20 > Locate the MDG Client S17CLNT100 under tree node Partner Profile LS > Maintain the settings for message type /UGI3/WRKCNTN under outbound parameters.

Partner profiles: Outbound parameters

Partner No. S17 200
 Partn. Type Logical system
 Partner Role

Message Type UGI workcenter IDOC for MDG MSG...
 Message code
 Message function ☐ Test

Outbound Options | Message Control | Post Processing: Permitted Agent | Tel...

Receiver port Transactional RFC S17 200
 Pack. Size
☐ Queue Processing



Output Mode
☒ Pass IDoc Immediately Output Mode 2
☐ Collect IDocs

IDoc Type
 Basic type Workcenter multilanguage te...
 Extension
 View
☒ Cancel Processing After Syntax Error
 Seg. release in IDoc type Segment Appl. Rel.

Define Object Types


Go to MDGIMG > Master Data Governance > General Settings > Data Transfer > Select Node

“Define Object Types for Data Transfer”.




Use the following steps to set the Data Import Framework.


1. Click on sub-node "Detailed information for Object Types"
2. Enter the message types to be recognized in the file while importing the data.



3. Click on the sub-node "Maintain Business Activity". This refers to the CR type to be created while importing the data to staging area.



- Maintain Object List for Data Import.




File Source and Archive directories

To set up the data import, source and archive logical directories in the MDG Data Transfer Customizing activity needs to be defined.

The logical file name and the logical path should be maintained to get an appropriate physical file name and physical path name.

Use the following steps to define file source and archive directories:

- Define a Logical Path Name: First determine the target directory in which you want to create the archive files of a certain archiving object. The physical name of this directory is stored in a logical path name.
- Define a Logical File Name: After creating the logical path name, you need to create a logical file name.
- Assign a Logical File Name to the archiving Object.
Note: Contact BASIS for directory paths creation.
- To assign directories as sources or archives, the physical directory paths must be created in the file system initially.
- Use the t-code SFILE to map them to logical names.
Run the t-code AL11 to verify the directory path creation:



- Run the t-code FILE to map directory path to logical names:

Change View "Logical File Path Definition": Overview

New entries Select all Select Configuration

Dialog Structure

- Logical File Path Definition
 - Assignment of Physical Path
 - Logical File Name Definition
 - Definition of Variables
 - Syntax Group Definition

Create a logical file path

Logical File Path	Name
ZDIR_WCDIF	File Path for Work Center

7. Assign physical path for ZDIR_WCDIF.

New Entries: Details of Added Entries


Dialog Structure

- Logical File Path Definition
 - Assignment of Physical Path
 - Logical File Name Definition
 - Definition of Variables
 - Syntax Group Definition
 - Assignment of Operating System

Logical path	ZDIR_WCDIF
Name	File Path for Work Center
Syntax group	WINDOWS NT Microsoft Windows NT
Physical path	\\ULABSHAN17\ZDIR_WCDIF\<FILENAME>

8. Assign physical path for ZDIR_WCDIF_ARCHIVE.

Change View "Assignment of Physical Paths to Logical Path": Details

New Entries 


Dialog Structure

- Logical File Path Definition
 - Assignment of Physical Path
 - Logical File Name Definition
 - Definition of Variables
 - Syntax Group Definition


Logical path	ZDIR_WCDIF_ARCHIVE
Name	FILE PATH FOR WCDIF ARCHIVE
Syntax group	WINDOWS NT Microsoft Windows NT
Physical path	\\ULABSHAN17\ZDIR_WCDIF_ARCHIVE\<FILENAME>

Defining Source and Logical Directories


Go to MDGIMG > Master data Governance > General Settings > Data Transfer > Define File Source and Archive Directories for Data Transfer.



1. Click on Data Transfer Directories > Maintain the Work Center directory which is created in t-code FILE.




2. Click on Archive Path Object Types to maintain the archiving path of files used.




Define the Technical Settings for Business Systems

Go to Master Data Governance > General Settings > Key Mapping > Define Technical Settings > Define Technical Settings for Business Systems.




Use the following steps to define technical settings for Business Systems:

1. Define the Business System.



2. Add the Work Center BO Type for the Business System:

- BO Types 493 (Work Center)



3. For Harmonized scenarios, update the communication channel settings as explained in the following section:

Change View "Define Bus. Systems, BOs, Communication Channel": Overview

New Entries

Dialog Structure

- Define Business Systems
 - Define Bus. Systems
 - Define Bus. System

Business System: S17_ULABSHAN17_S17CLNT200

Bus. Obj. Type: 493

Description: Workcenter

Define Bus. Systems, BOs, Communication Channel			
C. Channel	Key Harm.	Upd. KM	Storage
2 Replication via IDoc	1 Harmonized IDs (no Key Map)	<input checked="" type="checkbox"/>	Not Defined

Note: For Work Center there is only harmonized scenario, Key Mapping scenario is not possible.

Test Scenario for DIF

Use the following steps for Test Scenario for DIF:

1. Download the XML file in your local machine.
2. Go to t-code AL11 and get the directory name for file.

ZDIR_WCDIF	\\ULABSHAN17\ZDIR_WCDIF
------------	-------------------------

3. Open directory and get the file name to download.

Directory: ||ULABSHAN17\ZDIR_WCDIF

Usable	Viewed	Changed	Length	File Owner	Lastchange	Lastchange	File Name
					31.12.1969	19:00:00	.
					31.12.1969	19:00:00	..
				fs3adm	20.12.2016	10:51:25	ARCHIVE
				fs3adm	24.04.2017	03:39:44	SOURCE
X			4885	SAPServiceS17	06.10.2017	04:49:11	WC_DIF.xml

4. Go to t-code CG3Y to download the file. Enter the source file name and the target file name.
5. Click on Overwrite checkbox, to overwrite if file exist with same name.

Download File: Parameters

Source file on application server

\\ULABSHAN17\ZDIR_WCDIF\WC_DIF.xml

Target file on front end

C:\Users\pharidasan\Desktop\WC_DIF.xml

Transfer format for data: BIN

☒ Overwrite file

6. Click on "Download" button, file will be downloaded in the specified location.

The following steps are required to run the DIF for Work Center.

You can run the DIF for Work center in Manual Processing / Defined by Change Request / Governance modes with/without Key Mapping.


Use the following steps to test the DIF:

1. Received below IDoc XML for DIF Import from client system:



WC_New.xml

2. Upload the file.
3. Run the t-code CG3Z > Choose the upload file Parameters-Source file on front end and Target file on application server paths > Click on upload icon.




4. Check file in AL11 System.

X			5048	SAPServiceS17	03.10.2017	01:51:05	WC_DIF.xml
---	--	--	------	---------------	------------	----------	------------

Data Import

Use the following steps to import data:

1. Navigate to the Data Exchange tab > Data load > Import Master data



2. Scenario 1 – Manual Post Processing.
 - a. Enter the following details in the new Data Import screen:
 - Object type – UWCK
 - Provide mandatory description

- Choose overwrite check box if you want the object to be overwritten
- Select the Post Processing as Manual Post Processing
- Data Sources – Add the Object Type Workcenter and Source Directory ZDIR_WCDIF

Simulate Import Custom Converter Settings Display Monitoring

Import Settings

* Object Type:

* Description:

Overwrite: ☒

Custom Converter:

Governance Settings

Governance: ☐

Post Processing:

Change Request Type:

Scheduling Settings

Scheduling:

Date: Time:

Parallel Processing Settings

Parallel Processing: ☐

Queue name:

Number of Processes:

Data Sources

<input checked="" type="checkbox"/>	Object Type	Source Directory
<input checked="" type="checkbox"/>	Workcenter	ZDIR_WCDIF


b. Click on “Import” button.

✅ Data import started with run number 10000802

c. Click on “Display Monitoring” button to check the import log > Click on Run number to see details log.

Data Transfer Logs	
<input type="button" value="Replicate"/>	
	Propagated Type/Date/Time/User
<input type="radio"/>	10.10.2017 06:39:29 [REDACTED]
<input type="radio"/>	Description: TEST DIF - MANUAL POST PROCESSING
<input type="radio"/>	Object Type Processing Sequence: Workcenter
<input type="radio"/>	Processing files from directory \\ULABSHAN17\ZDIR_WCDIF\
<input type="radio"/>	Message Type _UGI3_-WRKCNTRO1 detected for file WC_DIF.xml
<input type="radio"/>	Work Center exists in active area; Work Center overwritten
<input type="radio"/>	IDoc processed successfully for Work Center ZVAS2000 Plant 0001
<input checked="" type="radio"/>	10.10.2017 06:39:29 [REDACTED]
<input type="radio"/>	Object type is Workcenter
<input type="radio"/>	Description: TEST DIF - MANUAL POST PROCESSING

d. Enter the t-code IR03 if Work Center is created.



Display Work Center: Basic Data

HR assignment Hierarchy

Plant: 0001 Werk 0001
Work center: ZVAS2000 MDG EAM Planning Plant Work Center

Basic Data | Default Values | Capacities | Scheduling | Costing | Technology

General Data

Work Center Category	0005	Plant maintenance
Person Responsible	001	SAP Beispiel: Verantwortlicher 001
Location	0001	Werk 0001 Standort 0001
QDR System	000001	CAQ subsystem 1
Supply Area		
Usage	009	All task list types
Backflush	<input type="checkbox"/>	Advanced Planning <input type="checkbox"/>

Standard Value Maintenance

Standard value key: SAP0 No standard values


Standard Values Overview

Key Word	Description

3. Scenario 2 – Defined by Change Request without governance

a. Update the following details in the new Data Import screen

- Object type – UWCK
- Enter the Description
- Select overwrite checkbox if you want the object to be overwritten
- Select the Post Processing – Defined by Change Request.
- Select the Change Request type as “WRKCTR0B”
- Data Sources – Add the Object Type Workcenter and Source Directory ZDIR_WCDIF



SAP Import Master Data and Mapping Information

Simulate Import | Custom Converter Settings | Display Monitoring

Import Settings

* Object Type: Work Center - UWCK*
* Description: TEST DIF - WC
Overwrite: ☒
Custom Converter:

Governance Settings

Governance: ☐
Post Processing: Defined by Change F
* Change Request Type: WRKCTR0B

Scheduling Settings

Scheduling: Import Now
Date: Time: 00:00:00

Parallel Processing Settings

Parallel Processing: ☐
Queue name:
Number of Processes: 0

Data Sources

+ Add - Show Directory Content

Source	Source Directory
<input checked="" type="checkbox"/> Object Type	
<input checked="" type="checkbox"/> Workcenter	ZDIR_WCDIF

b. Click on “Import” button.

✓ Data import started with run number 10000387

- c. Click on “Display Monitoring” button to check the import log > Click on Run number to see details log.

Data Transfer Logs	
Replicate	
<input type="radio"/>	Propagated Type/Date/Time/User
<input checked="" type="radio"/>	03.10.2017 06:37:18 [REDACTED]
<input type="radio"/>	Description: TEST DIF WC
<input type="radio"/>	Object Type Processing Sequence: Workcenter
<input type="radio"/>	Processing files from directory \\ULABSHAN17\ZDIR_WCDIF\
<input type="radio"/>	Message Type _-UGI3_-WRKCNT01 detected for file WC_DIF.xml
<input type="radio"/>	IDoc processed successfully for Work Center WC_TSTDI Plant 0001
<input checked="" type="radio"/>	03.10.2017 06:37:18 [REDACTED]
<input type="radio"/>	Object type is Workcenter
<input type="radio"/>	Description: TEST DIF WC
<input type="radio"/>	Data import started with run number 10000387

- d. Check in the t-code IR03 is Work Center is created.

Display Work Center: Basic Data

HR assignment Hierarchy

Plant Werk 0001
 Work center DIF Testing

Basic Data Default Values Capacities Scheduling Costing Technology

General Data

Work Center Category	0005	Plant maintenance
Person Responsible	001	SAP Beispiel: Verantwortlicher 001
Location	0001	Werk 0001 Standort 0001
QDR System	000001	CAQ subsystem 1
Supply Area	BEREICH 1	SAP area 1
Usage	004	Only maintenance task lists
Backflush	<input checked="" type="checkbox"/>	Advanced Planning <input type="checkbox"/>

Standard Value Maintenance

Standard value key Normal production

Standard Values Overview

Key Word	Rule for Maint.	K...	Description
Setup	no checking	001	SAP example
Machine	no checking	001	SAP example
Labor	no checking	001	SAP example

4. Scenario 3 - Defined by Change Request with governance.

- a. Update the following details in the new Data Import screen:
 - Object Type – UWCK
 - Provide mandatory description
 - Choose overwrite check box if you want the object to be overwritten
 - Select the Post Processing – Defined by Change Request.
 - Select Governance checkbox.
 - Choose the Change Request type “WRKCTR0B”
 - Data Sources – Add the Object Type Workcenter and source directory ZDIR_WCDIF

Simulate Import
Custom Converter Settings
Display Monitoring

Import Settings	Governance Settings
* Object Type: <input type="text" value="Work Center - UWCK"/>	Governance: <input checked="" type="checkbox"/>
* Description: <input type="text" value="TEST DIF - MANUAL F"/>	Post Processing: <input type="text" value="Defined by Change F"/>
Overwrite: <input checked="" type="checkbox"/>	* Change Request Type: <input type="text" value="WRKCTR0B"/>
Custom Converter: <input type="text"/>	
Scheduling Settings	Parallel Processing Settings
Scheduling: <input type="text" value="Import Now"/>	Parallel Processing: <input type="checkbox"/>
Date: <input type="text"/> Time: <input type="text" value="00:00:00"/>	Queue name: <input type="text"/>
	Number of Processes: <input type="text" value="0"/>

Data Sources

Add
Remove
Show Directory Content

	Object Type	Source Directory
<input checked="" type="checkbox"/>	Object Type	
<input checked="" type="checkbox"/>	Workcenter	ZDIR_WCDIF

- b. Click on “Import” button.

 Data import started with run number 10000812

- c. Click on “Display Monitoring” button to check the import log > Click on Run number to see details log.

Data Transfer Logs	
Replicate	
	Propagated Type/Date/Time/User
<input type="radio"/>	10.10.2017 06:55:46 [REDACTED]
<input type="radio"/>	Description: TEST DIF - MANUAL POST PROCESSING
<input type="radio"/>	Object Type Processing Sequence: Workcenter
<input type="radio"/>	Processing files from directory \\ULABSHAN17\ZDIR_WCDIF\
<input type="radio"/>	Message Type _UGI3_-WRKCNTRO1 detected for file WC_DIF.xml
<input type="radio"/>	Work Center exists in active area; Work Center overwritten
<input type="radio"/>	Work Center uploaded to staging area with change request 000000008021
<input type="radio"/>	10.10.2017 06:55:46 [REDACTED]
<input type="radio"/>	Object type is Workcenter
<input type="radio"/>	Description: TEST DIF - MANUAL POST PROCESSING

d. Open Change Request from Reporting tab in NWBC.

<div> <div>Home</div> <div>Process EAM Objects</div> <div>Processing of Multiple EAM Objects</div> <div>Reporting</div> <div>Display Change Requests</div> <div>Change Documents</div> <div>Process Reporting</div> <div>Data Exchange</div> <div>Process EAM Objects</div> </div>		<div>SAP</div> <div>Print Preview Refresh</div> <div>Name: [REDACTED]</div> <div>Change Requests</div> <div>Show: Created by Me From: 03.10.2017 To: [REDACTED]</div> <div>Export Workflow Log</div> <table border="1"> <thead> <tr> <th>Change Request</th><th>Description</th></tr> </thead> <tbody> <tr> <td>8021</td><td>Created Using MDG Initial Load</td></tr> </tbody> </table>		Change Request	Description	8021	Created Using MDG Initial Load
Change Request	Description						
8021	Created Using MDG Initial Load						

e. Click on Finalize Processing the Change Request.

Read Only Print Preview Check Run Validation Validation Log Related Services ▾ Side Panel

Change Request: 8021 Type: Import Work Center Status: Changes to Be Executed

Overview Changes Notes Attachments

General Data

Processing: You are the processor of the change request

* Description: Created Using MDG Initial Load

Priority: ▾

Created On: 10.10.2017 06:55:46

Changed On: 10.10.2017 06:55:47

Finalized On:

Due Date:

Reason: ▾

Created By: XXXXXXXXXX

Changed By: XXXXXXXXXX

Finalized By:

Notes / Attachments

Notes: 1 note(s) exist(s)

Attachments: 0 attachment(s) exist(s)

Objects

Entity Type	Number
<input type="text"/>	<input type="text"/>

Finalize Processing Send for Revision

f. Click on “Approve” button in the Change Request.

Read Only Print Preview Run Validation Validation Log Related Services ▾ Side Panel

Change Request: 8021 Type: Import Work Center Status: Final Check to Be Performed

Overview Changes Notes Attachments

General Data

Processing: You are the processor of the change request

* Description: Created Using MDG Initial Load

Priority: ▾

Created On: 10.10.2017 06:55:46

Changed On: 10.10.2017 06:57:37

Finalized On:

Due Date:

Reason: ▾

Created By: XXXXXXXXXX

Changed By: XXXXXXXXXX

Finalized By:

Notes / Attachments

Notes: 1 note(s) exist(s)

Attachments: 0 attachment(s) exist(s)

Objects

Entity Type	Number
<input type="text"/>	<input type="text"/>

Approve Reject

After Approval CR Status Changed to Final Check Approved.

g. Check the Work Center.

Home

- Process EAM Objects
- Processing of Multiple EAM Objects
- Reporting**
 - Display Change Requests**
 - Change Documents
- Process Reporting
- Data Exchange
- Process EAM Objects

SAP My Change Requests

Print Preview Refresh

Name: XXXXXXXXXX

Change Requests

Show: Created by Me ▾ From: 03.10.2017 To: 10.10.2017 Go View: [Standard View]

Change Request	Description	Status	Changed On
<input checked="" type="radio"/> 8021	Created Using MDG Initial Load	Final Check Approved	10.10.2017

Expand all Collapse all Assignment Block:

▼ Work Center Edit

Work Center

Plant: 0001

Work center: ZVAS2000

Work Center Description: MDG EAM Planning Plant Work Center

Work Center Category: 0005 Plant maintenance

Deletion Flag: ☐ Locked: ☐

Basic Data

Person Responsible: 001 SAP Beispiel: Verantwortliche...

Location: 0001 Werk 0001 Standort 0001


QDR System: 000001 CAQ subsystem 1

Prodn Supply Area:

Usage: 009 All task list types

Backflush: ☐

h. Enter the t-code IR03 if Work Center is created.

 **Display Work Center: Basic Data**

HR assignment Hierarchy

Plant 0001 Werk 0001

Work center ZVAS2000 MDG EAM Planning Plant Work Center

Basic Data Default Values Capacities Scheduling Costing Technology

General Data

Work Center Category 0005 Plant maintenance

Person Responsible 001 SAP Beispiel: Verantwortlicher 001

Location 0001 Werk 0001 Standort 0001

QDR System 000001 CAQ subsystem 1

Supply Area

Usage 009 All task list types

Backflush ☐ Advanced Planning ☐

Standard Value Maintenance

Standard value key SAP0 No standard values

Standard Values Overview

Key Word	Description