

[Ciências](#) / [Ciência da computação](#) / [Introduction to the Theory of Computation \(3rd Edition\)](#)

Exercício 5

Capítulo 2, Página 155



Introduction to the Theory of Computation

ISBN: 9781133187790

[Índice](#)

Solução Certificado

Passo 1

1 de 11

Part a.


Pushdown automaton is actually a DFA, i.e. it does not use its stack. The state diagram is given in *Exercise 1.6*.

Part b.

This language is again regular, we draw a NFA recognizing it (it can also be regarded as PDA not using its stack). Informally, it branches on first symbol and then non-deterministically guesses the end of string (and checks whether last symbol is the same as first).

Passo 2


2 de 11

**Passo 3**

3 de 11

Part c.**Passo 4**

4 de 11

**Passo 5**


5 de 11

Part d.

First we put symbol \$ onto stack, and then symbol # in order to count the length of first part of string. On every 0 in input, the machine non-deterministically branches to determine whether that is the midpoint of string.

Passo 6

6 de 11

**Passo 7**


7 de 11

Part e.

The idea is the same as in previous *Exercise*, just now we put the symbol read directly to stack, and branch without trigger.

Passo 8

8 de 11

**Passo 9**


9 de 11

Part f.

"Empty machine" recognizes empty language.

Passo 10

10 de 11

**Resultado**

11 de 11

We draw the machines.

[< Exercício 4](#)**Avaliar esta solução**[Exercício 6 >](#)