

React con Tailwind

1 - Iniciar la aplicación con vite (Puede ser desde la terminal)

npm init vite

Luego seguir los pasos y ejecutar con **npm run dev**.

2 - para instalar Tailwind seguir los sig. pasos.

ir a:

<https://tailwindcss.com/>
Get started
Instalation
Framework Guides
Vite

Install Tailwind CSS

```
npm install -D tailwindcss postcss autoprefixer  
npx tailwindcss init -p
```

Luego en el archivo dentro del proyecto llamado **tailwind.config.js** borrar TODO lo que contiene y copiar el sig. código.

```
/** @type {import('tailwindcss').Config} */  
export default {  
  content: [  
    "./index.html",  
    "./src/**/*.{js,ts,jsx,tsx}",  
  ],  
  theme: {  
    extend: {},  
  },  
  plugins: [],  
}
```

Luego borrar todo el contenido del archivo **index.css** y pegar el sig. código.

```
@tailwind base;  
@tailwind components;  
@tailwind utilities;
```

Listo, ahora si quieres probar el proyecto en **App.jsx** copiando el sig. código.

```
<h1 className="text-3xl font-bold underline">  
  Hello world!  
</h1>
```

Aquí les dejo unos botones para probar el código, para ello reemplazar todo el código en App.jsx por:

```
import './App.css';

function App() {
  return (
    <>
      <div className="px-4 py-8 flex flex-wrap md:items-center md:justify-center gap-8">
        <button className="relative py-2 px-6 text-center text-green-600 border border-green-600 overflow-hidden transition-all ease-in-out before:absolute before:bg-green-600 before:top-1/2 before:left-1/2 before:-translate-x-1/2 before:-translate-y-1/2 before:-z-10 before:transition-all before:duration-300 before:w-0 before:h-full hover:before:w-full hover:text-white">
          Success
        </button>
        <button className="relative py-2 px-6 text-center text-amber-600 border border-amber-600 overflow-hidden transition-all ease-in-out before:absolute before:bg-amber-600 before:top-1/2 before:left-1/2 before:-translate-x-1/2 before:-translate-y-1/2 before:-z-10 before:transition-all before:duration-300 before:w-0 before:h-full hover:before:w-full hover:text-white">
          Warning
        </button>
        <button className="relative py-2 px-6 text-center text-red-600 border border-red-600 overflow-hidden transition-all ease-in-out before:absolute before:bg-red-600 before:top-1/2 before:left-1/2 before:-translate-x-1/2 before:-translate-y-1/2 before:-z-10 before:transition-all before:duration-300 before:w-0 before:h-full hover:before:w-full hover:text-white">
          Danger
        </button>
        <button className="relative py-2 px-6 text-center text-sky-600 border border-sky-600 overflow-hidden transition-all ease-in-out before:absolute before:bg-sky-600 before:top-1/2 before:left-1/2 before:-translate-x-1/2 before:-translate-y-1/2 before:-z-10 before:transition-all before:duration-300 before:w-0 before:h-full hover:before:w-full hover:text-white">
          Info
        </button>
      </div>
    </>
  );
}

export default App;
```