

Gracias Demetrio



Contents

1	Data structures	2
1.1	Segment tree	2
1.2	Segment tree - Lazy propagation	2
1.3	Segment tree - Persistence	3
1.4	Segment tree - 2D	3
1.5	Sparse table (static RMQ)	4
1.6	Fenwick tree	4
1.7	Wavelet tree	4
1.8	STL extended set	5
1.9	STL rope	5
1.10	Treap (as BST)	5
1.11	Treap (implicit key)	5
1.12	Link-Cut tree	6
1.13	Convex hull trick (static)	7
1.14	Convex hull trick (dynamic)	7
1.15	Gain-cost-set	8
1.16	Disjoint intervals	8
2	Graphs	8
2.1	Topological sort	8
2.2	Kruskal (+ Union-Find)	8
2.3	Dijkstra	9
2.4	Bellman-Ford	9

2.5	Floyd-Warshall	9
2.6	Strongly connected components (+ 2-SAT)	9
2.7	Articulation - Bridges - Biconnected	10
2.8	Chu-Liu (minimum spanning arborescence)	10
2.9	LCA - Binary Lifting	11
2.10	Heavy-Light decomposition	11
2.11	Centroid decomposition	12
2.12	Parallel DFS	12
2.13	Eulerian path	12
2.14	Dynamic connectivity	13
2.15	Edmond's blossom (matching in general graphs)	13
3	Math	14
3.1	Identities	14
3.2	Theorems	14
3.3	Integer floor division	14
3.4	Sieve of Eratosthenes	15
3.5	Generate divisors	15
3.6	Pollard's rho	15
3.7	Simpson's rule	15
3.8	Polynomials	16
3.9	Bairstow	17
3.10	Fast Fourier Transform	17
3.11	Fast Hadamard Transform	18
3.12	Karatsuba	18
3.13	Diophantine	18
3.14	Modular inverse	19
3.15	Chinese remainder theorem	19
3.16	Mobius	19
3.17	Matrix operations	19
3.18	Simplex	19
4	Geometry	20
4.1	Point	20
4.2	Line	20
4.3	Circle	21
4.4	Polygon	22
4.5	Plane	23
4.6	Radial order of points	23
4.7	Convex hull	24
4.8	Dual from planar graph	24
5	Strings	24

5.1	KMP	24
5.2	Z function	24
5.3	Manacher	25
5.4	Aho-Corasick	25
5.5	Suffix automaton	25
5.6	Suffix array	26
5.7	LCP (Longest Common Prefix)	26
5.8	Suffix Tree (Ukkonen's algorithm)	26
5.9	Hashing	27
5.10	Hashing with ll (using __int128)	27
6	Flow	27
6.1	Matching (slower)	27
6.2	Matching (Hopcroft-Karp)	28
6.3	Hungarian	28
6.4	Dinic	29
6.5	Min cost max flow	29
7	Other	30
7.1	Mo's algorithm	30
7.2	Divide and conquer DP optimization	30
7.3	Dates	30
7.4	C++ stuff	30
7.5	Interactive problem tester template	31
7.6	Max number of divisors up to 10^n	31
7.7	Template	31

1 Data structures

1.1 Segment tree

```

1  #define oper min
2  #define NEUT INF
3  struct STree { // segment tree for min over integers
4      vector<int> st;int n;
5      STree(int n): st(4*n+5,NEUT), n(n) {}
6      void init(int k, int s, int e, int *a){
7          if(s+1==e){st[k]=a[s];return;}
8          int m=(s+e)/2;
9          init(2*k,s,m,a);init(2*k+1,m,e,a);
10         st[k]=oper(st[2*k],st[2*k+1]);
11     }
12     void upd(int k, int s, int e, int p, int v){
13         if(s+1==e){st[k]=v;return;}
14         int m=(s+e)/2;
15         if(p<m)upd(2*k,s,m,p,v);
16         else upd(2*k+1,m,e,p,v);
17         st[k]=oper(st[2*k],st[2*k+1]);
18     }
19     int query(int k, int s, int e, int a, int b){
20         if(s>=b||e<=a)return NEUT;
21         if(s>=a&&e<=b)return st[k];
22         int m=(s+e)/2;
23         return oper(query(2*k,s,m,a,b),query(2*k+1,m,e,a,b));
24     }
25     void init(int *a){init(1,0,n,a);}
26     void upd(int p, int v){upd(1,0,n,p,v);}
27     int query(int a, int b){return query(1,0,n,a,b);}
28 }; // usage: STree rmq(n);rmq.init(x);rmq.upd(i,v);rmq.query(s,e);

```

1.2 Segment tree - Lazy propagation

```

1  struct STree { // example: range sum with range addition
2      vector<int> st,lazy;int n;
3      STree(int n): st(4*n+5,0), lazy(4*n+5,0), n(n) {}
4      void init(int k, int s, int e, int *a){
5          lazy[k]=0; // lazy neutral element
6          if(s+1==e){st[k]=a[s];return;}
7          int m=(s+e)/2;
8          init(2*k,s,m,a);init(2*k+1,m,e,a);

```

```

9     st[k]=st[2*k]+st[2*k+1]; // operation
10 }
11 void push(int k, int s, int e){
12     if(!lazy[k])return; // if neutral, nothing to do
13     st[k]+=(e-s)*lazy[k]; // update st according to lazy
14     if(s+1<e){ // propagate to children
15         lazy[2*k]+=lazy[k];
16         lazy[2*k+1]+=lazy[k];
17     }
18     lazy[k]=0; // clear node lazy
19 }
20 void upd(int k, int s, int e, int a, int b, int v){
21     push(k,s,e);
22     if(s>=b||e<=a)return;
23     if(s>=a&&e<=b){
24         lazy[k]+=v; // accumulate lazy
25         push(k,s,e);return;
26     }
27     int m=(s+e)/2;
28     upd(2*k,s,m,a,b,v);upd(2*k+1,m,e,a,b,v);
29     st[k]=st[2*k]+st[2*k+1]; // operation
30 }
31 int query(int k, int s, int e, int a, int b){
32     if(s>=b||e<=a)return 0; // operation neutral
33     push(k,s,e);
34     if(s>=a&&e<=b)return st[k];
35     int m=(s+e)/2;
36     return query(2*k,s,m,a,b)+query(2*k+1,m,e,a,b); // operation
37 }
38 void init(int *a){init(1,0,n,a);}
39 void upd(int a, int b, int v){upd(1,0,n,a,b,v);}
40 int query(int a, int b){return query(1,0,n,a,b);}
41 }; // usage: STree rmq(n);rmq.init(x);rmq.upd(s,e,v);rmq.query(s,e);
    
```

1.3 Segment tree - Persistence

```

1 #define oper min
2 #define NEUT INF
3 struct STree { // persistent segment tree for min over integers
4     vector<int> st,l,r;int n,sz,rt;
5     STree(int n): st(24*n,NEUT),l(24*n,0),r(24*n,0),n(n),rt(0),sz(1){}
6     // be careful with memory! 4*n+q*log(n) . 24*n should be enough
7     int init(int s, int e, int *a){ // not necessary in most cases
    
```

```

8         int k=sz++;
9         if(s+1==e){st[k]=a[s];return k;}
10        int m=(s+e)/2;
11        l[k]=init(s,m,a);r[k]=init(m,e,a);
12        st[k]=oper(st[l[k]],st[r[k]]);
13        return k;
14    }
15    int upd(int k, int s, int e, int p, int v){
16        int nk=sz++;l[nk]=l[k];r[nk]=r[k];
17        if(s+1==e){st[nk]=v;return nk;}
18        int m=(s+e)/2;
19        if(p<m)l[nk]=upd(l[k],s,m,p,v);
20        else r[nk]=upd(r[k],m,e,p,v);
21        st[nk]=oper(st[l[nk]],st[r[nk]]);
22        return nk;
23    }
24    int query(int k, int s, int e, int a, int b){
25        if(s>=b||e<=a)return NEUT;
26        if(s>=a&&e<=b)return st[k];
27        int m=(s+e)/2;
28        return oper(query(l[k],s,m,a,b),query(r[k],m,e,a,b));
29    }
30    int init(int *a){return init(0,n,a);}
31    int upd(int k, int p, int v){return rt=upd(k,0,n,p,v);}
32    int upd(int p, int v){return upd(rt,p,v);} // update on last root
33    int query(int k, int a, int b){return query(k,0,n,a,b);}
34 }; // usage: STree rmq(n);root=rmq.init(x);new_root=rmq.upd(root,i,v);
    rmq.query(root,s,e);
    
```

1.4 Segment tree - 2D

```

1 int n,m;
2 int a[MAXN][MAXN],st[2*MAXN][2*MAXN];
3 void build(){
4     fore(i,0,n)fore(j,0,m)st[i+n][j+m]=a[i][j];
5     fore(i,0,n)for(int j=m-1;j>=0;j--)
6         st[i+n][j]=op(st[i+n][j<<1],st[i+n][j<<1|1]);
7     for(int i=n-1;i>=0;i--)fore(j,0,2*m)
8         st[i][j]=op(st[i<<1][j],st[i<<1|1][j]);
9 }
10 void upd(int x, int y, int v){
11     st[x+n][y+m]=v;
12     for(int j=y+m;j>1;j>=1)st[x+n][j>>1]=op(st[x+n][j],st[x+n][j^1]);
    
```

```

13 for(int i=x+n;i>1;i>=1)for(int j=y+m;j>=1)
14     st[i>>1][j]=op(st[i][j],st[i^1][j]);
15 }
16 int query(int x0, int x1, int y0, int y1){
17     int r=NEUT;
18     for(int i0=x0+n,i1=x1+n;i0<i1;i0>=1,i1>=1){
19         int t[4],q=0;
20         if(i0&1)t[q++]=i0++;
21         if(i1&1)t[q++] = --i1;
22         fore(k,0,q)for(int j0=y0+m,j1=y1+m;j0<j1;j0>=1,j1>=1){
23             if(j0&1)r=op(r,st[t[k]][j0++]);
24             if(j1&1)r=op(r,st[t[k]][--j1]);
25         }
26     }
27     return r;
28 }
    
```

1.5 Sparse table (static RMQ)

```

1 #define oper min
2 int st[K][1<<K];int n; // K such that 2^K>n
3 void st_init(int *a){
4     fore(i,0,n)st[0][i]=a[i];
5     fore(k,1,K)fore(i,0,n-(1<<k)+1)
6         st[k][i]=oper(st[k-1][i],st[k-1][i+(1<<(k-1))]);
7 }
8 int st_query(int s, int e){
9     int k=31-__builtin_clz(e-s);
10    return oper(st[k][s],st[k][e-(1<<k)]);
11 }
    
```

1.6 Fenwick tree

```

1 int ft[MAXN+1]; // for more dimensions, make ft multi-dimensional
2 void upd(int i0, int v){ // add v to i0th element (0-based)
3     // add extra fors for more dimensions
4     for(int i=i0+1;i<=MAXN;i+=i&-i)ft[i]+=v;
5 }
6 int get(int i0){ // get sum of range [0,i0)
7     int r=0;
8     // add extra fors for more dimensions
9     for(int i=i0;i; i-=i&-i)r+=ft[i];
10    return r;
11 }
    
```

```

12 int get_sum(int i0, int i1){ // get sum of range [i0,i1) (0-based)
13     return get(i1)-get(i0);
14 }
    
```

1.7 Wavelet tree

```

1 struct WT {
2     vector<int> wt[1<<20];int n;
3     void init(int k, int s, int e){
4         if(s+1==e)return;
5         wt[k].clear();wt[k].pb(0);
6         int m=(s+e)/2;
7         init(2*k,s,m);init(2*k+1,m,e);
8     }
9     void add(int k, int s, int e, int v){
10        if(s+1==e)return;
11        int m=(s+e)/2;
12        if(v<m)wt[k].pb(wt[k].back()),add(2*k,s,m,v);
13        else wt[k].pb(wt[k].back()+1),add(2*k+1,m,e,v);
14    }
15    int query0(int k, int s, int e, int a, int b, int i){
16        if(s+1==e)return s;
17        int m=(s+e)/2;
18        int q=(b-a)-(wt[k][b]-wt[k][a]);
19        if(i<q)return query0(2*k,s,m,a-wt[k][a],b-wt[k][b],i);
20        else return query0(2*k+1,m,e,wt[k][a],wt[k][b],i-q);
21    }
22    void upd(int k, int s, int e, int i){
23        if(s+1==e)return;
24        int m=(s+e)/2;
25        int v0=wt[k][i+1]-wt[k][i],v1=wt[k][i+2]-wt[k][i+1];
26        if(!v0&&!v1)upd(2*k,s,m,i-wt[k][i]);
27        else if(v0&&v1)upd(2*k+1,m,e,wt[k][i]);
28        else if(v0)wt[k][i+1]--;
29        else wt[k][i+1]++;
30    }
31    void init(int _n){n=_n;init(1,0,n);} // (values in range [0,n))
32    void add(int v){add(1,0,n,v);}
33    int query0(int a, int b, int i){ // ith element in range [a,b)
34        return query0(1,0,n,a,b,i); // (if it was sorted)
35    }
36    void upd(int i){ // swap positions i,i+1
37        upd(1,0,n,i);
    }
}
    
```

```
38 }
39 };
```

1.8 STL extended set

```
1 #include<ext/pb_ds/assoc_container.hpp>
2 #include<ext/pb_ds/tree_policy.hpp>
3 using namespace __gnu_pbds;
4 typedef tree<int,null_type,less<int>,rb_tree_tag,
   tree_order_statistics_node_update> ordered_set;
5 // find_by_order(i) -> iterator to ith element
6 // order_of_key(k) -> position (int) of lower_bound of k
```

1.9 STL rope

```
1 #include <ext/rope>
2 using namespace __gnu_cxx;
3 rope<int> s;
4 // Sequence with O(log(n)) random access, insert, erase at any position
5 // s.push_back(x);
6 // s.insert(i,r) // insert rope r at position i
7 // s.erase(i,k) // erase subsequence [i,i+k)
8 // s.substr(i,k) // return new rope corresponding to subsequence [i,i+k)
9 // s[i] // access ith element (cannot modify)
10 // s.mutable_reference_at(i) // acces ith element (allows modification)
11 // s.begin() and s.end() are const iterators (use mutable_begin(),
   mutable_end() to allow modification)
```

1.10 Treap (as BST)

```
1 typedef struct item *pitem;
2 struct item {
3     int pr,key,cnt;
4     pitem l,r;
5     item(int key):key(key),pr(rand()),cnt(1),l(0),r(0) {}
6 };
7 int cnt(pitem t){return t?t->cnt:0;}
8 void upd_cnt(pitem t){if(t)t->cnt=cnt(t->l)+cnt(t->r)+1;}
9 void split(pitem t, int key, pitem& l, pitem& r){ // l: < key, r: >= key
10     if(!t)l=r=0;
11     else if(key<t->key)split(t->l,key,l,t->l),r=t;
12     else split(t->r,key,t->r,r),l=t;
13     upd_cnt(t);
14 }
```

```
15 void insert(pitem& t, pitem it){
16     if(!t)t=it;
17     else if(it->pr>t->pr)split(t,it->key,it->l,it->r),t=it;
18     else insert(it->key<t->key?t->l:t->r,it);
19     upd_cnt(t);
20 }
21 void merge(pitem& t, pitem l, pitem r){
22     if(!l||!r)t=l?l:r;
23     else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
24     else merge(r->l,l,r->l),t=r;
25     upd_cnt(t);
26 }
27 void erase(pitem& t, int key){
28     if(t->key==key)merge(t,t->l,t->r);
29     else erase(key<t->key?t->l:t->r,key);
30     upd_cnt(t);
31 }
32 pitem kth(pitem t, int k){
33     if(!t)return 0;
34     if(k==cnt(t->l))return t;
35     return k<cnt(t->l)?kth(t->l,k):kth(t->r,k-cnt(t->l)-1);
36 }
37 pair<int,int> lb(pitem t, int key){ // position and value of lower_bound
38     if(!t)return mp(0,1<<30); // (special value)
39     if(key>t->key){
40         auto w=lb(t->r,key);w.fst+=cnt(t->l)+1;return w;
41     }
42     auto w=lb(t->l,key);
43     if(w.fst==cnt(t->l))w.snd=t->key;
44     return w;
45 }
```

1.11 Treap (implicit key)

```
1 // example that supports range reverse and addition updates, and range
   sum query
2 // (commented parts are specific to this problem)
3 typedef struct item *pitem;
4 struct item {
5     int pr,cnt,val;
6     // int sum; // (paramters for range query)
7     // bool rev;int add; // (parameters for lazy prop)
8     pitem l,r;
```

```

9  item(int val): pr(rand()),cnt(1),val(val),l(0),r(0)/*,sum(val),rev(0),
    add(0)*/ {}
10 };
11 void push(pitem it){
12     if(it){
13         /*if(it->rev){
14             swap(it->l,it->r);
15             if(it->l)it->l->rev^=true;
16             if(it->r)it->r->rev^=true;
17             it->rev=false;
18         }
19         it->val+=it->add;it->sum+=it->cnt*it->add;
20         if(it->l)it->l->add+=it->add;
21         if(it->r)it->r->add+=it->add;
22         it->add=0;*/
23     }
24 }
25 int cnt(pitem t){return t->cnt:0;}
26 // int sum(pitem t){return t?push(t),t->sum:0;}
27 void upd_cnt(pitem t){
28     if(t){
29         t->cnt=cnt(t->l)+cnt(t->r)+1;
30         // t->sum=t->val+sum(t->l)+sum(t->r);
31     }
32 }
33 void merge(pitem& t, pitem l, pitem r){
34     push(l);push(r);
35     if(!l||!r)t=l?l:r;
36     else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
37     else merge(r->l,l,r->l),t=r;
38     upd_cnt(t);
39 }
40 void split(pitem t, pitem& l, pitem& r, int sz){ // sz:desired size of l
41     if(!t){l=r=0;return;}
42     push(t);
43     if(sz<=cnt(t->l))split(t->l,l,t->l,sz),r=t;
44     else split(t->r,t->r,r,sz-1-cnt(t->l)),l=t;
45     upd_cnt(t);
46 }
47 void output(pitem t){ // useful for debugging
48     if(!t)return;
49     push(t);
50     output(t->l);printf("\u% d",t->val);output(t->r);

```

```

51 }
52 // use merge and split for range updates and queries

```

1.12 Link-Cut tree

```

1  typedef struct item *pitem;
2  struct item {
3      int pr;bool rev;
4      pitem l,r,f,d;
5      item():pr(rand()),l(0),r(0),f(0),d(0),rev(0){}
6  };
7  void push(pitem t){
8      if(t&& t->rev){
9          swap(t->l,t->r);
10         if(t->l)t->l->rev^=1;
11         if(t->r)t->r->rev^=1;
12         t->rev=0;
13     }
14 }
15 void merge(pitem& t, pitem l, pitem r){
16     push(l);push(r);
17     if(!l||!r)t=l?l:r;
18     else if(l->pr>r->pr)merge(l->r,l->r,r),l->r->f=t=l;
19     else merge(r->l,l,r->l),r->l->f=t=r;
20 }
21 void push_all(pitem t){
22     if(t->f)push_all(t->f);
23     push(t);
24 }
25 void split(pitem t, pitem& l, pitem& r){
26     push_all(t);
27     l=t->l;r=t->r;t->l=t->r=0;
28     while(t->f){
29         pitem f=t->f;t->f=0;
30         if(t==f->l){
31             if(r)r->f=f;
32             f->l=r;r=f;
33         }
34         else {
35             if(l)l->f=f;
36             f->r=l;l=f;
37         }
38         t=f;

```

```

39 }
40 if(l)l->f=0;
41 if(r)r->f=0;
42 }
43 pitem path(pitem p){return p->f?path(p->f):p;}
44 pitem tail(pitem p){push(p);return p->r?tail(p->r):p;}
45 pitem expose(pitem p){
46     pitem q,r,t;
47     split(p,q,r);
48     if(q)tail(q)->d=p;
49     merge(p,p,r);
50     while(t=tail(p),t->d){
51         pitem d=t->d;t->d=0;
52         split(d,q,r);
53         if(q)tail(q)->d=d;
54         merge(p,p,d);merge(p,p,r);
55     }
56     return p;
57 }
58 pitem root(pitem v){return tail(expose(v));}
59 void evert(pitem v){expose(v)->rev^=1;v->d=0;}
60 void link(pitem v, pitem w){ // make v son of w
61     evert(v);
62     pitem p=path(v);
63     merge(p,p,expose(w));
64 }
65 void cut(pitem v){ // cut v from its father
66     pitem p,q;
67     expose(v);split(v,p,q);v->d=0;
68 }
69 void cut(pitem v, pitem w){evert(w);cut(v);}
    
```

1.13 Convex hull trick (static)

```

1 typedef ll tc;
2 struct Line{tc m,h};
3 struct CHT { // for minimum (for maximum just change the sign of lines)
4     vector<Line> c;
5     int pos=0;
6     tc in(Line a, Line b){
7         tc x=b.h-a.h,y=a.m-b.m;
8         return x/y+(x%y?!((x>0)^(y>0)):0); // ==ceil(x/y)
9     }
    
```

```

10 void add(tc m, tc h){ // m's should be non increasing
11     Line l=(Line){m,h};
12     if(c.size()&&m==c.back().m){
13         l.h=min(h,c.back().h);c.pop_back();if(pos)pos--;
14     }
15     while(c.size()>1&&in(c.back(),l)<=in(c[c.size()-2],c.back())){
16         c.pop_back();if(pos)pos--;
17     }
18     c.pb(l);
19 }
20 inline bool fbin(tc x, int m){return in(c[m],c[m+1])>x;}
21 tc eval(tc x){
22     // O(log n) query:
23     int s=0,e=c.size();
24     while(e-s>1){int m=(s+e)/2;
25         if(fbin(x,m-1))e=m;
26         else s=m;
27     }
28     return c[s].m*x+c[s].h;
29     // O(1) query (for ordered x's):
30     while(pos>0&&fbin(x,pos-1))pos--;
31     while(pos<c.size()-1&&!fbin(x,pos))pos++;
32     return c[pos].m*x+c[pos].h;
33 }
34 };
    
```

1.14 Convex hull trick (dynamic)

```

1 typedef ll tc;
2 const tc is_query=-(1LL<<62); // special value for query
3 struct Line {
4     tc m,b;
5     mutable multiset<Line>::iterator it,end;
6     const Line* succ(multiset<Line>::iterator it) const {
7         return (++it==end? NULL : &*it);}
8     bool operator<(const Line& rhs) const {
9         if(rhs.b!=is_query)return m<rhs.m;
10         const Line *s=succ(it);
11         if(!s)return 0;
12         return b-s->b<(s->m-m)*rhs.m;
13     }
14 };
15 struct HullDynamic : public multiset<Line> { // for maximum
    
```



```

16 bool bad(iterator y){
17     iterator z=next(y);
18     if(y==begin()){
19         if(z==end())return false;
20         return y->m==z->m&& y->b<=z->b;
21     }
22     iterator x=prev(y);
23     if(z==end())return y->m==x->m&& y->b<=x->b;
24     return (x->b-y->b)*(z->m-y->m)>=(y->b-z->b)*(y->m-x->m);
25 }
26 iterator next(iterator y){return ++y;}
27 iterator prev(iterator y){return --y;}
28 void add(tc m, tc b){
29     iterator y=insert((Line){m,b});
30     y->it=y;y->end=end();
31     if(bad(y)){erase(y);return;}
32     while(next(y)!=end()&&bad(next(y)))erase(next(y));
33     while(y!=begin()&&bad(prev(y)))erase(prev(y));
34 }
35 tc eval(tc x){
36     Line l=*lower_bound((Line){x,is_query});
37     return l.m*x+l.b;
38 }
39 };

```

1.15 Gain-cost-set

```

1 // stores pairs (benefit,cost) (erases non-optimal pairs)
2 struct GCS {
3     set<pair<int,int> > s;
4     void add(int g, int c){
5         auto x=mp(g,c);
6         auto p=s.lower_bound(x);
7         if(p!=s.end()&&p->snd<=x.snd)return;
8         if(p!=s.begin()){ // erase pairs with less benefit
9             --p;           // and more cost
10            while(p->snd>=x.snd){
11                if(p==s.begin()){s.erase(p);break;}
12                s.erase(p--);
13            }
14        }
15        s.insert(x);
16    }

```

```

17 int get(int gain){ // min cost for some benefit
18     auto p=s.lower_bound(mp(gain,-INF));
19     int r=p==s.end()?INF:p->snd;
20     return r;
21 }
22 };

```

1.16 Disjoint intervals

```

1 // stores disjoint intervals as [first, second)
2 struct disjoint_intervals {
3     set<pair<int,int> > s;
4     void insert(pair<int,int> v){
5         if(v.fst>=v.snd) return;
6         auto at=s.lower_bound(v);auto it=at;
7         if(at!=s.begin()&&(--at)->snd>=v.fst)v.fst=at->fst,--it;
8         for(;it!=s.end()&&it->fst<=v.snd;s.erase(it++))
9             v.snd=max(v.snd,it->snd);
10        segs.insert(v);
11    }
12 };

```

2 Graphs

2.1 Topological sort

```

1 vector<int> g[MAXN];int n;
2 vector<int> tsort(){ // lexicographically smallest topological sort
3     vector<int> r;priority_queue<int> q;
4     vector<int> d(2*n,0);
5     for(i,0,n)for(j,0,g[i].size())d[g[i][j]]++;
6     for(i,0,n)if(!d[i])q.push(-i);
7     while(!q.empty()){
8         int x=-q.top();q.pop();r.pb(x);
9         for(i,0,g[x].size()){
10             d[g[x][i]]--;
11             if(!d[g[x][i]])q.push(-g[x][i]);
12         }
13     }
14     return r; // if not DAG it will have less than n elements
15 }

```

2.2 Kruskal (+ Union-Find)


```

1 int uf[MAXN];
2 void uf_init(){memset(uf,-1,sizeof(uf));}
3 int uf_find(int x){return uf[x]<0?x:uf[x]=uf_find(uf[x]);}
4 bool uf_join(int x, int y){
5     x=uf_find(x);y=uf_find(y);
6     if(x==y)return false;
7     if(uf[x]>uf[y])swap(x,y);
8     uf[x]+=uf[y];uf[y]=x;
9     return true;
10 }
11 vector<pair<ll,pair<int,int> > > es; // edges (cost,(u,v))
12 ll kruskal(){ // assumes graph is connected
13     sort(es.begin(),es.end());uf_init();
14     ll r=0;
15     fore(i,0,es.size()){
16         int x=es[i].snd.fst,y=es[i].snd.snd;
17         if(uf_join(x,y))r+=es[i].fst; // (x,y,c) belongs to mst
18     }
19     return r; // total cost
20 }

```

2.3 Dijkstra

```

1 vector<pair<int,int> > g[MAXN]; // u->[(v,cost)]
2 ll dist[MAXN];
3 void dijkstra(int x){
4     memset(dist,-1,sizeof(dist));
5     priority_queue<pair<ll,int> > q;
6     dist[x]=0;q.push(mp(0,x));
7     while(!q.empty()){
8         x=q.top().snd;ll c=-q.top().fst;q.pop();
9         if(dist[x]!=c)continue;
10        fore(i,0,g[x].size()){
11            int y=g[x][i].fst,c=g[x][i].snd;
12            if(dist[y]<0||dist[x]+c<dist[y])
13                dist[y]=dist[x]+c,q.push(mp(-dist[y],y));
14        }
15    }
16 }

```

2.4 Bellman-Ford

```

1 int n;
2 vector<pair<int,int> > g[MAXN]; // u->[(v,cost)]

```

```

3 ll dist[MAXN];
4 void bford(int src){ // 0(nm)
5     fill(dist,dist+n,INF);dist[src]=0;
6     fore(_,0,n-1)fore(x,0,n)if(dist[x]!=INF)for(auto t:g[x]){
7         dist[t.fst]=min(dist[t.fst],dist[x]+t.snd);
8     }
9     fore(x,0,n)if(dist[x]!=INF)for(auto t:g[x]){
10        if(dist[t.fst]>dist[x]+t.snd){
11            // neg cycle: all nodes reachable from t.fst have -INF distance
12            // to reconstruct neg cycle: save "prev" of each node, go up from
13            // t.fst until repeating a node. this node and all nodes between
14            // the two occurrences form a neg cycle
15        }
16    }
17 }

```

2.5 Floyd-Warshall

```

1 // g[i][j]: weight of edge (i, j) or INF if there's no edge
2 // g[i][i]=0
3 ll g[MAXN][MAXN];int n;
4 void floyd(){ // 0(n^3) . Replaces g with min distances
5     fore(k,0,n)fore(i,0,n)if(g[i][k]<INF)fore(j,0,n)if(g[k][j]<INF)
6         g[i][j]=min(g[i][j],g[i][k]+g[k][j]);
7 }
8 bool inNegCycle(int v){return g[v][v]<0;}
9 bool hasNegCycle(int a, int b){ // true iff there's neg cycle in between
10    fore(i,0,n)if(g[a][i]<INF&&g[i][b]<INF&&g[i][i]<0)return true;
11    return false;
12 }

```

2.6 Strongly connected components (+ 2-SAT)

```

1 // MAXN: max number of nodes or 2 * max number of variables (2SAT)
2 bool truth[MAXN]; // truth[cmp[i]]=value of variable i (2SAT)
3 int nvar;int neg(int x){return MAXN-1-x;} // (2SAT)
4 vector<int> g[MAXN];
5 int n,lw[MAXN],idx[MAXN],qidx,cmp[MAXN],qcmp;
6 stack<int> st;
7 void tjn(int u){
8     lw[u]=idx[u]==qidx;
9     st.push(u);cmp[u]=-2;
10    for(int v:g[u]){
11        if(!idx[v]||cmp[v]==-2){

```

```

12     if(!idx[v]) tjn(v);
13     lw[u]=min(lw[u],lw[v]);
14 }
15 }
16 if(lw[u]==idx[u]){
17     int x;
18     do{x=st.top();st.pop();cmp[x]=qcmp;}while(x!=u);
19     truth[qcmp]=(cmp[neg(u)]<0); // (2SAT)
20     qcmp++;
21 }
22 }
23 void scc(){
24     memset(idx,0,sizeof(idx));qidx=0;
25     memset(cmp,-1,sizeof(cmp));qcmp=0;
26     fore(i,0,n)if(!idx[i])tjn(i);
27 }
28 // Only for 2SAT:
29 void addor(int a, int b){g[neg(a)].pb(b);g[neg(b)].pb(a);}
30 bool satisf(int _nvar){
31     nvar=_nvar;n=MAXN;scc();
32     fore(i,0,nvar)if(cmp[i]==cmp[neg(i)])return false;
33     return true;
34 }

```

2.7 Articulation - Bridges - Biconnected

```

1 vector<int> g[MAXN];int n;
2 struct edge {int u,v,comp;bool bridge;};
3 vector<edge> e;
4 void add_edge(int u, int v){
5     g[u].pb(e.size());g[v].pb(e.size());
6     e.pb((edge){u,v,-1,false});
7 }
8 int D[MAXN],B[MAXN],T;
9 int nbc; // number of biconnected components
10 int art[MAXN]; // articulation point iff !=0
11 stack<int> st; // only for biconnected
12 void dfs(int u,int pe){
13     B[u]=D[u]=T++;
14     for(int ne:g[u])if(ne!=pe){
15         int v=e[ne].u^e[ne].v^u;
16         if(D[v]<0){
17             st.push(ne);dfs(v,ne);

```

```

18         if(B[v]>D[u])e[ne].bridge = true; // bridge
19         if(B[v]>=D[u]){
20             art[u]++; // articulation
21             int last; // start biconnected
22             do {
23                 last=st.top();st.pop();
24                 e[last].comp=nbc;
25             } while(last!=ne);
26             nbc++; // end biconnected
27         }
28         B[u]=min(B[u],B[v]);
29     }
30     else if(D[v]<D[u])st.push(ne),B[u]=min(B[u],D[v]);
31 }
32 }
33 void doit(){
34     memset(D,-1,sizeof(D));memset(art,0,sizeof(art));
35     nbc=T=0;
36     fore(i,0,n)if(D[i]<0)dfs(i,-1),art[i]--;
37 }

```

2.8 Chu-Liu (minimum spanning arborescence)

```

1 typedef ll tw;const tw INF=1LL<<60;
2 struct edge {int src,dst;tw w;};
3 struct ChuLiu {
4     int n,r;tw cost;bool found;
5     vector<int> no,pr,mark;
6     vector<vector<int> > comp,nx;
7     vector<tw> mcost;
8     vector<vector<edge> > h;
9     ChuLiu(int n):n(n),h(n){}
10    void add_edge(int x, int y, tw w){h[y].pb((edge){x,y,w});}
11    void visit(int v, int s){
12        if(mark[v]){
13            vector<int> temp=no;found=true;
14            do {
15                cost+=mcost[v];v=pr[v];
16                if(v!=s)while(comp[v].size()>0){
17                    no[comp[v].back()]=s;
18                    comp[s].pb(comp[v].back());
19                    comp[v].pop_back();
20                }

```

```

21     }while(v!=s);
22     for(int j:comp[s])if(j!=r)for(edge& e:h[j])
23         if(no[e.src]!=s)e.w-=mcost[temp[j]];
24 }
25 mark[v]=true;
26 for(int i:nx[v])if(no[i]!=no[v]&&pr[no[i]]==v)
27     if(!mark[no[i]]||i==s)
28         visit(i,s);
29 }
30 tw doit(int _r){ // r: root (0(nm))
31     r=_r;
32     no.resize(n);comp.clear();comp.resize(n);
33     fore(x,0,n)comp[x].pb(no[x]=x);
34     for(cost=0;;){
35         pr.clear();pr.resize(n,-1);
36         mcost=vector<tw>(n,INF);
37         fore(j,0,n)if(j!=r)for(edge e:h[j])
38             if(no[e.src]!=no[j]&&e.w<mcost[no[j]])
39                 mcost[no[j]]=e.w,pr[no[j]]=no[e.src];
40         nx.clear();nx.resize(n);
41         fore(x,0,n)if(pr[x]>=0)nx[pr[x]].pb(x);
42         bool stop=true;
43         mark.clear();mark.resize(n);
44         fore(x,0,n)if(x!=r&&!mark[x]&&!comp[x].empty()){
45             found=false;visit(x,x);
46             if(found)stop=false;
47         }
48         if(stop){
49             fore(x,0,n)if(pr[x]>=0)cost+=mcost[x];
50             return cost;
51         }
52     }
53 }
54 };

```

2.9 LCA - Binary Lifting

```

1 vector<int> g[1<<K];int n; // K such that 2^K>=n
2 int F[K][1<<K],D[1<<K];
3 void lca_dfs(int x){
4     fore(i,0,g[x].size()){
5         int y=g[x][i];if(y==F[0][x])continue;
6         F[0][y]=x;D[y]=D[x]+1;lca_dfs(y);

```

```

7     }
8 }
9 void lca_init(){
10     D[0]=0;F[0][0]=-1;
11     lca_dfs(0);
12     fore(k,1,K)fore(x,0,n)
13         if(F[k-1][x]<0)F[k][x]=-1;
14         else F[k][x]=F[k-1][F[k-1][x]];
15 }
16 int lca(int x, int y){
17     if(D[x]<D[y])swap(x,y);
18     for(int k=K-1;k>=0;--k)if(D[x]-(1<<k)>=D[y])x=F[k][x];
19     if(x==y)return x;
20     for(int k=K-1;k>=0;--k)if(F[k][x]!=F[k][y])x=F[k][x],y=F[k][y];
21     return F[0][x];
22 }

```

2.10 Heavy-Light decomposition

```

1 vector<int> g[MAXN];
2 int wg[MAXN],dad[MAXN],dep[MAXN]; // weight,father,depth
3 void dfs1(int x){
4     wg[x]=1;
5     for(int y:g[x])if(y!=dad[x]){
6         dad[y]=x;dep[y]=dep[x]+1;dfs1(y);
7         wg[x]+=wg[y];
8     }
9 }
10 int curpos,pos[MAXN],head[MAXN];
11 void hld(int x, int c){
12     if(c<0)c=x;
13     pos[x]=curpos++;head[x]=c;
14     int mx=-1;
15     for(int y:g[x])if(y!=dad[x]&&(mx<0||wg[mx]<wg[y]))mx=y;
16     if(mx>=0)hld(mx,c);
17     for(int y:g[x])if(y!=mx&&y!=dad[x])hld(y,-1);
18 }
19 void hld_init(){dad[0]=-1;dep[0]=0;dfs1(0);curpos=0;hld(0,-1);}
20 int query(int x, int y, STree& rmq){
21     int r=NEUT;
22     while(head[x]!=head[y]){
23         if(dep[head[x]]>dep[head[y]])swap(x,y);
24         r=oper(r,rmq.query(pos[head[y]],pos[y]+1));

```

```

25     y=dad[head[y]];
26 }
27 if(dep[x]>dep[y])swap(x,y); // now x is lca
28 r=oper(r,rmq.query(pos[x],pos[y]+1));
29 return r;
30 }
31 // for updating: rmq.upd(pos[x],v);
    
```

2.11 Centroid decomposition

```

1 vector<int> g[MAXN];int n;
2 bool tk[MAXN];
3 int fat[MAXN]; // father in centroid decomposition
4 int szt[MAXN]; // size of subtree
5 int calcsz(int x, int f){
6     szt[x]=1;
7     for(auto y:g[x])if(y!=f&&!tk[y])szt[x]+=calcsz(y,x);
8     return szt[x];
9 }
10 void cdfs(int x=0, int f=-1, int sz=-1){ // 0(nlogn)
11     if(sz<0)sz=calcsz(x,-1);
12     for(auto y:g[x])if(!tk[y]&&sz[y]*2>=sz){
13         szt[x]=0;cdfs(y,f,sz);return;
14     }
15     tk[x]=true;fat[x]=f;
16     for(auto y:g[x])if(!tk[y])cdfs(y,x);
17 }
18 void centroid(){memset(tk,false,sizeof(tk));cdfs();}
    
```

2.12 Parallel DFS

```

1 struct Tree {
2     int n,z[2];
3     vector<vector<int>> g;
4     vector<int> ex,ey,p,w,f,v[2];
5     Tree(int n):g(n),w(n),f(n){}
6     void add_edge(int x, int y){
7         p.pb(g[x].size());g[x].pb(ex.size());ex.pb(x);ey.pb(y);
8         p.pb(g[y].size());g[y].pb(ex.size());ex.pb(y);ey.pb(x);
9     }
10    bool go(int k){ // returns true if it finds new node
11        int& x=z[k];
12        while(x>=0&&
13            (w[x]==g[x].size()||w[x]==g[x].size()-1&&(g[x].back()^1)==f[x]))
    
```

```

14        x=f[x]>=0?ex[f[x]]:-1;
15        if(x<0)return false;
16        if((g[x][w[x]]^1)==f[x])w[x]++;
17        int e=g[x][w[x]],y=ey[e];
18        f[y]=e;w[x]++;w[y]=0;x=y;
19        v[k].pb(x);
20        return true;
21    }
22    vector<int> erase_edge(int e){
23        e*=2; // erases eth edge, returns smaller component
24        int x=ex[e],y=ey[e];
25        p[g[x].back()]=p[e];
26        g[x][p[e]]=g[x].back();g[x].pop_back();
27        p[g[y].back()]=p[e^1];
28        g[y][p[e^1]]=g[y].back();g[y].pop_back();
29        f[x]=f[y]=-1;
30        w[x]=w[y]=0;
31        z[0]=x;z[1]=y;
32        v[0]={x};v[1]={y};
33        bool d0=true,d1=true;
34        while(d0&&d1)d0=go(0),d1=go(1);
35        if(d1)return v[0];
36        return v[1];
37    }
38 };
    
```

2.13 Eulerian path

```

1 // Directed version (uncomment commented code for undirected)
2 struct edge {
3     int y;
4     // list<edge>::iterator rev;
5     edge(int y):y(y){}
6 };
7 list<edge> g[MAXN];
8 void add_edge(int a, int b){
9     g[a].push_front(edge(b));//auto ia=g[a].begin();
10    // g[b].push_front(edge(a));auto ib=g[b].begin();
11    // ia->rev=ib;ib->rev=ia;
12 }
13 vector<int> p;
14 void go(int x){
15     while(g[x].size()){
    
```

```

16     int y=g[x].front().y;
17     //g[y].erase(g[x].front().rev);
18     g[x].pop_front();
19     go(y);
20 }
21 p.push_back(x);
22 }
23 vector<int> get_path(int x){ // get a path that begins in x
24 // check that a path exists from x before calling to get_path!
25     p.clear();go(x);reverse(p.begin(),p.end());
26     return p;
27 }

```

2.14 Dynamic connectivity

```

1 struct UnionFind {
2     int n,comp;
3     vector<int> uf,si,c;
4     UnionFind(int n=0):n(n),comp(n),uf(n),si(n,1){
5         for(i,0,n)uf[i]=i;}
6     int find(int x){return x==uf[x]?x:find(uf[x]);}
7     bool join(int x, int y){
8         if((x=find(x))==find(y))return false;
9         if(si[x]<si[y])swap(x,y);
10        si[x]+=si[y];uf[y]=x;comp--;c.pb(y);
11        return true;
12    }
13    int snap(){return c.size();}
14    void rollback(int snap){
15        while(c.size()>snap){
16            int x=c.back();c.pop_back();
17            si[uf[x]]-=si[x];uf[x]=x;comp++;
18        }
19    }
20 };
21 enum {ADD,DEL,QUERY};
22 struct Query {int type,x,y;};
23 struct DynCon {
24     vector<Query> q;
25     UnionFind dsu;
26     vector<int> mt;
27     map<pair<int,int>,int> last;
28     DynCon(int n):dsu(n){}

```

```

29     void add(int x, int y){
30         if(x>y)swap(x,y);
31         q.pb((Query){ADD,x,y});mt.pb(-1);last[mp(x,y)]=q.size()-1;
32     }
33     void remove(int x, int y){
34         if(x>y)swap(x,y);
35         q.pb((Query){DEL,x,y});
36         int pr=last[mp(x,y)];mt[pr]=q.size()-1;mt.pb(pr);
37     }
38     void query(){q.pb((Query){QUERY,-1,-1});mt.pb(-1);}
39     void process(){ // answers all queries in order
40         if(!q.size())return;
41         for(i,0,q.size())if(q[i].type==ADD&&mt[i]<0)mt[i]=q.size();
42         go(0,q.size());
43     }
44     void go(int s, int e){
45         if(s+1==e){
46             if(q[s].type==QUERY) // answer query using DSU
47                 printf("%d\n",dsu.comp);
48             return;
49         }
50         int k=dsu.snap(),m=(s+e)/2;
51         for(int i=e-1;i>=m;--i)if(mt[i]>=0&&mt[i]<s)dsu.join(q[i].x,q[i].y);
52         go(s,m);dsu.rollback(k);
53         for(int i=m-1;i>=s;--i)if(mt[i]>=e)dsu.join(q[i].x,q[i].y);
54         go(m,e);dsu.rollback(k);
55     }
56 };

```

2.15 Edmond's blossom (matching in general graphs)

```

1 vector<int> g[MAXN];
2 int n,m,mt[MAXN],qh,qt,q[MAXN],ft[MAXN],bs[MAXN];
3 bool inq[MAXN],inb[MAXN],inp[MAXN];
4 int lca(int root, int x, int y){
5     memset(inp,0,sizeof(inp));
6     while(1){
7         inp[x=bs[x]]=true;
8         if(x==root)break;
9         x=ft[mt[x]];
10    }
11    while(1){
12        if(inp[y=bs[y]])return y;

```

```

13     else y=ft[mt[y]];
14 }
15 }
16 void mark(int z, int x){
17     while(bs[x]!=z){
18         int y=mt[x];
19         inb[bs[x]]=inb[bs[y]]=true;
20         x=ft[y];
21         if(bs[x]!=z)ft[x]=y;
22     }
23 }
24 void contr(int s, int x, int y){
25     int z=lca(s,x,y);
26     memset(inb,0,sizeof(inb));
27     mark(z,x);mark(z,y);
28     if(bs[x]!=z)ft[x]=y;
29     if(bs[y]!=z)ft[y]=x;
30     fore(x,0,n)if(inb[bs[x]]){
31         bs[x]=z;
32         if(!inq[x])inq[q[++qt]=x]=true;
33     }
34 }
35 int findp(int s){
36     memset(inq,0,sizeof(inq));
37     memset(ft,-1,sizeof(ft));
38     fore(i,0,n)bs[i]=i;
39     inq[q[qh=qt=0]=s]=true;
40     while(qh<=qt){
41         int x=q[qh++];
42         for(int y:g[x])if(bs[x]!=bs[y]&&mt[x]!=y){
43             if(y==s||mt[y]>=0&&ft[mt[y]]>=0)contr(s,x,y);
44             else if(ft[y]<0){
45                 ft[y]=x;
46                 if(mt[y]<0)return y;
47                 else if(!inq[mt[y]])inq[q[++qt]=mt[y]]=true;
48             }
49         }
50     }
51     return -1;
52 }
53 int aug(int s, int t){
54     int x=t,y,z;
55     while(x>=0){

```

```

56     y=ft[x];
57     z=mt[y];
58     mt[y]=x;mt[x]=y;
59     x=z;
60 }
61 return t>=0;
62 }
63 int edmonds(){ // O(n^2 m)
64     int r=0;
65     memset(mt,-1,sizeof(mt));
66     fore(x,0,n)if(mt[x]<0)r+=aug(x,findp(x));
67     return r;
68 }

```

3 Math

3.1 Identities

$$C_n = \frac{2(2n-1)}{n+1} C_{n-1}$$

$$C_n = \frac{1}{n+1} \binom{2n}{n}$$

$$C_n \sim \frac{4^n}{n^{3/2}\sqrt{\pi}}$$

$$\sigma(n) = O(\log(\log(n))) \text{ (number of divisors of } n)$$

$$F_{2n+1} = F_n^2 + F_{n+1}^2$$

$$F_{2n} = F_{n+1}^2 - F_{n-1}^2$$

$$\sum_{i=1}^n F_i = F_{n+2} - 1$$

$$F_{n+i}F_{n+j} - F_nF_{n+i+j} = (-1)^n F_i F_j$$

(Möbius Inv. Formula) Let $g(n) = \sum_{d|n} f(d)$, then $f(n) = \sum_{d|n} d \mu\left(\frac{n}{d}\right)$.

3.2 Theorems

- 1 (Tutte) A graph, $G = (V, E)$, has a perfect matching **if and only if for**
every subset U of V , the subgraph induced by $V - U$ has at most $|U|$
connected components with an odd number of vertices.
- 2 Petersens Theorem. Every cubic, bridgeless graph contains a perfect
matching.
- 3 (Dilworth) In any finite partially ordered set, the maximum number of
elements in any antichain equals the minimum number of chains in any
partition of the set into chains
- 4 Pick: $A = I + B/2 - 1$ (area of polygon, points inside, points on border)

3.3 Integer floor division

```

1 void floordiv(ll x, ll y, ll& q, ll& r) { // (for negative x)

```

```

2   q=x/y;r=x%y;
3   if((r!=0)&&((r<0)!=(y<0)))q--,r+=y;
4 }

```

3.4 Sieve of Eratosthenes

```

1 int cr[MAXN]; // -1 if prime, some not trivial divisor if not
2 void init_sieve(){
3     memset(cr,-1,sizeof(cr));
4     fore(i,2,MAXN)if(cr[i]<0)for(ll j=1LL*i*i;j<MAXN;j+=i)cr[j]=i;
5 }
6 map<int,int> fact(int n){ // must call init_cribe before
7     map<int,int> r;
8     while(cr[n]>=0)r[cr[n]]++,n/=cr[n];
9     if(n>1)r[n]++;
10    return r;
11 }

```

3.5 Generate divisors

```

1 void div_rec(vector<ll>& r, vector<pair<ll,int> >& f, int k, ll c){
2     if(k==f.size()){r.pb(c);return;}
3     fore(i,0,f[k].snd+1)div_rec(r,f,k+1,c,c*f[k].fst;
4 }
5 vector<ll> divisors(vector<pair<ll,int> > f){
6     vector<ll> r; // returns divisors given factorization
7     div_rec(r,f,0,1);
8     return r;
9 }

```

3.6 Pollard's rho

```

1 ll gcd(ll a, ll b){return a?gcd(b%a,a):b;}
2 ll mulmod(ll a, ll b, ll m) {
3     if(!b)return 0;
4     ll q=mulmod(a,b/2,m);q=(q+q)%m;
5     return b&1?(q+a)%m:q;
6 }
7 ll expmod(ll b, ll e, ll m){
8     if(!e)return 1;
9     ll q=expmod(b,e/2,m);q=mulmod(q,q,m);
10    return e&1?mulmod(b,q,m):q;
11 }
12 bool is_prime_prob(ll n, int a){

```

```

13     if(n==a)return true;
14     ll s=0,d=n-1;
15     while(d%2==0)s++,d/=2;
16     ll x=expmod(a,d,n);
17     if((x==1)|| (x+1==n))return true;
18     fore(_,0,s-1){
19         x=mulmod(x,x,n);
20         if(x==1)return false;
21         if(x+1==n)return true;
22     }
23     return false;
24 }
25 bool rabin(ll n){ // true iff n is prime
26     if(n==1)return false;
27     int ar[]={2,3,5,7,11,13,17,19,23};
28     fore(i,0,9)if(!is_prime_prob(n,ar[i]))return false;
29     return true;
30 }
31 ll rho(ll n){
32     if(!(n&1))return 2;
33     ll x=2,y=2,d=1;
34     ll c=rand()%n+1;
35     while(d==1){
36         x=(mulmod(x,x,n)+c)%n;
37         y=(mulmod(y,y,n)+c)%n;
38         y=(mulmod(y,y,n)+c)%n;
39         if(x>y)d=gcd(x-y,n);
40         else d=gcd(y-x,n);
41     }
42     return d==n?rho(n):d;
43 }
44 void fact(ll n, map<ll,int>& f){ //O (lg n)^3
45     if(n==1)return;
46     if(rabin(n)){f[n]++;return;}
47     ll q=rho(n);fact(q,f);fact(n/q,f);
48 }

```

3.7 Simpson's rule

```

1 double integrate(double f(double), double a, double b, int n=10000){
2     double r=0,h=(b-a)/n,fa=f(a),fb;
3     fore(i,0,n){
4         fb=f(a+h*(i+1));

```



```

5     r+=fa+4*f(a+h*(i+0.5))+fb;fa=fb;
6 }
7 return r*h/6.;
8 }

```

3.8 Polynomials

```

1 typedef int tp; // type of polynomial
2 template<class T=tp>
3 struct poly { // poly<> : 1 variable, poly<poly<>>: 2 variables, etc.
4     vector<T> c;
5     T& operator[](int k){return c[k];}
6     poly(vector<T>& c):c(c){}
7     poly(initializer_list<T> c):c(c){}
8     poly(int k):c(k){}
9     poly(){}
10    poly operator+(poly<T> o){
11        int m=c.size(),n=o.c.size();
12        poly res(max(m,n));
13        fore(i,0,m)res[i]=res[i]+c[i];
14        fore(i,0,n)res[i]=res[i]+o.c[i];
15        return res;
16    }
17    poly operator*(tp k){
18        poly res(c.size());
19        fore(i,0,c.size())res[i]=c[i]*k;
20        return res;
21    }
22    poly operator*(poly o){
23        int m=c.size(),n=o.c.size();
24        poly res(m+n-1);
25        fore(i,0,m)fore(j,0,n)res[i+j]=res[i+j]+c[i]*o.c[j];
26        return res;
27    }
28    poly operator-(poly<T> o){return *this+(o*-1);}
29    T operator()(tp v){
30        T sum(0);
31        for(int i=c.size()-1;i>=0;--i)sum=sum*v+c[i];
32        return sum;
33    }
34 };
35 // example: p(x,y)=2*x^2+3*x*y-y+4
36 // poly<poly<>> p={{4,-1},{0,3},{2}}

```

```

37 // printf("%d\n",p(2)(3)) // 27 (p(2,3))
38 set<tp> roots(poly<> p){ // only for integer polynomials
39     set<tp> r;
40     while(!p.c.empty()&&!p.c.back())p.c.pop_back();
41     if(!p(0))r.insert(0);
42     if(p.c.empty())return r;
43     tp a0=0,an=abs(p[p.c.size()-1]);
44     for(int k=0;!a0;a0=abs(p[k++]));
45     vector<tp> ps,qs;
46     fore(i,1,sqrt(a0)+1)if(a0%i==0)ps.pb(i),ps.pb(a0/i);
47     fore(i,1,sqrt(an)+1)if(an%i==0)qs.pb(i),qs.pb(an/i);
48     for(auto pt:ps)for(auto qt:qs)if(pt%qt==0){
49         tp x=pt/qt;
50         if(!p(x))r.insert(x);
51         if(!p(-x))r.insert(-x);
52     }
53     return r;
54 }
55 pair<poly<>,tp> ruffini(poly<> p, tp r){ // returns pair (result,rem)
56     int n=p.c.size()-1;
57     vector<tp> b(n);
58     b[n-1]=p[n];
59     for(int k=n-2;k>=0;--k)b[k]=p[k+1]+r*b[k+1];
60     return mp(poly<>(b),p[0]+r*b[0]);
61 }
62 // only for double polynomials
63 pair<poly<>,poly<>> polydiv(poly<> p, poly<> q){ // returns pair (
64     result,rem)
65     int n=p.c.size()-q.c.size()+1;
66     vector<tp> b(n);
67     for(int k=n-1;k>=0;--k){
68         b[k]=p.c.back()/q.c.back();
69         fore(i,0,q.c.size())p[i+k]-=b[k]*q[i];
70         p.c.pop_back();
71     }
72     while(!p.c.empty()&&abs(p.c.back())<EPS)p.c.pop_back();
73     return mp(poly<>(b),p);
74 }
75 // only for double polynomials
76 poly<> interpolate(vector<tp> x, vector<tp> y){ //TODO TEST
77     poly<> q={1},S={0};
78     for(tp a:x)q=poly<>((-a,1))*q;
79     fore(i,0,x.size()){

```

```

79     poly<> Li=ruffini(q,x[i]).fst;
80     Li=Li*(1.0/Li(x[i])); // change for int polynomials
81     S=S+Li*y[i];
82 }
83 return S;
84 }

```

3.9 Bairstow

```

1 double pget(poly<> p, int k){return k<p.c.size()?p[k]:0;}
2 poly<> bairstow(poly<> p){ // returns polynomial of degree 2 that
3     int n=p.c.size()-1; // divides p
4     assert(n>=3&&abs(p.c.back())>EPS);
5     double u=p[n-1]/p[n],v=p[n-2]/p[n];
6     fore(_,0,ITER){
7         auto w=polydiv(p,{v,u,1});
8         poly<> q=w.fst,r0=w.snd;
9         poly<> r1=polydiv(q,{v,u,1}).snd;
10        double c=pget(r0,1),d=pget(r0,0),g=pget(r1,1),h=pget(r1,0);
11        double det=1/(v*g*g+h*(h-u*g)),uu=u;
12        u=-det*(-h*c+g*d);v=-det*(-g*v*c+(g*uu-h)*d);
13    }
14    return {v,u,1};
15 }
16 void addr(vector<double>& r, poly<> p){
17     assert(p.c.size()<=3);
18     if(p.c.size()<=1)return;
19     if(p.c.size()==2)r.pb(-p[0]/p[1]);
20     if(p.c.size()==3){
21         double a=p[2],b=p[1],c=p[0];
22         double d=b*b-4*a*c;
23         if(d<-0.1)return; // huge epsilon because of bad precision
24         d=d>0?sqrt(d):0;r.pb((-b-d)/2/a);r.pb((-b+d)/2/a);
25     }
26 }
27 vector<double> roots(poly<> p){
28     while(!p.c.empty()&&abs(p.c.back())<EPS)p.c.pop_back();
29     fore(i,0,p.c.size())p[i]/=p.c.back();
30     vector<double> r;int n;
31     while((n=p.c.size()-1)>=3){
32         poly<> q=bairstow(p);addr(r,q);
33         p=polydiv(p,q).fst;
34     }

```

```

35     while(p.c.size()>n-1)p.c.pop_back();
36 }
37 addr(r,p);
38 return r;
39 }

```

3.10 Fast Fourier Transform

```

1 struct CD { // or typedef complex<double> CD; (but 4x slower)
2     double r,i;
3     CD(double r=0, double i=0):r(r),i(i){}
4     double real()const{return r;}
5     void operator/=(const int c){r/=c, i/=c;}
6 };
7 CD operator*(const CD& a, const CD& b){
8     return CD(a.r*b.r-a.i*b.i,a.r*b.i+a.i*b.r);}
9 CD operator+(const CD& a, const CD& b){return CD(a.r+b.r,a.i+b.i);}
10 CD operator-(const CD& a, const CD& b){return CD(a.r-b.r,a.i-b.i);}
11 const double pi=acos(-1.0);
12 CD cp1[MAXN+9],cp2[MAXN+9]; // MAXN must be power of 2 !!
13 int R[MAXN+9];
14 void dft(CD* a, int n, bool inv){
15     fore(i,0,n)if(R[i]<i)swap(a[R[i]],a[i]);
16     for(int m=2;m<=n;m*=2){
17         double z=2*pi/m*(inv?-1:1);
18         CD wi=CD(cos(z),sin(z));
19         for(int j=0;j<n;j+=m){
20             CD w=1;
21             for(int k=j,k2=j+m/2;k2<j+m;k++,k2++){
22                 CD u=a[k];CD v=a[k2]*w;a[k]=u+v;a[k2]=u-v;w=w*wi;
23             }
24         }
25     }
26     if(inv)fore(i,0,n)a[i]/=n;
27 }
28 vector<int> multiply(vector<int>& p1, vector<int>& p2){
29     int n=p1.size()+p2.size()+1;
30     int m=1,cnt=0;
31     while(m<=n)m+=m,cnt++;
32     fore(i,0,m){R[i]=0;fore(j,0,cnt)R[i]=(R[i]<<1)|((i>>j)&1);}
33     fore(i,0,m)cp1[i]=0,cp2[i]=0;
34     fore(i,0,p1.size())cp1[i]=p1[i];
35     fore(i,0,p2.size())cp2[i]=p2[i];

```

```

36 dft(cp1,m,false);dft(cp2,m,false);
37 fore(i,0,m)cp1[i]=cp1[i]*cp2[i];
38 dft(cp1,m,true);
39 vector<int> res;
40 n-=2;
41 fore(i,0,n)res.pb((ll)floor(cp1[i].real()+0.5));
42 return res;
43 }
    
```

3.11 Fast Hadamard Transform

```

1 ll c1[MAXN+9],c2[MAXN+9]; // MAXN must be power of 2 !!
2 void fht(ll* p, int n, bool inv){
3     for(int l=1;2*l<=n;l*=2){
4         for(int i=0;i<n;i+=2*l){
5             fore(j,0,l){
6                 ll u=p[i+j],v=p[i+l+j];
7                 // XOR
8                 if(!inv)p[i+j]=u+v,p[i+l+j]=u-v;
9                 else p[i+j]=(u+v)/2,p[i+l+j]=(u-v)/2;
10                // AND
11                //if(!inv)p[i+j]=v,p[i+l+j]=u+v;
12                //else p[i+j]=-u+v,p[i+l+j]=u;
13                // OR
14                //if(!inv)p[i+j]=u+v,p[i+l+j]=u;
15                //else p[i+j]=v,p[i+l+j]=u-v;
16            }
17        }
18    }
19 }
20 // like polynomial multiplication, but XORing exponents
21 // instead of adding them (also ANDing, ORing)
22 vector<ll> multiply(vector<ll>& p1, vector<ll>& p2){
23     int n=1<<(32-__builtin_clz(max(SZ(p1),SZ(p2))-1));
24     fore(i,0,n)c1[i]=0,c2[i]=0;
25     fore(i,0,SZ(p1))c1[i]=p1[i];
26     fore(i,0,SZ(p2))c2[i]=p2[i];
27     fht(c1,n,false);fht(c2,n,false);
28     fore(i,0,n)c1[i]*=c2[i];
29     fht(c1,n,true);
30     return vector<ll>(c1,c1+n);
31 }
    
```

3.12 Karatsuba

```

1 typedef ll tp;
2 #define add(n,s,d,k) fore(i,0,n)(d)[i]+=(s)[i]*k
3 tp* ini(int n){tp *r=new tp[n];fill(r,r+n,0);return r;}
4 void karatsura(int n, tp* p, tp* q, tp* r){
5     if(n<=0)return;
6     if(n<35)fore(i,0,n)fore(j,0,n)r[i+j]+=p[i]*q[j];
7     else {
8         int nac=n/2,nbd=n-n/2;
9         tp *a=p,*b=p+nac,*c=q,*d=q+nac;
10        tp *ab=ini(nbd+1),*cd=ini(nbd+1),*ac=ini(nac*2),*bd=ini(nbd*2);
11        add(nac,a,ab,1);add(nbd,b,ab,1);
12        add(nac,c,cd,1);add(nbd,d,cd,1);
13        karatsura(nac,a,c,ac);karatsura(nbd,b,d,bd);
14        add(nac*2,ac,r+nac,-1);
15        add(nbd*2,bd,r+nac,-1);
16        add(nac*2,ac,r,1);
17        add(nbd*2,bd,r+nac*2,1);
18        karatsura(nbd+1,ab,cd,r+nac);
19        free(ab);free(cd);free(ac);free(bd);
20    }
21 }
22 vector<tp> multiply(vector<tp> p0, vector<tp> p1){
23     int n=max(p0.size(),p1.size());
24     tp *p=ini(n),*q=ini(n),*r=ini(2*n);
25     fore(i,0,p0.size())p[i]=p0[i];
26     fore(i,0,p1.size())q[i]=p1[i];
27     karatsura(n,p,q,r);
28     vector<tp> rr(r,r+p0.size()+p1.size()-1);
29     free(p);free(q);free(r);
30     return rr;
31 }
    
```

3.13 Diophantine

```

1 pair<ll,ll> extendedEuclid (ll a, ll b){ //a * x + b * y = gcd(a,b)
2     ll x,y;
3     if (b==0) return mp(1,0);
4     auto p=extendedEuclid(b,a%b);
5     x=p.snd;
6     y=p.fst-(a/b)*x;
7     if(a*x+b*y==gcd(a,b)) x=-x, y=-y;
    
```

```

8   return mp(x,y);
9   }
10  pair<pair<ll,ll>,pair<ll,ll> > diophantine(ll a,ll b, ll r) {
11      //a*x+b*y=r where r is multiple of gcd(a,b);
12      ll d=gcd(a,b);
13      a/=d; b/=d; r/=d;
14      auto p = extendedEuclid(a,b);
15      p.fst*=r; p.snd*=r;
16      assert(a*p.fst+b*p.snd==r);
17      return mp(p,mp(-b,a)); // solutions: p+t*ans.snd
18  }

```

3.14 Modular inverse

```

1  ll inv(ll a, ll mod) { //inverse of a modulo mod
2      assert(gcd(a,mod)==1);
3      pl sol = extendedEuclid(a,mod);
4      return ((sol.fst%mod)+mod)%mod;
5  }

```

3.15 Chinese remainder theorem

```

1  #define mod(a,m) (((a)%m+m)%m)
2  pair<ll,ll> sol(tuple<ll,ll,ll> c){ //requires inv, diophantine
3      ll a=get<0>(c), x1=get<1>(c), m=get<2>(c), d=gcd(a,m);
4      if(d==1) return mp(mod(x1*inv(a,m),m), m);
5      else return x1%d ? mp(-1LL,-1LL) : sol(make_tuple(a/d,x1/d,m/d));
6  }
7  pair<ll,ll> crt(vector< tuple<ll,ll,ll> > cond) { // returns: (sol, lcm)
8      if(cond.size()==1) return sol(cond[0]);
9      ll a1,x1,m1,a2,x2,m2,n=cond.size();
10     tie(a1,x2,m1)=cond[n-1]; tie(a2,x2,m2)=cond[n-2];
11     tie(x1,m1)=sol(cond[n-1]); tie(x2,m2)=sol(cond[n-2]);
12     cond.pop_back();cond.pop_back();
13     if((x1-x2)%gcd(m1,m2)) return mp(-1,-1);
14     else if(m1==m2) cond.pb(make_tuple(1,x1,m1));
15     else {
16         ll k=diophantine(m2,-m1,x1-x2).fst.snd;
17         ll mcm=m1*(m2/gcd(m1,m2)), x=mod((__int128)m1*k+x1,mcm);
18         cond.pb(make_tuple(1,x,mcm));
19     }
20     return crt(cond);
21 } //cond[i]={ai,bi,mi} ai*xi=bi (mi); assumes lcm fits in ll

```

3.16 Mobius

```

1  short mu[MAXN] = {0,1};
2  void mobius(){
3      fore(i,1,MAXN)if(mu[i])for(int j=i+i;j<MAXN;j+=i)mu[j]-=mu[i];
4  }

```

3.17 Matrix operations

```

1  double reduce(vector<vector<double> >& x){ // returns determinant
2      int n=x.size(),m=x[0].size();
3      int i=0,j=0;double r=1.;
4      while(i<n&&j<m){
5          int l=i;
6          fore(k,i+1,n)if(abs(x[k][j])>abs(x[l][j]))l=k;
7          if(abs(x[l][j])<EPS){j++;r=0.;continue;}
8          if(l!=i){r=-r;swap(x[i],x[l]);}
9          r*=x[i][j];
10         for(int k=m-1;k>j;k--)x[i][k]/=x[i][j];
11         fore(k,0,n){
12             if(k==i)continue;
13             for(int l=m-1;l>j;l--)x[k][l]-=x[k][j]*x[i][l];
14         }
15         i++;j++;
16     }
17     return r;
18 }

```

3.18 Simplex

```

1  vector<int> X,Y;
2  vector<vector<double> > A;
3  vector<double> b,c;
4  double z;
5  int n,m;
6  void pivot(int x,int y){
7      swap(X[y],Y[x]);
8      b[x]/=A[x][y];
9      fore(i,0,m)if(i!=y)A[x][i]/=A[x][y];
10     A[x][y]=1/A[x][y];
11     fore(i,0,n)if(i!=x&&abs(A[i][y])>EPS){
12         b[i]-=A[i][y]*b[x];
13         fore(j,0,m)if(j!=y)A[i][j]-=A[i][y]*A[x][j];
14         A[i][y]=-A[i][y]*A[x][y];

```

```

15 }
16 z+=c[y]*b[x];
17 fore(i,0,m)if(i!=y)c[i]-=c[y]*A[x][i];
18 c[y]=-c[y]*A[x][y];
19 }
20 pair<double,vector<double>> simplex( // maximize c^T x s.t. Ax<=b, x>=0
21     vector<vector<double>> _A, vector<double> _b, vector<double> _c){
22     // returns pair (maximum value, solution vector)
23     A=_A;b=_b;c=_c;
24     n=b.size();m=c.size();z=0.;
25     X=vector<int>(m);Y=vector<int>(n);
26     fore(i,0,m)X[i]=i;
27     fore(i,0,n)Y[i]=i+m;
28     while(1){
29         int x=-1,y=-1;
30         double mn=-EPS;
31         fore(i,0,n)if(b[i]<mn)mn=b[i],x=i;
32         if(x<0)break;
33         fore(i,0,m)if(A[x][i]< -EPS){y=i;break;}
34         assert(y>0); // no solution to Ax<=b
35         pivot(x,y);
36     }
37     while(1){
38         double mx=EPS;
39         int x=-1,y=-1;
40         fore(i,0,m)if(c[i]>mx)mx=c[i],y=i;
41         if(y<0)break;
42         double mn=1e200;
43         fore(i,0,n)if(A[i][y]>EPS&&b[i]/A[i][y]<mn)mn=b[i]/A[i][y],x=i;
44         assert(x>0); // c^T x is unbounded
45         pivot(x,y);
46     }
47     vector<double> r(m);
48     fore(i,0,n)if(Y[i]<m)r[Y[i]]=b[i];
49     return mp(z,r);
50 }

```

4 Geometry

4.1 Point

```

1 struct pt { // for 3D add z coordinate
2     double x,y;

```

```

3     pt(double x, double y):x(x),y(y){}
4     pt(){}
5     double norm2(){return *this**this;}
6     double norm(){return sqrt(norm2());}
7     bool operator==(pt p){return abs(x-p.x)<EPS&&abs(y-p.y)<EPS;}
8     pt operator+(pt p){return pt(x+p.x,y+p.y);}
9     pt operator-(pt p){return pt(x-p.x,y-p.y);}
10    pt operator*(double t){return pt(x*t,y*t);}
11    pt operator/(double t){return pt(x/t,y/t);}
12    double operator*(pt p){return x*p.x+y*p.y;}
13    // pt operator^(pt p){ // only for 3D
14    //     return pt(y*p.z-z*p.y,z*p.x-x*p.z,x*p.y-y*p.x);}
15    double angle(pt p){ // redefine acos for values out of range
16        return acos(*this*p/(norm()*p.norm()));}
17    pt unit(){return *this/norm();}
18    double operator%(pt p){return x*p.y-y*p.x;}
19    // 2D from now on
20    bool operator<(pt p)const{ // for convex hull
21        return x<p.x-EPS|| (abs(x-p.x)<EPS&&y<p.y-EPS);}
22    bool left(pt p, pt q){ // is it to the left of directed line pq?
23        return (q-p)%(*this-p)>EPS;}
24    pt rot(pt r){return pt(*this/r,*this*r);}
25    pt rot(double a){return rot(pt(sin(a),cos(a)));}
26 };
27 pt ccw90(1,0);
28 pt cw90(-1,0);

```

4.2 Line

```

1 int sgn2(double x){return x<0?-1:1;}
2 struct ln {
3     pt p,pq;
4     ln(pt p, pt q):p(p),pq(q-p){}
5     ln(){}
6     bool has(pt r){return dist(r)<EPS;}
7     bool seghas(pt r){return has(r)&&(r-p)*(r-(p+pq))-EPS<0;}
8     // bool operator/(ln l){return (pq.unit()^l.pq.unit()).norm()<EPS;} //
9     // 3D
10    bool operator/(ln l){return abs(pq.unit()%l.pq.unit())<EPS;} // 2D
11    bool operator==(ln l){return *this/l&&has(l.p);}
12    pt operator^(ln l){ // intersection
13        if(*this/l)return pt(DINF,DINF);
14        pt r=l.p+l.pq*((p-l.p)%pq/(l.pq%pq));

```

```

14 // if(!has(r)){return pt(NAN,NAN,NAN);} // check only for 3D
15 return r;
16 }
17 double angle(ln l){return pq.angle(l.pq);}
18 int side(pt r){return has(r)?0:sgn2(pq%(r-p));} // 2D
19 pt proj(pt r){return p+pq*((r-p)*pq/pq.norm2());}
20 pt ref(pt r){return proj(r)*2-r;}
21 double dist(pt r){return (r-proj(r)).norm();}
22 // double dist(ln l){ // only 3D
23 // if(*this/l)return dist(l.p);
24 // return abs((l.p-p)*(pq^l.pq))/(pq^l.pq).norm();
25 // }
26 ln rot(auto a){return ln(p,p+pq.rot(a));} // 2D
27 };
28 ln bisector(ln l, ln m){ // angle bisector
29 pt p=l^m;
30 return ln(p,p+l.pq.unit()+m.pq.unit());
31 }
32 ln bisector(pt p, pt q){ // segment bisector (2D)
33 return ln((p+q)*.5,p).rot(ccw90);
34 }

```

4.3 Circle

```

1 struct circle {
2 pt o;double r;
3 circle(pt o, double r):o(o),r(r){}
4 circle(pt x, pt y, pt z){o=bisector(x,y)^bisector(x,z);r=(o-x).norm()
5 ;}
6 bool has(pt p){return (o-p).norm()<r+EPS;}
7 vector<pt> operator^(circle c){ // ccw
8 vector<pt> s;
9 double d=(o-c.o).norm();
10 if(d>r+c.r+EPS||d+min(r,c.r)+EPS<max(r,c.r))return s;
11 double x=(d*d-c.r*c.r+r*r)/(2*d);
12 double y=sqrt(r*r-x*x);
13 pt v=(c.o-o)/d;
14 s.pb(o+v*x-v.rot(ccw90)*y);
15 if(y>EPS)s.pb(o+v*x+v.rot(ccw90)*y);
16 return s;
17 }
18 vector<pt> operator^(ln l){
19 vector<pt> s;

```

```

19 pt p=l.proj(o);
20 double d=(p-o).norm();
21 if(d-EPS>r)return s;
22 if(abs(d-r)<EPS){s.pb(p);return s;}
23 d=sqrt(r*r-d*d);
24 s.pb(p+l.pq.unit()*d);
25 s.pb(p-l.pq.unit()*d);
26 return s;
27 }
28 vector<pt> tang(pt p){
29 double d=sqrt((p-o).norm2()-r*r);
30 return *this^circle(p,d);
31 }
32 bool in(circle c){ // non strict
33 double d=(o-c.o).norm();
34 return d+r<c.r+EPS;
35 }
36 double intertriangle(pt a, pt b){ // area of intersection with oab
37 if(abs((o-a)%(o-b))<EPS)return 0.;
38 vector<pt> q={a},w=*this^ln(a,b);
39 if(w.size()==2)for(auto p:w)if((a-p)*(b-p)<-EPS)q.pb(p);
40 q.pb(b);
41 if(q.size()==4&&(q[0]-q[1])*(q[2]-q[1])>EPS)swap(q[1],q[2]);
42 double s=0;
43 fore(i,0,q.size()-1){
44 if(!has(q[i])||!has(q[i+1]))s+=r*r*(q[i]-o).angle(q[i+1]-o)/2;
45 else s+=abs((q[i]-o)%(q[i+1]-o)/2);
46 }
47 return s;
48 }
49 };
50 vector<double> intercircles(vector<circle> c){
51 vector<double> r(SZ(c)+1); // r[k]: area covered by at least k circles
52 fore(i,0,SZ(c)){ // 0(n^2 log n) (high constant)
53 int k=1;Cmp s(c[i].o);
54 vector<pair<pt,int>> p={
55 mp(c[i].o+pt(1,0)*c[i].r,0),
56 mp(c[i].o-pt(1,0)*c[i].r,0)};
57 fore(j,0,SZ(c))if(j!=i){
58 bool b0=c[i].in(c[j]),b1=c[j].in(c[i]);
59 if(b0&&(!b1||i<j))k++;
60 else if(!b0&&!b1){
61 auto v=c[i]^c[j];

```

```

62     if(SZ(v)==2){
63         p.pb(mp(v[0],1));p.pb(mp(v[1],-1));
64         if(s(v[1],v[0]))k++;
65     }
66 }
67 }
68 sort(p.begin(),p.end(),
69 [&](pair<pt,int> a, pair<pt,int> b){return s(a.fst,b.fst);});
70 fore(j,0,SZ(p)){
71     pt p0=p[j?j-1:SZ(p)-1].fst,p1=p[j].fst;
72     double a=(p0-c[i].o).angle(p1-c[i].o);
73     r[k]+=(p0.x-p1.x)*(p0.y+p1.y)/2+c[i].r*c[i].r*(a-sin(a))/2;
74     k+=p[j].snd;
75 }
76 }
77 return r;
78 }

```

4.4 Polygon

```

1 int sgn(double x){return x<-EPS?-1:x>EPS;}
2 struct pol {
3     int n;vector<pt> p;
4     pol(){
5     pol(vector<pt> _p){p=_p;n=p.size();}
6     double area(){
7         double r=0.;
8         fore(i,0,n)r+=p[i]%p[(i+1)%n];
9         return abs(r)/2; // negative if CW, positive if CCW
10    }
11    pt centroid(){ // (barycenter)
12        pt r(0,0);double t=0;
13        fore(i,0,n){
14            r=r+(p[i]+p[(i+1)%n])*(p[i]%p[(i+1)%n]);
15            t+=p[i]%p[(i+1)%n];
16        }
17        return r/t/3;
18    }
19    bool has(pt q){ // O(n)
20        fore(i,0,n)if(ln(p[i],p[(i+1)%n]).seghas(q))return true;
21        int cnt=0;
22        fore(i,0,n){
23            int j=(i+1)%n;

```

```

24        int k=sgn((q-p[j])%(p[i]-p[j]));
25        int u=sgn(p[i].y-q.y),v=sgn(p[j].y-q.y);
26        if(k>0&&u<0&&v>=0)cnt++;
27        if(k<0&&v<0&&u>=0)cnt--;
28    }
29    return cnt!=0;
30 }
31 void normalize(){ // (call before haslog, remove collinear first)
32     if(p[2].left(p[0],p[1]))reverse(p.begin(),p.end());
33     int pi=min_element(p.begin(),p.end())-p.begin();
34     vector<pt> s(n);
35     fore(i,0,n)s[i]=p[(pi+i)%n];
36     p.swap(s);
37 }
38 bool haslog(pt q){ // O(log(n)) only CONVEX. Call normalize first
39     if(q.left(p[0],p[1])||q.left(p.back(),p[0]))return false;
40     int a=1,b=p.size()-1; // returns true if point on boundary
41     while(b-a>1){ // (change sign of EPS in left
42         int c=(a+b)/2; // to return false in such case)
43         if(!q.left(p[0],p[c]))a=c;
44         else b=c;
45     }
46     return !q.left(p[a],p[a+1]);
47 }
48 pt farthest(pt v){ // O(log(n)) only CONVEX
49     if(n<10){
50         int k=0;
51         fore(i,1,n)if(v*(p[i]-p[k])>EPS)k=i;
52         return p[k];
53     }
54     if(n==SZ(p))p.pb(p[0]);
55     pt a=p[1]-p[0];
56     int s=0,e=n,ua=v*a>EPS;
57     if(!ua&&v*(p[n-1]-p[0])<=EPS)return p[0];
58     while(1){
59         int m=(s+e)/2;pt c=p[m+1]-p[m];
60         int uc=v*c>EPS;
61         if(!uc&&v*(p[m-1]-p[m])<=EPS)return p[m];
62         if(ua&&(!uc|v*(p[s]-p[m])>EPS))e=m;
63         else if(ua|uc|v*(p[s]-p[m])>=-EPS)s=m,a=c,ua=uc;
64         else e=m;
65         assert(e>s+1);
66     }

```



```

67 }
68 pol cut(ln l){ // cut CONVEX polygon by line l
69     vector<pt> q; // returns part at left of l.pq
70     fore(i,0,n){
71         int d0=sgn(l.pq%(p[i]-l.p)),d1=sgn(l.pq%(p[(i+1)%n]-l.p));
72         if(d0>=0)q.pb(p[i]);
73         ln m(p[i],p[(i+1)%n]);
74         if(d0*d1<0&&!(1/m)q.pb(l~m);
75     }
76     return pol(q);
77 }
78 double intercircle(circle c){ // area of intersection with circle
79     double r=0.;
80     fore(i,0,n){
81         int j=(i+1)%n;double w=c.intertriangle(p[i],p[j]);
82         if((p[j]-c.o)%(p[i]-c.o)>0)r+=w;
83         else r-=w;
84     }
85     return abs(r);
86 }
87 double callipers(){ // square distance of most distant points
88     double r=0; // prereq: convex, ccw, NO COLLINEAR POINTS
89     for(int i=0,j=n<2?0:1;i<j;++i){
90         for(;j=(j+1)%n){
91             r=max(r,(p[i]-p[j]).norm2());
92             if((p[(i+1)%n]-p[i])%(p[(j+1)%n]-p[j])<=EPS)break;
93         }
94     }
95     return r;
96 }
97 };
98 // Dynamic convex hull trick
99 vector<pol> w;
100 void add(pt q){ // add(q), O(log^2(n))
101     vector<pt> p={q};
102     while(!w.empty()&&SZ(w.back().p)<2*SZ(p)){
103         for(pt v:w.back().p)p.pb(v);
104         w.pop_back();
105     }
106     w.pb(pol(chull(p)));
107 }
108 ll query(pt v){ // max(q*v:q in w), O(log^2(n))
109     ll r=-INF;

```

```

110     for(auto& p:w)r=max(r,p.farthest(v)*v);
111     return r;
112 }

```

4.5 Plane

```

1 struct plane {
2     pt a,n; // n: normal unit vector
3     plane(pt a, pt b, pt c):a(a),n(((b-a)^(c-a)).unit()){
4     plane(){}
5     bool has(pt p){return abs((p-a)*n)<EPS;}
6     double angle(plane w){return acos(n*w.n);}
7     double dist(pt p){return abs((p-a)*n);}
8     pt proj(pt p){inter(ln(p,p+n),p);return p;}
9     bool inter(ln l, pt& r){
10         double x=n*(l.p+l.pq-a),y=n*(l.p-a);
11         if(abs(x-y)<EPS)return false;
12         r=(l.p*x-(l.p+l.pq)*y)/(x-y);
13         return true;
14     }
15     bool inter(plane w, ln& r){
16         pt nn=n^w.n;
17         pt v=n^nn;
18         double d=w.n*v;
19         if(abs(d)<EPS)return false;
20         pt p=a+v*(w.n*(w.a-a)/d);
21         r=ln(p,p+nn);
22         return true;
23     }
24 };

```

4.6 Radial order of points

```

1 struct Cmp { // IMPORTANT: add const in pt operator -
2     pt r;
3     Cmp(pt r):r(r){}
4     int cuad(const pt &a)const {
5         if(a.x>0&&a.y>=0)return 0;
6         if(a.x<=0&&a.y>0)return 1;
7         if(a.x<0&&a.y<=0)return 2;
8         if(a.x>=0&&a.y<0)return 3;
9         assert(a.x==0&&a.y==0);
10        return -1;
11    }

```

```

12 bool cmp(const pt& p1, const pt& p2) const {
13     int c1=cuad(p1),c2=cuad(p2);
14     if(c1==c2) return p1.y*p2.x<p1.x*p2.y;
15     return c1<c2;
16 }
17 bool operator()(const pt& p1, const pt& p2) const {
18     return cmp(p1-r,p2-r);
19 }
20 };

```

4.7 Convex hull

```

1 // CCW order
2 // Includes collinear points (change sign of EPS in left to exclude)
3 vector<pt> chull(vector<pt> p){
4     vector<pt> r;
5     sort(p.begin(),p.end()); // first x, then y
6     fore(i,0,p.size()){ // lower hull
7         while(r.size()>=2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
8         r.pb(p[i]);
9     }
10    r.pop_back();
11    int k=r.size();
12    for(int i=p.size()-1;i>=0;--i){ // upper hull
13        while(r.size()>=k+2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
14        r.pb(p[i]);
15    }
16    r.pop_back();
17    return r;
18 }

```

4.8 Dual from planar graph

```

1 vector<int> g[MAXN];int n; // input graph (must be connected)
2 vector<int> gd[MAXN];int nd; // output graph
3 vector<int> nodes[MAXN]; // nodes delimiting region (in CW order)
4 map<pair<int,int>,int> ps,es;
5 void get_dual(vector<pt> p){ // p: points corresponding to nodes
6     ps.clear();es.clear();
7     fore(x,0,n){
8         Cmp pc(p[x]); // (radial order of points)
9         auto comp=[&](int a, int b){return pc(p[a],p[b]);};
10        sort(g[x].begin(),g[x].end(),comp);
11        fore(i,0,g[x].size())ps[mp(x,g[x][i])]=i;

```

```

12     }
13     nd=0;
14     fore(xx,0,n)for(auto yy:g[xx])if(!es.count(mp(xx,yy))){
15         int x=xx,y=yy;gd[nd].clear();nodes[nd].clear();
16         while(!es.count(mp(x,y))){
17             es[mp(x,y)]=nd;nodes[nd].pb(y);
18             int z=g[y][(ps[mp(y,x)]+1)%g[y].size()];x=y;y=z;
19         }
20         nd++;
21     }
22     for(auto p:es){
23         pair<int,int> q=mp(p.fst.snd,p.fst.fst);
24         assert(es.count(q));
25         if(es[q]!=p.snd)gd[p.snd].pb(es[q]);
26     }
27     fore(i,0,nd){
28         sort(gd[i].begin(),gd[i].end());
29         gd[i].erase(unique(gd[i].begin(),gd[i].end()),gd[i].end());
30     }
31 }

```

5 Strings

5.1 KMP

```

1 vector<int> kmppre(string& t){ // r[i]: longest border of t[0,i)
2     vector<int> r(t.size()+1);r[0]=-1;
3     int j=-1;
4     fore(i,0,t.size()){
5         while(j>=0&&t[i]!=t[j])j=r[j];
6         r[i+1]=++j;
7     }
8     return r;
9 }
10 void kmp(string& s, string& t){ // find t in s
11     int j=0;vector<int> b=kmppre(t);
12     fore(i,0,s.size()){
13         while(j>=0&&s[i]!=t[j])j=b[j];
14         if(++j==t.size())printf("Match_at_%d\n",i-j+1),j=b[j];
15     }
16 }

```

5.2 Z function

```

1 vector<int> z_function(string& s){
2     int l=0,r=0,n=s.size();
3     vector<int> z(s.size(),0); // z[i] = max k: s[0,k] == s[i,i+k]
4     for(i,1,n){
5         if(i<=r)z[i]=min(r-i+1,z[i-l]);
6         while(i+z[i]<n&&s[z[i]]==s[i+z[i]])z[i]++;
7         if(i+z[i]-1>r)l=i,r=i+z[i]-1;
8     }
9     return z;
10 }

```

5.3 Manacher

```

1 int d1[MAXN]; //d1[i] = max odd palindrome centered on i
2 int d2[MAXN]; //d2[i] = max even palindrome centered on i
3 //s aabbaacaabbaa
4 //d1 111111711111
5 //d2 0103010010301
6 void manacher(string& s){
7     int l=0,r=-1,n=s.size();
8     for(i,0,n){
9         int k=i>r?1:min(d1[l+r-i],r-i);
10        while(i+k<n&&i-k>=0&&s[i+k]==s[i-k])k++;
11        d1[i]=k--;
12        if(i+k>r)l=i-k,r=i+k;
13    }
14    l=0;r=-1;
15    for(i,0,n){
16        int k=i>r?0:min(d2[l+r-i+1],r-i+1);k++;
17        while(i+k<=n&&i-k>=0&&s[i+k-1]==s[i-k-1])k++;
18        d2[i]=--k;
19        if(i+k-1>r)l=i-k,r=i+k-1;
20    }
21 }

```

5.4 Aho-Corasick

```

1 struct vertex {
2     map<char,int> next,go;
3     int p,link;
4     char pch;
5     vector<int> leaf;
6     vertex(int p=-1, char pch=-1):p(p),pch(pch),link(-1){}
7 };

```

```

8 vector<vertex> t;
9 void aho_init(){ //do not forget!!
10     t.clear();t.pb(vertex());
11 }
12 void add_string(string s, int id){
13     int v=0;
14     for(char c:s){
15         if(!t[v].next.count(c)){
16             t[v].next[c]=t.size();
17             t.pb(vertex(v,c));
18         }
19         v=t[v].next[c];
20     }
21     t[v].leaf.pb(id);
22 }
23 int go(int v, char c);
24 int get_link(int v){
25     if(t[v].link<0)
26         if(!v||!t[v].p)t[v].link=0;
27         else t[v].link=get_link(t[v].p),t[v].pch;
28     return t[v].link;
29 }
30 int go(int v, char c){
31     if(!t[v].go.count(c))
32         if(t[v].next.count(c))t[v].go[c]=t[v].next[c];
33         else t[v].go[c]=v==0?0:go(get_link(v),c);
34     return t[v].go[c];
35 }

```

5.5 Suffix automaton

```

1 struct state {int len,link;map<char,int> next;}; //clear next!!
2 state st[100005];
3 int sz,last;
4 void sa_init(){
5     last=st[0].len=0;sz=1;
6     st[0].link=-1;
7 }
8 void sa_extend(char c){
9     int k=sz++,p;
10    st[k].len=st[last].len+1;
11    for(p=last;p!=-1&&!st[p].next.count(c);p=st[p].link)st[p].next[c]=k;
12    if(p==-1)st[k].link=0;

```

```

13 else {
14     int q=st[p].next[c];
15     if(st[p].len+1==st[q].len)st[k].link=q;
16     else {
17         int w=sz++;
18         st[w].len=st[p].len+1;
19         st[w].next=st[q].next;st[w].link=st[q].link;
20         for(;p!=-1&&st[p].next[c]==q;p=st[p].link)st[p].next[c]=w;
21         st[q].link=st[k].link=w;
22     }
23 }
24 last=k;
25 }
26 // input: abcbcbcb
27 // i,link,len,next
28 // 0 -1 0 (a,1) (b,5) (c,7)
29 // 1 0 1 (b,2)
30 // 2 5 2 (c,3)
31 // 3 7 3 (b,4)
32 // 4 9 4 (c,6)
33 // 5 0 1 (c,7)
34 // 6 11 5 (b,8)
35 // 7 0 2 (b,9)
36 // 8 9 6 (c,10)
37 // 9 5 3 (c,11)
38 // 10 11 7
39 // 11 7 4 (b,8)

```

5.6 Suffix array

```

1 #define RB(x) (x<n?r[x]:0)
2 void csort(vector<int>& sa, vector<int>& r, int k){
3     int n=sa.size();
4     vector<int> f(max(255,n),0),t(n);
5     fore(i,0,n)f[RB(i+k)]++;
6     int sum=0;
7     fore(i,0,max(255,n))f[i]=(sum+=f[i])-f[i];
8     fore(i,0,n)t[f[RB(sa[i]+k)]++]=sa[i];
9     sa=t;
10 }
11 vector<int> constructSA(string& s){ // O(n logn)
12     int n=s.size(),rank;
13     vector<int> sa(n),r(n),t(n);

```

```

14     fore(i,0,n)sa[i]=i,r[i]=s[i];
15     for(int k=1;k<n;k*=2){
16         csort(sa,r,k);csort(sa,r,0);
17         t[sa[0]]=rank=0;
18         fore(i,1,n){
19             if(r[sa[i]]!=r[sa[i-1]]||RB(sa[i]+k)!=RB(sa[i-1]+k))rank++;
20             t[sa[i]]=rank;
21         }
22         r=t;
23         if(r[sa[n-1]]==n-1)break;
24     }
25     return sa;
26 }

```

5.7 LCP (Longest Common Prefix)

```

1 vector<int> computeLCP(string& s, vector<int>& sa){
2     int n=s.size(),L=0;
3     vector<int> lcp(n),plcp(n),phi(n);
4     phi[sa[0]]=-1;
5     fore(i,1,n)phi[sa[i]]=sa[i-1];
6     fore(i,0,n){
7         if(phi[i]<0){plcp[i]=0;continue;}
8         while(s[i+L]==s[phi[i]+L])L++;
9         plcp[i]=L;
10        L=max(L-1,0);
11    }
12    fore(i,0,n)lcp[i]=plcp[sa[i]];
13    return lcp; // lcp[i]=LCP(sa[i-1],sa[i])
14 }

```

5.8 Suffix Tree (Ukkonen's algorithm)

```

1 struct SuffixTree {
2     char s[MAXN];
3     map<int,int> to[MAXN];
4     int len[MAXN]={INF},fpos[MAXN],link[MAXN];
5     int node,pos,sz=1,n=0;
6     int make_node(int p, int l){
7         fpos[sz]=p;len[sz]=l;return sz++;}
8     void go_edge(){
9         while(pos>len[to[node][s[n-pos]]]){
10             node=to[node][s[n-pos]];
11             pos-=len[node];

```

```

12     }
13 }
14 void add(int c){
15     s[n++]=c;pos++;
16     int last=0;
17     while(pos>0){
18         go_edge();
19         int edge=s[n-pos];
20         int& v=to[node][edge];
21         int t=s[fpos[v]+pos-1];
22         if(v==0){
23             v=make_node(n-pos,INF);
24             link[last]=node;last=0;
25         }
26         else if(t==c){link[last]=node;return;}
27         else {
28             int u=make_node(fpos[v],pos-1);
29             to[u][c]=make_node(n-1,INF);
30             to[u][t]=v;
31             fpos[v]+=pos-1;len[v]-=pos-1;
32             v=u;link[last]=u;last=u;
33         }
34         if(node==0)pos--;
35         else node=link[node];
36     }
37 }
38 };

```

5.9 Hashing

```

1 struct Hash {
2     int P=1777771,MOD[2],PI[2];
3     vector<int> h[2],pi[2];
4     Hash(string& s){
5         MOD[0]=999727999;MOD[1]=107077777;
6         PI[0]=325255434;PI[1]=10018302;
7         for(k,0,2)h[k].resize(s.size()+1),pi[k].resize(s.size()+1);
8         for(k,0,2){
9             h[k][0]=0;pi[k][0]=1;
10            ll p=1;
11            for(i,1,s.size()+1){
12                h[k][i]=(h[k][i-1]+p*s[i-1])%MOD[k];
13                pi[k][i]=(1LL*pi[k][i-1]*PI[k])%MOD[k];

```

```

14         p=(p*P)%MOD[k];
15     }
16 }
17 }
18 ll get(int s, int e){
19     ll h0=(h[0][e]-h[0][s]+MOD[0])%MOD[0];
20     h0=(1LL*h0*pi[0][s])%MOD[0];
21     ll h1=(h[1][e]-h[1][s]+MOD[1])%MOD[1];
22     h1=(1LL*h1*pi[1][s])%MOD[1];
23     return (h0<<32)|h1;
24 }
25 };

```

5.10 Hashing with ll (using __int128)

```

1 #define bint __int128
2 struct Hash {
3     bint MOD=212345678987654321LL,P=1777771,PI=106955741089659571LL;
4     vector<bint> h,pi;
5     Hash(string& s){
6         assert((P*PI)%MOD==1);
7         h.resize(s.size()+1);pi.resize(s.size()+1);
8         h[0]=0;pi[0]=1;
9         bint p=1;
10        for(i,1,s.size()+1){
11            h[i]=(h[i-1]+p*s[i-1])%MOD;
12            pi[i]=(pi[i-1]*PI)%MOD;
13            p=(p*P)%MOD;
14        }
15    }
16    ll get(int s, int e){
17        return (((h[e]-h[s]+MOD)%MOD)*pi[s])%MOD;
18    }
19 };

```

6 Flow

6.1 Matching (slower)

```

1 vector<int> g[MAXN]; // [0,n)->[0,m)
2 int n,m;
3 int mat[MAXM];bool vis[MAXN];
4 int match(int x){

```

```

5   if(vis[x])return 0;
6   vis[x]=true;
7   for(int y:g[x])if(mat[y]<0||match(mat[y])){mat[y]=x;return 1;}
8   return 0;
9 }
10 vector<pair<int,int> > max_matching(){
11     vector<pair<int,int> > r;
12     memset(mat,-1,sizeof(mat));
13     fore(i,0,n)memset(vis,false,sizeof(vis)),match(i);
14     fore(i,0,m)if(mat[i]>=0)r.pb(mp(mat[i],i));
15     return r;
16 }
    
```

6.2 Matching (Hopcroft-Karp)

```

1 vector<int> g[MAXN]; // [0,n)->[0,m)
2 int n,m;
3 int mt[MAXN],mt2[MAXN],ds[MAXN];
4 bool bfs(){
5     queue<int> q;
6     memset(ds,-1,sizeof(ds));
7     fore(i,0,n)if(mt2[i]<0)ds[i]=0,q.push(i);
8     bool r=false;
9     while(!q.empty()){
10         int x=q.front();q.pop();
11         for(int y:g[x]){
12             if(mt[y]>=0&&ds[mt[y]]<0)ds[mt[y]]=ds[x]+1,q.push(mt[y]);
13             else if(mt[y]<0)r=true;
14         }
15     }
16     return r;
17 }
18 bool dfs(int x){
19     for(int y:g[x])if(mt[y]<0||ds[mt[y]]==ds[x]+1&&dfs(mt[y])){
20         mt[y]=x;mt2[x]=y;
21         return true;
22     }
23     ds[x]=1<<30;
24     return false;
25 }
26 int mm(){
27     int r=0;
28     memset(mt,-1,sizeof(mt));memset(mt2,-1,sizeof(mt2));
    
```

```

29 while(bfs()){
30     fore(i,0,n)if(mt2[i]<0)r+=dfs(i);
31 }
32 return r;
33 }
    
```

6.3 Hungarian

```

1 typedef double th;
2 const th INF=1e18; // to maximize: set INF to 1, use negative values
3 struct Hungarian {
4     int n,m; // important: n must be <=m
5     vector<vector<th> > a;
6     vector<th> u,v;vector<int> p,way; // p: assignment
7     Hungarian(int n, int m):
8         n(n),m(m),a(n+1,vector<th>(m+1,INF-1)),u(n+1),v(m+1),p(m+1),way(m+1){}
9     void set(int x, int y, th v){a[x+1][y+1]=v;}
10    th assign(){
11        fore(i,1,n+1){
12            int j0=0;p[0]=i;
13            vector<th> minv(m+1,INF);
14            vector<char> used(m+1,false);
15            do {
16                used[j0]=true;
17                int i0=p[j0],j1;th delta=INF;
18                fore(j,1,m+1)if(!used[j]){
19                    th cur=a[i0][j]-u[i0]-v[j];
20                    if(cur<minv[j])minv[j]=cur,way[j]=j0;
21                    if(minv[j]<delta)delta=minv[j],j1=j;
22                }
23                fore(j,0,m+1)
24                    if(used[j])u[p[j]]+=delta,v[j]-=delta;
25                else minv[j]-=delta;
26                j0=j1;
27            } while(p[j0]);
28            do {
29                int j1=way[j0];p[j0]=p[j1];j0=j1;
30            } while(j0);
31        }
32        return -v[0]; // cost
33    }
34 };
    
```

6.4 Dinic

```

1 // Min cut: nodes with dist>=0 vs nodes with dist<0
2 // Matching MVC: left nodes with dist<0 + right nodes with dist>0
3 int nodes,src,dst; // remember to init nodes
4 int dist[MAXN],q[MAXN],work[MAXN];
5 struct edge {int to,rev;ll f,cap;};
6 vector<edge> g[MAXN];
7 void add_edge(int s, int t, ll cap){
8     g[s].pb((edge){t,g[t].size(),0,cap});
9     g[t].pb((edge){s,g[s].size()-1,0,0});
10 }
11 bool dinic_bfs(){
12     fill(dist,dist+nodes,-1);dist[src]=0;
13     int qt=0;q[qt++]=src;
14     for(int qh=0;qh<qt;qh++){
15         int u=q[qh];
16         fore(i,0,g[u].size()){
17             edge &e=g[u][i];int v=g[u][i].to;
18             if(dist[v]<0&&e.f<e.cap)dist[v]=dist[u]+1,q[qt++]=v;
19         }
20     }
21     return dist[dst]>=0;
22 }
23 ll dinic_dfs(int u, ll f){
24     if(u==dst)return f;
25     for(int &i=work[u];i<g[u].size();i++){
26         edge &e=g[u][i];
27         if(e.cap<=e.f)continue;
28         int v=e.to;
29         if(dist[v]==dist[u]+1){
30             ll df=dinic_dfs(v,min(f,e.cap-e.f));
31             if(df>0){e.f+=df;g[v][e.rev].f-=df;return df;}
32         }
33     }
34     return 0;
35 }
36 ll max_flow(int _src, int _dst){
37     src=_src;dst=_dst;
38     ll result=0;
39     while(dinic_bfs()){
40         fill(work, work+nodes, 0);
41         while(ll delta=dinic_dfs(src,INF))result+=delta;

```

```

42     }
43     return result;
44 }

```

6.5 Min cost max flow

```

1 typedef ll tf;const tf INFFLUJO=1e14;
2 typedef ll tc;const tc INFCOST0=1e14;
3 struct edge {
4     int u,v;tf cap,flow;tc cost;
5     tf rem(){return cap-flow;}
6 };
7 int nodes; // remember to init nodes
8 vector<int> g[MAXN];
9 vector<edge> e;
10 void add_edge(int u, int v, tf cap, tc cost) {
11     g[u].pb(e.size());e.pb((edge){u,v,cap,0,cost});
12     g[v].pb(e.size());e.pb((edge){v,u,0,0,-cost});
13 }
14 tc dist[MAXN],mncost;
15 int pre[MAXN];
16 tf cap[MAXN],mxflow;
17 bool in_queue[MAXN];
18 void flow(int s, int t){
19     memset(in_queue,0,sizeof(in_queue));
20     mxflow=mncost=0;
21     while(1){
22         fill(dist,dist+nodes,INFCOST0);dist[s]=0;
23         memset(pre,-1,sizeof(pre));pre[s]=0;
24         memset(cap,0,sizeof(cap));cap[s]=INFFLUJO;
25         queue<int> q;q.push(s);in_queue[s]=1;
26         while(q.size()){
27             int u=q.front();q.pop();in_queue[u]=0;
28             fore(_,0,g[u].size()){
29                 int i=g[u][_];
30                 edge &E=e[i];
31                 if(E.rem()&&dist[E.v]>dist[u]+E.cost+1e-9){
32                     dist[E.v]=dist[u]+E.cost;
33                     pre[E.v]=i;
34                     cap[E.v]=min(cap[u],E.rem());
35                     if(!in_queue[E.v])q.push(E.v),in_queue[E.v]=1;
36                 }
37             }

```



```

38     }
39     if(pre[t]<0)break;
40     mxflow+=cap[t];mncost+=cap[t]*dist[t];
41     for(int v=t;v!=s;v=e[pre[v]].u){
42         e[pre[v]].flow+=cap[t];e[pre[v]^1].flow-=cap[t];
43     }
44 }
45 }

```

7 Other

7.1 Mo's algorithm

```

1 int n,sq,nq; // array size, sqrt(array size), #queries
2 struct qu{int l,r,id;};
3 qu qs[MAXN];
4 ll ans[MAXN]; // ans[i] = answer to ith query
5 bool qcomp(const qu &a, const qu &b){
6     if(a.l/sq!=b.l/sq) return a.l<b.l;
7     return (a.l/sq)&1?a.r<b.r:a.r>b.r;
8 }
9 void mos(){
10     fore(i,0,nq)qs[i].id=i;
11     sq=sqrt(n)+.5;
12     sort(qs,qs+nq,qcomp);
13     int l=0,r=0;
14     init();
15     fore(i,0,nq){
16         qu q=qs[i];
17         while(l>q.l)add(--l);
18         while(r<q.r)add(r++);
19         while(l<q.l)remove(l++);
20         while(r>q.r)remove(--r);
21         ans[q.id]=get_ans();
22     }
23 }

```

7.2 Divide and conquer DP optimization

```

1 // O(knlogn). For 2D dps, when the position of optimal choice is non-
   decreasing as the second variable increases
2 int k,n,f[MAXN],f2[MAXN];
3 void doit(int s, int e, int s0, int e0, int i){

```

```

4     // [s,e): range of calculation, [s0,e0): range of optimal choice
5     if(s==e)return;
6     int m=(s+e)/2,r=INF,rp;
7     fore(j,s0,min(e0,m)){
8         int r0=something(i,j); // "something" usually depends on f
9         if(r0<r)r=r0,rp=j; // position of optimal choice
10    }
11    f2[m]=r;
12    doit(s,m,s0,rp+1,i);doit(m+1,e,rp,e0,i);
13 }
14 int doall(){
15     init_base_cases();
16     fore(i,1,k)doit(1,n+1,0,n,i),memcpy(f,f2,sizeof(f));
17     return f[n];
18 }

```

7.3 Dates

```

1 int dateToInt(int y, int m, int d){
2     return 1461*(y+4800+(m-14)/12)/4+367*(m-2-(m-14)/12*12)/12-
3         3*((y+4900+(m-14)/12)/100)/4+d-32075;
4 }
5 void intToDate(int jd, int& y, int& m, int& d){
6     int x,n,i,j;x=jd+68569;
7     n=4*x/146097;x-=(146097*n+3)/4;
8     i=(4000*(x+1))/1461001;x-=1461*i/4-31;
9     j=80*x/2447;d=x-2447*j/80;
10    x=j/11;m=j+2-12*x;y=100*(n-49)+i+x;
11 }

```

7.4 C++ stuff

```

1 // double inf
2 const double DINF=numeric_limits<double>::infinity();
3 // Custom comparator for set/map
4 struct comp {
5     bool operator()(const double& a, const double& b) const {
6         return a+EPS<b;}
7 };
8 set<double,comp> w; // or map<double,int,comp>
9 // Iterate over non empty subsets of bitmask
10 for(int s=m;s=(s-1)&m) // Decreasing order
11 for (int s=0;s=s-m&m;) // Increasing order
12 // Return the numbers the numbers of 1-bit in x

```

```

13 int __builtin_popcount (unsigned int x)
14 // Returns the number of trailing 0-bits in x. x=0 is undefined.
15 int __builtin_ctz (unsigned int x)
16 // Returns the number of leading 0-bits in x. x=0 is undefined.
17 int __builtin_clz (unsigned int x)
18 // x of type long long just add 'll' at the end of the function.
19 int __builtin_popcountll (unsigned long long x)
20 // Get the value of the least significant bit that is one.
21 v=(x&(-x))
    
```

7.5 Interactive problem tester template

```

1 # tester for cf 101021A (guess a number, queries: is it >=k?)
2 import random
3 import subprocess as sp
4 seed = random.randint(0, sys.maxint);random.seed(seed)
5 n=random.randint(1,1000000)
6 try:
7     p=sp.Popen(['./a.out'],stdin=sp.PIPE,stdout=sp.PIPE)
8     it=0
9     s=p.stdout.readline()
10    while it<25 and s and s[0]!='!':
11        k=int(s)
12        assert k>=1 and k<=1000000
13        if n>=k: p.stdin.write('>=\n')
14        else: p.stdin.write('<\n')
15        s=p.stdout.readline()
16        it+=1
17    assert s and s[0]=='!'
18    k=int(s.split()[1])
19    assert k==n
20 except:
21    print 'failed_with_seed_%s' % seed
22    raise
    
```

7.6 Max number of divisors up to 10^n

```

1 (0,1) (1,4) (2,12) (3,32) (4,64) (5,128) (6,240) (7,448) (8,768)
   (9,1344) (10,2304) (11,4032) (12,6720) (13,10752) (14,17280)
   (15,26880) (16,41472) (17,64512) (18,103680)
    
```

7.7 Template

```

1 #include <bits/stdc++.h>
    
```

```

2 #ifdef DEMETRIO
3 #define deb(...) fprintf(stderr,__VA_ARGS__)
4 #define deb1(x) cerr << #x << " = " << x << endl
5 #else
6 #define deb(...) 0
7 #define deb1(x) 0
8 #endif
9 #define pb push_back
10 #define mp make_pair
11 #define fst first
12 #define snd second
13 #define fore(i,a,b) for(int i=a,ThxDem=b;i<ThxDem;++i)
14 #define SZ(x) ((int)x.size())
15 using namespace std;
16 typedef long long ll;
17
18 int main(){
19     return 0;
20 }
    
```