

Table of Contents

Final Exam Practical: 420-635-AB	4
Server Preparation	4
Modify the Hostname	4
Install and Start Apache Server	4
Create the /var/www/exam Directory and Homepage	5
Configure Apache to Serve from /var/www/exam.....	5
Website Creation.....	6
Create the /var/www/exam/q2 Directory and Web Page	6
Configure Access Restriction to 192.168.200.0/24 Subnet	7
Update Homepage to Test Access.....	7
Validating Question 2.....	7
Authentication and Secure Server	8
Create the /secure_exam Directory and Web Page	8
Create the Authentication User	8
Configure Apache Authentication for /secure_exam	8
Create the /secure_exam2 Directory and Web Page	9
Create a .htaccess File in /secure_exam2.....	9
Allow Apache to Read .htaccess for /secure_exam2.....	10
Update the Homepage for Question 3 Hyperlinks.....	10
Validating Question 3.....	11
Validation of /secure_exam Access	11
Access /secure_exam from 192.168.200.1 with user roger	11
Access /secure_exam from 127.0.0.1 (localhost).....	11
Validation of /secure_exam2 Access	12
Access /secure_exam2 from 192.168.200.1	12
Access /secure_exam2 from 127.0.0.1 with user roger	12
DNS and Virtual Hosts	13
Creation of Website Directories and Pages	13

Configuration of Apache Virtual Hosts.....	14
DNS Server Configuration (BIND)	14
Creation of Zone File /var/named/exam.com.zone	15
Validation of DNS Server	16
Update of Exam Homepage Hyperlinks for Question 4.....	17
Validating Question 4	17
CGI/Perl Script	18
Creation of CGI Directory	18
Creation of Perl CGI Script.....	18
Apache Configuration for CGI Access	18
Update of Exam Homepage Hyperlinks	19
Validating Question 5	19

Table of Figures

Figure 1 Hostname successfully changed to server07.exam.com	4
Figure 2 Apache httpd service active and running	4
Figure 3 Homepage with test links	5
Figure 4 server07.exam.com succesfully loaded in web browser	6
Figure 5 Access Denied to /q2 via 127.0.0.1	7
Figure 6 Access Authorized to /q2 via server07.exam.com (192.168.200.1)	7
Figure 7 /secure_exam directory and index page created	8
Figure 8 Creation of authentication user "roger"	8
Figure 9 Apache configuration for /secure_exam requiring IP and authentication	9
Figure 10 /secure_exam2 directory and index page created	9
Figure 11 .htaccess configuration for /secure_exam2	10
Figure 12 Apache configuration to allow .htaccess in /secure_exam2	10
Figure 13 Updated index.html homepage hyperlinks for Question 3	10
Figure 14 Access Authorized to /secure_exam with 192.168.200 and roger	11
Figure 15 Access Denied to /secure_exam with 127.0.0.1	11
Figure 16 Access Authorized to /secure_exam2 with 192.168.200.1	12
Figure 17 Access Authorized to /secure_exam2 with 127.0.0.1 and roger	12
Figure 18 Creation of VirtualHost directories and sample webpages	13
Figure 19 Apache VirtualHost configuration for Final Exam	14
Figure 20 BIND main configuration file named.conf	15
Figure 21 Updated /etc/resolv.conf pointing to local DNS serv	15
Figure 22 exam.com.zone file content	15
Figure 23 Successful DNS resolution of Virtual Hosts	16
Figure 24 Updated Final Exam homepage with Question 4 hyperlinks	17
Figure 25 Final Exam Homepage loaded via 192.168.200.1	17
Figure 26 Access to Virtuel1 VirtualHost	17
Figure 27 Access to Virtuel2 VirtualHost on Port 8000	17
Figure 28 Creation of the /var/www/exam/cgi-bin directory	18
Figure 29 Creation and permission adjustment of the exam.pl Perl script	18
Figure 30 Apache configuration for enabling CGI access and applying IP restrictions	19
Figure 31 Updated Final Exam homepage with Question 5 hyperlinks	19
Figure 32 Successful authorized access from 192.168.200.1	19
Figure 33 Denied access from 127.0.0.1	19

Final Exam Practical: 420-635-AB

Server Preparation

Modify the Hostname

To configure the hostname according to the exam requirements, I used the nmcli tool. then verified the change

```
[root@server07 ~]# nmcli general hostname server07.exam.com  
  
[root@server07 ~]# nmcli general hostname  
server07.exam.com
```

Figure 1 Hostname successfully changed to server07.exam.com

Update the /etc/hosts File

To allow correct testing of hyperlink access in the web browser, I modified the /etc/hosts file to map the hostname to the server's LAN IP.

```
[root@server07 ~]# vim /etc/hosts  
  
192.168.200.1    server07.exam.com
```

Install and Start Apache Server

Apache was installed and started using the following commands.

```
[root@server07 ~]# dnf install -y httpd  
  
[root@server07 ~]# systemctl enable --now httpd  
Created symlink /etc/systemd/system/multi-user.target.wants/httpd.service → /usr/lib/systemd/system/httpd.service.  
  
[root@server07 ~]# systemctl status httpd  
● httpd.service - The Apache HTTP Server  
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)  
   Active: active (running) since Mon 2025-04-28 09:35:36 EDT; 29s ago  
     Docs: man:httpd.service(8)  
   Main PID: 3477 (httpd)
```

Figure 2 Apache httpd service active and running

Create the /var/www/exam Directory and Homepage

I created the /var/www/exam directory and added the required index.html homepage, containing hyperlinks to test all exam tasks.

```
[root@server07 ~]# mkdir -p /var/www/exam
```

```
[root@server07 ~]# vim /var/www/exam/index.html
```

```
<!DOCTYPE html>
<html>
<head>
    <title>Final Exam Homepage</title>
</head>
<body>
    <h1>Welcome to Server07 Exam Homepage</h1>

    <h2>Question 2</h2>
```

Figure 3 Homepage with test links

Configure Apache to Serve from /var/www/exam

I made a backup of the main apache configuration file before making changes and then I edited the Apache configuration file /etc/httpd/conf/httpd.conf to:

- Change DocumentRoot to /var/www/exam
- Update the <Directory> path accordingly.

After restarting the Apache service, the homepage became accessible using the server hostname.

```
[root@server07 ~]# cp /etc/httpd/conf/httpd.conf /etc/httpd/conf/httpd.conf.bak
```

```
DocumentRoot "/var/www/exam"
```

```
<Directory "/var/www/exam">
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
```

```
[root@server07 ~]# httpd -t
Syntax OK
[root@server07 ~]# systemctl restart httpd
[root@server07 ~]#
```




Figure 4 server07.exam.com succesfully loaded in web browser

Website Creation

Create the /var/www/exam/q2 Directory and Web Page

I created the directory /var/www/exam/q2 to host the Question 2 web content.

Inside /q2, I placed a simple index.html page displaying the text "Q2".

```
[root@server07 ~]# mkdir -p /var/www/exam/q2
```

```
[root@server07 ~]# vim /var/www/exam/q2/index.html
```

```
<!DOCTYPE html>
<html>
<head>
    <title>Website "Q2"</title>
</head>
<body>
    <h1>Q2</h1>
</body>
</html>
```

Configure Access Restriction to 192.168.200.0/24 Subnet

I configured Apache to allow access to /q2 **only** for clients in the 192.168.200.0/24 network by adding the following block inside /etc/httpd/conf/httpd.conf:

```
<Directory "/var/www/exam/q2">  
    Require ip 192.168.200.0/24  
</Directory>
```

Update Homepage to Test Access

I updated the homepage (index.html) with two hyperlinks for testing. The first link simulates denied access (localhost 127.0.0.1), and the second simulates authorized access (LAN IP 192.168.200.1).

```
<h2>Question 2</h2>  
<ul>  
  <li><a href="http://127.0.0.1/q2/">Access to Q2 with 127.0.0.1 - Denied</a></li>  
  <li><a href="http://192.168.200.1/q2/">Access to Q2 with 192.168.200 - Authorized</a></li>  
</ul>
```

Validating Question 2

Access from 127.0.0.1 (localhost) results in a **403 Forbidden** error, as expected.

Question 2

- [Access to Q2 with 127.0.0.1 - Denied](http://127.0.0.1/q2/)
- [Access to Q2 with 192.168.200 - Authorized](http://192.168.200.1/q2/)




Figure 5 Access Denied to /q2 via 127.0.0.1

Access from server07.exam.com (resolving to 192.168.200.1) correctly shows the "Q2" web page.

Question 2

- [Access to Q2 with 127.0.0.1 - Denied](http://127.0.0.1/q2/)
- [Access to Q2 with 192.168.200 - Authorized](http://192.168.200.1/q2/)




Figure 6 Access Authorized to /q2 via server07.exam.com (192.168.200.1)

Authentication and Secure Server

Create the /secure_exam Directory and Web Page

I created the directory /var/www/exam/secure_exam and placed a simple web page for testing.

```
[root@server07 ~]# mkdir -p /var/www/exam/secure_exam
```

```
[root@server07 ~]# vim /var/www/exam/secure_exam/index.html
```

```
<!DOCTYPE html>
<html>
<head>
  <title>Secure Exam</title>
</head>
<body>
  <h1>Secure Exam Area</h1>
</body>
</html>
```

Figure 7 /secure_exam directory and index page created

Create the Authentication User

I created the authentication user **roger** with password **exam** using the htpasswd command

```
[root@server07 ~]# htpasswd -bc /var/www/.htpasswd roger exam
Adding password for user roger
```

Figure 8 Creation of authentication user "roger"

Configure Apache Authentication for /secure_exam

I edited /etc/httpd/conf/httpd.conf to secure the /secure_exam directory.

The configuration requires users to satisfy **both** conditions:

- The client must have an IP address of 192.168.200.1
- The client must log in with the username **roger** and the correct password.

The configuration block:


```
<Directory "/var/www/exam/secure_exam">
    AuthType Basic
    AuthName "Restricted Area"
    AuthUserFile /var/www/.htpasswd

    <RequireAll>
        Require ip 192.168.200.1
        Require user roger
    </RequireAll>
</Directory>
```

Figure 9 Apache configuration for /secure_exam requiring IP and authentication

Create the /secure_exam2 Directory and Web Page

I created another directory /var/www/exam/secure_exam2 for the second part of Question 3.

```
[root@server07 ~]# mkdir -p /var/www/exam/secure_exam2
```

```
[root@server07 ~]# vim /var/www/exam/secure_exam2/index.html
```

I placed a basic index.html file for testing inside.

```
<!DOCTYPE html>
<html>
<head>
    <title>Secure Exam 2</title>
</head>
<body>
    <h1>Secure Exam 2 Area</h1>
</body>
</html>
```

Figure 10 /secure_exam2 directory and index page created

Create a .htaccess File in /secure_exam2

I created a .htaccess file inside /secure_exam2 to allow access using **either** condition:

- the client has IP 192.168.200.1
- OR the client successfully logs in as user **roger**.

The .htaccess content:

```
vim /var/www/exam/secure_exam2/.htaccess

AuthType Basic
AuthName "Restricted Area"
AuthUserFile /var/www/.htpasswd
<RequireAny>
    Require ip 192.168.200.1
    Require user roger
</RequireAny>
```

Figure 11 .htaccess configuration for /secure_exam2

Allow Apache to Read .htaccess for /secure_exam2

I updated /etc/httpd/conf/httpd.conf to allow .htaccess overrides for /secure_exam2:

```
[root@server07 ~]# vim /etc/httpd/conf/httpd.conf

<Directory "/var/www/exam/secure_exam2">
    AllowOverride All
</Directory>
```

Figure 12 Apache configuration to allow .htaccess in /secure_exam2

Update the Homepage for Question 3 Hyperlinks

To simplify validation, I updated the /var/www/exam/index.html homepage to include hyperlinks for testing all access scenarios in Question 3.

```
[root@server07 ~]# vim /var/www/exam/index.html

<h2>Question 3</h2>
<ul>
  <li><a href="http://192.168.200.1/secure_exam/">Access to secure_exam with 192.168.200 and roger - Authorised</a></li>
  <li><a href="http://127.0.0.1/secure_exam/">Access to secure_exam with 127.0.0.1 - Denied</a></li>
  <li><a href="http://192.168.200.1/secure_exam2/">Access to secure_exam2 with 192.168.200 and roger - Authorised</a></li>
  <li><a href="http://127.0.0.1/secure_exam2/">Access to secure_exam2 with 127.0.0.1 with roger - Authorised</a></li>
</ul>
```

Figure 13 Updated index.html homepage hyperlinks for Question 3

Validating Question 3

Validation of /secure_exam Access

Access /secure_exam from 192.168.200.1 with user roger

I clicked the hyperlink: http://192.168.200.1/secure_exam/

- Apache prompted for username and password.
- After entering username roger and password exam, access was granted.



Figure 14 Access Authorized to /secure_exam with 192.168.200 and roger

Access /secure_exam from 127.0.0.1 (localhost)

I clicked the hyperlink: http://127.0.0.1/secure_exam/

- Access was denied because neither IP nor credentials satisfied the access control.




Figure 15 Access Denied to /secure_exam with 127.0.0.1

Validation of /secure_exam2 Access

Access /secure_exam2 from 192.168.200.1

I clicked the hyperlink: http://192.168.200.1/secure_exam2/

- Access was automatically authorized based on the IP address alone, without prompting for a password.




Figure 16 Access Authorized to /secure_exam2 with 192.168.200.1

Access /secure_exam2 from 127.0.0.1 with user roger

We clicked the hyperlink: http://127.0.0.1/secure_exam2/

- Apache prompted for username and password.
- After entering username roger and password exam, access was authorized.




Figure 17 Access Authorized to /secure_exam2 with 127.0.0.1 and roger

DNS and Virtual Hosts

Creation of Website Directories and Pages

I created two separate directories for the Virtual Hosts. I created a simple index.html file for each site.

```
[root@server07 ~]# mkdir -p /var/www/exam/q5/virtuel1_80
[root@server07 ~]# mkdir -p /var/www/exam/q5/virtuel2_8000
```

```
[root@server07 ~]# vim /var/www/exam/q5/virtuel1_80/index.html
```

```
<!DOCTYPE html>
<html>
<head>
  <title>Virtuel1 - Port 80</title>
</head>
<body>
  <h1>Welcome to virtuel1.exam.com (Port 80)</h1>
</body>
</html>
```

```
[root@server07 ~]# vim /var/www/exam/q5/virtuel2_8000/index.html
```

```
<!DOCTYPE html>
<html>
<head>
  <title>Virtuel2 - Port 8000</title>
</head>
<body>
  <h1>Welcome to virtuel2.exam.com (Port 8000)</h1>
</body>
</html>
```

Figure 18 Creation of VirtualHost directories and sample webpages

Configuration of Apache Virtual Hosts

I edited /etc/httpd/conf/httpd.conf and added a **default VirtualHost** to access the exam homepage by typing the IP: 192.168.200.1 and two **exam VirtualHosts**.

```
[root@server07 ~]# vim /etc/httpd/conf/httpd.conf
```

```
Listen 80
Listen 8000
```

```
<VirtualHost 192.168.200.1:80>
    DocumentRoot /var/www/exam
</VirtualHost>
```

```
<VirtualHost 192.168.200.1:80>
    ServerName virtuel1.exam.com
    DocumentRoot /var/www/exam/q5/virtuel1_80
</VirtualHost>

<VirtualHost 192.168.200.1:8000>
    ServerName virtuel2.exam.com
    DocumentRoot /var/www/exam/q5/virtuel2_8000
</VirtualHost>
```

Figure 19 Apache VirtualHost configuration for Final Exam

DNS Server Configuration (BIND)

I installed and started the BIND DNS server

```
[root@server07 ~]# dnf install -y bind
```

```
[root@server07 ~]# systemctl enable --now named.service
Created symlink /etc/systemd/system/multi-user.target.wants/named.service → /usr/lib/systemd/system/named.service.
```

I edited /etc/named.conf:

```
vim /etc/named.conf
```

```
options {
    listen-on port 53 { 127.0.0.1; 192.168.200.1; };
    listen-on-v6 port 53 { ::1; };
    directory "/var/named";
    dump-file "/var/named/data/cache_dump.db";
    statistics-file "/var/named/data/named_stats.txt";
    memstatistics-file "/var/named/data/named_mem_stats.txt";
    secroots-file "/var/named/data/named.secroots";
    recursing-file "/var/named/data/named.recursing";
    allow-query { localhost; };
}
```

```
zone "exam.com" IN {
    type master;
    file "/var/named/exam.com.zone";
};
```

Figure 20 BIND main configuration file named.conf

I also manually edited /etc/resolv.conf

```
nameserver 127.0.0.1
```

Figure 21 Updated /etc/resolv.conf pointing to local DNS serv

Creation of Zone File /var/named/exam.com.zone

The zone file /var/named/exam.com.zone contains, This points all the required names to the IP 192.168.200.1:

```
[root@server07 ~]# vim /var/named/exam.com.zone
```

```
$TTL 80000
@      IN      SOA      server07.exam.com. root.exam.com. (
    40          ; Serial
    1D          ; Refresh
    1H          ; Retry
    1W          ; Expire
    3H          ; Minimum TTL
)

@      IN      NS       server07.exam.com.
server07      IN      A       192.168.200.1
virtuel1      IN      A       192.168.200.1
virtuel2      IN      A       1 192.168.200.1
```

Figure 22 exam.com.zone file content

Validation of DNS Server

I validated the DNS setup, all DNS queries correctly resolved to 192.168.200.1.

```
;; ANSWER SECTION:
virtuell1.exam.com.      80000    IN      A       192.168.200.1

;; Query time: 0 msec
;; SERVER: 127.0.0.1#53(127.0.0.1)
;; WHEN: Mon Apr 28 12:45:39 EDT 2025
;; MSG SIZE rcvd: 90

[root@server07 ~]# dig virtuel2.exam.com

; <<>> DiG 9.16.23-RH <<>> virtuel2.exam.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 32067
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
; COOKIE: a7412cfbcd6c39a001000000680fb0ce5835d73de16f06ae (good)
;; QUESTION SECTION:
;virtuel2.exam.com.      IN      A

;; ANSWER SECTION:
virtuel2.exam.com.      80000    IN      A       192.168.200.1

[root@server07 ~]# ping virtuell1.exam.com
PING virtuell1.exam.com (192.168.200.1) 56(84) bytes of data.
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=1 ttl=64 time=0.016 ms
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=2 ttl=64 time=0.083 ms
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=3 ttl=64 time=0.046 ms
^C
--- virtuell1.exam.com ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2067ms
rtt min/avg/max/mdev = 0.016/0.048/0.083/0.027 ms
[root@server07 ~]# ping virtuel2.exam.com
PING virtuel2.exam.com (192.168.200.1) 56(84) bytes of data.
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=1 ttl=64 time=0.014 ms
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=2 ttl=64 time=0.043 ms
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=3 ttl=64 time=0.044 ms
64 bytes from server07.exam.com (192.168.200.1): icmp_seq=4 ttl=64 time=0.050 ms
^C
--- virtuel2.exam.com ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3094ms
rtt min/avg/max/mdev = 0.014/0.037/0.050/0.014 ms
```

Figure 23 Successful DNS resolution of Virtual Hosts

Update of Exam Homepage Hyperlinks for Question 4

I updated the index.html file located in /var/www/exam/ to create the necessary hyperlinks to validate the Virtual Hosts.

```
<h2>Question 4</h2>
<ul>
  <li><a href="http://virtuel1.exam.com/">Access to virtuel1.exam.com port 80</a></li>
  <li><a href="http://virtuel2.exam.com:8000/">Access to virtuel2.exam.com port 8000</a></li>
</ul>
```

Figure 24 Updated Final Exam homepage with Question 4 hyperlinks

Validating Question 4

I accessed the servers via the browser

Question 4

- [Access to virtuel1.exam.com port 80](http://virtuel1.exam.com)
- [Access to virtuel2.exam.com port 8000](http://virtuel2.exam.com:8000)

Figure 25 Final Exam Homepage loaded via 192.168.200.1

Question 4

- [Access to virtuel1.exam.com port 80](http://virtuel1.exam.com)
- [Access to virtuel2.exam.com port 8000](http://virtuel2.exam.com:8000)




Figure 26 Access to Virtuel1 VirtualHost

Question 4

- [Access to virtuel1.exam.com port 80](http://virtuel1.exam.com)
- [Access to virtuel2.exam.com port 8000](http://virtuel2.exam.com:8000)




Figure 27 Access to Virtuel2 VirtualHost on Port 8000

CGI/Perl Script

Creation of CGI Directory

I created the directory /var/www/exam/cgi-bin to store the Perl CGI script:

```
[root@server07 ~]# mkdir -p /var/www/exam/cgi-bin
[root@server07 ~]#
```

Figure 28 Creation of the /var/www/exam/cgi-bin directory

Creation of Perl CGI Script

I created a Perl script named exam.pl inside /var/www/exam/cgi-bin

```
[root@server07 ~]# vim /var/www/exam/cgi-bin/exam.pl

#!/usr/bin/perl

print "Content-type: text/html\n\n";
print "<html><head><title>Examen CGI</title></head><body>";
print "<h1>Examen CGI</h1>";
print "</body></html>";
```

I then made the script executable:

```
[root@server07 ~]# chmod +x /var/www/exam/cgi-bin/exam.pl
```

Figure 29 Creation and permission adjustment of the exam.pl Perl script

Apache Configuration for CGI Access

I edited the Apache configuration file /etc/httpd/conf/httpd.conf to enable CGI execution and restrict access. First, I added a ScriptAlias to map /cgi-bin/ to our custom directory:

```
[root@server07 ~]# vim /etc/httpd/conf/httpd.conf

ScriptAlias /cgi-bin/ "/var/www/exam/cgi-bin/"
```

Then I added a <Directory> block to allow CGI execution and restrict it by IP:

```
<Directory "/var/www/exam/cgi-bin">
  Options +ExecCGI
  AddHandler cgi-script .pl
  Require ip 192.168.200.1
</Directory>
```

Figure 30 Apache configuration for enabling CGI access and applying IP restrictions

Update of Exam Homepage Hyperlinks

I updated /var/www/exam/index.html to add links for Question 5:

```
[root@server07 ~]# vim /var/www/exam/index.html
```

```
<h2>Question 5</h2>
<ul>
  <li><a href="http://192.168.200.1/cgi-bin/exam.pl">CGI/PERL with 192.168.200.1 - Authorised</a></li>
  <li><a href="http://127.0.0.1/cgi-bin/exam.pl">CGI/PERL with 127.0.0.1 - Denied</a></li>
</ul>
```

Figure 31 Updated Final Exam homepage with Question 5 hyperlinks

Validating Question 5

I validated the functionality by accessing the hyperlinks from the "Final Exam" homepage.




Figure 32 Successful authorized access from 192.168.200.1




Figure 33 Denied access from 127.0.0.1