

## 2. Add Two Numbers


Medium

156593387Add to ListShare

You are given two **non-empty** linked lists representing two non-negative integers. The digits are stored in **reverse order**, and each of their nodes contains a single digit. Add the two numbers and return the sum as a linked list.

You may assume the two numbers do not contain any leading zero, except the number 0 itself.

**Example 1:**



**Input:** l1 = [2,4,3], l2 = [5,6,4]

**Output:** [7,0,8]

**Explanation:** 342 + 465 = 807.

**Example 2:**

**Input:** l1 = [0], l2 = [0]

**Output:** [0]

**Example 3:**

**Input:** l1 = [9,9,9,9,9,9,9], l2 = [9,9,9,9]

**Output:** [8,9,9,9,0,0,0,1]

**Constraints:**

- The number of nodes in each linked list is in the range [1, 100].
- $0 \leq \text{Node.val} \leq 9$
- It is guaranteed that the list represents a number that does not have leading zeros.

Accepted

2,415,624

Submissions

6,432,773

Seen this question in a real interview before?

Yes

No

Companies

Related Topics

[Linked List](#)[Math](#)[Recursion](#)

Similar Questions

[Multiply Strings](#)

Medium

[Add Binary](#)

Easy

[Sum of Two Integers](#)

Medium

[Add Strings](#)

Easy

[Add Two Numbers II](#)

Medium

[Add to Array-Form of Integer](#)

Easy

[Add Two Polynomials Represented as Linked Lists](#)

Medium

From <<https://leetcode.com/problems/add-two-numbers/>>

## Solution

### Approach 1: Elementary Math

#### Intuition

Keep track of the carry using a variable and simulate digits-by-digits sum starting from the head of list, which contains the least-significant digit.

*Figure 1. Visualization of the addition of two numbers:  $342 + 465 = 807$*

*Each node contains a single digit and the digits are stored in reverse order.*

#### Algorithm

Just like how you would sum two numbers on a piece of paper, we begin by summing the least-significant digits, which is the head of  $l1$  and  $l2$ . Since each digit is in the range of  $0 \dots 9$ , summing two digits may "overflow". For example  $5 + 7 = 12$ . In this case, we set the current digit to 2 and bring over the carry = 1 to the next iteration. carry must be either 0 or 1 because the largest possible sum of two digits (including the carry) is  $9 + 9 + 1 = 19$ .

The pseudocode is as following:

- Initialize current node to dummy head of the returning list.

- Initialize carry to 00.
- Initialize  $pp$  and  $qq$  to head of  $l1/1$  and  $l2/2$  respectively.
- Loop through lists  $l1/1$  and  $l2/2$  until you reach both ends.
  - Set  $xx$  to node  $pp$ 's value. If  $pp$  has reached the end of  $l1/1$ , set to 00.
  - Set  $yy$  to node  $qq$ 's value. If  $qq$  has reached the end of  $l2/2$ , set to 00.
  - Set  $sum = x + y + carry$ .
  - Update  $carry = sum / 10$ .
  - Create a new node with the digit value of  $(sum \% 10)$  and set it to current node's next, then advance current node to next.
  - Advance both  $pp$  and  $qq$ .
- Check if  $carry = 1$ , if so append a new node with digit 1 to the returning list.
- Return dummy head's next node.

Note that we use a dummy head to simplify the code. Without a dummy head, you would have to write extra conditional statements to initialize the head's value.

Take extra caution of the following cases:

Test case	Explanation
$l1=[0,1]/l1=[0,1]$ $l2=[0,1,2]/l2=[0,1,2]$	When one list is longer than the other.
$l1=[]/l1=[]$ $l2=[0,1]/l2=[0,1]$	When one list is null, which means an empty list.
$l1=[9,9]/l1=[9,9]$ $l2=[1]/l2=[1]$	The sum could have an extra carry of one at the end, which is easy to forget.

### Complexity Analysis

- Time complexity :  $O(\max(m, n))$ . Assume that  $m$  and  $n$  represents the length of  $l1/1$  and  $l2/2$  respectively, the algorithm above iterates at most  $\max(m, n)$  times.
- Space complexity :  $O(\max(m, n))$ . The length of the new list is at most  $\max(m, n) + 1$ .

### Follow up

What if the the digits in the linked list are stored in non-reversed order? For example:

$(3 \rightarrow 4 \rightarrow 2) + (4 \rightarrow 6 \rightarrow 5) = 8 \rightarrow 0 \rightarrow 7$

From <https://leetcode.com/problems/add-two-numbers/solution/>

```
public class addTwoNumbers{
    public ListNode addTwoNumbers(ListNode l1, ListNode l2) {
        ListNode dummyHead = new ListNode(0);
        ListNode p = l1, q = l2, curr = dummyHead;
        int carry = 0;
        while (p != null || q != null) {
            int x = (p != null) ? p.val : 0;
            int y = (q != null) ? q.val : 0;
            int sum = carry + x + y;
            carry = sum / 10;
            curr.next = new ListNode(sum % 10);
            curr = curr.next;
            if (p != null) p = p.next;
            if (q != null) q = q.next;
        }
        if (carry > 0) {
            curr.next = new ListNode(carry);
        }
        return dummyHead.next;
    }
}
```

```
    }  
    public static void main(String[] args) {  
    }  
}
```