










Architecture des Systèmes d'Information


Servlet Listener








Big Picture





Listeners







- <<Java Interface>>
 ServletRequestListener
 javax.servlet
 o requestDestroyed()
 o requestInitialized()
- <<Java Interface>>
 ① ServletContextListener
 javax.servlet

 contextInitialized()
 contextDestroyed()





Listeners





<<Java Interface>>

EventListener

java.util



<<Java Interface>>
 ServletRequestListener
 javax.servlet
 requestDestroyed()
 requestInitialized()


<<Java Interface>>
ServletContextAttributeListener
javax.servlet

attributeAdded()

- attributeRemoved()
- attributeReplaced()







Package javax.servlet.http: Interface







HttpSessionActivationListener	Objects that are bound to a session may listen to container events notifying them that sessions will be passivated and that session will be activated.
HttpSessionAttributeListener	This listener interface can be implemented in order to get notifications of changes to the attribute lists of sessions within this web application.
HttpSessionBindingListener	Causes an object to be notified when it is bound to or unbound from a session.
HttpSessionListener	Implementations of this interface are notified of changes to the list of active sessions in a web application.



Package javax.servlet : Class




ServletContextAttributeEvent	This is the event class for notifications about changes to the attributes of the servlet context of a web application.
ServletContextEvent	This is the event class for notifications about changes to the servlet context of a web application.
ServletRequestAttributeEvent	This is the event class for notifications of changes to the attributes of the servlet request in an application.
ServletRequestEvent	Events of this kind indicate lifecycle events for a ServletRequest.

Package javax.servlet.http: Class



HttpSessionBindingEvent	Events of this type are either sent to an object that implements HttpSessionBindingListener when it is bound or unbound from a session, or to a HttpSessionAttributeListener that has been configured in the deployment descriptor when any attribute is bound, unbound or replaced in a session.
HttpSessionEvent	This is the class representing event notifications for changes to sessions within a web application










€ 0 0	Create Listener	
Create Listene Specify class fi	er le destination.	Mic
Project:	servlet listenner ‡	
Source folder:	/servlet listenner/src	Browse
Java package:	com.fuchs	Browse
Class name:	ContextListenner	
Superclass:		Browse
Use existing	Listener class	
Class name:	ContextListenner	Browse
?	< Back Next > Cancel	Finish






















```
package com.fuchs;
mport javax.servlet.ServletContextEvent;
@/**
   * Application Lifecycle Listener implementation class ContextListenner
 public class ContextListenner implements ServletContextListener {
     public void contextInitialized(ServletContextEvent arg0) {
         System.out.println("ServletContextListener started");
     public void contextDestroyed(ServletContextEvent arg0) {
         System.out.println("ServletContextListener destroyed");
```










Boss 6.x Runtime Server [Boss Application Server Startup Configuration] /System/Library/Java/JavaVirtualMachines/1.6.0.jdk/Contents/Home/bin/Java (2 févr. 2014 11:35:25)


20:52:59,929 INFO [org.jboss.web.tomcat.service.deployers.TomcatDeployment] deploy, ctxPath=/servletlistenner

20:53:00,021 INFO [STDOUT] ServletContextListener started

JBoss 6.x Runtime Server (JBoss Application Server Startup Configuration) | System/Library/Java/JavaVirtualMachines/1.6.0.jdk/Contents/Home/bin/jav [org.jboss.web.tomcat.service.deployers.TomcatDeployment] deploy, ctxPath*/servletlistenner 20:52:59,929 INFO 20:53:00,021 INFO [STDOUT] ServletContextListener started 20:54:49.401 INFO [org.jboss.web.tomcat.service.deployers.TomcatDeployment] undeploy, ctxPath+/servletlistenner 20:54:49,429 INFO [STDOUT] ServletContextListener destroyed







Attribute context listener



```
import java.io.IOException;

  * Servlet implementation class AttribEvent
 public class AttribEvent extends HttpServlet {
     private static final long serialVersionUID = 1L;
     protected void doGet(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
         System.out.println( "Servlet Set context OK");
         PrintWriter out = response.getWriter();
         ServletContext context = getServletContext();
         getServletContext().setAttribute("lastName", "fuchs");
         out.println("My last name is " + context.getAttribute("lastName"));
```







Context attribute listener





```
• import javax.servlet.ServletContextAttributeEvent;
    Application Lifecycle Listener implementation class AttribContextListener
 public class AttribContextListener implements ServletContextAttributeListener, ServletContextListener {
     public void contextInitialized(ServletContextEvent arg0) {
         System.out.println("ServletContextListener started");
     public void attributeAdded(ServletContextAttributeEvent arg0) {
         System.out.println("ServletContextListener Attribute added");
     public void attributeReplaced(ServletContextAttributeEvent arg0) {
         System.out.println("ServletContextListener Attribute replaced");
      public void attributeRemoved(ServletContextAttributeEvent arg0) {
         System.out.println("ServletContextListener Attribute removed");
     public void contextDestroyed(ServletContextEvent arg0) {
         System.out.println("ServletContextListener Context destroyed");
```





JBoss 6.x Runtime S	erver [JBoss Application Server Startup Configuration] /System/Library/Java/JavaVirtualMachines/1.6.0.jdk/Contents/Home/bin/java
17:40:09,878 IN	FO [org.jboss.web.tomcat.service.deployers.TomcatDeployment] deploy, ctxPath=/attribEvent
17:40:09,892 IN	FO [STDOUT] ServletContextListener started
17:40:10,794 IN	FO [STDOUT] Servlet Set context OK
17:40:10,795 IN	FO [STDOUT] ServletContextListener Attribute added
17:40:14,905 IN	FO [org.jboss.web.tomcat.service.deployers.TomcatDeployment] undeploy, ctxPath=/attribEvent
17:40:14,907 IN	[STDOUT] ServletContextListener Context destroyed
17:40:15,011 IN	[Org.jboss.web.tomcat.service.deployers.TomcatDeployment] deploy, ctxPath=/attribEvent
17:40:15,025 IN	FO [STDOUT] ServletContextListener started
17:40:37,410 IN	FO [STDOUT] Servlet Set context OK
17:40:37,411 IN	FO [STDOUT] ServletContextListener Attribute added
17:40:51,659 IN	FO [STDOUT] Servlet Set context OK
17:40:51,660 IN	FO [STDOUT] ServletContextListener Attribute replaced
17:41:08,405 IN	[Org.jboss.web.tomcat.service.deployers.TomcatDeployment] undeploy, ctxPath=/attribEvent
17:41:08,407 IN	[STDOUT] ServletContextListener Context destroyed









Emmanuel fuchs Architecture des Systèmes d'Information