

Started on	Monday, 28 April 2025, 3:17 PM
State	Finished
Completed on	Monday, 28 April 2025, 3:26 PM
Time taken	9 mins 35 secs
Marks	7.00/10.00
Grade	70.00 out of 100.00

Question 1

Complete

Mark 1.00 out of 1.00

```
ExecutorService service = Executors.newFixedThreadPool(2);  
Future<Integer> future1 = service.submit() -> 1);  
Future<Integer> future2 = service.submit() -> 2);  
System.out.print(future1.isDone() + " " + future2.isDone());  
service.shutdown();
```

At the point of printing, what is most likely?

- ☐ a. true false
- ☒ b. Any combination depending on timing
- ☐ c. false false
- ☐ d. true true

Question 2

Complete

Mark 0.00 out of 1.00

What is wrong with this Runnable usage?

```
Runnable r = () -> {  
    Thread.sleep(1000);  
    System.out.println("Done");  
};  
new Thread(r).start();
```

- ☐ a. Thread.sleep must be inside try-catch block
- ☒ b. Multiple threads will be created
- ☐ c. No problem
- ☐ d. Compile-time error due to missing return

Question 3

Complete

Mark 0.00 out of 1.00

What happens for the following code?

```
Callable<String> c = () -> {  
    Thread.sleep(2000);  
    return "Result";  
};  
ExecutorService executor = Executors.newFixedThreadPool(1);  
Future<String> future = executor.submit(c);  
System.out.print(future.get(1, TimeUnit.SECONDS));
```

- ☐ a. TimeoutException
- ☐ b. IllegalStateException
- ☐ c. ExecutionException
- ☒ d. "Result" will be printed

Question 4

Complete

Mark 1.00 out of 1.00

What will happen when the following code is executed?

```
class MyCallable implements Callable<Integer> {  
    public Integer call() {  
        return 100;  
    }  
}  
  
public class Test {  
    public static void main(String[] args) {  
        ExecutorService service = Executors.newSingleThreadExecutor();  
        Future<Integer> future = service.submit(new MyCallable());  
        service.shutdown();  
    }  
}
```

- ☐ a. call() will never be executed because get() is missing.
- ☐ b. Compile-time error.
- ☐ c. call() will throw an exception.
- ☒ d. call() will still be executed even without future.get().

Question 5

Complete

Mark 1.00 out of 1.00

What will be the output of the following code?

```
class MyRunnable implements Runnable {  
    public void run() {  
        System.out.print("Runnable");  
    }  
}  
  
public class Test {  
    public static void main(String[] args) {  
        Thread t = new Thread(new MyRunnable());  
        t.start();  
    }  
}
```

- ☒ a. Runnable
- ☐ b. Compile-time error
- ☐ c. No output
- ☐ d. Runtime exception

Question 6

Complete

Mark 1.00 out of 1.00

In the following code, how many threads are created?

```
public class Test {  
    public static void main(String[] args) {  
        ExecutorService service = Executors.newFixedThreadPool(5);  
        for (int i = 0; i < 10; i++) {  
            service.submit(() -> System.out.print(Thread.currentThread().getName() + " "));  
        }  
        service.shutdown();  
    }  
}
```

- ☒ a. 5
- ☐ b. 10
- ☐ c. Depends on JVM
- ☐ d. 15

Question 7

Complete

Mark 0.00 out of 1.00

In this code, what type does the Future hold?

```
Future<?> future = executor.submit() -> System.out.println("Task");
```

- ☒ a. Future<String>
- ☐ b. Future<Object>
- ☐ c. Future<Integer>
- ☐ d. Future<Void>

Question 8

Complete

Mark 1.00 out of 1.00

Identify the problem in the following code:

```
class MyTask implements Runnable {  
    public String run() {  
        return "Hello";  
    }  
}
```

- ☐ a. Valid code
- ☐ b. Infinite loop
- ☐ c. Runtime exception
- ☒ d. Compile-time error because Runnable.run() must return void

Question 9

Complete

Mark 1.00 out of 1.00

What will be the output?

```
class MyCallable implements Callable<String> {  
    public String call() {  
        return "Callable";  
    }  
}  
  
public class Test {  
    public static void main(String[] args) throws Exception {  
        FutureTask<String> task = new FutureTask<>(new MyCallable());  
        new Thread(task).start();  
        System.out.print(task.get());  
    }  
}
```

- ☐ a. Runtime exception
- ☐ b. null
- ☒ c. Callable
- ☐ d. Compile-time error

Question 10

Complete

Mark 1.00 out of 1.00

What happens in this code?

```
ExecutorService executor = Executors.newSingleThreadExecutor();  
Future<String> future = executor.submit() -> {  
    throw new RuntimeException("Error occurred!");  
});  
future.get();
```

- ☐ a. Future returns null
- ☐ b. Thread terminates silently
- ☒ c. ExecutionException is thrown when get() is called
- ☐ d. No Exception is thrown