

Ex. No: 6

```
CREATE TABLE customer (sid NUMBER PRIMARY KEY, sname  
VARCHAR2(30), salary NUMBER);
```

Output:

Table created.

```
INSERT INTO customer VALUES (1, 'Aarthi', 300);  
INSERT INTO customer VALUES (2, 'Ramya', 500);  
INSERT INTO customer VALUES (3, 'Sakthi', 670);
```

Output:

3 rows created.

BEFORE UPDATE Trigger:

```
CREATE OR REPLACE TRIGGER up_classd  
BEFORE UPDATE ON customer  
FOR EACH ROW  
BEGIN  
    DBMS_OUTPUT.PUT_LINE('new value is ' || :new.salary);  
    DBMS_OUTPUT.PUT_LINE('old value is ' || :old.salary);  
END;  
/
```

Output:

Trigger created.

```
UPDATE customer SET salary = 500 WHERE sid = 1;
```

Output:

*new value is 500
old value is 300
1 row updated.*

```
SELECT * FROM customer;
```

Output:

SID	SNAME	SALARY
1	Aarthi	500
2	Ramya	500
3	Sakthi	670

BEFORE DELETE Trigger:

```
CREATE OR REPLACE TRIGGER del_classb
BEFORE DELETE ON customer
FOR EACH ROW
BEGIN
    DBMS_OUTPUT.PUT_LINE('row deleted');
END;
/
```

Output:

Trigger created.

```
DELETE FROM customer WHERE sid = 1;
```

Output:

row deleted
1 row deleted.

```
SELECT * FROM customer;
```

Output:

SID	SNAME	SALARY
2	Ramya	500
3	Sakthi	670

```
CREATE TABLE classb (sid NUMBER, sname VARCHAR2(20), dept
VARCHAR2(10), stotal NUMBER, grade VARCHAR2(2));
```

Output:

Table created.

BEFORE INSERT Trigger:

```
CREATE OR REPLACE TRIGGER ins_classb
BEFORE INSERT ON classb
FOR EACH ROW
DECLARE
    InvTot EXCEPTION;
BEGIN
    IF :new.stotal > 1000 THEN
        RAISE InvTot;
    END IF;
```

```
EXCEPTION
  WHEN InvTot THEN
    RAISE_APPLICATION_ERROR(-20000, 'Total not valid');
END;
/
```

Output:

Trigger created.

```
INSERT INTO classb VALUES (5, 'vino', 'it', 500, 'a');
```

Output:

1 row created.

```
INSERT INTO classb VALUES (6, 'jana', 'it', 2000, 'a');
```

Output:

ERROR at line 1:

ORA-20000: Total not valid

ORA-06512: at "SCOTT.INS_CLASSB", line 11

ORA-04088: error during execution of trigger 'SCOTT.INS_CLASSB'