


Lexical Analyzer (Scanner)

Lexical Analyzer

- **Lexical Analyzer** reads the source program character by character to produce tokens.
- Normally a lexical analyzer doesn't return a list of tokens at one shot, it returns a token when the parser asks a token from it.



Why to separate Lexical Analyzer And parsing

- Simplicity of design
- Improving compiler efficiency
- Enhancing compiler portability

Tokens, Lexemes, Patterns

- A *token* is a pair - a token name and an optional token value
 - For example: **id** and **num**
- *Lexemes* are sequence of characters in the source program that matches pattern for a token
 - For example: **abc** and **1233**
- *Patterns* are rules describing the set of lexemes belonging to a token
 - For example: “*letter followed by letters and digits*” and “*non-empty sequence of digits*”

Example

Token	Informal description	Sample lexemes
if	Characters I ,f	If
Comparison	< , > , <= , >=	<= . !=
Number	Any numeric constant	3.14,0
literal	Anything but “ surrounded by”	“core dumped”
id	Letters followed by letters and digit	Pi,D2

Example

$E = M * C ** 2$

- <id, symbol table entry for E>
- < assign – op>
- <id, symbol table entry for M>
- < mult – op>
- <id, symbol table entry for C>
- <exp – op>
- <number , interger value 2 >

Lexical Errors

- Unterminated comments
- Length of longest identifier
- Invalid identifiers
- Invalid constants
- Invalid symbols

Handwritten blue text: C1(12) C5

Lexical Errors

- Delete one character from the remaining input
- Insert a missing character into the remaining input
- Replace a character by another character

Specification of Token

- Any language has an alphabet which defines the characters or symbols that language can have.
- In theory of compilation regular expression are used to formalize the specification of tokens
- Example :
 - `letter(letter | digit)*`
- Each regular expression is a pattern specifying the form of strings

Regular Expressions

- We use regular expressions to describe tokens of a programming language.
- A regular expression is built up of simpler regular expressions (using defining rules)
- Each regular expression denotes a language.
- A language denoted by a regular expression is called as a **regular set**.

Terminology of Languages

- **Alphabet** : a finite set of symbols (ASCII characters)
- **String** :
 - Finite sequence of symbols on an alphabet
 - Sentence and word are also used in terms of string
 - ϵ is the empty string
 - $|s|$ is the length of string s .
- **Language**: sets of strings over some fixed alphabet
 - \emptyset the empty set is a language.
 - $\{\epsilon\}$ the set containing empty string is a language
 - The set of well-formed C programs is a language
 - The set of all possible identifiers is a language.

Operations on Languages

- Concatenation:

- $L_1 L_2 = \{ s_1 s_2 \mid s_1 \in L_1 \text{ and } s_2 \in L_2 \}$

- Union

- $L_1 \cup L_2 = \{ s \mid s \in L_1 \text{ or } s \in L_2 \}$

Example

- $L_1 = \{a,b,c,d\}$ $L_2 = \{1,2\}$
- $L_1 L_2 = \{a1,a2,b1,b2,c1,c2,d1,d2\}$
- $L_1 \cup L_2 = \{a,b,c,d,1,2\}$
- $L_1^3 =$ all strings with length three (using a,b,c,d)
- $L_1^* =$ all strings using letters a,b,c,d and empty string
- $L_1^+ =$ doesn't include the empty string

Regular Expressions (Rules)

Regular expressions over alphabet Σ

<u>Reg. Expr</u>	<u>Language it denotes</u>
ε	$\{\varepsilon\}$
$a \in \Sigma$	$\{a\}$
$(r_1) \mid (r_2)$	$L(r_1) \cup L(r_2)$
$(r_1) (r_2)$	$L(r_1) L(r_2)$
$(r)^*$	$(L(r))^*$
(r)	$L(r)$

- $(r)^+ = (r)(r)^*$
- $(r)? = (r) \mid \varepsilon$


Regular Expressions (cont.)

- Ex:
 - $\Sigma = \{0,1\}$
 - $0|1 \Rightarrow \{0,1\}$
 - $(0|1)(0|1) \Rightarrow \{00,01,10,11\}$
 - $0^* \Rightarrow \{\varepsilon, 0, 00, 000, 0000, \dots\}$
 - $(0|1)^* \Rightarrow$ all strings with 0 and 1, including the empty string
 - $0(0|1)^*0 \Rightarrow$ All binary strings of length at least 2, starting and ending with 0's
 - $(0|1)^*0(0|1)(0|1)(0|1) :$ All binary strings with at least three characters in which the 3rd last character is always 0

Recognition of tokens

- Digit - [0-9]
- Digits – digit+
- Letter – [A-Za-z_]
- Id – letter(letter|digit)*
- If – if
- Then – then
- Else – else
- Relop - < | > | <= | >= | = | < >

Recognition of tokens



Disambiguation Rules

- 1) **longest match rule:** from all tokens that match the input prefix, choose the one that matches the most characters
- 2) **rule priority:** if more than one token has the longest match, choose the one listed first

Examples:

- for8 is it the for-keyword, the identifier “f”, the identifier “fo”, the identifier “for”, or the identifier “for8”?
Use rule 1: “for8” matches the most characters.
- for is it the for-keyword, the identifier “f”, the identifier “fo”, or the identifier “for”?
Use rule 1 & 2: the for-keyword and the “for” identifier have the longest match but the for-keyword is listed first.

How Scanner Generators Work


- Translate REs into a finite state machine
- Done in three steps:
 - 1) translate REs into a no-deterministic finite automaton (NFA)
 - 2) translate the NFA into a deterministic finite automaton (DFA)
 - 3) optimize the DFA (optional)

Finite Automata

- A *recognizer* for a language is a program that takes a string x , and answers “yes” if x is a sentence of that language, and “no” otherwise.
- We call the recognizer of the tokens as a *finite automaton*.
- A finite automaton can be: *deterministic*(DFA) or *non-deterministic* (NFA)
- This means that we may use a deterministic or non-deterministic automaton as a lexical analyzer.
- Both deterministic and non-deterministic finite automaton recognize regular sets.
- Which one?
 - deterministic – faster recognizer, but it may take more space
 - non-deterministic – slower, but it may take less space
 - Deterministic automata are widely used lexical analyzers.
- First, we define regular expressions for tokens; Then we convert them into a DFA to get a lexical analyzer for our tokens.
 - Algorithm1: Regular Expression \rightarrow NFA \rightarrow DFA (two steps: first to NFA, then to DFA)
 - Algorithm2: Regular Expression \rightarrow DFA (directly convert a regular expression into a DFA)

Deterministic Finite Automaton (DFA)

- A Deterministic Finite Automaton (DFA) is a special form of a NFA.
 - no state has ϵ - transition
 - for each symbol **a** and state **s**, there is at most one labeled edge **a** leaving **s**.
i.e. transition function is from pair of state-symbol to state (not set of states)



The language recognized by
this DFA is also $(a|b)^* a b$

Non-Deterministic Finite Automaton (NFA)


- A non-deterministic finite automaton (NFA) is a mathematical model that consists of:
 - S - a set of states
 - Σ - a set of input symbols (alphabet)
 - move – a transition function move to map state-symbol pairs to sets of states.
 - s_0 - a start (initial) state
 - F – a set of accepting states (final states)
- ϵ - transitions are allowed in NFAs. In other words, we can move from one state to another one without consuming any symbol.
- A NFA accepts a string x , if and only if there is a path from the starting state to one of accepting states such that edge labels along this path spell out x .

Converting A Regular Expression into A NFA (Thomson's Construction)


- This is one way to convert a regular expression into a NFA.
- There can be other ways (much efficient) for the conversion.
- Thomson's Construction is simple and systematic method.
It guarantees that the resulting NFA will have exactly one final state, and one start state.
- Construction starts from simplest parts (alphabet symbols).
To create a NFA for a complex regular expression, NFAs of its sub-expressions are combined to create its NFA,

Thomson's Construction (cont.)


- To recognize an empty string ε



- To recognize a symbol a in the alphabet Σ




- If $N(r_1)$ and $N(r_2)$ are NFAs for regular expressions r_1 and r_2
 - For regular expression $r_1 \mid r_2$



NFA for $r_1 \mid r_2$

Thomson's Construction (cont.)


- For regular expression $r_1 r_2$



Final state of $N(r_2)$ become final state of $N(r_1 r_2)$






NFA for $r_1 r_2$

- For regular expression r^*



NFA for r^*

Thomson's Construction (Example - $(a|b)^* a$)



Converting a NFA into a DFA (subset construction)

put ϵ -closure($\{s_0\}$) as an unmarked state into the set of DFA (DS)

while (there is one unmarked S_1 in DS) do

begin

mark S_1

for each input symbol a do

begin

$S_2 \leftarrow \epsilon$ -closure(move(S_1, a))

if (S_2 is not in DS) then

add S_2 into DS as an unmarked state

transfunc[S_1, a] $\leftarrow S_2$

end

end


ϵ -closure($\{s_0\}$) is the set of all states can be accessible from s_0 by ϵ -transition.

set of states to which there is a transition on a from a state s in S_1



- a state S in DS is an accepting state of DFA if a state in S is an accepting state of NFA
- the start state of DFA is ϵ -closure($\{s_0\}$)

Converting a NFA into a DFA (Example)



$$S_0 = \varepsilon\text{-closure}(\{0\}) = \{0,1,2,4,7\}$$

S_0 into DS as an unmarked state

\Downarrow mark S_0

$$\varepsilon\text{-closure}(\text{move}(S_0, a)) = \varepsilon\text{-closure}(\{3,8\}) = \{1,2,3,4,6,7,8\} = S_1$$

S_1 into DS

$$\varepsilon\text{-closure}(\text{move}(S_0, b)) = \varepsilon\text{-closure}(\{5\}) = \{1,2,4,5,6,7\} = S_2$$

S_2 into DS

$$\text{transfunc}[S_0, a] \leftarrow S_1$$

$$\text{transfunc}[S_0, b] \leftarrow S_2$$

\Downarrow mark S_1

$$\varepsilon\text{-closure}(\text{move}(S_1, a)) = \varepsilon\text{-closure}(\{3,8\}) = \{1,2,3,4,6,7,8\} = S_1$$

$$\varepsilon\text{-closure}(\text{move}(S_1, b)) = \varepsilon\text{-closure}(\{5\}) = \{1,2,4,5,6,7\} = S_2$$

$$\text{transfunc}[S_1, a] \leftarrow S_1$$

$$\text{transfunc}[S_1, b] \leftarrow S_2$$

\Downarrow mark S_2

$$\varepsilon\text{-closure}(\text{move}(S_2, a)) = \varepsilon\text{-closure}(\{3,8\}) = \{1,2,3,4,6,7,8\} = S_1$$

$$\varepsilon\text{-closure}(\text{move}(S_2, b)) = \varepsilon\text{-closure}(\{5\}) = \{1,2,4,5,6,7\} = S_2$$

$$\text{transfunc}[S_2, a] \leftarrow S_1$$

$$\text{transfunc}[S_2, b] \leftarrow S_2$$

Converting a NFA into a DFA (Example – cont.)

S_0 is the start state of DFA since 0 is a member of $S_0 = \{0, 1, 2, 4, 7\}$

S_1 is an accepting state of DFA since 8 is a member of $S_1 = \{1, 2, 3, 4, 6, 7, 8\}$

