

Interchange: Interchange Tags Reference

Table of Contents

<u>1. Interchange Tags Reference.....</u>	<u>1</u>
<u>1.1. Looping tags and Sub-tags.....</u>	<u>2</u>
<u>2. TAGS.....</u>	<u>9</u>
<u>2.1. accessories.....</u>	<u>9</u>
<u>2.2. and.....</u>	<u>14</u>
<u>2.3. area.....</u>	<u>15</u>
<u>2.4. attr_list.....</u>	<u>16</u>
<u>2.5. banner.....</u>	<u>17</u>
<u>2.6. bounce.....</u>	<u>18</u>
<u>2.7. calc.....</u>	<u>19</u>
<u>2.8. cart.....</u>	<u>19</u>
<u>2.9. catch.....</u>	<u>20</u>
<u>2.10. cgi.....</u>	<u>20</u>
<u>2.11. checked.....</u>	<u>21</u>
<u>2.12. control.....</u>	<u>22</u>
<u>2.13. control_set.....</u>	<u>23</u>
<u>2.14. counter.....</u>	<u>23</u>
<u>2.15. currency.....</u>	<u>24</u>
<u>2.16. data.....</u>	<u>25</u>
<u>2.17. default.....</u>	<u>26</u>
<u>2.18. description.....</u>	<u>26</u>
<u>2.19. discount.....</u>	<u>27</u>
<u>2.20. dump.....</u>	<u>29</u>
<u>2.21. ecml.....</u>	<u>29</u>
<u>2.22. either.....</u>	<u>30</u>
<u>2.23. error.....</u>	<u>30</u>
<u>2.24. export.....</u>	<u>32</u>
<u>2.25. field.....</u>	<u>33</u>
<u>2.26. file.....</u>	<u>33</u>
<u>2.27. filter.....</u>	<u>34</u>
<u>2.28. flag.....</u>	<u>39</u>
<u>2.29. fly_list.....</u>	<u>39</u>
<u>2.30. fly_tax.....</u>	<u>40</u>
<u>2.31. goto.....</u>	<u>41</u>
<u>2.32. handling.....</u>	<u>41</u>
<u>2.33. harness.....</u>	<u>42</u>
<u>2.34. html_table.....</u>	<u>42</u>
<u>2.35. if.....</u>	<u>43</u>
<u>2.36. import.....</u>	<u>48</u>
<u>2.37. include.....</u>	<u>49</u>
<u>2.38. index.....</u>	<u>50</u>
<u>2.39. input_filter.....</u>	<u>50</u>
<u>2.40. item_list.....</u>	<u>51</u>
<u>2.41. label.....</u>	<u>54</u>
<u>2.42. log.....</u>	<u>54</u>
<u>2.43. loop.....</u>	<u>55</u>

Table of Contents

2.44. mail	57
2.45. mvasp	58
2.46. nitems	59
2.47. onfly	59
2.48. options	60
2.49. or	60
2.50. order	61
2.51. page	62
2.52. perl	65
2.53. price	67
2.54. process	69
2.55. profile	69
2.56. query	70
2.57. read_cookie	70
2.58. record	71
2.59. region	71
2.60. row	72
2.61. salestax	73
2.62. scratch	74
2.63. scratchd	74
2.64. search_region	75
2.65. selected	75
2.66. set	76
2.67. set_cookie	77
2.68. seti	78
2.69. setlocale	78
2.70. shipping	79
2.71. shipping_desc	79
2.72. soap	80
2.73. sql	80
2.74. strip	81
2.75. subtotal	81
2.76. tag	82
2.77. time	84
2.78. timed_build	86
2.79. tmp	88
2.80. total_cost	88
2.81. tree	89
2.82. try	93
2.83. update	93
2.84. userdb	94
2.85. value	95
2.86. value_extended	96
3. User-defined Tags	99

1. Interchange Tags Reference

ITL stands for Interchange Tag Language. ITL is a superset of MML, or Minivend Markup Language. Minivend was the predecessor to Interchange.

There are dozens of ITL pre-defined tag functions. If you don't see just what you need, you can create user-defined tags to just as powerful as the pre-defined ones.

There are two styles of supplying parameters to a tag — named and positional. In addition, you can usually embed Interchange tags within HTML tags.

In the named style you supply a parameter/value pair just as most HTML tags use:

```
[value name="foo"]
```

The same thing can be accomplished for the [value] tag with

```
[value foo]
```

The parameter name is the first positional parameter for the [value] tag. Some people find positional usage simpler for common tags, and Interchange interprets them somewhat faster. If you wish to avoid ambiguity you can always use named calling.

In most cases, tags specified in the positional fashion will work the same as named parameters. The only time you will need to modify them is when there is some ambiguity as to which parameter is which (usually due to whitespace), or when you need to use the output of a tag as the attribute parameter for another tag.

TIP: This will not work:

```
[page scan se=[scratch somevar]]
```

To get the output of the [scratch somevar] interpreted, you must place it within a named and quoted attribute:

```
[page href=scan arg="se=[scratch somevar]"]
```

Interchange tags can be specified within HTML to make it easier to interface to some HTML editors. Consider:

```
<TABLE MV="if items">
<TR MV="item-list">
<TD> [item-code] </TD>
<TD> [item-description] </TD>
<TD> [item-price] </TD>
</TR></TABLE>
```

The above will loop over any items in the shopping cart, displaying their part number, description, and price, but only IF there are items in the cart.

The same thing can be achieved with:

```
[if items]
```

```

<TABLE>
[item-list]
<TR>
<TD> [item-code] </TD>
<TD> [item-description] </TD>
<TD> [item-price] </TD>
</TR>
[/item-list]</TABLE>
[/if]

```

What is done with the results of the tag depends on whether it is a *container* or *standalone* tag. A container tag is one which has an end tag, i.e. [tag] stuff [/tag]. A standalone tag has no end tag, as in [area href=somepage]. (Note that [page ...] and [order ..] are **not** container tags.)

A container tag will have its output re-parsed for more Interchange tags by default. If you wish to inhibit this behavior, you must explicitly set the attribute **reparse** to 0. Note that you will almost always wish the default action. The only container ITL tag that doesn't have reparse set by default is [mvasp].

With some exceptions ([include] is among them) among them) the output of a standalone tag will not be re-interpreted for Interchange tag constructs. All tags accept the INTERPOLATE=1 tag modifier, which causes the interpretation to take place. It is frequent that you will **not** want to interpret the contents of a [set variable] TAGS [/set] pair, as that might contain tags which should only be upon evaluating an order profile, search profile, or *mv_click* operation. If you wish to perform the evaluation at the time a variable is set, you would use [set name=variable interpolate=1] TAGS [/set].

1.1. Looping tags and Sub-tags

Certain tags are not standalone; these are the ones that are interpreted as part of a surrounding looping tag like [loop], [item-list], [query], or [region].

```

[PREFIX-accessories]
[PREFIX-alternate]
[PREFIX-calc]
[PREFIX-change]
[PREFIX-change]
[PREFIX-code]
[PREFIX-data]
[PREFIX-description]
[PREFIX-discount]
[PREFIX-field]
[PREFIX-increment]
[PREFIX-last]
[PREFIX-match]
[PREFIX-modifier]
[PREFIX-next]
[PREFIX-param]
[PREFIX-price]
[PREFIX-quantity]
[PREFIX-subtotal]
[if-PREFIX-data]
[if-PREFIX-field]
[modifier-name]
[quantity-name]

```

PREFIX represents the prefix that is used in that looping tag. They are only interpreted within their container and only accept positional parameters. The default prefixes:

Interchange: Interchange Tags Reference

Tag	Prefix	Examples
-----	-----	-----
[loop]	loop	[loop-code], [loop-field price], [loop-increment]
[item-list]	item	[item-code], [item-field price], [item-increment]
[search-list]	item	[item-code], [item-field price], [item-increment]
[query]	sql	[sql-code], [sql-field price], [sql-increment]

Sub-tag behavior is consistent among the looping tags.

There are two types of looping lists; ARRAY and HASH.

An array list is the normal output of a [query], a search, or a [loop] tag. It returns from 1 to N return fields, defined in the mv_return_fields or rf variable or implicitly by means of a SQL field list.

The two queries below are essentially identical:

```
[query sql="select foo, bar from products"]
[/query]

[loop search="
    ra=yes
    fi=products
    rf=foo,bar
"]
```

Both will return an array of arrays consisting of the foo column and the bar column. The Perl data structure would look like:

```
[
  ['foo0', 'bar0'],
  ['foo1', 'bar1'],
  ['foo2', 'bar2'],
  ['fooN', 'barN'],
]
```

A hash list is the normal output of the [item-list] tag. It returns the value of all return fields in an array of hashes. A normal [item-list] return might look like:

```
[
  {
    code      => '99-102',
    quantity  => 1,
    size      => 'XL',
    color     => 'blue',
    mv_ib     => 'products',
  },
  {
    code      => '00-341',
    quantity  => 2,
    size      => undef,
    color     => undef,
    mv_ib     => 'products',
  },
]
```

You can also return hash lists in queries:

```
[query sql="select foo, bar from products" type=hashref]
```

1.1. Looping tags and Sub-tags

```
[/query]
```

Now the data structure will look like:

```
[
  { foo => 'foo0', bar => 'bar0' },
  { foo => 'foo1', bar => 'bar1' },
  { foo => 'foo2', bar => 'bar2' },
  { foo => 'fooN', bar => 'barN' },
]
```

[PREFIX-accessories arglist]

The same as the [accessories ...] tag except always supplied the current item code. If the list is a hash list, i.e. an [item-list], then the value of the current item hash is passed so that a value default can be established.

[PREFIX-alternate N] DIVISIBLE [else] NOT DIVISIBLE [/else][PREFIX-alternate]

Set up an alternation sequence. If the item-increment is divisible by `N', the text will be displayed. If an `[else]NOT DIVISIBLE TEXT[/else]' is present, then the NOT DIVISIBLE TEXT will be displayed. For example:

```
[item-alternate 2]EVEN[else]ODD[/else][item-alternate]
[item-alternate 3]BY 3[else]NOT by 3[/else][item-alternate]
```

[PREFIX-calc] 2 + [item-field price] [/PREFIX-calc]

Calls perl via the equivalent of the [calc] [/calc] tag pair. Much faster to execute.

[PREFIX-change][condition] ... [/condition] TEXT [/PREFIX-change]

Sets up a breaking sequence that occurs when the contents of [condition] [/condition] change. The most common one is a category break to nest or place headers.

The region is only output when a field or other repeating value between [condition] and [/condition] changes its value. This allows indented lists similar to database reports to be easily formatted. The repeating value must be a tag interpolated in the search process, such as [PREFIX-field field] or [PREFIX-data database field]. If you need access to ITL tags, you can use [PREFIX-calc] with a \$Tag->foo() call. Of course, this will only work as you expect when the search results are properly sorted.

The value to be tested is contained within a [condition]value[/condition] tag pair. The [PREFIX-change] tag also processes an [else] [/else] pair for output when the value does not change.

Here is a simple example for a search list that has a field category and subcategory associated with each item:

```
<TABLE>
<TR><TH>Category</TH><TH>Subcategory</TH><TH>Product</TH></TR>
[search-list]
<TR>
  <TD>
    [item-change cat]

    [condition][item-field category][condition]

    [item-field category]
```



```

        [else]
            &nbsp;
        [/else]
    [/item-change cat]
</TD>
<TD>
    [item-change sub]

    [condition][item-field subcategory][/condition]

    [item-field subcategory]
    [else]
        &nbsp;
    [/else]
    [/item-change sub]
</TD>
<TD> [item-field name] </TD>
[/search-list]
</TABLE>

```

The above should put out a table that only shows the category and subcategory once, while showing the name for every product. (The ` ` will prevent blanked table cells if you use a border.)

[PREFIX-code]

The key or code of the current loop. In an `[item-list]` this is always the product code; in a loop list it is the value of the current argument; in a search it is whatever you have defined as the first `mv_return_field` (rf).

[PREFIX-data table field]

Calls the column `field` in database table `table` for the current `[PREFIX-code]`. This may or may not be equivalent to `[PREFIX-field field]` depending on whether your search table is defined as one of the `ProductFiles`.

[PREFIX-description]

The description of the current item, as defined in the `catalog.cfg` directive `DescriptionField`. In the demo, it would be the value of the field `description` in the table `products`. If the list is a hash list, and the lookup of `DescriptionField` fails, then the attribute `description` will be substituted. This is useful to supply shopping cart descriptions for on-the-fly items.

[PREFIX-discount]

The price of the current item is calculated, and the difference between that price and the list price (quantity one) price is output. This may have different behavior than you expect if you set the `[discount] [/discount]` tag along with quantity pricing.

[PREFIX-field]

Looks up a field value for the current item in one of several places, in this order:

1. The first `ProductFiles` entry.
2. Additional `ProductFiles` in the order they occur.
3. The attribute value for the item in a hash list.
4. Blank

A common user error is to do this:

```
[loop search="
        fi=foo
        se=bar
"]

[loop-field foo_field]
[/loop]
```

In this case, you are searching the table `foo` for a string of `bar`. When it is found, you wish to display the value of `foo_field`. Unless `foo` is in `ProductFiles` and the code is not present in a previous product file, you will get a blank or some value you don't want. What you really want is `[loop-data foo foo_field]`, which specifically addresses the table `foo`.

[PREFIX-increment]

The current count on the list, starting from either 1 in a zero-anchored list like `[loop]` or `[item-list]`, or from the match count in a search list.

If you skip items with `[PREFIX-last]` or `[PREFIX-next]`, the count is NOT adjusted.

[PREFIX-last] CONDITION [/PREFIX-last]

If `CONDITION` evaluates true (a non-whitespace value that is not specifically zero) then this will be the last item displayed.

[PREFIX-modifier attribute]

If the item is a hash list (i.e. `[item-list]`), this will return the value of the `attribute`.

[PREFIX-next] CONDITION [/PREFIX-next]

If `CONDITION` evaluates true (a non-whitespace value that is not specifically zero) then this item is skipped.

[PREFIX-param name]

[PREFIX-param N]

Returns the array parameter associated with the looping tag row. Each looping list returns an array of `return fields`, set in searches with `mv_return_field` or `rf`. The default is only to return the code of the search result, but by setting those parameters you can return more than one item.

In a `[query ...]` ITL tag you can select multiple return fields with something like:

```
[query prefix=prefix sql="select foo, bar from baz where foo=buz"]
    [prefix-code] [prefix-param foo] [prefix-param bar]
[/query]
```

In this case, `[prefix-code]` and `[prefix-param foo]` are synonymns, for `foo` is the first returned parameter and becomes the code for this row. Another synonym is `[prefix-param 0]`; and `[prefix-param 1]` is the same as `[prefix-param bar]`.

[PREFIX-price]

The price of the current code, formatted for currency. If Interchange's pricing routines cannot determine the price (i.e. it is not a valid product or on-the-fly item) then zero is returned. If the list is a hash list, the price will be modified by its `quantity` or other applicable attributes (like `size` in the demo).

[PREFIX-quantity]

The value of the `quantity` attribute in a hash list. Most commonly used to display the quantity of an item in a shopping cart [item-list].

[PREFIX-subtotal]

The [PREFIX-quantity] times the [PREFIX-price]. This does take discounts into effect.

[if-PREFIX-data table field] IF text [else] ELSE text [/else] [/if-PREFIX-data]

Examines the data field, i.e. [PREFIX-data table field], and if it is non-blank and non-zero then the `IF text` will be returned. If it is false, i.e. blank or zero, the `ELSE text` will be returned to the page.

This is much more efficient than the otherwise equivalent `[if type=data term=table::field::[PREFIX-code]]`.

You cannot place a condition; i.e. [if-PREFIX-data table field eq 'something']. Use `[if type=data ...]` for that.

Careful, a space is not a false value!

[if-PREFIX-field field] IF text [else] ELSE text [/else] [/if-PREFIX-field]

Same as [if-PREFIX-data ...] except uses the same data rules as `[PREFIX-field]`.

[modifier-name attribute]

Outputs a variable name which will set an appropriate variable name for setting the attribute in a form (usually a shopping cart). Outputs for successive items in the list:

1. `attribute0`
2. `attribute1`
3. `attribute2`

etc.

[quantity-name]

Outputs for successive items in the list:

1. `quantity0`
2. `quantity1`
3. `quantity2`

etc. `[modifier-name quantity]` would be the same as `[quantity-name]`.

2. TAGS

Each ITL tag is show below. Calling information is defined for the main tag, sub-tags are described in Sub-tags.

2.1. accessories

CALL INFORMATION

Parameters: **code arg**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->accessories(  
    {  
        code => VALUE,  
        arg => VALUE,  
    }  
)
```

OR

```
$Tag->accessories($code, $arg, $ATTRHASH);
```

Attribute aliases

```
base ==> table  
col ==> column  
database ==> table  
db ==> table  
field ==> column  
key ==> code  
row ==> code
```

DESCRIPTION

The [accessories ...] tag allows you to access Interchange's option attribute facility in any of several ways.

If passed any of the optional arguments, initiates special processing of item attributes based on entries in the product database.

Interchange allows item attributes to be set for each ordered item. This allows a size, color, or other modifier to be attached to a line item in the shopping cart. Previous attribute values can be resubmitted by means of a hidden field on a form.

The catalog.cfg file directive *UseModifier* is used to set the name of the modifier or modifiers. For example

```
UseModifier      size color
```

will attach both a size and color attribute to each item code that is ordered.

IMPORTANT NOTE: You may not use the following names for attributes:

```
item group quantity code mv_ib mv_mi mv_si
```

You can also set it in scratch with the `mv_UseModifier` scratch variable -- `[set mv_UseModifier]size color[/set]` has the same effect as above. This allows multiple options to be set for products. Whichever one is in effect at order time will be used. Be careful, you cannot set it more than once on the same page. Setting the `mv_separate_items` or global directive *SeparateItems* places each ordered item on a separate line, simplifying attribute handling. The scratch setting for `mv_separate_items` has the same effect.

The modifier value is accessed in the `[item-list]` loop with the `[item-param attribute]` tag, and form input fields are placed with the `[modifier-name attribute]` tag. This is similar to the way that quantity is handled.

NOTE: You must be sure that no fields in your forms have digits appended to their names if the variable is the same name as the attribute name you select, as the `[modifier-name size]` variables will be placed in the user session as the form variables `size0`, `size1`, `size2`, etc.

Interchange will automatically generate the select boxes when the `[accessories <code size>]` or `[item-accessories size]` tags are called. They have the syntax:

```
[item_accessories attribute, type*, column*, table*, name*, outboard*]

[accessories code=sku
  attribute=modifier
  type="select|radio|display|show|checkbox|text|textarea"*
  column=column_name*
  table=db_table*
  name=varname
  outboard=key
  passed="value=label, value2, value3=label 3" ]
```

code

Not needed for `item-accessories`, this is the product code of the item to reference.

STYLE="font-weight: bold"> **attribute**

The item attribute as specified in the `UseModifier` configuration directive. Typical are `size` or `color`.

STYLE="font-weight: bold"> **type**

The action to be taken. One of:

<code>select</code>	Builds a dropdown <code><SELECT></code> menu for the attribute. NOTE: This is the default.
<code>multiple</code>	Builds a multiple dropdown <code><SELECT></code> menu for the attribute. The size is equal to the number of option choices.
<code>display</code>	Shows the label text for *only the selected option*.
<code>show</code>	Shows the option choices (no labels) for the option.
<code>radio</code>	Builds a radio box group for the item, with spaces separating the elements.

Interchange: Interchange Tags Reference

<code>radio nbsp</code>	Builds a radio box group for the item, with <code>&nbsp;</code> separating the elements.
<code>radio left n</code>	Builds a radio box group for the item, inside a table, with the checkbox on the left side. If "n" is present and is a digit from 2 to 9, it will align the options in that many columns.
<code>radio right n</code>	Builds a radio box group for the item, inside a table, with the checkbox on the right side. If "n" is present and is a digit from 2 to 9, it will align the options in that many columns.
<code>check</code>	Builds a checkbox group for the item, with spaces separating the elements.
<code>check nbsp</code>	Builds a checkbox group for the item, with <code>&nbsp;</code> separating the elements.
<code>check left n</code>	Builds a checkbox group for the item, inside a table, with the checkbox on the left side. If "n" is present and is a digit from 2 to 9, it will align the options in that many columns.
<code>check right n</code>	Builds a checkbox group for the item, inside a table, with the checkbox on the right side. If "n" is present and is a digit from 2 to 9, it will align the options in that many columns.
<code>textarea_XX_YY</code>	A textarea with XX columns and YY rows
<code>text_XX</code>	A text box with XX size in characters
<code>combo</code>	Special type, used with <code>nullselect</code> filter, for selecting from a list or inputting a new value
<code>reverse_combo</code>	Special type, used with <code>last_non_null</code> filter, for selecting from a list or inputting a new value -- differs from <code>combo</code> in order of presentation
<code>move_combo</code>	Special type, used with <code>null_to_space</code> or <code>null_to_comma</code> filter, for selecting multiple non-ordered values from a list or inputting into a textarea
<code>links</code>	Produces a series of links based on the option values. The base form value is passed via the form parameter, just like in an <code>[area ...]</code> or <code>[page ...]</code> tag, and the value is named with the passed NAME attribute.

The default is 'select', which builds an HTML select form entry for the attribute. Also recognized is 'multiple', which generates a multiple-selection drop down list, 'show', which shows the list of possible attributes, and 'display', which shows the label text for the selected option only.

STYLE="font-weight: bold"> **column**

The database column name to be used to build the entry (usually a field in the products database). Defaults to a field named the same as the attribute.

STYLE="font-weight: bold"> **table**

The database table to find **column** in, defaults to the first products file where the item code is found.

STYLE="font-weight: bold"> **name**

Name of the form variable to use if a form is being built. Defaults to mv_order_**attribute** — i.e. if the attribute is **size**, the form variable will be named **mv_order_size**. If the variable is set in the user session, the widget will "remember" its previous setting.

STYLE="font-weight: bold"> **outboard**

If calling the item-accessories tag, and you wish to select from an outboard database table with a different key from the item code, you can pass the key to use to find the accessory data.

STYLE="font-weight: bold"> **passed**

Options for the widget if set explicitly, i.e. overrides a database fetch of the attribute input string.

For example, to generate a select box with a blank option (perhaps forcing a select), the value of blue with a label of **Blue**, and the value of green with a label of **Sea Green**, do:

```
[accessories
  type=select
  name=color
  passed="---select--, blue=Blue, green=Sea Green"
]
```

This will generate:

```
<SELECT NAME="color">
<OPTION VALUE="">---select--
<OPTION VALUE="blue">Blue
<OPTION VALUE="green">Sea Green
</SELECT>
```

href

Base HREF for the link in a links type. Default is the current page.

STYLE="font-weight: bold"> **form**

Base value for the form in a links type. Default is mv_action=return, which will simply set the variable value in the link.

For example, to generate a series of links that set the variable "color" to the same as the options described in the passed attribute (blank, blue, or green), do

```
[accessories
  type=links
  name=color
  passed="---select--, blue=Blue, green=Sea Green"
]
```

This will generate:

```
<A HREF="VENDURL/MV_PAGE?mv_action=return&color=blue">Blue</A><BR>
<A HREF="VENDURL/MV_PAGE?mv_action=return&color=green">Sea Green</A>
```

where VENDURL is your Interchange URL for the catalog

Interchange: Interchange Tags Reference

MV_PAGE is the current page

If you want the empty "--select--" option to show up, pass an empty=1 parameter.

When called with an attribute, the database is consulted and looks for a comma-separated list of attribute options. They take the form:

```
name=Label Text, name=Label Text*
```

The label text is optional -- if none is given, the **name** will be used.

If an asterisk is the last character of the label text, the item is the default selection. If no default is specified, the first will be the default. An example:

```
[item_accessories color]
```

This will search the product database for a field named "color". If an entry "beige=Almond, gold=Harvest Gold, White*, green=Avocado" is found, a select box like this will be built:

```
<SELECT NAME="mv_order_color">
<OPTION VALUE="beige">Almond
<OPTION VALUE="gold">Harvest Gold
<OPTION SELECTED>White
<OPTION VALUE="green">Avocado
</SELECT>
```

In combination with the mv_order_item and mv_order_quantity variables this can be used to allow entry of an attribute at time of order.

If used in an item list, and the user has changed the value, the generated select box will automatically retain the current value the user has selected.

The value can then be displayed with [item-modifier size] on the order report, order receipt, or any other page containing an [item-list].

When called with an attribute, the database is consulted and looks for a comma-separated list of attribute options. They take the form:

```
name=Label Text, name=Label Text*
```

The label text is optional -- if none is given, the **name** will be used.

If an asterisk is the last character of the label text, the item is the default selection. If no default is specified, the first will be the default. An example:

```
[accessories TK112 color]
```

This will search the product database for a field named "color". If an entry "beige=Almond, gold=Harvest Gold, White*, green=Avocado" is found, a select box like this will be built:

```
<SELECT NAME="mv_order_color">
<OPTION VALUE="beige">Almond
<OPTION VALUE="gold">Harvest Gold
<OPTION SELECTED>White
<OPTION VALUE="green">Avocado
</SELECT>
```

In combination with the mv_order_item and mv_order_quantity variables this can be used to allow entry of an attribute at time of order.

STYLE="font-weight: bold"> **EMULATING WITH LOOP**

Below is a fragment from a shopping basket display form which shows a selectable size with "sticky" setting and a price that changes based upon the modifier setting. Note that this would normally be contained within the [item_list] [/item-list] pair.

```
<SELECT NAME="[modifier-name size]">
[loop option="[modifier-name size]" list="S, M, L, XL"]
<OPTION> [loop-code] -- [price code="[item-code]" size="[loop-code]"]
[/loop]
</SELECT>
```

The above is essentially the same as would be output with the [item-accessories size] tag if the product database field size contained the value S, M, L, XL, but contains the adjusted price.

2.2. and

CALL INFORMATION

Parameters: **type term op compare**

THIS TAG HAS SPECIAL POSITIONAL PARAMETER HANDLING.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

Called Routine for positional:

ASP/perl tag calls:

```
$Tag->and(
{
    type => VALUE,
    term => VALUE,
    op => VALUE,
    compare => VALUE,
}
)
```

OR

```
$Tag->and($type, $term, $op, $compare);
```

Attribute aliases

```
base ==> type
comp ==> compare
operator ==> op
```

DESCRIPTION

The [and ...] tag is only used in conjunction with [if ...]. Example:

```
[if value fname]
[and value lname]
Both first and last name are present.
[else]
Missing one of "fname" and "lname" from $Values.
[/else]
```

```
[/if]
```

See `[if ...]`.

2.3. area

CALL INFORMATION

Aliases for tag

href

Parameters: **href arg**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->area(
    {
        href => VALUE,
        arg  => VALUE,
    }
)
```

OR

```
$Tag->area($href, $arg, $ATTRHASH);
```

DESCRIPTION

Named call example:

```
<A HREF="[area href=scan arg="
                                se=Impressionists
                                sf=category
                                "
                                ]">Impressionists</A>
```

Positional call example:

```
<A HREF="[area ord/basket]">Check basket</A>
```

HTML example:

```
<A MV="area dir/page" HREF="dir/page.html">
```

Produces the URL to call a Interchange page, without the surrounding A HREF notation. This can be used to get control of your HREF items, perhaps to place an ALT string or a Javascript construct.

It was originally named `area` because it also can be used in a client-side image map, and has an alias of `href`. The two links below are identical in operation:

```
<A HREF="[area href=catalog]" ALT="Main catalog page">Catalog Home</A>
```

```
<A HREF="[href href=catalog]" ALT="Main catalog page">Catalog Home</A>
```

The optional *arg* is used just as in the *page* tag.

The optional *form* argument allows you to encode a form in the link.

```
<A HREF="[area form="
    mv_order_item=99-102
    mv_order_size=L
    mv_order_quantity=1
    mv_separate_items=1
    mv_todo=refresh"
]"> Order t-shirt in Large size </A>
```

The two form values *mv_session_id* and *mv_arg* are automatically added when appropriate. (*mv_arg* is the *arg* parameter for the tag.)

If the parameter *href* is not supplied, *process* is used, causing normal Interchange form processing.

This would generate a form that ordered item number 99–102 on a separate line

(*mv_separate_items* being set), with size L, in quantity 2. Since the page is not set, you will go to the default shopping cart page — equally you could set *mv_orderpage*=*yourpage* to go to *yourpage*.

All normal Interchange form caveats apply — you must have an action, you must supply a page if you don't want to go to the default, etc.

You can theoretically submit any form with this, though none of the included values can have newlines or trailing whitespace. If you want to do something like that you will have to write a UserTag.

2.4. attr_list

CALL INFORMATION

Parameters: **hash**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter *interpolate*=1 to cause interpolation.

This is a container tag, i.e. [*attr_list*] FOO [*/attr_list*]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->attr_list(
    {
        hash => VALUE,
    },
    BODY
)
```

OR

```
$Tag->attr_list($hash, $BODY);
```

DESCRIPTION

Tags an attribute list with values from a hash. Designed for use in embedded Perl.

Example:

```
[perl tables=products]
```

```

my %opt = (
    hashref => 1,
    sql => 'select * from products',
);
my $ary_of_hash = $Db{products}->query(\%opt);
my $template = <<EOF;
{sku} - {description} - {price|Call for price}
      {image?}<IMG SRC="{image}">{/image?}
      {image:}No image available{/image:}
EOF
      foreach my $ref (@$ary_of_hash) {
          $out .= $Tag->attr_list($template, $ref);
      }
      return $out;
[/perl]

```

Tags according to the following rules:

STYLE="font-weight: bold"> **{key}**

Inserts the value of the key for the reference. In a database query, this is the column name.

STYLE="font-weight: bold"> **{key|fallback string}**

Displays the value of {key} or if it is zero or blank, the fallback string.

STYLE="font-weight: bold"> **{key true string}**

Displays true string if the value of {key} is non-blank, non-zero, or displays nothing if the key is false.

STYLE="font-weight: bold"> **{key?} true text {/key?}**

Displays true text if the value of {key} is non-blank, non-zero, and nothing otherwise.

STYLE="font-weight: bold"> **{key:} false text {/key:}**

Displays false text if the value of {key} is blank or zero, and nothing otherwise.

2.5. banner

CALL INFORMATION

Parameters: **category**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

$Tag->banner(
    {
        category => VALUE,
    }
)

```

OR

```
$Tag->banner($category, $ATTRHASH);
```

DESCRIPTION

The [banner ...] tag is designed to implement random or rotating banner displays in your Interchange pages. See the main Interchange documentation, section *Banner/Ad rotation*.

2.6. bounce

CALL INFORMATION

Parameters: **href if**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->bounce(
    {
        href => VALUE,
        if => VALUE,
    }
)
```

OR

```
$Tag->bounce($href, $if);
```

DESCRIPTION

The [bounce ...] tag is designed to send an HTTP redirect (302 status code) to the browser and redirect it to another (possibly Interchange-parsed) page.

It will stop ITL code execution at that point; further tags will not be run through the parser. Bear in mind that if you are inside a looping list, that list will run to completion and the [bounce] tag will not be seen until the loop is complete.

Example of bouncing to an Interchange parsed page:

```
[if !scratch real_user]
[bounce href="[area violation]"]
[/if]
```

Note the URL is produced by the [area ...] ITL tag.

Since the HTTP says the URL needs to be absolute, this one might cause a browser warning:

```
[if value go_home]
[bounce href="/"]
[/if]
```

But running something like one of the Interchange demos you can do:

```
[if value go_home]
```

```
[bounce href="__SERVER_NAME__/" ]
[/if]

[if value go_home]
[bounce href="/"]
[/if]
```

2.7. calc

CALL INFORMATION

No parameters.

Pass attribute hash as last to subroutine: **no**

Interpolates **container text** by default>.

This is a container tag, i.e. [calc] FOO [/calc]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->calc(
    {
    },
    BODY
)
```

OR

```
$Tag->calc($BODY);
```

DESCRIPTION

syntax: [calc] EXPRESSION [/calc]

Starts a region where the arguments are calculated according to normal arithmetic symbols. For instance:

```
[calc] 2 + 2 [/calc]
```

will display:

```
4
```

The [calc] tag is really the same as the [perl] tag, except that it doesn't accept arguments, interpolates surrounded Interchange tags by default, and is slightly more efficient to parse.

TIP: The [calc] tag will remember variable values inside one page, so you can do the equivalent of a memory store and memory recall for a loop.

ASP NOTE: There is never a reason to use this tag in a [perl] or ASP section.

2.8. cart

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->cart(  
    {  
        name => VALUE,  
    }  
)
```

OR

```
$Tag->cart($name);
```

DESCRIPTION

Sets the name of the current shopping cart for display of shipping, price, total, subtotal, shipping, and nitems tags.

2.9. catch

CALL INFORMATION

Parameters: **label**

ONLY THE PARAMETERS ARE POSITIONAL.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [catch] FOO [/catch]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->catch(  
    {  
        label => VALUE,  
    },  
    BODY  
)
```

OR

```
$Tag->catch($label, $ATTRHASH, $BODY);
```

DESCRIPTION

NO DESCRIPTION

2.10. cgi

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->cgi(
    {
        name => VALUE,
    }
)

OR

$Tag->cgi($name);
```

DESCRIPTION

Displays the value of a CGI variable **submitted to the current page**. This is similar to [value ...], except it displays the transitory values that are submitted with every request.

For instance, if you access the following URL:

```
http://VENDURL/pagename?foo=bar
```

bar will be substituted for [cgi foo].

This is the same as \$CGI->{foo} in embedded Perl.

2.11. checked

CALL INFORMATION

Parameters: **name value**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->checked(
    {
        name => VALUE,
        value => VALUE,
    }
)

OR

$Tag->checked($name, $value, $ATTRHASH);
```

DESCRIPTION

You can provide a "memory" for drop-down menus, radio buttons, and checkboxes with the [checked] and [selected] tags.

```
<INPUT TYPE=radio NAME=foo
      VALUE=on [checked name=foo value=on default=1]>
<INPUT TYPE=radio NAME=foo
      VALUE=off [checked name=foo value=off]>
```

This will output CHECKED if the variable `var_name` is equal to `value`. Not case sensitive unless the optional `case=1` parameter is used.

The `default` parameter, if true (non-zero and non-blank), will cause the box to be checked if the variable has never been defined.

Note that CHECKBOX items will never submit their value if not checked, so the box will not be reset. You must do something like:

```
<INPUT TYPE=checkbox NAME=foo
      VALUE=1 [checked name=foo value=1 default=1]>
[value name=foo set=""]
```

By default, the Values space (i.e. [value foo]) is checked -- if you want to use the volatile CGI space (i.e. [cgi foo]) use the option `cgi=1`.

2.12. control

CALL INFORMATION

Parameters: **name default**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->control(
    {
        name => VALUE,
        default => VALUE,
    }
)
```

OR

```
$Tag->control($name, $default, $ATTRHASH);
```

DESCRIPTION

NO DESCRIPTION

2.13. control_set

CALL INFORMATION

Parameters: **index**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [control_set] FOO [/control_set]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->control_set(
    {
        index => VALUE,
    },
    BODY
)

OR

$Tag->control_set($index, $ATTRHASH, $BODY);
```

DESCRIPTION

NO DESCRIPTION

2.14. counter

CALL INFORMATION

Parameters: **file**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->counter(
    {
        file => VALUE,
    }
)

OR

$Tag->counter($file, $ATTRHASH);
```

Attribute aliases

```
name ==> file
```

DESCRIPTION

Manipulates a file-based counter, by default incrementing it. The file name is passed with the parameter `file` — default is `etc/counter`.

WARNING: This tag will not work under Safe, i.e. in embedded Perl.

Additional parameters:

`STYLE="font-weight: bold"> decrement=1`

Causes the counter to count down instead of up.

`STYLE="font-weight: bold"> value=1`

Shows the value of the counter without incrementing or decrementing it.

2.15. currency

CALL INFORMATION

Parameters: **convert noformat**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Interpolates **container text** by default>.

This is a container tag, i.e. `[currency] FOO [/currency]`. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->currency(
    {
        convert => VALUE,
        noformat => VALUE,
    },
    BODY
)
```

OR

```
$Tag->currency($convert, $noformat, $BODY);
```

DESCRIPTION

When passed a value of a single number, formats it according to the currency specification. For instance:

```
[currency]4[/currency]
```

will display:

```
4.00
```

or something else depending on the *Locale* and *PriceCommas* settings. It can contain a `[calc]` region. If the optional "convert" parameter is set, it will convert the value according to `PriceDivide>` for the current locale. If *Locale* is set to `fr_FR`, and *PriceDivide* for `fr_FR` is 0.167, the following sequence

```
[currency convert=1] [calc] 500.00 + 1000.00 [/calc] [/currency]
```

will cause the number 8.982,04 to be displayed.

2.16. data

CALL INFORMATION

Parameters: **table field key**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->data(
    {
        table => VALUE,
        field => VALUE,
        key => VALUE,
    }
)

OR

$Tag->data($table, $field, $key, $ATTRHASH);
```

Attribute aliases

```
base ==> table
code ==> key
col ==> field
column ==> field
database ==> table
name ==> field
row ==> key
```

DESCRIPTION

Syntax: `[data table=db_table column=column_name key=key filter="uc|lc|name|namecase|no_white|etc."* append=1* value="value to set to"* increment=1*]`

Returns the value of the field in a database table, or (DEPRECATED) from the `session` namespace. If the optional **value** is supplied, the entry will be changed to that value. If the option `increment*` is present, the field will be atomically incremented with the value in **value**. Use negative numbers in `value` to decrement. The `append` attribute causes the value to be appended; and finally, the `filter` attribute is a set of Interchange filters that are applied to the data 1) after it is read; or 2) before it is placed in the table. If a DBM-based database is to be modified, it must be flagged writable on the page calling the write tag. Use `[tag flag write]products[/tag]` to mark the `products` database writable, for example. **This must be done before ANY access to that table.**

DEPRECATED BEHAVIOR: (replace with `session` tag). In addition, the `[data ...]` tag can access a number of elements in the Interchange session database:

Interchange: Interchange Tags Reference

accesses	Accesses within the last 30 seconds
arg	The argument passed in a [page ...] or [area ...] tag
browser	The user browser string
cybercash_error	Error from last CyberCash operation
cybercash_result	Hash of results from CyberCash (access with usertag)
host	Interchange's idea of the host (modified by DomainTail)
last_error	The last error from the error logging
last_url	The current Interchange path_info
logged_in	Whether the user is logged in (add-on UserDB feature)
pageCount	Number of unique URLs generated
prev_url	The previous path_info
referer	HTTP_REFERER string
ship_message	The last error messages from shipping
source	Source of original entry to Interchange
time	Time (seconds since Jan 1, 1970) of last access
user	The REMOTE_USER string
username	User name logged in as (UserDB feature)

NOTE: Databases will hide session values, so don't name a database "session". or you won't be able to use the [data ...] tag to read them. Case is sensitive, so in a pinch you could call the database "Session", but it would be better not to use that name at all.

2.17. default

CALL INFORMATION

Parameters: **name default**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->default(  
    {  
        name => VALUE,  
        default => VALUE,  
    }  
)
```

OR

```
$Tag->default($name, $default, $ATTRHASH);
```

DESCRIPTION

Returns the value of the user form variable `variable` if it is non-empty. Otherwise returns `default`, which is the string "default" if there is no default supplied. Got that? This tag is DEPRECATED anyway.

2.18. description

CALL INFORMATION

Parameters: **code base**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

$Tag->description(
    {
        code => VALUE,
        base => VALUE,
    }
)

OR

$Tag->description($code, $base);

```

DESCRIPTION

Expands into the description of the product identified by code as found in the products database. This is the value of the database field that corresponds to the `catalog.cfg` directive `DescriptionField`. If there is more than one products file defined, they will be searched in order unless constrained by the optional argument **base**.

This tag is especially useful for multi-language catalogs. The `DescriptionField` directive can be set for each locale and point to a different database field; for example `desc_en` for English, `desc_fr` for French, etc.

2.19. discount

CALL INFORMATION

Parameters: **code**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[discount] FOO [/discount]`. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```

$Tag->discount(
    {
        code => VALUE,
    },
    BODY
)

OR

$Tag->discount($code, $BODY);

```

DESCRIPTION

Product discounts can be set upon display of any page. The discounts apply only to the customer receiving them, and are of one of three types:

1. A discount for one particular item code (code/key is the item-code)
2. A discount applying to all item codes (code/key is ALL_ITEMS)
3. A discount applied after all items are totaled
(code/key is ENTIRE_ORDER)

The discounts are specified via a formula. The formula is scanned for the variables \$q and \$s, which are substituted for with the item *quantity* and *subtotal* respectively. In the case of the item and all items discount, the formula must evaluate to a new subtotal for all items *of that code* that are ordered. The discount for the entire order is applied to the entire order, and would normally be a monetary amount to subtract or a flat percentage discount.

Discounts are applied to the effective price of the product, including any quantity discounts.

To apply a straight 20% discount to all items:

```
[discount ALL_ITEMS] $s * .8 [/discount]
```

or with named attributes:

```
[discount code=ALL_ITEMS] $s * .8 [/discount]
```

To take 25% off of only item 00–342:

```
[discount 00-342] $s * .75 [/discount]
```

To subtract \$5.00 from the customer's order:

```
[discount ENTIRE_ORDER] $s - 5 [/discount]
```

To reset a discount, set it to the empty string:

```
[discount ALL_ITEMS][[/discount]
```

Perl code can be used to apply the discounts. Here is an example of a discount for item code 00–343 which prices the *second* one ordered at 1 cent:

```
[discount 00-343]
return $s if $q == 1;
my $p = $s/$q;
my $t = ($q - 1) * $p;
$t .= 0.01;
return $t;
[/discount]
```

If you want to display the discount amount, use the [item–discount] tag.

```
[item-list]
Discount for [item-code]: [item-discount]
[/item-list]
```

Finally, if you want to display the discounted subtotal in a way that doesn't correspond to a standard Interchange tag, you can use the [calc] tag:


```
[item-list]
Discounted subtotal for [item-code]: [currency][calc]
                                [item-price noformat] * [item-quantity]
                                [/calc][/currency]

[/item-list]
```

%% dump %% Prints a dump of the current user session as expanded by Data::Dumper. Includes any CGI environment passed from the server.

For an example, create a page containing <XMP>[dump]</XMP> and see what it displays.

%% either %% The [either]this[or]that[/either] implements a check for the first non-zero, non-blank value. It splits on [or], and then parses each piece in turn. If a value returns true (in the Perl sense — non-zero, non-blank) then subsequent pieces will be discarded without interpolation.

Example:

```
[either][value must_be_here][or][bounce href="[area incomplete]"[/either]
```

Always strips leading and trailing whitespace.

2.20. dump

CALL INFORMATION

No parameters.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->dump(
    {
    }
)
```

OR

```
$Tag->dump($);
```

DESCRIPTION

NO DESCRIPTION

2.21. ecml

CALL INFORMATION

Parameters: **name function**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->ecml(
    {
        name => VALUE,
        function => VALUE,
    }
)
```

OR

```
$Tag->ecml($name, $function, $ATTRHASH);
```

DESCRIPTION

NO DESCRIPTION

2.22. either

CALL INFORMATION

No parameters.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [either] FOO [/either]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->either(
    {
    },
    BODY
)
```

OR

```
$Tag->either($BODY);
```

DESCRIPTION

NO DESCRIPTION

2.23. error

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->error(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->error($name, $ATTRHASH);
```

DESCRIPTION

```
[error var options]
    var is the error name, e.g. "session"
```

The [error ...] tag is designed to manage form variable checking for the Interchange submit form processing action. It works in conjunction with the definition set in `mv_order_profile`, and can generate error messages in any format you desire.

If the variable in question passes order profile checking, it will output a label, by default **bold** text if the item is required, or normal text if not (controlled by the `<require>` parameter. If the variable fails one or more order checks, the error message will be substituted into a template and the error cleared from the user's session.

(Below is as of 4.03, the equivalent in 4.02 is [if type=explicit compare="[error all=1 keep=1]" ... [/if].)

To check errors without clearing them, you can use the idiom:

```
[if errors]
<FONT SIZE="+1" COLOR=RED>
    There were errors in your form submission.
</FONT>
<BLOCKQUOTE>
    [error all=1 show_error=1 joiner="<BR>"]
</BLOCKQUOTE>
[/if]
```

The options are:

STYLE="font-weight: bold"> **all=1**

Display all error messages, not just the one referred to by `<var>`. The default is only display the error message assigned to `<var>`.

text=<optional string to embed the error message(s) in>

place a "%s" somewhere in 'text' to mark where you want the error message placed, otherwise it's appended on the end. This option also implies `show_error`.

STYLE="font-weight: bold"> **joiner=<char>**

Character used to join multiple error messages. Default is '\n', a newline.

STYLE="font-weight: bold"> **keep=1**

keep=1 means don't delete the error messages after copy; anything else deletes them.

STYLE="font-weight: bold"> **show_var=1**

show_var=1 means include the variable relating to the error message as part of the error message (E.g.: "email: not a valid email address").

show_error=1 show_error=1 means return the error message text; otherwise just the number of errors found is returned.

STYLE="font-weight: bold"> **std_label**

std_label=<label string for error message>

used with 'required' to display a standardized error format. The HTML formatting can be set via the global variable MV_ERROR_STD_LABEL with the default being:

```
<FONT COLOR=RED>label_str<SMALL><I> (%s) </I></SMALL></FONT>
```

where <label_str> is what you set std_label to and %s is substituted with the error message. This option can not be used with the text= option.

STYLE="font-weight: bold"> **required=1**

Specifies that this is a required field for formatting purposes. In the std_label format, it means the field will be bolded. If you specify your own label string, it will insert HTML anywhere you have {REQUIRED: HTML}, but only when the field is required.

2.24. export

CALL INFORMATION

Parameters: **table**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->export(
    {
        table => VALUE,
    }
)
```

OR

```
$Tag->export($table, $ATTRHASH);
```

Attribute aliases

```
base ==> table
database ==> table
```

DESCRIPTION

NO DESCRIPTION

2.25. field

CALL INFORMATION

Parameters: **name code**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->field(
    {
        name => VALUE,
        code => VALUE,
    }
)

OR

$Tag->field($name, $code);
```

Attribute aliases

```
col ==> name
column ==> name
field ==> name
key ==> code
row ==> code
```

DESCRIPTION

HTML example: `<PARAM MV=field MV.COL=column MV.ROW=key>`

Expands into the value of the field *name* for the product identified by *code* as found by searching the products database. It will return the first entry found in the series of *Product Files*, the products database. If you want to constrain it to a particular database, use the `[data base name code]` tag.

Note that if you only have one `ProductFile` products, which is the default, `[field column key]` is the same as `[data products column key]`.

2.26. file

CALL INFORMATION

Parameters: **name type**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->file(
```

```

        {
            name => VALUE,
            type => VALUE,
        }
    )

```

OR

```
$Tag->file($name, $type);
```

DESCRIPTION

Inserts the contents of the named file. The file should normally be relative to the catalog directory — file names beginning with / or .. are not allowed if the Interchange server administrator has set *NoAbsolute* to Yes.

The optional `type` parameter will do an appropriate ASCII translation on the file before it is sent.

2.27. filter

CALL INFORMATION

Parameters: **op**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[filter] FOO [/filter]`. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

$Tag->filter(
    {
        op => VALUE,
    },
    BODY
)

```

OR

```
$Tag->filter($op, $BODY);
```

DESCRIPTION

Applies any of Interchange's standard filters to an arbitrary value, or you may define your own. The filters are also available as parameters to the `cgi`, `data`, and `value` tags.

Filters can be applied in sequence and as many as needed can be applied.

Here is an example. If you store your author or artist names in the database "LAST, First" so that they sort properly, you still might want to display them normally as "First Last". This call

```
[filter op="name namecase"]WOOD, Grant[/filter]
```

will display as

```
Grant Wood
```

Another way to do this would be:

```
[data table=products column=artist key=99-102 filter="name namecase"]
```

Filters available include:

STYLE="font-weight: bold"> **cgi**

Returns the value of the CGI variable. Useful for starting a filter sequence with a seed value.

```
'cgi' => sub {
    return $CGI::values(shift);
},
```

digits

Returns only digits.

```
'digits' => sub {
    my $val = shift;
    $val =~ s/\D+//g;
    return $val;
},
```

digits_dot

Returns only digits and periods, i.e. [.0–9]. Useful for decommifying numbers.

```
'digits_dot' => sub {
    my $val = shift;
    $val =~ s/[^\d.]+//g;
    return $val;
},
```

dos

Turns linefeeds into carriage–return / linefeed pairs.

```
'dos' => sub {
    my $val = shift;
    $val =~ s/\r?\n/\r\n/g;
    return $val;
},
```

entities

Changes < to < , " to " , etc.

```
'entities' => sub {
    return HTML::Entities::encode(shift);
},
```

gate

Performs a security screening by testing to make sure a corresponding scratch variable has been set.

Interchange: Interchange Tags Reference

```
'gate' => sub {  
    my ($val, $var) = @_;  
    return ' ' unless $::Scratch->{$var};  
    return $val;  
},
```

lc

Lowercases the text.

```
'lc' => sub {  
    return lc(shift);  
},
```

lookup

Looks up an item in a database based on the passed table and column. Call would be:

```
[filter op="uc lookup.country.name"]us[/filter]
```

This would be the equivalent of [data table=country column=name key=US].

```
'lookup' => sub {  
    my ($val, $tag, $table, $column) = @_;  
    return tag_data($table, $column, $val) || $val;  
},
```

mac

Changes newlines to carriage returns.

```
'mac' => sub {  
    my $val = shift;  
    $val =~ s/\r?\n|\r\n?/\r/g;  
    return $val;  
},
```

name

Transposes a LAST, First name pair.

```
'name' => sub {  
    my $val = shift;  
    return $val unless $val =~ /,/;  
    my($last, $first) = split /\s*,\s*/, $val, 2;  
    return "$first $last";  
},
```

namecase

Namecases the text. Only works on values that are uppercase in the first letter, i.e. [filter op=namecase]LEONARDO da Vinci[/filter] will return "Leonardo da Vinci".

```
'namecase' => sub {  
    my $val = shift;  
    $val =~ s/([A-Z]\w+)/\L\u$1/g;
```



```
        return $val;
    },
```

no_white

Strips all whitespace.

```
'no_white' => sub {
    my $val = shift;
    $val =~ s/\s+//g;
    return $val;
},
```

pagefile

Strips leading slashes and dots.

```
'pagefile' => sub {
    $_[0] =~ s:^(./*)+::;
    return $_[0];
},
```

sql

Change single-quote characters into doubled versions, i.e. ' becomes ".

```
'sql'      => sub {
    my $val = shift;
    $val =~ s/:''/:g; # '
    return $val;
},
```

strip

Strips leading and trailing whitespace.

```
'strip' => sub {
    my $val = shift;
    $val =~ s/^\s+//;
    $val =~ s/\s+$//;
    return $val;
},
```

text2html

Rudimentary HTMLizing of text.

```
'text2html' => sub {
    my $val = shift;
    $val =~ s|\r?\n\r?\n|<P>;
    $val =~ s|\r?\n|<BR>;
    return $val;
},
```

uc

Uppercases the text.

```
'uc' =>    sub {
              return uc(shift);
            },
```

unix

Removes those crufty carriage returns.

```
'unix' =>    sub {
              my $val = shift;
              $val =~ s/\r?\n/\n/g;
              return $val;
            },
```

urlencode

Changes non-word characters (except colon) to %3c notation.

```
'urlencode' => sub {
                  my $val = shift;
                  $val =~ s|[^w:]|sprintf "%%%02x", ord $1|eg;
                  return $val;
                },
```

value

Returns the value of the user session variable. Useful for starting a filter sequence with a seed value.

```
'value' =>    sub {
              return $::Values->(shift);
            },
```

word

Only returns word characters. Locale does apply if collation is properly set.

```
'word' =>    sub {
              my $val = shift;
              $val =~ s/\W+//g;
              return $val;
            },
```

You can define your own filters in an GlobalSub (or Sub or ActionMap):

```
package Vend::Interpolate;

$Filter{reverse} = sub { $val = shift; return scalar reverse $val };
```

That filter will reverse the characters sent.

The arguments sent to the subroutine are the value to be filtered, any associated variable or tag name, and any arguments appended to the filter name with periods as the separator.

A `[filter op=lookup.products.price]99-102[/filter]` will send ('99-102', undef, 'products', 'price') as the parameters. Assuming the value of the user variable `foo` is `bar`, the call `[value`

name=foo filter="lookup.products.price.extra"] will send ('bar', 'foo', 'products', 'price', 'extra').

2.28. flag

CALL INFORMATION

Parameters: **type**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->flag(
    {
        type => VALUE,
    }
)
```

OR

```
$Tag->flag($type, $ATTRHASH);
```

Attribute aliases

```
flag ==> type
name ==> type
```

DESCRIPTION

NO DESCRIPTION

2.29. fly_list

CALL INFORMATION

Parameters: **code base**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [fly_list] FOO [/fly_list]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->fly_list(
    {
        code => VALUE,
        base => VALUE,
    },
)
```

```
        BODY
    )

OR

    $Tag->fly_list($code, $base, $BODY);
```

DESCRIPTION

Syntax: [fly-list prefix=tag_prefix* code=code*]

Defines an area in a random page which performs the flypage lookup function, implementing the tags below.

```
[fly-list]
  (contents of flypage.html)
[/fly-list]
```

If you place the above around the contents of the demo flypage, in a file named flypage2.html, it will make these two calls display identical pages:

```
[page 00-0011] One way to display the Mona Lisa [/page]
[page flypage2 00-0011] Another way to display the Mona Lisa [/page]
```

If you place a [fly-list] tag alone at the top of the page, it will cause any page to act as a flypage. By default, the prefix is item, meaning the [item-code] tag will display the code of the item, the [item-price] tag will display price, etc. But if you use the prefix, i.e. [fly-list prefix=fly], then it will be [fly-code]; prefix=foo would cause [foo-code], etc.

2.30. fly_tax

CALL INFORMATION

Parameters: **area**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
    $Tag->fly_tax(
        {
            area => VALUE,
        }
    )

OR

    $Tag->fly_tax($area);
```

DESCRIPTION

NO DESCRIPTION

2.31. goto

CALL INFORMATION

Parameters: **name if**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->goto(
    {
        name => VALUE,
        if => VALUE,
    }
)

OR

$Tag->goto($name, $if);
```

DESCRIPTION

NO DESCRIPTION

2.32. handling

CALL INFORMATION

Parameters: **mode**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->handling(
    {
        mode => VALUE,
    }
)

OR

$Tag->handling($mode, $ATTRHASH);
```

Attribute aliases

```
carts ==> cart
```

```

modes ==> mode
name ==> mode
tables ==> table

```

DESCRIPTION**NO DESCRIPTION****2.33. harness****CALL INFORMATION**

No parameters.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [harness] FOO [/harness]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

$Tag->harness(
    {
    },
    BODY
)

```

OR

```

$Tag->harness($ATTRHASH, $BODY);

```

DESCRIPTION**NO DESCRIPTION****2.34. html_table****CALL INFORMATION**

No parameters.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [html_table] FOO [/html_table]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

$Tag->html_table(
    {
    },
    BODY
)

```

OR

```
$Tag->html_table($ATTRHASH, $BODY);
```

DESCRIPTION

NO DESCRIPTION

2.35. if

CALL INFORMATION

Parameters: **type term op compare**

THIS TAG HAS SPECIAL POSITIONAL PARAMETER HANDLING.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [if] FOO [/if]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

Called Routine for positional:

ASP/perl tag calls:

```
$Tag->if(
    {
        type => VALUE,
        term => VALUE,
        op   => VALUE,
        compare => VALUE,
    },
    BODY
)
```

OR

```
$Tag->if($type, $term, $op, $compare, $BODY);
```

Attribute aliases

```
base ==> type
comp ==> compare
condition ==> compare
operator ==> op
```

DESCRIPTION

Named call example: [if type="type" term="field" op="op" compare="compare"]

Positional call example: [if type field op compare]

negated: [if type="!type" term="field" op="op" compare="compare"]

Positional call example: [if !type field op compare]

Allows conditional building of HTML based on the setting of various Interchange session and database values. The general form is:

```
[if type term op compare]
```

Interchange: Interchange Tags Reference

```
[then]
    If true, this is printed on the document.
    The [then] [/then] is optional in most
    cases. If ! is prepended to the type
    setting, the sense is reversed and
    this will be output for a false condition.

[/then]
[elsif type term op compare]
    Optional, tested when if fails

[/elsif]
[else]
    Optional, printed when all above fail

[/else]
[/if]
```

The `[if]` tag can also have some variants:

```
[if type=explicit compare=`$perl_code`]
    Displayed if valid Perl CODE returns a true value.
[/if]
```

You can do some Perl-style regular expressions:

```
[if value name =~ /^mike/]
    This is the if with Mike.
[elsif value name =~ /^sally/]
    This is an elsif with Sally.
[/elsif]
[elsif value name =~ /^pat/]
    This is an elsif with Pat.
[/elsif]
[else]
    This is the else, no name I know.
[/else]
[/if]
```

While named parameter tag syntax works for `[if ...]`, it is more convenient to use positional calls in most cases. The only exception is if you are planning on doing a test on the results of another tag sequence:

```
[if value name =~ /[value b_name]/]
    Shipping name matches billing name.
[/if]
```

Oops! This will not work. You must do instead

```
[if base=value field=name op="=~" compare="/[value b_name]/"]
    Shipping name matches billing name.
[/if]
```

or better yet

```
[if type=explicit compare=`
    $Value->{name} =~ /$Value->{b_name}/
`]
    Shipping name matches billing name.
[/if]
```

Interchange also supports a limited `[and ...]` and `[or ...]` capability:


```
[if value name =~ /Mike/]
[or value name =~ /Jean/]
Your name is Mike or Jean.
[/if]

[if value name =~ /Mike/]
[and value state =~ /OH/]
Your name is Mike and you live in Ohio.
[/if]
```

If you wish to do very complex AND and OR operations, you will have to use `[if explicit]` or better yet embedded Perl/ASP. This allows complex testing and parsing of values.

There are many test targets available:

`STYLE="font-weight: bold"> config Directive`

The Interchange configuration variables. These are set by the directives in your Interchange configuration file (or the defaults).

```
[if config CreditCardAuto]
Auto credit card validation is enabled.
[/if]
```

data database::field::key

The Interchange databases. Retrieves a field in the database and returns true or false based on the value.

```
[if data products::size::99-102]
There is size information.
[else]
No size information.
[/else]
[/if]

[if data products::size::99-102 =~ /small/i]
There is a small size available.
[else]
No small size available.
[/else]
[/if]
```

discount

Checks to see if a discount is present for an item.

```
[if discount 99-102]
Item is discounted.
[/if]
```

explicit

A test for an explicit value. If perl code is placed between a `[condition]` `[/condition]` tag pair, it will be used to make the comparison. Arguments can be passed to import data from user space, just as with the `[perl]` tag.

```
[if explicit]
[condition]
    $country = '[value country]';
    return 1 if $country =~ /u\.?s\.?a?/i;
[/condition]
[/if]
```

```
        return 0;
[/condition]
You have indicated a US address.
[/else]
You have indicated a non-US address.
[/else]
[/if]
```

This example is a bit contrived, as the same thing could be accomplished with `[if value country =~ /u\.?s\.?a?/i]`, but you will run into many situations where it is useful. This will work for *Variable* values:

```
[if type=explicit compare="__MYVAR__"] .. [/if]
```

file

Tests for existence of a file. Useful for placing image tags only if the image is present.

```
[if file /home/user/www/images/[item-code].gif]
<IMG SRC="[item-code].gif">
[/if]
```

The `file` test requires that the *SafeUntrap* directive contains `ftfile` (which is the default).
`STYLE="font-weight: bold"> items`

The Interchange shopping carts. If not specified, the cart used is the main cart. Usually used as a litmus test to see if anything is in the cart, for example:

```
[if items]You have items in your shopping cart.[/if]

[if items layaway]You have items on layaway.[/if]
```

ordered

Order status of individual items in the Interchange shopping carts. If not specified, the cart used is the main cart. The following items refer to a part number of 99–102.

```
[if ordered 99-102] Item 99-102 is in your cart. [/if]
  Checks the status of an item on order, true if item
  99-102 is in the main cart.

[if ordered 99-102 layaway] ... [/if]
  Checks the status of an item on order, true if item
  99-102 is in the layaway cart.

[if ordered 99-102 main size] ... [/if]
  Checks the status of an item on order in the main cart,
  true if it has a size attribute.

[if ordered 99-102 main size =~ /large/i] ... [/if]
  Checks the status of an item on order in the main cart,
  true if it has a size attribute containing 'large'.
```

To make sure it is exactly large, you could use:

```
[if ordered 99-102 main size eq 'large'] ... [/if]
```

scratch

The Interchange scratchpad variables, which can be set with the [set name]value[/set] element.

```
[if scratch mv_separate_items]
ordered items will be placed on a separate line.
[else]
ordered items will be placed on the same line.
[/else]
[/if]
```

session

the interchange session variables. of particular interest are i<login>, i<frames>, i<secure>, and i<browser>.

STYLE="font-weight: bold"> **validcc**

a special case, takes the form [if validcc no type exp_date]. evaluates to true if the supplied credit card number, type of card, and expiration date pass a validity test. does a luhn-10 calculation to weed out typos or phony card numbers. Uses the standard CreditCardAuto variables for targets if nothing else is passed.

STYLE="font-weight: bold"> **value**

the interchange user variables, typically set in search, control, or order forms. variables beginning with c<mv_> are interchange special values, and should be tested/used with caution.

The *field* term is the specifier for that area. For example, [if session logged_in] would return true if the logged_in session parameter was set.

As an example, consider buttonbars for frame-based setups. It would be nice to display a different buttonbar (with no frame targets) for sessions that are not using frames:

```
[if scratch frames]
__BUTTONBAR_FRAMES__
[else]
__BUTTONBAR__
[/else]
[/if]
```

Another example might be the when search matches are displayed. If you use the string '[value mv_match_count] titles found', it will display a plural for only one match. Use:

```
[if value mv_match_count != 1]
[value mv_match_count] matches found.
[else]
Only one match was found.
[/else]
[/if]
```

The *op* term is the compare operation to be used. Compare operations are as in Perl:

```
== numeric equivalence
eq  string equivalence
>  numeric greater-than
gt  string greater-than
<  numeric less-than
lt  string less-than
```

```
!=  numeric non-equivalence
ne  string equivalence
```

Any simple perl test can be used, including some limited regex matching. More complex tests are best done with `[if explicit]`.

STYLE="font-weight: bold"> **[then] text [/then]**

This is optional if you are not nesting if conditions, as the text immediately following the `[if ..]` tag is used as the conditionally substituted text. If nesting `[if ...]` tags you should use a `[then]/[then]` on any outside conditions to ensure proper interpolation.

STYLE="font-weight: bold"> **[elsif type field op* compare*]**

named attributes: `[elsif type="type" term="field" op="op" compare="compare"]`

Additional conditions for test, applied if the initial `[if ...]` test fails.

STYLE="font-weight: bold"> **[else] text [/else]**

The optional else-text for an if or if_field conditional.

STYLE="font-weight: bold"> **[condition] text [/condition]**

Only used with the `[if explicit]` tag. Allows an arbitrary expression **in Perl** to be placed inside, with its return value interpreted as the result of the test. If arguments are added to `[if explicit args]`, those will be passed as arguments are in the `[perl]` construct.

2.36. import

CALL INFORMATION

Parameters: **table type**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Interpolates **container text** by default>.

This is a container tag, i.e. `[import] FOO [/import]`. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->import(
    {
        table => VALUE,
        type => VALUE,
    },
    BODY
)
```

OR

```
$Tag->import($table, $type, $ATTRHASH, $BODY);
```

Attribute aliases

```
base ==> table
database ==> table
```

DESCRIPTION

Named attributes:

```
[import table=table_name
      type=(TAB|PIPE|CSV|%%|LINE)
      continue=(NOTES|UNIX|DITTO)
      separator=c]
```

Import one or more records into a database. The `type` is any of the valid Interchange delimiter types, with the default being defined by the setting of the database *DELIMITER*. The table must already be a defined Interchange database table; it cannot be created on the fly. (If you need that, it is time to use SQL.)

The `type` of `LINE` and `continue` setting of `NOTES` is particularly useful, for it allows you to name your fields and not have to remember the order in which they appear in the database. The following two imports are identical in effect:

```
[import table=orders]
code: [value mv_order_number]
shipping_mode: [shipping-description]
status: pending
[/import]

[import table=orders]
shipping_mode: [shipping-description]
status: pending
code: [value mv_order_number]
[/import]
```

The `code` or `key` must always be present, and is always named `code`.

If you do not use `NOTES` mode, you must import the fields in the same order as they appear in the ASCII source file.

The `[import] TEXT [/import]` region may contain multiple records. If using `NOTES` mode, you must use a separator, which by default is a form-feed character (^L).

2.37. include**CALL INFORMATION**

Parameters: **file locale**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->include(
{
  file => VALUE,
  locale => VALUE,
})
```

OR

```
$Tag->include($file, $locale);
```

DESCRIPTION

Same as [file name] except interpolates for all Interchange tags and variables. Does NOT do locale translations.

2.38. index

CALL INFORMATION

Parameters: **table**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->index(
    {
        table => VALUE,
    }
)
```

OR

```
$Tag->index($table, $ATTRHASH);
```

Attribute aliases

```
base ==> table
database ==> table
```

DESCRIPTION

NO DESCRIPTION

2.39. input_filter

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [input_filter] FOO [/input_filter]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```

$Tag->input_filter(
    {
        name => VALUE,
    },
    BODY
)

OR

$Tag->input_filter($name, $ATTRHASH, $BODY);

```

Attribute aliases

```

ops ==> op
var ==> name
variable ==> name

```

DESCRIPTION

NO DESCRIPTION

2.40. item_list

CALL INFORMATION

Parameters: **name**

ONLY THE PARAMETERS ARE POSITIONAL.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [item_list] FOO [/item_list]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```

$Tag->item_list(
    {
        name => VALUE,
    },
    BODY
)

OR

$Tag->item_list($name, $ATTRHASH, $BODY);

```

Attribute aliases

```

cart ==> name

```

DESCRIPTION

Within any page, the [item_list cart*] element shows a list of all the items ordered by the customer so far. It works by repeating the source between [item_list] and [/item_list] once for each item ordered.

NOTE: The special tags that reference item within the list are not normal Interchange tags, do not

take named attributes, and cannot be contained in an HTML tag (other than to substitute for one of its values or provide a conditional container). They are interpreted only inside their corresponding list container. Normal Interchange tags can be interspersed, though they will be interpreted *after* all of the list-specific tags.

Between the `item_list` markers the following elements will return information for the current item:
`STYLE="font-weight: bold"> [if-data table column]`

If the database field `column` in table *table* is non-blank, the following text up to the `[/if_data]` tag is substituted. This can be used to substitute `IMG` or other tags only if the corresponding source item is present. Also accepts a `[else]else text[/else]` pair for the opposite condition.
`STYLE="font-weight: bold"> [if-data ! table column]`

Reverses sense for `[if-data]`.

`STYLE="font-weight: bold"> [/if-data]`

Terminates an `[if_data table column]` element.

`STYLE="font-weight: bold"> [if-field fieldname]`

If the products database field *fieldname* is non-blank, the following text up to the `[/if_field]` tag is substituted. If you have more than one products database table (see *ProductFiles*), it will check them in order until a matching key is found. This can be used to substitute `IMG` or other tags only if the corresponding source item is present. Also accepts a `[else]else text[/else]` pair for the opposite condition.

`STYLE="font-weight: bold"> [if-field ! fieldname]`

Reverses sense for `[if-field]`.

`STYLE="font-weight: bold"> [/if-field]`

Terminates an `[if_field fieldname]` element.

`STYLE="font-weight: bold"> [item-accessories attribute*, type*, field*, database*, name*]`

Evaluates to the value of the Accessories database entry for the item. If passed any of the optional arguments, initiates special processing of item attributes based on entries in the product database.

`STYLE="font-weight: bold"> [item-code]`

Evaluates to the product code for the current item.

`STYLE="font-weight: bold"> [item-data database fieldname]`

Evaluates to the field name *fieldname* in the arbitrary database table *database*, for the current item.

`STYLE="font-weight: bold"> [item-description]`

Evaluates to the product description (from the products file) for the current item.

In support of `OnFly`, if the description field is not found in the database, the `description` setting in the shopping cart will be used instead.

`STYLE="font-weight: bold"> [item-field fieldname]`

Evaluates to the field name *fieldname* in the products database, for the current item. If the item is not found in the first of the *ProductFiles*, all will be searched in sequence.

`STYLE="font-weight: bold"> [item-increment]`

Evaluates to the number of the item in the match list. Used for numbering search matches or order

items in the list.

STYLE="font-weight: bold"> **[item-last]tags[/item-last]**

Evaluates the output of the Interchange tags encased inside the tags, and if it evaluates to a numerical non-zero number (i.e. 1, 23, or -1) then the list iteration will terminate. If the evaluated number is **negative**, then the item itself will be skipped. If the evaluated number is **positive**, then the item itself will be shown but will be last on the list.

```
[item-last][calc]
  return -1 if '[item-field weight]' eq '';
  return 1 if '[item-field weight]' < 1;
  return 0;
[/calc][item-last]
```

If this is contained in your [item-list] (or [search-list] or flypage) and the weight field is empty, then a numerical -1 will be output from the [calc]/[calc] tags; the list will end and the item will **not** be shown. If the product's weight field is less than 1, a numerical 1 is output. The item will be shown, but will be the last item shown. (If it is an [item-list], any price for the item will still be added to the subtotal.) NOTE: no HTML style.

STYLE="font-weight: bold"> **[item-modifier attribute]**

Evaluates to the modifier value of attribute for the current item.

STYLE="font-weight: bold"> **[item-next]tags[/item_next]**

Evaluates the output of the Interchange tags encased inside, and if it evaluates to a numerical non-zero number (i.e. 1, 23, or -1) then the item will be skipped with no output. Example:

```
[item-next][calc][item-field weight] < 1[/calc][item-next]
```

If this is contained in your [item-list] (or [search-list] or flypage) and the product's weight field is less than 1, then a numerical 1 will be output from the [calc]/[calc] operation. The item will not be shown. (If it is an [item-list], any price for the item will still be added to the subtotal.)

STYLE="font-weight: bold"> **[item-price n* noformat*]**

Evaluates to the price for quantity n (from the products file) of the current item, with currency formatting. If the optional "noformat" is set, then currency formatting will not be applied.

STYLE="font-weight: bold"> **[discount-price n* noformat*]**

Evaluates to the discount price for quantity n (from the products file) of the current item, with currency formatting. If the optional "noformat" is set, then currency formatting will not be applied. Returns regular price if not discounted.

STYLE="font-weight: bold"> **[item-discount]**

Returns the difference between the regular price and the discounted price.

STYLE="font-weight: bold"> **[item-quantity]**

Evaluates to the quantity ordered for the current item.

STYLE="font-weight: bold"> **[item-subtotal]**

Evaluates to the subtotal (quantity * price) for the current item. Quantity price breaks are taken into account.

STYLE="font-weight: bold"> [**modifier-name attribute**]

Evaluates to the name to give an input box in which the customer can specify the modifier to the ordered item.

STYLE="font-weight: bold"> [**quantity-name**]

Evaluates to the name to give an input box in which the customer can enter the quantity to order.

2.41. label

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->label(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->label($name);
```

DESCRIPTION

NO DESCRIPTION

2.42. log

CALL INFORMATION

Parameters: **file**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [log] FOO [/log]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->log(
    {
        file => VALUE,
    },
```

```

        BODY
    )

OR

    $Tag->log($file, $ATTRHASH, $BODY);

```

Attribute aliases

```
arg ==> file
```

DESCRIPTION

NO DESCRIPTION

2.43. loop

CALL INFORMATION

Parameters: **list**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[loop] FOO [/loop]`. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

    $Tag->loop(
        {
            list => VALUE,
        },
        BODY
    )

OR

    $Tag->loop($list, $ATTRHASH, $BODY);

```

Attribute aliases

```
arg ==> list
args ==> list
```

DESCRIPTION

HTML example:

```
<TABLE><TR MV="loop 1 2 3"><TD>[loop-code]</TD></TR></TABLE>
```

Returns a string consisting of the LIST, repeated for every item in a comma-separated or space-separated list. Operates in the same fashion as the `[item-list]` tag, except for order-item-specific values. Intended to pull multiple attributes from an item modifier — but can be useful for other things, like building a

pre-ordained product list on a page.

Loop lists can be nested reliably in Interchange by using the `prefix="tag"` parameter. New syntax:

```
[loop arg="A B C"]
  [loop prefix=mid arg="[loop-code]1 [loop-code]2 [loop-code]3"]
    [loop prefix=inner arg="X Y Z"]
      [mid-code]-[inner-code]
    [/loop]
  [/loop]
[/loop]
```

You can do an arbitrary search with the `search="args"` parameter, just as in a one-click search:

```
[loop search="se=Americana/sf=category"]
  [loop-code] [loop-field title]
[/loop]
```

The above will show all items with a category containing the whole word "Americana", and will work the same in both old and new syntax.

`STYLE="font-weight: bold"> [if-loop-data table column] IF [else] ELSE [/else][if-loop-field]`

Outputs the **IF** if the `column` in `table` is non-empty, and the **ELSE** (if any) otherwise.
See [if-PREFIX-data].

`STYLE="font-weight: bold"> [if-loop-field column] IF [else] ELSE [/else][if-loop-field]`

Outputs the **IF** if the `column` in the `products` table is non-empty, and the **ELSE** (if any) otherwise. Will fall through to the first non-empty field if there are multiple `ProductFiles`.
See [if-PREFIX-field].

`STYLE="font-weight: bold"> [if-loop-param param] IF [else] ELSE [/else][if-loop-param]`

Only works if you have named return fields from a search (or from a passed list with the `lr=1` parameter).

Outputs the **IF** if the returned `param` is non-empty, and the **ELSE** (if any) otherwise.
See [if-PREFIX-param].

`STYLE="font-weight: bold"> [if-loop-pos N] IF [else] ELSE [/else][if-loop-param]`

Only works if you have multiple return fields from a search (or from a passed list with the `lr=1` parameter).

Parameters are numbered from ordinal 0, with [loop-pos 0] being the equivalent of [loop-code].

Outputs the **IF** if the returned positional parameter `N` is non-empty, and the **ELSE** (if any) otherwise.
See [if-PREFIX-pos].

`STYLE="font-weight: bold"> [loop-accessories]`

Outputs an [accessories ...] item.

See [PREFIX-accessories].

`STYLE="font-weight: bold"> [loop-change marker]`

See [PREFIX-change].

`STYLE="font-weight: bold"> [loop-code]`

Evaluates to the code for the current item.

See [PREFIX-code].

`STYLE="font-weight: bold"> [loop-data database fieldname]`

Evaluates to the field name *fieldname* in the arbitrary database table *database*, for the current item.
See [PREFIX–data].

STYLE="font-weight: bold"> [loop–description]

Evaluates to the product description (from the products file, passed description in on–fly item, or description attribute in cart) for the current item.

See [PREFIX–description].

STYLE="font-weight: bold"> [loop–field fieldname]

Evaluates to the field name *fieldname* in the database, for the current item.

See [PREFIX–field].

STYLE="font-weight: bold"> [loop–increment]

Evaluates to the number of the item in the list. Used for numbering items in the list.

Starts from integer 1.

See [PREFIX–increment].

STYLE="font-weight: bold"> [loop–last]tags[/loop–last]

Evaluates the output of the Interchange tags encased inside, and if it evaluates to a numerical non–zero number (i.e. 1, 23, or –1) then the loop iteration will terminate. If the evaluated number is **negative**, then the item itself will be skipped. If the evaluated number is **positive**, then the item itself will be shown but will be last on the list.

```
[loop-last][calc]
  return -1 if '[loop-field weight]' eq '';
  return 1 if '[loop-field weight]' < 1;
  return 0;
[/calc][loop-last]
```

If this is contained in your [loop list] and the weight field is empty, then a numerical –1 will be output from the [calc]/[calc] tags; the list will end and the item will **not** be shown. If the product's weight field is less than 1, a numerical 1 is output. The item will be shown, but will be the last item shown.

STYLE="font-weight: bold"> [loop–next]tags[/loop–next]

Evaluates the output of the Interchange tags encased inside, and if it evaluates to a numerical non–zero number (i.e. 1, 23, or –1) then the loop will be skipped with no output. Example:

```
[loop-next][calc][loop-field weight] < 1[/calc][loop-next]
```

If this is contained in your [loop list] and the product's weight field is less than 1, then a numerical 1 will be output from the [calc]/[calc] operation. The item will not be shown.

STYLE="font-weight: bold"> [loop–price n* noformat*]

Evaluates to the price for optional quantity n (from the products file) of the current item, with currency formatting. If the optional "noformat" is set, then currency formatting will not be applied.

2.44. mail

CALL INFORMATION

Parameters: **to**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [mail] FOO [/mail]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->mail(  
    {  
        to => VALUE,  
    },  
    BODY  
)
```

OR

```
$Tag->mail($to, $ATTRHASH, $BODY);
```

DESCRIPTION

NO DESCRIPTION

2.45. mvasp

CALL INFORMATION

Parameters: **tables**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [mvasp] FOO [/mvasp]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->mvasp(  
    {  
        tables => VALUE,  
    },  
    BODY  
)
```

OR

```
$Tag->mvasp($tables, $ATTRHASH, $BODY);
```

Attribute aliases

```
table ==> tables
```

DESCRIPTION**NO DESCRIPTION****2.46. nitems****CALL INFORMATION**

Parameters: **name**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->nitems(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->nitems($name, $ATTRHASH);
```

DESCRIPTION

Expands into the total number of items ordered so far. Takes an optional cart name as a parameter.

2.47. onfly**CALL INFORMATION**

Parameters: **code quantity**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->onfly(
    {
        code => VALUE,
        quantity => VALUE,
    }
)
```

OR

```
$Tag->onfly($code, $quantity, $ATTRHASH);
```

DESCRIPTION**NO DESCRIPTION****2.48. options****CALL INFORMATION**Parameters: **code**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->options(
    {
        code => VALUE,
    }
)
```

OR

```
$Tag->options($code, $ATTRHASH);
```

DESCRIPTION**NO DESCRIPTION****2.49. or****CALL INFORMATION**Parameters: **type term op compare**

THIS TAG HAS SPECIAL POSITIONAL PARAMETER HANDLING.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

Called Routine for positional:

ASP/perl tag calls:

```
$Tag->or(
    {
        type => VALUE,
        term => VALUE,
        op => VALUE,
        compare => VALUE,
    }
)
```



```

    )

OR

    $Tag->or($type, $term, $op, $compare);

```

Attribute aliases

```

    base ==> type
    comp ==> compare
    operator ==> op

```

DESCRIPTION

NO DESCRIPTION

2.50. order

CALL INFORMATION

Parameters: **code quantity**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

    $Tag->order(
        {
            code => VALUE,
            quantity => VALUE,
        }
    )

OR

    $Tag->order($code, $quantity);

```

DESCRIPTION

Expands into a hypertext link which will include the specified code in the list of products to order and display the order page. **code** should be a product code listed in one of the "products" databases. The optional argument **cart/page** selects the shopping cart the item will be placed in (begin with / to use the default cart main) and the order page that will display the order. The optional argument **database** constrains the order to a particular products file — if not specified, all databases defined as products files will be searched in sequence for the item.

Example:

```
Order a [order TK112]Toaster[/order] today.
```

Note: `[/order]` simply expands to ``.

2.51. page

CALL INFORMATION

Parameters: **href arg**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->page(
  {
    href => VALUE,
    arg  => VALUE,
  }
)
```

OR

```
$Tag->page($href, $arg, $ATTRHASH);
```

Attribute aliases

```
base ==> arg
```

DESCRIPTION

Insert a hyperlink to the specified catalog page pg. For example, `[page shirts]` will expand into ``. The catalog page displayed will come from "shirts.html" in the pages directory.

The additional argument will be passed to Interchange and placed in the `{arg}` session parameter. This allows programming of a conditional page display based on where the link came from. The argument is then available with the tag `[data session arg]`, or the embedded Perl session variable `$Session->{arg}`. Spaces and some other characters will be escaped with the %NN HTTP-style notation and unescaped when the argument is read back into the session.

A bit of magic occurs if Interchange has built a static plain HTML page for the target page. Instead of generating a normal Interchange-parsed page reference, a static page reference will be inserted if the user has accepted and sent back a cookie with the session ID.

The optional `form` argument allows you to encode a form in the link.

```
[page form="
  mv_order_item=99-102
  mv_order_size=L
  mv_order_quantity=1
  mv_separate_items=1
  mv_todo=refresh"] Order t-shirt in Large size </A>
```

The two form values `mv_session_id` and `mv_arg` are automatically added when appropriate. (`mv_arg` is the `arg` parameter for the tag.)

If the parameter `href` is not supplied, *process* is used, causing normal Interchange form processing. If the

href points to an http:// link no Interchange URL processing will be done, but the mv_session_id This would generate a form that ordered item number 99–102 on a separate line (mv_separate_items being set), with size L, in quantity 2. Since the page is not set, you will go to the default shopping cart page -- equally you could set mv_orderpage=yourpage to go to yourpage. All normal Interchange form caveats apply -- you must have an action, you must supply a page if you don't want to go to the default, etc. You can theoretically submit any form with this, though none of the included values can have newlines or trailing whitespace. If you want to do something like that you will have to write a UserTag. Interchange allows you to pass a search in a URL. Just specify the search with the special page reference scan. Here is an example:

```
[page scan
    se=Impressionists
    sf=category]
    Impressionist Paintings
[/page]
```

Here is the same thing from a home page (assuming /cgi-bin/vlink is the CGI path for Interchange's vlink):

```
<A HREF="/cgi-bin/vlink/scan/se=Impressionists/sf=category">
    Impressionist Paintings
</A>
```

Sometimes, you will find that you need to pass characters that will not be interpreted positionally. In that case, you should quote the arguments:

```
[page href=scan
    arg=|
        se="Something with spaces"
    |]
```

The two-letter abbreviations are mapped with these letters:

DL	mv_raw_dict_look
MM	mv_more_matches
SE	mv_raw_searchspec
ac	mv_all_chars
ar	mv_arg
bd	mv_base_directory
bs	mv_begin_string
ck	mv_cache_key
co	mv_coordinate
cs	mv_case
cv	mv_verbatim_columns
de	mv_dict_end
df	mv_dict_fold
di	mv_dict_limit
dl	mv_dict_look
do	mv_dict_order
dp	mv_delay_page
dr	mv_record_delim
em	mv_exact_match
er	mv_spelling_errors
fi	mv_search_file
fm	mv_first_match
fn	mv_field_names
hs	mv_head_skip

```
id mv_session_id
il mv_index_delim
ix mv_index_delim
lb mv_search_label
lo mv_list_only
lr mv_line_return
lr mv_search_line_return
ml mv_matchlimit
mm mv_max_matches
mp mv_profile
ms mv_min_string
ne mv_negate
np mv_nextpage
nu mv_numeric
op mv_column_op
os mv_orsearch
pc mv_pc
ra mv_return_all
rd mv_return_delim
rf mv_return_fields
rg mv_range_alpha
rl mv_range_look
rm mv_range_min
rn mv_return_file_name
rr mv_return_reference
rs mv_return_spec
rx mv_range_max
se mv_searchspec
sf mv_search_field
si mv_search_immediate
sp mv_search_page
sq mv_sql_query
st mv_searchtype
su mv_substring_match
tf mv_sort_field
to mv_sort_option
un mv_unique
va mv_value
```

They can be treated just the same as form variables on the page, except that they can't contain spaces, '/' in a file name, or quote marks. These characters can be used in URL hex encoding, i.e. %20 is a space, %2F is a /, etc. — &sp; or will not be recognized. If you use one of the methods below to escape these "unsafe" characters, you won't have to worry about this.

You may specify a one-click search in three different ways. The first is as used in previous versions, with the scan URL being specified completely as the page name. The second two use the "argument" parameter to the [page ...] or [area ...] tags to specify the search (an argument to a scan is never valid anyway).

STYLE="font-weight: bold"> **Original**

If you wish to do an OR search on the fields category and artist for the strings "Surreal" and "Gogh", while matching substrings, you would do:

```
[page scan se=Surreal/se=Gogh/os=yes/su=yes/sf=artist/sf=category]
  Van Gogh -- compare to surrealists
[/page]
```

In this method of specification, to replace a / (slash) in a file name (for the sp, bd, or fi parameter) you must use the shorthand of ::, i.e. sp=results::standard. (This may not work for some browsers, so

you should probably either put the page in the main pages directory or define the page in a search profile.)

STYLE="font-weight: bold"> **Ampersand**

You can substitute & for / in the specification and be able to use / and quotes and spaces in the specification.

```
[page scan se="Van Gogh"&sp=lists/surreal&os=yes&su=yes&sf=artist&sf=category]
  Van Gogh -- compare to surrealists
[/page]
```

Any "unsafe" characters will be escaped.

STYLE="font-weight: bold"> **Multi-line**

You can specify parameters one to a line, as well.

```
[page scan
  se="Van Gogh"
  sp=lists/surreal
  os=yes
  su=yes
  sf=artist
  sf=category
] Van Gogh -- compare to surrealists [/page]
```

Any "unsafe" characters will be escaped. You may not search for trailing spaces in this method; it is allowed in the other notations.

New syntax and old syntax handle the tags the same, though if by some odd chance you wanted to be able to search for a] (right square bracket) you would need to use new syntax.

The optional *arg* is used just as in the *page* tag.

[/page]

Expands into . Used with the page element, such as:

```
[page shirts]Our shirt collection[/page].
```

TIP: A small efficiency boost in large pages is to just use the tag.

2.52. perl

CALL INFORMATION

Parameters: **tables**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [perl] FOO [/perl]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->perl(
```

```
{
  tables => VALUE,
},
BODY
)
```

OR

```
$Tag->perl($tables, $ATTRHASH, $BODY);
```

Attribute aliases

```
table ==> tables
```

DESCRIPTION

```
[perl]
$name      = $Values->{name};
$browser   = $Session->{browser};
return "Hi, $name! How do you like your $browser?"
[/perl]
```

HTML example:

```
<PRE mv=perl>
$name      = $Values->{name};
$browser   = $Session->{browser};
return "Hi, $name! How do you like your $browser?"
</PRE>
```

Perl code can be directly embedded in Interchange pages. The code is specified as [perl arguments*] any_legal_perl_code [/perl]. The value returned by the code will be inserted on the page. Object references are available for most Interchange tags and functions, as well as direct references to Interchange session and configuration values.

<code>\$CGI->{key}</code>	Hash reference to raw submitted values
<code>\$CGI_array->{key}</code>	Arrays of submitted values
<code>\$Carts->{cartname}</code>	Direct reference to shopping carts
<code>\$Config->{key}</code>	Direct reference to <code>\$Vend::Cfg</code>
<code>\$DbSearch->array(@args)</code>	Do a DB search and get results
<code>\$Document->header()</code>	Writes header lines
<code>\$Document->send()</code>	Writes to output
<code>\$Document->write()</code>	Writes to page
<code>\$Scratch->{key}</code>	Direct reference to scratch area
<code>\$Session->{key}</code>	Direct reference to session area
<code>\$Tag->tagname(@args)</code>	Call a tag as a routine (UserTag too!)
<code>\$TextSearch->array(@args)</code>	Do a text search and get results
<code>\$Values->{key}</code>	Direct reference to user form values
<code>\$Variable->{key}</code>	Config variables (same as <code>\$Config->{Variable}</code>);
<code>&HTML(\$html)</code>	Same as <code>\$Document->write(\$html)</code> ;
<code>&Log(\$msg)</code>	Log to the error log

For full descriptions of these objects, see *Interchange Programming*.

If you wish to use database values in your Perl code, you must pre-open the table(s) you will be using. This can be done by including the table name in the `tables` parameter of the Perl tag:

```
[perl tables=products]
$result = "You asked about $Values->{code}. Here is the description: ";
```

```

    $result .= $Tag->data('products', 'description', $Values->{code});
    return $result;
[/perl]

```

If you do not do this, your code will fail with a runtime Safe error.

2.53. price

CALL INFORMATION

Parameters: **code**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

    $Tag->price(
        {
            code => VALUE,
        }
    )

```

OR

```

    $Tag->price($code, $ATTRHASH);

```

Attribute aliases

```
base ==> mv_ib
```

DESCRIPTION

Arguments:

<code>code</code>	Product code/SKU
<code>base</code>	Only search in product table <code>*base*</code>
<code>quantity</code>	Price for a quantity
<code>discount</code>	If <code>true(1)</code> , check discount coupons and apply
<code>noformat</code>	If <code>true(1)</code> , don't apply currency formatting

Expands into the price of the product identified by code as found in the products database. If there is more than one products file defined, they will be searched in order unless constrained by the optional argument **base**. The optional argument **quantity** selects an entry from the quantity price list. To receive a raw number, with no currency formatting, use the option `noformat=1`.

Interchange maintains a price in its database for every product. The price field is the one required field in the product database — it is necessary to build the price routines.

For speed, Interchange builds the code that is used to determine a product's price at catalog configuration time. If you choose to change a directive that affects product pricing you must reconfigure the catalog.

Quantity price breaks are configured by means of the *CommonAdjust* directive. There are a number of CommonAdjust recipes which can be used; the standard example in the demo calls for a separate pricing table called `pricing`. Observe the following:

Interchange: Interchange Tags Reference

```
CommonAdjust pricing:q2,q5,q10,q25, ;products:price, ==size:pricing
```

This says to check quantity and find the applicable column in the pricing database and apply it. In this case, it would be:

2-4	Column	*q2*
5-9	Column	*q5*
10-24	Column	*q10*
25 up	Column	*q25*

What happens if quantity is one? It "falls back" to the price that is in the table `products`, column `price`. After that, if there is a size attribute for the product, the column in the pricing database corresponding to that column is checked for additions or subtractions (or even percentage changes).

If you use this tag in the demo:

```
[price code=99-102 quantity=10 size=XL]
```

the price will be according to the `q10` column, adjusted by what is in the `XL` column. (The row is of course 99-102.) The following entry in pricing:

code	q2	q5	q10	q25	XL
99-102	10	9	8	7	.50

Would yield 8.50 for the price. Quantity of 10 in the `q10` column, with 50 cents added for extra large (XL). Following are several examples based on the above entry as well as this the entry in the `products` table:

code	description	price	size
99-102	T-Shirt	10.00	S=Small, M=Medium, L=Large*, XL=Extra Large

NOTE: The examples below assume a US locale with 2 decimal places, use of commas to separate, and a dollar sign (\$) as the currency formatting.

TAG	DISPLAYS
[price 99-102]	\$10.00
[price code="99-102"]	\$10.00
[price code="99-102" quantity=1]	\$10.00
[price code="99-102" noformat=1]	10
[price code="99-102" quantity=5]	\$9.00
[price code="99-102" quantity=5 size=XL]	\$9.50
[price code="99-102" size=XL]	\$10.50
[price code="99-102" size=XL noformat=1]	10.5

Product discounts for specific products, all products, or the entire order can be configured with the [discount ...] tag. Discounts are applied on a per-user basis — you can gate the discount based on membership in a club or other arbitrary means.

Adding [discount 99-102] \$s *.9[/discount] deducts 10% from the price at checkout, but the price tag will not show that unless you add the `discount=1` parameter.

[price code="99-102"]	-->	\$10.00
[price code="99-102" discount=1]	-->	\$9.00

See *Product Discounts*.

2.54. process

CALL INFORMATION

Aliases for tag

process_target

Parameters: **target secure**

ONLY THE PARAMETERS ARE POSITIONAL.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->process(
    {
        target => VALUE,
        secure => VALUE,
    }
)
```

OR

```
$Tag->process($target, $secure, $ATTRHASH);
```

DESCRIPTION

NO DESCRIPTION

2.55. profile

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->profile(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->profile($name, $ATTRHASH);
```

DESCRIPTION**NO DESCRIPTION****2.56. query****CALL INFORMATION**

Parameters: **sql**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [query] FOO [/query]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->query(
    {
        sql => VALUE,
    },
    BODY
)
```

OR

```
$Tag->query($sql, $ATTRHASH, $BODY);
```

Attribute aliases

```
query ==> sql
```

DESCRIPTION**NO DESCRIPTION****2.57. read_cookie****CALL INFORMATION**

Parameters: **name**

ONLY THE PARAMETERS ARE POSITIONAL.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->read_cookie(
    {
        name => VALUE,
```

```

    }
)

OR

$Tag->read_cookie($name);

```

DESCRIPTION**NO DESCRIPTION****2.58. record****CALL INFORMATION**

No parameters.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```

$Tag->record(
    {
    }
)

OR

$Tag->record($ATTRHASH);

```

Attribute aliases

```

code ==> key
column ==> col
field ==> col

```

DESCRIPTION**NO DESCRIPTION****2.59. region****CALL INFORMATION**

No parameters.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [region] FOO [/region]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->region(
    {
    },
    BODY
)
```

OR

```
$Tag->region($ATTRHASH, $BODY);
```

Attribute aliases

```
args ==> arg
params ==> arg
search ==> arg
```

DESCRIPTION

NO DESCRIPTION

2.60. row

CALL INFORMATION

Parameters: **width**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Interpolates **container text** by default.

This is a container tag, i.e. [row] FOO [/row]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->row(
    {
        width => VALUE,
    },
    BODY
)
```

OR

```
$Tag->row($width, $BODY);
```

DESCRIPTION

Formats text in tables. Intended for use in emailed reports or <PRE></PRE> HTML areas. The parameter *nn* gives the number of columns to use. Inside the row tag, [col param=value ...] tags may be used.

STYLE="font-weight: bold"> [col width=nn wrap=yes|no gutter=n align=left|right|input spacing=n]

Sets up a column for use in a [row]. This parameter can only be contained inside a [row nn] [/row] tag pair. Any number of columns (that fit within the size of the row) can be defined.

The parameters are:

width=nn	The column width, I<including the gutter>. Must be supplied, there is no default. A shorthand method is to just supply the number as the I<first> parameter, as in [col 20].
gutter=n	The number of spaces used to separate the column (on the right-hand side) from the next. Default is 2.
spacing=n	The line spacing used for wrapped text. Default is 1, or single-spaced.
wrap=(yes no)	Determines whether text that is greater in length than the column width will be wrapped to the next line. Default is I<yes>.
align=(L R I)	Determines whether text is aligned to the left (the default), the right, or in a way that might display an HTML text input field correctly.

[/col]

Terminates the column field.

2.61. saletax

CALL INFORMATION

Parameters: **name noformat**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->saletax(
    {
        name => VALUE,
        noformat => VALUE,
    }
)

OR

$Tag->saletax($name, $noformat);
```

Attribute aliases

```
cart ==> name
```

DESCRIPTION

Expands into the sales tax on the subtotal of all the items ordered so far for the cart, default cart is `main`. If there is no key field to derive the proper percentage, such as state or zip code, it is set to 0. If the `noformat` tag is present and non-zero, the raw number with no currency formatting will be given.

2.62. scratch

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->scratch(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->scratch($name);
```

DESCRIPTION

Returns the contents of a scratch variable to the page. (A scratch variable is set with a `[set]` value `[/set]` container pair.)

2.63. scratchd

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->scratchd(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->scratchd($name);
```

DESCRIPTION**NO DESCRIPTION****2.64. search_region****CALL INFORMATION**

Parameters: **arg**

ONLY THE PARAMETERS ARE POSITIONAL.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [search_region] FOO [/search_region]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->search_region(
    {
        arg => VALUE,
    },
    BODY
)
```

OR

```
$Tag->search_region($arg, $ATTRHASH, $BODY);
```

Attribute aliases

```
args ==> arg
params ==> arg
search ==> arg
```

DESCRIPTION**NO DESCRIPTION****2.65. selected****CALL INFORMATION**

Parameters: **name value**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->selected(
    {
        name => VALUE,
        value => VALUE,
    }
)
```

OR

```
$Tag->selected($name, $value, $ATTRHASH);
```

DESCRIPTION

You can provide a "memory" for drop-down menus, radio buttons, and checkboxes with the [checked] and [selected] tags.

This will output SELECTED if the variable `var_name` is equal to `value`. If the optional `MULTIPLE` argument is present, it will look for any of a variety of values. Not case sensitive unless the optional `case=1` parameter is used.

Here is a drop-down menu that remembers an item-modifier color selection:

```
<SELECT NAME="color">
<OPTION [selected color blue]> Blue
<OPTION [selected color green]> Green
<OPTION [selected color red]> Red
</SELECT>
```

Here is the same thing, but for a shopping-basket color selection

```
<SELECT NAME="[modifier-name color]">
<OPTION [selected [modifier-name color] blue]> Blue
<OPTION [selected [modifier-name color] green]> Green
<OPTION [selected [modifier-name color] red]> Red
</SELECT>
```

By default, the Values space (i.e. [value foo]) is checked -- if you want to use the volatile CGI space (i.e. [cgi foo]) use the option `cgi=1`.

2.66. set

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. [set] FOO [/set]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->set(
    {
        name => VALUE,
    },
    BODY
)
```



```

    )

OR

    $Tag->set($name, $BODY);

```

DESCRIPTION

Sets a scratch variable to *value*.

Most of the `mv_*` variables that are used for search and order conditionals are in another namespace — they can be set by means of hidden fields in a form.

You can set an order profile with:

```

[set checkout]
name=required
address=required
[/set]
<INPUT TYPE=hidden NAME=mv_order_profile VALUE="checkout">

```

A search profile would be set with:

```

[set substring_case]
mv_substring_match=yes
mv_case=yes
[/set]
<INPUT TYPE=hidden NAME=mv_profile VALUE="substring_case">

```

Any of these profile values can be set in the OrderProfile files as well.

2.67. set_cookie

CALL INFORMATION

Parameters: **name value expire**

ONLY THE PARAMETERS ARE POSITIONAL.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```

    $Tag->set_cookie(
        {
            name => VALUE,
            value => VALUE,
            expire => VALUE,
        }
    )

OR

    $Tag->set_cookie($name, $value, $expire);

```

DESCRIPTION

NO DESCRIPTION**2.68. seti****CALL INFORMATION**

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Interpolates **container text** by default>.

This is a container tag, i.e. [seti] FOO [/seti]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->seti(
    {
        name => VALUE,
    },
    BODY
)

OR

$Tag->seti($name, $BODY);
```

DESCRIPTION**NO DESCRIPTION****2.69. setlocale****CALL INFORMATION**

Parameters: **locale currency**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->setlocale(
    {
        locale => VALUE,
        currency => VALUE,
    }
)

OR

$Tag->setlocale($locale, $currency, $ATTRHASH);
```

DESCRIPTION**NO DESCRIPTION****2.70. shipping****CALL INFORMATION**

Parameters: **mode**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```

$Tag->shipping(
    {
        mode => VALUE,
    }
)

```

OR

```

$Tag->shipping($mode, $ATTRHASH);

```

Attribute aliases

```

carts ==> cart
modes ==> mode
name ==> mode
tables ==> table

```

DESCRIPTION

The shipping cost of the items in the basket via mode -- the default mode is the shipping mode currently selected in the mv_shipmode variable. See *SHIPPING*.

2.71. shipping_desc**CALL INFORMATION**

Aliases for tag

shipping_description

Parameters: **mode**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->shipping_desc(
    {
        mode => VALUE,
    }
)
```

OR

```
$Tag->shipping_desc($mode);
```

DESCRIPTION**NO DESCRIPTION****2.72. soap****CALL INFORMATION**

Parameters: **call uri proxy**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->soap(
    {
        call => VALUE,
        uri => VALUE,
        proxy => VALUE,
    }
)
```

OR

```
$Tag->soap($call, $uri, $proxy, $ATTRHASH);
```

DESCRIPTION**NO DESCRIPTION****2.73. sql****CALL INFORMATION**

Parameters: **type query**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [sql] FOO [/sql]. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->sql(
    {
        type => VALUE,
        query => VALUE,
    },
    BODY
)

OR

$Tag->sql($type, $query, $ATTRHASH, $BODY);
```

DESCRIPTION

NO DESCRIPTION

2.74. strip

CALL INFORMATION

No parameters.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [strip] FOO [/strip]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->strip(
    {
    },
    BODY
)

OR

$Tag->strip($BODY);
```

DESCRIPTION

NO DESCRIPTION

2.75. subtotal

CALL INFORMATION

Parameters: **name noformat**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->subtotal(  
    {  
        name => VALUE,  
        noformat => VALUE,  
    }  
)
```

OR

```
$Tag->subtotal($name, $noformat);
```

Attribute aliases

```
cart ==> name
```

DESCRIPTION

Positional: [subtotal cart* noformat*]

mandatory: NONE

optional: cart noformat

Expands into the subtotal cost, exclusive of sales tax, of all the items ordered so far for the optional `cart`. If the `noformat` tag is present and non-zero, the raw number with no currency formatting will be given.

2.76. tag

CALL INFORMATION

Parameters: **op arg**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. This may mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. [tag] FOO [/tag]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->tag(  
    {  
        op => VALUE,  
        arg => VALUE,  
    },  
    BODY  
)
```

OR

```
$Tag->tag($op, $arg, $ATTRHASH, $BODY);
```

Attribute aliases

```
description ==> arg
```

DESCRIPTION

Performs any of a number of operations, based on the presence of `arg`. The arguments that may be given are:

STYLE="font-weight: bold"> **export database file* type***

Exports a complete Interchange database to its text source file (or any specified file). The integer `n`, if specified, will select export in one of the enumerated Interchange export formats. The following tag will export the products database to `products.txt` (or whatever you have defined its source file as), in the format specified by the *Database* directive:

```
[tag export products][/tag]
```

Same thing, except to the file `products/new_products.txt`:

```
[tag export products products/newproducts.txt][/tag]
```

Same thing, except the export is done with a PIPE delimiter:

```
[tag export products products/newproducts.txt 5][/tag]
```

The file is relative to the catalog directory, and only may be an absolute path name if *NoAbsolute* is set to No.

STYLE="font-weight: bold"> **flag arg**

Sets an Interchange condition.

The following enables writes on the `products` and `sizes` databases held in Interchange internal DBM format:

```
[tag flag write]products sizes[/tag]
```

SQL databases are always writable if allowed by the SQL database itself — in-memory databases will never be written.

The `[tag flag build][/tag]` combination forces static build of a page, even if dynamic elements are contained. Similarly, the `[tag flag cache][/tag]` forces search or page caching (not usually wise).

STYLE="font-weight: bold"> **log dir/file**

Logs a message to a file, fully interpolated for Interchange tags. The following tag will send every item code and description in the user's shopping cart to the file `logs/transactions.txt`:

```
[tag log logs/transactions.txt]
[item_list][item-code] [item-description]
[/item_list][/tag]
```

The file is relative to the catalog directory, and only may be an absolute path name if *NoAbsolute* is set to No.

STYLE="font-weight: bold"> **mime description_string**

Returns a MIME-encapsulated message with the boundary as employed in the other mime tags, and the `description_string` used as the Content-Description. For example

```
[tag mime My Plain Text]Your message here.[/tag]
```

will return

```
Content-Type: TEXT/PLAIN; CHARSET=US-ASCII
Content-ID: [sequential, lead as in mime boundary]
Content-Description: My Plain Text

Your message here.
```

When used in concert with `[tag mime boundary]`, `[tag mime header]`, and `[tag mime id]`, allows MIME attachments to be included — typically with PGP-encrypted credit card numbers. See the demo page [ord/report.html](#) for an example.

STYLE="font-weight: bold"> **mime boundary**

Returns a MIME message boundary with unique string keyed on session ID, page count, and time.

STYLE="font-weight: bold"> **mime header**

Returns a MIME message header with the proper boundary for that session ID, page count, and time.

STYLE="font-weight: bold"> **mime id**

Returns a MIME message id with the proper boundary for that session ID, page count, and time.

STYLE="font-weight: bold"> **show_tags**

The encased text will not be substituted for with Interchange tags, with `<` and `[` characters changed to `&#lt;` and `[` respectively.

```
[tag show_tags][value whatever][/tag]
```

time

Formats the current time according to POSIX `strftime` arguments. The following is the string for Thursday, April 30, 1997.

```
[tag time]%A, %B %d, %Y[/tag]
```

touch

Touches a database to allow use of the `tag_data()` routine in user-defined subroutines. If this is not done, the routine will error out if the database has not previously been accessed on the page.

```
[tag touch products][/tag]
```

2.77. time

CALL INFORMATION

Parameters: **locale**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[time] FOO [/time]`. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->time(
    {
        locale => VALUE,
    },
    BODY
)

OR

$Tag->time($locale, $ATTRHASH, $BODY);
```

DESCRIPTION

Formats the current time according to POSIX `strftime` arguments. The following is the string for Monday, January 1, 2001.

```
[time]%A, %B %d, %Y[/tag]
```

See the `strftime` man page for information on the arguments (which are the same as modern UNIX date commands).

Accepts the following options:

`STYLE="font-weight: bold"> adjust`

If you wish to temporarily adjust the time for display purposes, you can pass an `adjust` parameter with the number of hours (plus or minus) from the local time or from GMT:

```
[time]%c[/time]
[time adjust="-3"]%c[/time]
```

Will display:

```
Mon 01 Jan 2001 11:29:03 AM EST
Mon 01 Jan 2001 08:29:03 AM EST
```

Note that the time zone does not change — you should either pick a format which doesn't display zone, use the `tz` parameter, or manage it yourself.

NOTE: You can adjust time globally for an Interchange installation by setting the `$ENV{TZ}` variable on many systems. Set `TZ` in your environment and then restart interchange:

```
## bash/ksh/sh
TZ=PST7PDT; export TZ
interchange -restart

## csh/tcsh
setenv TZ PST7PDT
interchange -restart
```

On most modern UNIX systems, all times will now be in the PST zone.

`STYLE="font-weight: bold"> gmt`

If you want to display time as GMT, use the `gmt` parameter:

```
[time]%c[/time]
[time gmt=1]%c[/time]
```

will display:

```
Mon 01 Jan 2001 11:33:26 AM EST
Mon 01 Jan 2001 04:33:26 PM EST
```

Once again, the zone will not be set to GMT, so you should pick a format string which doesn't use zone, use the `tz` parameter, or manage it yourself.

`STYLE="font-weight: bold"> locale`

Format the time according to the named `locale`, assuming that `locale` is available on your operating system. For example, the following:

```
[time locale=en_US]%B %d, %Y[/time]
[time locale=fr_FR]%B %d, %Y[/time]
```

should display:

```
January 01, 2001
janvier 01, 2001
```

tz

Use the passed `tz` to display the time. Will adjust for hours difference.

Example:

```
[time tz=GMT0]
[time tz=CST6CDT]
[time tz=PST8PDT]
```

will display:

```
Mon 01 Jan 2001 04:43:02 PM GMT
Mon 01 Jan 2001 10:43:02 AM CST
Mon 01 Jan 2001 08:43:02 AM PST
```

Note that the first alphabetical string is the zone name when not under daylight savings time, the digit is the number of hours displacement from GMT, and the second alphabetical string is the zone name when in daylight savings time. NOTE: This may not work on all operating systems.

2.78. **timed_build**

CALL INFORMATION

Parameters: **file**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[timed_build] FOO [/timed_build]`. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->timed_build(
    {
        file => VALUE,
    },
    BODY
)
```

OR

```
$Tag->timed_build($file, $ATTRHASH, $BODY);
```

DESCRIPTION

Allows you to build CPU-intensive regions of ITL tags on a timed basis.

In the simplest case, surround a region of ITL with `[timed-build]` and `[/timed-build]`:

```
[timed-build]
    Built at [time]%c[/time].
[/timed-build]
```

If a `file` parameter is not passed, saves to the directory *timed* in catalog root, with the file name of the current page. If the `minutes` parameter is not passed specifying how often the page should be rebuilt, then it will not be rebuilt until the output file is removed.

Accepts the following parameters:

`STYLE="font-weight: bold"> file`

Name of the file to save the results in. Relative to catalog root. The directory must exist.

`STYLE="font-weight: bold"> if`

Allows you to only display the cached region when the `if` parameter is true. For example, you can do:

```
[timed-build if="[value timed]"]
ITL tags....
[/timed-build]
```

The cached region will only be displayed if the variable `timed` is set to a non-zero, non-blank value. Otherwise, the ITL tags will be re-interpreted every time.

`STYLE="font-weight: bold"> minutes`

The number of minutes after which the timed build should be repeated. If set to 0, it will be built once and then not rebuilt until the output file is removed.

`STYLE="font-weight: bold"> period`

Alternative way of expressing time. You can pass a string describing the rebuild time period:

```
[timed-build period="4 hours"]
```

```
ITL tags....
[/timed-build]
```

This is really the same as `minutes=240`. Useful for passing seconds:

```
[timed-build period="5 seconds"]
ITL tags....
[/timed-build]
```

The region will be rebuilt every 5 seconds. **PERFORMANCE TIP:** use minutes of .08 instead; avoids having to parse the period string.

If you have the StaticDir catalog.cfg parameter set to a writable path, you can build a cached static version of your catalog over time. Simply place a `[timed-build]` tag at the top of pages you wish to build statically.

Assuming the catalog is not busy and write lock can be obtained, the StaticDBM database will be updated to mark the page as static and the next time a link is made for that page the static version will be presented.

2.79. tmp

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Interpolates **container text** by default>.

This is a container tag, i.e. `[tmp] FOO [/tmp]`. Nesting: NO

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->tmp(
    {
        name => VALUE,
    },
    BODY
)
```

OR

```
$Tag->tmp($name, $BODY);
```

DESCRIPTION

Sets a scratch variable to *value*, but at the end of the user session the Scratch key is deleted. This saves session write time in many cases.

This tag interpolates automatically. (Interpolation can be turned off with `interpolate=0`.)

IMPORTANT NOTE: the `[tmp ...][tmp]` tag is not appropriate for setting order profiles or `mv_click` actions. If you want to avoid that, use a profile stored via the catalog.cfg directive `OrderProfile`.

2.80. total_cost

CALL INFORMATION

Parameters: **name noformat**

Positional parameters in same order.

Pass attribute hash as last to subroutine: **no**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->total_cost(
    {
        name => VALUE,
        noformat => VALUE,
    }
)

OR

$Tag->total_cost($name, $noformat);
```

Attribute aliases

```
cart ==> name
```

DESCRIPTION

Expands into the total cost of all the items in the current shopping cart, including sales tax (if any).

2.81. tree

CALL INFORMATION

Parameters: **table master subordinate start**

ONLY THE PARAMETERS ARE POSITIONAL.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

This is a container tag, i.e. [tree] FOO [/tree]. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->tree(
    {
        table => VALUE,
        master => VALUE,
        subordinate => VALUE,
        start => VALUE,
    },
    BODY
)

OR

$Tag->tree($table, $master, $subordinate, $start, $ATTRHASH, $BODY);
```

Attribute aliases

```
sub ==> subordinate
```

DESCRIPTION

Provides iterative list capability for binary trees. It produces hash-based rows use the same tags as `[item-list]`; sets some additional hash key entries to describe the tree and provide display control. Works on a data set with the structure:

parent	child
99	a
a	b
a	c
a	d
a	x
x	y
x	z
99	m
99	n
99	o
o	e
o	f
o	g

Sets several keys which assist in walking and displaying the tree.

STYLE="font-weight: bold"> **mv_level**

Level of the item. If it is in the first level, it is 0. Sublevels are infinite (except for performance).

STYLE="font-weight: bold"> **mv_increment**

Increment label for the item. Normally goes from 1...n, but can be changed to A...Z or a...z in outline mode.

STYLE="font-weight: bold"> **mv_children**

If in autodetect mode, set to the number of children this branch has. If a leaf, set to 0.

STYLE="font-weight: bold"> **mv_spacing**

A multiple of level times the spacing option. Useful for setting width of spacer images.

The above sample data would produce:

a	mv_level=0, mv_increment=1, mv_children=4
b	mv_level=1, mv_increment=1, mv_children=0
c	mv_level=1, mv_increment=2, mv_children=0
d	mv_level=1, mv_increment=3, mv_children=0
x	mv_level=1, mv_increment=4, mv_children=2
y	mv_level=2, mv_increment=1, mv_children=0
z	mv_level=2, mv_increment=2, mv_children=0
m	mv_level=0, mv_increment=1, mv_children=0
n	mv_level=0, mv_increment=2, mv_children=0
o	mv_level=0, mv_increment=3, mv_children=3
e	mv_level=1, mv_increment=1, mv_children=0
f	mv_level=1, mv_increment=2, mv_children=0
g	mv_level=1, mv_increment=3, mv_children=0

from the tag call:

Interchange: Interchange Tags Reference

```
<table>
[tree    start=99
        parent=parent_fld
        child=child_fld
        autodetect=1
        spacing=4
        full=1]
<tr>
<td>
[if-item-param mv_level]
    [item-calc]
        return '&nbsp;' x [item-param mv_spacing];
    [/item-calc]
[/if-item-param]
[item-param child_fld]
</td>
<td>
        mv_level=[item-param mv_level],
        mv_increment=[item-param mv_increment],
        mv_children=[item-param mv_children]
</td>
</tr>
[/tree]
</table>
```

Accepts the following parameters:

STYLE="font-weight: bold"> **table**

Database table which contains the tree. Must be a valid Interchange table identifier.

STYLE="font-weight: bold"> **parent**

The column which is used to determine the parent of the item.

STYLE="font-weight: bold"> **subordinate**

The child column, which determines which items are sub-items of the current one. Used to re-query for items with its value in `parent`.

STYLE="font-weight: bold"> **start_item**

The first item to be followed, i.e. the `parent` value of all the top-level items.

STYLE="font-weight: bold"> **autodetect**

Specifies that the next level should be followed to detect the number of child items contained. Not recursive; only follows far enough to determine the children of the current item.

STYLE="font-weight: bold"> **full**

Specifies that all items should be followed. Essentially the same as specifying `memo` and passing the `explode` variable, but not dependent on them. Useful for building lists for inclusion in embedded Perl, among other things.

STYLE="font-weight: bold"> **stop**

An optional `stop` field which, when the value is true, can stop the following of the branch.

STYLE="font-weight: bold"> **continue**

An optional `continue` field which, when the value is true, can force the branch to be

followed.

STYLE="font-weight: bold"> **sort**

The column which should be used for ordering the items -- determines the order in which they will be displayed under the current parent.

STYLE="font-weight: bold"> **outline**

Sets outline mode, where `mv_increment` will be displayed with letter values or numeral values. If set to specifically 1, will produced outline increments like:

```

1
  A
  B
    1
    2
  C
    1
    2
      a
      b
        1
        2
          a
          b
2

```

memo

Indicates that the collapse/explode/toggle features are to be used, and names a Scratch variable where the values should be stored.

STYLE="font-weight: bold"> **collapse**

The name of a variable in the user's session which will determine that the tree should be "collapsed". When collapsed, the child items will not be followed unless they are set to be followed with `toggle`. Zeros all toggles.

Requires `memo` to be set if values are to be retained.

STYLE="font-weight: bold"> **toggle**

The name of a variable in the user's session which will determine that the current item should be either followed or not followed. The first time the `toggle` variable corresponding to its primary key is passed, the item will be expanded. The next call will "collapse" the item.

Requires `memo` to be set if values are to be retained.

STYLE="font-weight: bold"> **explode**

The name of a variable in the user's session which will determine that the tree should be "exploded". When exploded, all child items are followed and the full tree can be displayed.

Requires `memo` to be set if values are to be retained.

STYLE="font-weight: bold"> **pedantic**

When set to a true value, and an endless tree is detected (i.e. the child branch contains a parent) then the error will be logged to the catalog error log and the tree call will return with an error.

If `pedantic` is not set (the default), the current leaf will be shown but never followed. This allows partial display of the tree.

STYLE="font-weight: bold"> **log_error**

When set to a true value, and an endless tree is detected (i.e. the child branch contains a parent) then the error will be logged to the catalog error log. No logging done by default.

STYLE="font-weight: bold"> **show_error**

When set to a true value, and an endless tree is detected (i.e. the child branch contains a parent) then the error will be returned in the page. Errors are NOT shown by default.

In addition to the above values, all valid options for a list tag are in force. For example, you can set a "SELECTED" value on an option list with `option=1`, set the tag prefix with `prefix`, etc.

2.82. try

CALL INFORMATION

Parameters: **label**

Positional parameters in same order.

The attribute hash reference is passed after the parameters but before the container text argument. **This may mean that there are parameters not shown here.**

Must pass named parameter `interpolate=1` to cause interpolation.

This is a container tag, i.e. `[try] FOO [/try]`. Nesting: NO

Invalidates cache: **no**

Called Routine:

ASP/perl tag calls:

```
$Tag->try(
    {
        label => VALUE,
    },
    BODY
)
```

OR

```
$Tag->try($label, $ATTRHASH, $BODY);
```

DESCRIPTION

NO DESCRIPTION

2.83. update

CALL INFORMATION

Parameters: **function**

ONLY THE PARAMETERS ARE POSITIONAL.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->update(
    {
        function => VALUE,
    }
)
```

OR

```
$Tag->update($function, $ATTRHASH);
```

DESCRIPTION

NO DESCRIPTION

2.84. userdb**CALL INFORMATION**Parameters: **function**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. **This may mean that there are parameters not shown here.**

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->userdb(
    {
        function => VALUE,
    }
)
```

OR

```
$Tag->userdb($function, $ATTRHASH);
```

Attribute aliases

```
name ==> nickname
table ==> db
```

DESCRIPTION

Interchange provides a [userdb ...] tag to access the UserDB functions.

```
[userdb
    function=function_name
    username="username"*
    password="password"*
    verify="password"*
    oldpass="old password"*
    shipping="fields for shipping save"
    billing="fields for billing save"
    preferences="fields for preferences save"
    force_lower=1
```

```

param1=value*
param2=value*
...
]

```

* Optional

It is normally called in an mv_click or mv_check setting, as in:

```

[set Login]
mv_todo=return
mv_nextpage=welcome
[userdb function=login]
[/set]

<FORM ACTION="[process-target]" METHOD=POST>
<INPUT TYPE=hidden NAME=mv_click VALUE=Login>
Username <INPUT NAME=mv_username SIZE=10>
Password <INPUT NAME=mv_password SIZE=10>
</FORM>

```

There are several global parameters that apply to any use of the userdb functions. Most importantly, by default the database table is set to be *userdb*. If you must use another table name, then you should include a database=table parameter with any call to userdb. The global parameters (default in parens):

database	Sets user database table (userdb)
show	Show the return value of certain functions or the error message, if any (0)
force_lower	Force possibly upper-case database fields to lower case session variable names (0)
billing	Set the billing fields (see Accounts)
shipping	Set the shipping fields (see Address Book)
preferences	Set the preferences fields (see Preferences)
bill_field	Set field name for accounts (accounts)
addr_field	Set field name for address book (address_book)
pref_field	Set field name for preferences (preferences)
cart_field	Set field name for cart storage (carts)
pass_field	Set field name for password (password)
time_field	Set field for storing last login time (time)
expire_field	Set field for expiration date (expire_date)
acl	Set field for simple access control storage (acl)
file_acl	Set field for file access control storage (file_acl)
db_acl	Set field for database access control storage (db_acl)

2.85. value

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter interpolate=1 to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->value(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->value($name, $ATTRHASH);
```

DESCRIPTION

HTML examples:

```
<PARAM MV="value name">
<INPUT TYPE="text" NAME="name" VALUE="[value name]">
```

Expands into the current value of the customer/form input field named by field. If `flag` is present, single quotes will be escaped with a backslash; this allows you to contain the `[value ...]` tag within single quotes. (It is somewhat better to use other quoting methods.) When the value is returned, any Interchange tags present in the value will be escaped. This prevents users from entering Interchange tags in form values, which would be a serious security risk.

If the `set` value is present, the form variable value will be set to it and the empty string returned. Use this to "uncheck" a checkbox or set other form variable values to defaults. **NOTE:** This is only available in new-style tags, for safety reasons.

2.86. value_extended

CALL INFORMATION

Parameters: **name**

Positional parameters in same order.

The attribute hash reference is passed to the subroutine after the parameters as the last argument. This may mean that there are parameters not shown here.

Must pass named parameter `interpolate=1` to cause interpolation.

Invalidates cache: **YES**

Called Routine:

ASP/perl tag calls:

```
$Tag->value_extended(
    {
        name => VALUE,
    }
)
```

OR

```
$Tag->value_extended($name, $ATTRHASH);
```

DESCRIPTION

Named call example:

```
[value-extended
```

```

name=formfield
outfile=filename*
ascii=1*
yes="Yes" *
no="No" *
joiner="char|string" *
test="isfile|length|defined" *
index="N|N..N|*"
file_contents=1*
elements=1*]

```

Expands into the current value of the customer/form input field named by `field`. If there are multiple elements of that variable, it will return the value at `index`; by default all joined together with a space.

If the variable is a file variable coming from a multipart/form-data file upload, then the contents of that upload can be returned to the page or optionally written to the `outfile`.
STYLE="font-weight: bold"> name

The form variable `NAME`. If no other parameters are present, then the value of the variable will be returned. If there are multiple elements, then by default they will all be returned joined by a space. If `joiner` is present, then they will be joined by its value. In the special case of a file upload, the value returned is the name of the file as passed for upload.

STYLE="font-weight: bold"> joiner

The character or string that will join the elements of the array. Will accept string literals such as `"\n"` or `"\r"`.

STYLE="font-weight: bold"> test

Three tests -- `isfile` returns true if the variable is a file upload. `length` returns the length. `defined` returns whether the value has ever been set at all on a form.

STYLE="font-weight: bold"> index

The index of the element to return if not all are wanted. This is useful especially for pre-setting multiple search variables. If set to `*`, will return all (joined by `joiner`). If a range, such as `0..2`, will return multiple elements.

STYLE="font-weight: bold"> file_contents

Returns the contents of a file upload if set to a non-blank, non-zero value. If the variable is not a file, returns nothing.

STYLE="font-weight: bold"> outfile

Names a file to write the contents of a file upload to. It will not accept an absolute file name; the name must be relative to the catalog directory. If you wish to write images or other files that would go to HTML space, you must use the HTTP server's Alias facilities or make a symbolic link.

STYLE="font-weight: bold"> ascii

To do an auto-ASCII translation before writing the `outfile`, set the `ascii` parameter to a non-blank, non-zero value. Default is no translation.

STYLE="font-weight: bold"> yes

The value that will be returned if a test is true or a file is written successfully. Defaults to

Interchange: Interchange Tags Reference

1 for tests and the empty string for uploads.

STYLE="font-weight: bold"> **no**

The value that will be returned if a test is false or a file write fails. Defaults to the empty string.

3. User-defined Tags

To define a tag that is catalog-specific, place *UserTag* directives in your *catalog.cfg* file. For server-wide tags, define them in *interchange.cfg*. Catalog-specific tags take precedence if both are defined — in fact, you can override the base Interchange tag set with them. The directive takes the form:

```
UserTag tagname property value
```

where *tagname* is the name of the tag, *property* is the attribute (described below), and *value* is the value of the property for that *tagname*.

The user tags can either be based on Perl subroutines or just be aliases for existing tags. Some quick examples are below.

An alias:

```
UserTag product_name Alias      data products title
```

This will change [product_name 99-102] into [data products title 99-102], which will output the title database field for product code 99-102. Don't use this with [item-data ...] and [item-field ...], as they are parsed separately. You can do [product-name [item-code]], though.

A simple subroutine:

```
UserTag company_name Routine    sub { "Your company name" }
```

When you place a [company-name] tag in an Interchange page, the text *Your company name* will be substituted.

A subroutine with a passed text as an argument:

```
UserTag caps      Routine      sub { return "\U@" }
UserTag caps      HasEndTag
```

The tag [caps]This text should be all upper case[/caps] will become THIS TEXT SHOULD BE ALL UPPER CASE.

Here is a useful one you might wish to use:

```
UserTag quick_table HasEndTag
UserTag quick_table Interpolate
UserTag quick_table Order    border
UserTag quick_table Routine  <<EOF
sub {
    my ($border,$input) = @_;
    $border = " BORDER=$border" if $border;
    my $out = "<TABLE ALIGN=LEFT$border>";
    my @rows = split /\n+/, $input;
    my ($left, $right);
    for(@rows) {
        $out .= '<TR><TD ALIGN=RIGHT VALIGN=TOP>';
        ($left, $right) = split /\s*:\s*/, $_, 2;
        $out .= '<B>' unless $left =~ /</;
        $out .= $left;
        $out .= '</B>' unless $left =~ /</;
        $out .= '</TD><TD VALIGN=TOP>';
        $out .= $right;
        $out .= '</TD></TR>';
    }
}
```

Interchange: Interchange Tags Reference

```
        $out .= "\n";
    }
    $out .= '</TABLE>';
}
EOF
```

Called with:

```
[quick-table border=2]
Name: [value name]
City: [value city][if value state], [value state][if] [value country]
[/quick_table]
```

The properties for UserTag are are:

STYLE="font-weight: bold"> **Alias**

An alias for an existing (or other user-defined) tag. It takes the form:

```
UserTag tagname Alias    tag to insert
```

An Alias is the only property that does not require a *Routine* to process the tag.

STYLE="font-weight: bold"> **attrAlias**

An alias for an existing attribute for defined tag. It takes the form:

```
UserTag tagname attrAlias    alias attr
```

As an example, the standard Interchange `value` tag takes a named attribute of name for the variable name, meaning that `[value name=var]` will display the value of form field `var`. If you put this line in `catalog.cfg`:

```
UserTag value attrAlias    identifier name
```

then `[value identifier=var]` will be an equivalent tag.

STYLE="font-weight: bold"> **CanNest**

Notifies Interchange that this tag must be checked for nesting. Only applies to tags that have *HasEndTag* defined, of course. NOTE: Your routine must handle the subtleties of nesting, so don't use this unless you are quite conversant with parsing routines. See the routines `tag_loop_list` and `tag_if` in `lib/Vend/Interpolate.pm` for an example of a nesting tag.

```
UserTag tagname CanNest
```

HasEndTag

Defines an ending `[/tag]` to encapsulate your text --- the text in between the beginning `[tagname]` and ending `[/tagname]` will be the last argument sent to the defined subroutine.

```
UserTag tagname HasEndTag
```

Implicit

This defines a tag as implicit, meaning it can just be an attribute instead of an

Interchange: Interchange Tags Reference

attribute=value pair. It must be a recognized attribute in the tag definition, or there will be big problems. Use this with caution!

```
UserTag tagname Implicit attribute value
```

If you want to set a standard include file to a fixed value by default, but don't want to have to specify `[include file="/long/path/to/file"]` every time, you can just put:

```
UserTag include Implicit file file=/long/path/to/file
```

and `[include file]` will be the equivalent. You can still specify another value with `C[include file="/another/path/to/file"]`
`STYLE="font-weight: bold"> InsertHTML`

This attribute makes HTML tag output be inserted into the containing tag, in effect adding an attribute=value pair (or pairs).

```
UserTag tagname InsertHTML    htmltag    mvtag|mvtag2|mvtagN
```

In Interchange's standard tags, among others, the `<OPTION ...>` tag has the `[selected ..]` and `[checked ...]` tags included with them, so that you can do:

```
<INPUT TYPE=checkbox  
      MV="checked mvshipmode upsg" NAME=mv_shipmode> UPS Ground shipping
```

to expand to this:

```
<INPUT TYPE=checkbox CHECKED NAME=mv_shipmode> UPS Ground shipping
```

Providing, of course, that `mv_shipmode` is equal to `upsg`. If you want to turn off this behavior on a per-tag basis, add the attribute `mv.noinset=1` to the tag on your page.
`STYLE="font-weight: bold"> InsideHTML`

To make a container tag be placed **after** the containing HTML tag, use the `InsideHTML` setting.

```
UserTag tagname InsideHTML    htmltag    mvtag|mvtag2|mvtagN
```

In Interchange's standard tags, the only `InsideHTML` tag is the `<SELECT>` tag when used with *loop*, which causes this:

```
<SELECT MV="loop upsg upsb upsr" NAME=mv_shipmode>  
<OPTION VALUE="[loop-code]"> [shipping-desc [loop-code]]  
</SELECT>
```

to expand to this:

```
<SELECT NAME=mv_shipmode>  
[loop upsg upsb upsr]  
<OPTION VALUE="[loop-code]"> [shipping-desc [loop-code]]  
[/loop]  
</SELECT>
```

Without the `InsideHTML` setting, the `[loop ...]` would have been **outside** of the select -- not what you want. If you want to turn off this behavior on a per-tag basis, add the attribute `mv.noinside=1` to

the tag on your page.

STYLE="font-weight: bold"> **Interpolate**

The behavior for this attribute depends on whether the tag is a container (i.e. `HasEndTag` is defined). If it is not a container, the `Interpolate` attribute causes the **the resulting HTML** from the `UserTag` will be re-parsed for more Interchange tags. If it is a container, `Interpolate` causes the contents of the tag to be parsed **before** the tag routine is run.

```
UserTag tagname Interpolate
```

InvalidateCache

If this is defined, the presence of the tag on a page will prevent search cache, page cache, and static builds from operating on the page.

```
UserTag tagname InvalidateCache
```

It does not override `[tag flag build][tag]`, though.

STYLE="font-weight: bold"> **Order**

The optional arguments that can be sent to the tag. This defines not only the order in which they will be passed to *Routine*, but the name of the tags. If encapsulated text is appropriate (*HasEndTag* is set), it will be the last argument.

```
UserTag tagname Order param1 param2
```

PosRoutine

Identical to the `Routine` argument -- a subroutine that will be called when the new syntax is not used for the call, i.e. `[usertag argument]` instead of `[usertag ARG=argument]`. If not defined, *Routine* is used, and Interchange will usually do the right thing.

STYLE="font-weight: bold"> **ReplaceAttr**

Works in concert with `InsertHTML`, defining a **single** attribute which will be replaced in the insertion operation..

```
UserTag tagname ReplaceAttr htmltag attr
```

An example is the standard HTML `` tag. If you want to use the Interchange tag `[area pagename]` inside of it, then you would normally want to replace the `HREF` attribute. So the equivalent to the following is defined within Interchange:

```
UserTag area ReplaceAttr a href
```

Causing this

```
<A MV="area pagename" HREF="a_test_page.html">
```

to become

```
<A HREF="http://yourserver/cgi/simple/pagename?X8sl2lly; ;44">
```

when interpreted.

STYLE="font-weight: bold"> **ReplaceHTML**

For HTML-style tag use only. Causes the tag containing the Interchange tag to be stripped and the result of the tag to be inserted, for certain tags. For example:

```
UserTag company_name Routine sub { my $l = shift; return "$l: XYZ Company" }
UserTag company_name HasEndTag
UserTag company_name ReplaceHTML b      company_name
```


 is the HTML tag, and "company_name" is the Interchange tag. At that point, the usage:

```
<B MV="company-name"> Company </B> ----> Company: XYZ Company
```

Tags not in the list will not be stripped:

```
<I MV="company-name"> Company </I> ----> <I>Company: XYZ Company</I>
```

Routine

An inline subroutine that will be used to process the arguments of the tag. It must not be named, and will be allowed to access unsafe elements only if the `interchange.cfg` parameter *AllowGlobal* is set for the catalog.

```
UserTag tagname Routine sub { "your perl code here!" }
```

The routine may use a "here" document for readability:

```
UserTag tagname Routine <<EOF
sub {
    my ($param1, $param2, $text) = @_;
    return "Parameter 1 is $param1, Parameter 2 is $param2";
}
EOF
```

The usual *here documents* caveats apply.

Parameters defined with the *Order* property will be sent to the routine first, followed by any encapsulated text (*HasEndTag* is set).

Note that the UserTag facility, combined with AllowGlobal, allows the user to define tags just as powerful as the standard Interchange tags. This is not recommended for the novice, though — keep it simple. 8—)

