

Package com.mapmyjourney.backend.config

Class DatabaseSeeder

java.lang.Object[↗]
com.mapmyjourney.backend.config.DatabaseSeeder

All Implemented Interfaces:
org.springframework.boot.CommandLineRunner

@Component
public class **DatabaseSeeder**
extends Object[↗]
implements org.springframework.boot.CommandLineRunner

Executes the SQL statements contained in data.sql when the database is empty. IMPORTANT: This seeder is DISABLED in 'prod' profile to prevent overwriting user data.

Constructor Summary

Constructors
Constructor
Description
DatabaseSeeder (org.springframework.jdbc.core.JdbcTemplate jdbcTemplate, DataSource [↗] dataSource, org.springframework.core.env.Environment environment)

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method	Description
void	run (String [↗] ... args)	

Methods inherited from class java.lang.Object [↗]
clone [↗] , equals [↗] , finalize [↗] , getClass [↗] , hashCode [↗] , notify [↗] , notifyAll [↗] , toString [↗] , wait [↗] , wait [↗] , wait [↗]

Constructor Details

DatabaseSeeder
<pre>public DatabaseSeeder(org.springframework.jdbc.core.JdbcTemplate jdbcTemplate, DataSource[↗] dataSource, org.springframework.core.env.Environment environment)</pre>

Method Details

run
<pre>public void run(String[↗]... args) throws Exception[↗]</pre>
Specified by: run in interface org.springframework.boot.CommandLineRunner

Throws:

Exception[↗]