

Package com.mapmyjourney.backend.repository

Interface TripMemberRepository

All Superinterfaces:

org.springframework.data.repository.CrudRepository<TripMember,Long[↗]>,
org.springframework.data.jpa.repository.JpaRepository<TripMember,Long[↗]>,
org.springframework.data.repository.ListCrudRepository<TripMember,Long[↗]>,
org.springframework.data.repository.ListPagingAndSortingRepository<TripMember,Long[↗]>,
org.springframework.data.repository.PagingAndSortingRepository<TripMember,Long[↗]>,
org.springframework.data.repository.query.QueryByExampleExecutor<TripMember>,
org.springframework.data.repository.Repository<TripMember,Long[↗]>

@Repository
public interface TripMemberRepository
extends org.springframework.data.jpa.repository.JpaRepository<TripMember,Long[↗]>

Method Summary

- All Methods
- Instance Methods
- Abstract Methods

| Modifier and Type |
|---|
| Method |
| Description |
| List [↗] <TripMember> |
| findAllByTripId(Long [↗] tripId) |
| Obtiene todos los miembros de un viaje. |
| Optional [↗] <TripMember> |
| findByIdAndUserId(Long [↗] tripId, Long [↗] userId) |
| Obtiene el rol de un usuario en un viaje. |

| Methods inherited from interface org.springframework.data.repository.CrudRepository |
|--|
| count, delete, deleteAll, deleteAll, deleteAllById, deleteById, existsById, findById, save |

| Methods inherited from interface org.springframework.data.jpa.repository.JpaRepository |
|--|
| deleteAllByIdInBatch, deleteAllInBatch, deleteAllInBatch, deleteInBatch, findAll, findAll, flush, getById, getOne, getReferenceById, saveAllAndFlush, saveAndFlush |

| Methods inherited from interface org.springframework.data.repository.ListCrudRepository |
|---|
| findAll, findAllById, saveAll |

| Methods inherited from interface org.springframework.data.repository.ListPagingAndSortingRepository |
|---|
| findAll |

| Methods inherited from interface org.springframework.data.repository.PagingAndSortingRepository |
|---|
| findAll |

| Methods inherited from interface org.springframework.data.repository.query.QueryByExampleExecutor |
|---|
| count, exists, findAll, findBy, findOne |

Method Details

| |
|-------------------|
| findByIdAndUserId |
|-------------------|

```
Optional<TripMember> findByTripIdAndUserId(Long tripId,  
                                             Long userId)
```

Obtiene el rol de un usuario en un viaje.

findAllByTripId

```
List<TripMember> findAllByTripId(Long tripId)
```

Obtiene todos los miembros de un viaje.