

Package com.mapmyjourney.backend.security

Class SecurityConfig

java.lang.Object[↗]
com.mapmyjourney.backend.security.SecurityConfig

```
@Configuration
@EnableWebSecurity
@EnableMethodSecurity(prePostEnabled=true)
public class SecurityConfig
extends Object↗
```

Configuración de Spring Security con JWT y CORS. - Define rutas públicas (/register, /login, Swagger) - Protege endpoints privados que requieren autenticación - Configura CORS para Angular Frontend (localhost:4200) - Integra JwtAuthenticationFilter

Constructor Summary

Constructors
Constructor
Description
SecurityConfig()

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type		
Method		
Description		
org.springframework.security.authentication.AuthenticationManager		
authenticationManager (org.springframework.security.config.annotation.web.builders.HttpSecurity http)		
Configura el AuthenticationManager con DaoAuthenticationProvider.		
org.springframework.web.cors.CorsConfigurationSource		
corsConfigurationSource ()		
Configura CORS para permitir solicitudes desde el frontend en localhost:4200.		
org.springframework.security.authentication.dao.DaoAuthenticationProvider		
daoAuthenticationProvider ()		
Configura el proveedor de autenticación DAO.		
org.springframework.security.web.SecurityFilterChain		
filterChain (org.springframework.security.config.annotation.web.builders.HttpSecurity http)		
Configura la cadena de filtros de seguridad HTTP.		
org.springframework.security.crypto.password.PasswordEncoder		
passwordEncoder ()		
Define el encoder de contraseñas (BCrypt).		

Methods inherited from class java.lang.Object [↗]
clone [↗] , equals [↗] , finalize [↗] , getClass [↗] , hashCode [↗] , notify [↗] , notifyAll [↗] , toString [↗] , wait [↗] , wait [↗] , wait [↗]

Constructor Details

SecurityConfig

```
public SecurityConfig()
```

Method Details

filterChain

```
@Bean
public org.springframework.security.web.SecurityFilterChain filterChain
(org.springframework.security.config.annotation.web.builders.HttpSecurity http)
    throws Exception
```

Configura la cadena de filtros de seguridad HTTP. Define rutas públicas y privadas, y configura CORS.

Throws:

[Exception](#)

corsConfigurationSource

```
@Bean
public org.springframework.web.cors.CorsConfigurationSource corsConfigurationSource()
```

Configura CORS para permitir solicitudes desde el frontend en localhost:4200. Explícitamente permite el preflight (OPTIONS) que es obligatorio para CORS en navegadores.

authenticationManager

```
@Bean
public org.springframework.security.authentication.AuthenticationManager authenticationManager
(org.springframework.security.config.annotation.web.builders.HttpSecurity http)
    throws Exception
```

Configura el AuthenticationManager con DaoAuthenticationProvider.

Throws:

[Exception](#)

daoAuthenticationProvider

```
@Bean
public org.springframework.security.authentication.dao.DaoAuthenticationProvider daoAuthenticationProvider()
```

Configura el proveedor de autenticación DAO. Usa CustomUserDetailsService para cargar usuarios de la base de datos.

passwordEncoder

```
@Bean
public org.springframework.security.crypto.password.PasswordEncoder passwordEncoder()
```

Define el encoder de contraseñas (BCrypt).