

Package com.mapmyjourney.backend.repository

Interface ExpenseRepository

All Superinterfaces:

org.springframework.data.repository.CrudRepository<Expense, Long[↗]>,
org.springframework.data.jpa.repository.JpaRepository<Expense, Long[↗]>,
org.springframework.data.repository.ListCrudRepository<Expense, Long[↗]>,
org.springframework.data.repository.ListPagingAndSortingRepository<Expense, Long[↗]>,
org.springframework.data.repository.PagingAndSortingRepository<Expense, Long[↗]>,
org.springframework.data.repository.query.QueryByExampleExecutor<Expense>,
org.springframework.data.repository.Repository<Expense, Long[↗]>

@Repository
public interface ExpenseRepository
extends org.springframework.data.jpa.repository.JpaRepository<Expense, Long[↗]>

Method Summary

- All Methods
- Instance Methods
- Abstract Methods

| Modifier and Type |
|---------------------------------------|
| Method |
| Description |
| List [↗] <Expense> |
| findById(Long [↗] tripId) |
| Obtiene todos los gastos de un viaje. |

| Methods inherited from interface org.springframework.data.repository.CrudRepository |
|--|
| count, delete, deleteAll, deleteAll, deleteAllById, deleteById, existsById, findById, save |

| Methods inherited from interface org.springframework.data.jpa.repository.JpaRepository |
|--|
| deleteAllByIdInBatch, deleteAllInBatch, deleteAllInBatch, deleteInBatch, findAll, findAll, flush, getById, getOne, getReferenceById, saveAllAndFlush, saveAndFlush |

| Methods inherited from interface org.springframework.data.repository.ListCrudRepository |
|---|
| findAll, findAllById, saveAll |

| Methods inherited from interface org.springframework.data.repository.ListPagingAndSortingRepository |
|---|
| findAll |

| Methods inherited from interface org.springframework.data.repository.PagingAndSortingRepository |
|---|
| findAll |

| Methods inherited from interface org.springframework.data.repository.query.QueryByExampleExecutor |
|---|
| count, exists, findAll, findBy, findOne |

Method Details

| findById |
|--|
| List [↗] <Expense> findById(Long [↗] tripId) |
| Obtiene todos los gastos de un viaje. |

