

Package com.mapmyjourney.backend.repository

## Interface ExpenseRepository

All Superinterfaces:

org.springframework.data.repository.CrudRepository<Expense, Long<sup>↗</sup>>,  
org.springframework.data.jpa.repository.JpaRepository<Expense, Long<sup>↗</sup>>,  
org.springframework.data.repository.ListCrudRepository<Expense, Long<sup>↗</sup>>,  
org.springframework.data.repository.ListPagingAndSortingRepository<Expense, Long<sup>↗</sup>>,  
org.springframework.data.repository.PagingAndSortingRepository<Expense, Long<sup>↗</sup>>,  
org.springframework.data.repository.query.QueryByExampleExecutor<Expense>,  
org.springframework.data.repository.Repository<Expense, Long<sup>↗</sup>>

@Repository  
public interface **ExpenseRepository**  
extends org.springframework.data.jpa.repository.JpaRepository<Expense, Long<sup>↗</sup>>

### Method Summary

- All Methods
- Instance Methods
- Abstract Methods

| Modifier and Type                      |
|--|
| Method                                 |
| Description                            |
| List <sup>↗</sup> <Expense>            |
| findByTripId(Long <sup>↗</sup> tripId) |
| Obtiene todos los gastos de un viaje.  |

| Methods inherited from interface org.springframework.data.repository.CrudRepository        |
|--|
| count, delete, deleteAll, deleteAll, deleteAllById, deleteById, existsById, findById, save |

| Methods inherited from interface org.springframework.data.jpa.repository.JpaRepository   |
|--|
| deleteAllByIdInBatch, deleteAllInBatch, deleteAllInBatch, deleteInBatch, findAll, findAll, flush, getById, getOne, getReferenceById, saveAllAndFlush, saveAndFlush |

| Methods inherited from interface org.springframework.data.repository.ListCrudRepository |
|---|
| findAll, findAllById, saveAll   |

| Methods inherited from interface org.springframework.data.repository.ListPagingAndSortingRepository |
|---|
| findAll   |

| Methods inherited from interface org.springframework.data.repository.PagingAndSortingRepository |
|---|
| findAll   |

| Methods inherited from interface org.springframework.data.repository.query.QueryByExampleExecutor |
|---|
| count, exists, findAll, findBy, findOne   |

### Method Details

| findByTripId   |
|--|
| List <sup>↗</sup> <Expense> findByTripId(Long <sup>↗</sup> tripId) |
| Obtiene todos los gastos de un viaje.                              |

