

**Package** com.mapmyjourney.backend.config

## Class DatabaseSeeder

java.lang.Object<sup>↗</sup>  
com.mapmyjourney.backend.config.DatabaseSeeder

**All Implemented Interfaces:**  
org.springframework.boot.CommandLineRunner

@Component  
public class **DatabaseSeeder**  
extends Object<sup>↗</sup>  
implements org.springframework.boot.CommandLineRunner

Executes the SQL statements contained in data.sql when the database is empty. IMPORTANT: This seeder is DISABLED in 'prod' profile to prevent overwriting user data.

### Constructor Summary

Constructors
Constructor
Description
<b>DatabaseSeeder</b> (org.springframework.jdbc.core.JdbcTemplate jdbcTemplate, <b>DataSource</b> <sup>↗</sup> dataSource, org.springframework.core.env.Environment environment)

### Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method	Description
void	<b>run</b> (String <sup>↗</sup> ... args)	
Methods inherited from class java.lang.Object <sup>↗</sup>		
clone <sup>↗</sup> , equals <sup>↗</sup> , finalize <sup>↗</sup> , getClass <sup>↗</sup> , hashCode <sup>↗</sup> , notify <sup>↗</sup> , notifyAll <sup>↗</sup> , toString <sup>↗</sup> , wait <sup>↗</sup> , wait <sup>↗</sup> , wait <sup>↗</sup>		

### Constructor Details

DatabaseSeeder
<pre>public DatabaseSeeder(org.springframework.jdbc.core.JdbcTemplate jdbcTemplate,     DataSource<sup>↗</sup> dataSource,     org.springframework.core.env.Environment environment)</pre>

### Method Details

run
<pre>public void run(String<sup>↗</sup>... args)     throws Exception<sup>↗</sup></pre>
<b>Specified by:</b> run in interface org.springframework.boot.CommandLineRunner

**Throws:**

Exception<sup>↗</sup>