

Package com.mapmyjourney.backend.config

Class DatabaseSeeder

java.lang.Object[↗]
com.mapmyjourney.backend.config.DatabaseSeeder

All Implemented Interfaces:
org.springframework.boot.CommandLineRunner

@Component
public class **DatabaseSeeder**
extends Object[↗]
implements org.springframework.boot.CommandLineRunner

Executes the SQL statements contained in data.sql when the database is empty. IMPORTANT: This seeder is DISABLED in 'prod' profile to prevent overwriting user data.

Constructor Summary

| Constructors |
|--|
| Constructor |
| Description |
| DatabaseSeeder (org.springframework.jdbc.core.JdbcTemplate jdbcTemplate, DataSource [↗] dataSource, org.springframework.core.env.Environment environment) |

Method Summary

| All Methods | Instance Methods | Concrete Methods |
|---|---|------------------|
| Modifier and Type | Method | Description |
| void | run (String [↗] ... args) | |
| Methods inherited from class java.lang.Object [↗] | | |
| clone [↗] , equals [↗] , finalize [↗] , getClass [↗] , hashCode [↗] , notify [↗] , notifyAll [↗] , toString [↗] , wait [↗] , wait [↗] , wait [↗] | | |

Constructor Details

| DatabaseSeeder |
|--|
| <pre>public DatabaseSeeder(org.springframework.jdbc.core.JdbcTemplate jdbcTemplate, DataSource[↗] dataSource, org.springframework.core.env.Environment environment)</pre> |

Method Details

| run |
|---|
| <pre>public void run(String[↗]... args) throws Exception[↗]</pre> |
| Specified by: run in interface org.springframework.boot.CommandLineRunner |

Throws:

Exception[↗]