Package com.mapmyjourney.backend.model.enums

Enum Class ExpenseSplitType

java.lang.Object
    java.lang.Enum<ExpenseSplitType>
        com.mapmyjourney.backend.model.enums.ExpenseSplitType

All Implemented Interfaces:
Serializable, Comparable<ExpenseSplitType>, Constable

---

public enum **ExpenseSplitType**
extends Enum<ExpenseSplitType>

Enum que define cómo se divide un gasto entre los participantes.

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.Enum

Enum.EnumDesc<E> extends Enum<E>>

Enum Constant Summary

Enum Constants

Enum Constant
Description
CUSTOM
EQUAL
MANUAL
PERCENTAGE

Method Summary

[All Methods] [Static Methods] [Instance Methods] [Concrete Methods]

Modifier and Type
Method
Description
String
getDisplayName()
static **ExpenseSplitType**
valueOf(String name)
Returns the enum constant of this class with the specified name.
static **ExpenseSplitType**[]
values()
Returns an array containing the constants of this enum class, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, describeConstable, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Details

EQUAL

public static final ExpenseSplitType EQUAL

MANUAL

public static final ExpenseSplitType MANUAL

PERCENTAGE

public static final ExpenseSplitType PERCENTAGE

CUSTOM

public static final ExpenseSplitType CUSTOM

Method Details

values

public static ExpenseSplitType[] values()

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

public static ExpenseSplitType valueOf(String name)

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException - if this enum class has no constant with the specified name

NullPointerException - if the argument is null

getDisplayName

public String getDisplayName()