

Uses of Class

com.mapmyjourney.backend.dto.TripDTO

Packages that use TripDTO

| Package |
|-------------------------------------|
| Description |
| com.mapmyjourney.backend.controller |
| com.mapmyjourney.backend.service |

Uses of TripDTO in com.mapmyjourney.backend.controller

Methods in com.mapmyjourney.backend.controller that return types with arguments of type TripDTO

| Modifier and Type |
|---|
| Method |
| Description |
| org.springframework.http.ResponseEntity<TripDTO> TripController.createTrip (@Valid TripCreateRequestDTO request) |
| 1. |
| org.springframework.http.ResponseEntity<List<TripDTO>> TripController.getMyTrips (int page, int size) |
| 3. |
| org.springframework.http.ResponseEntity<TripDTO> TripController.getTripByCode (String tripCode) |
| 4. |
| org.springframework.http.ResponseEntity<TripDTO> TripController.getTripById (Long tripId) |
| 2. |
| org.springframework.http.ResponseEntity<TripDTO> TripController.updateTrip (Long tripId, @Valid TripCreateRequestDTO request) |
| 5. |

Uses of TripDTO in com.mapmyjourney.backend.service

Methods in com.mapmyjourney.backend.service that return TripDTO

| Modifier and Type |
|---|
| Method |
| Description |
| TripDTO TripService.createTrip (TripCreateRequestDTO request, Long creatorUserId) |
| Crea un nuevo viaje. |
| TripDTO TripService.getTripByCode (String tripCode) |
| Obtiene un viaje por su código (para invitaciones). |
| TripDTO |

TripService.getTripById([Long](#) tripId)

Obtiene un viaje por ID.

TripDTO

TripService.updateTrip([Long](#) tripId, **TripCreateRequestDTO** request, [Long](#) userId)

Actualiza un viaje existente.

Methods in **com.mapmyjourney.backend.service** that return types with arguments of type **TripDTO**

Modifier and Type

Method

Description

[List](#)<**TripDTO**>

TripService.getUserTrips([Long](#) userId)

Obtiene todos los viajes del usuario.