A Minor Issue in Line 8, Algorithm 1, RouteNet

Algorithm 1 Algorithm of RouteNet for #DRV Prediction

```
Input: Number of training placements: N, Features:
\{X_i \in \mathbb{R}^{w \times h \times 3} \mid i \in [1, N]\}, \text{ Targets: } \{y_i \in \mathbb{R} \mid i \in [1, N]\}
Preprocess:
  1: for each int i \in [1, N] do
           Resize X_i \in \mathbb{R}^{w \times h \times 3} into X_i^{\#DRV} \in \mathbb{R}^{224 \times 224 \times 3}
  3: Find 25%, 50%, 75% quantizes of y_i: q_1, q_2, q_3
  4: for each int i \in [1, N] do
           C_i \leftarrow 0
           for each int t \in [1, 3] do
                if y_i > q_t then
                     C_i \leftarrow t, break \longrightarrow continue
  9: Form dataset \{(X_i^{\#DRV}, C_i)|i \in [1, N]\}
 10: Training set \{(X_i^{\#DRV}, C_i) \mid C_i = 0 \text{ or } C_i = 3\}
```

Training:

- 1: Get pretrained ResNet18 $f_{Res}: \mathbb{R}^{224 \times 224 \times 3} \to \mathbb{R}^{1000}$
- 2: Replace output layer, s.t. $f_{\#DRV}: \mathbb{R}^{224 \times 224 \times 3} \to \mathbb{R}$
- 3: Choose MSE as loss function, SGD for optimization
- 4: Train $f_{\#DRV}$ with preprocessed dataset for ~30 epoches

Output: $f_{\#DRV}$ estimating #DRV level

Task

In the preprocess stage, the algorithm attempts to categorize the features X_i into 4 group, C_0 , C_1 , C_2 and C_3 , according to their labels y_i , the number of design rule violation (#DRV).

Issue

- The "for" loop in lines 6 to 8 is designed to iterate through each q_t . When the value of y_i exceeds q_t , it is categorized into group C_t .
- However, the presence of the "break" command in line 8 signifies a premature exit from the "for" loop initiated in line 6. This means that as soon as y_i surpasses q_1 , it is assigned to C_1 , and the algorithm abruptly terminates the "for" loop from line 6 onwards. As a result, the algorithm skips the potential categorization of y_i into C_2 or C_3 .

Remedy

• The "break" command in line 8 should be substituted with "continue" indicating the continuation of the "for" loop with an increment of t by 1. This adjustment ensures that the prospective classification of y_i into C_2 or C_3 is not skipped.

Some Minor Typos in APOLLO

In line 9-10, section 6

"interface", "power computation" and "T-cycle average". The "interface" latches the input signals using the register interface and

In line 13, section 6

timing impact from OPM on the original design. The "nterfac"

In line 25, section 6

The "power computation" component calculates the intermediate

In line 29-30, section 6

intermediate values are computed on a cycle-by-cycle basis, a cycle average component computes the average power over T

In line 31-32, section 7.4

as "Vector Execution" (19 out of 159), "Issue" (36 out of 159), and "Load Store" (28 out 159). These power proxies are critical indicators

Issue

• I have noticed that some of the left and right quotation in APOLLO marks don't seem to match properly. This might be due to a configuration issue with LaTeX.