When Can a Bandit Trust Correlation? Spatial and Temporal Dependence in Web Bandits

Anonymous Author(s)

ABSTRACT

Web recommendation and attention rewards combine persistent item appeal with correlated, evolving shocks. We distinguish two uses of a graph: a supplied restriction on long-run means and a model for innovation covariance. Under known stable Gaussian autoregressive dynamics, exact innovation regression converts adaptive, partially observed histories into predictable linear experiments. We derive simultaneous confidence sets, a spectral information sandwich, a sublinear mean-regret bound, and a certified component-rejection rule. Long-run graph-mode information and an exact two-arm schedule comparison explain how spatial shocks interact with temporal dependence. Experiments distinguish correctness from decision value. Across 360 KuaiRec user–subset instances, oracle-width pooling reduces aggregate regret by 36% against a matched conservative KL-UCB baseline, but remains worse than Thompson sampling; graph-free shrinkage is stronger on average. In centered Gaussian worlds calibrated to Wikipedia attention, iid upper certificates fail in 56–94% of runs, while known-model certificates have no observed failures but incur substantially higher mean regret. On chronological KuaiRec panels, joint-filter UCB reduces retrospective loss by 49–54% relative to iid Thompson sampling; comparisons with last observed value and graph rewirings are inconclusive. Open Bandit Dataset simulations provide a second mean-channel test, while an actual-log pilot is too sparse for a reliable policy ranking. The evidence supports calibrated confidence and persistence modeling, with limited support for useful graph-specific transfer at the tested budgets.

CCS CONCEPTS

• **Computing methodologies** → **Online learning settings**; • **Information systems** → *Recommender systems.*

KEYWORDS

multi-armed bandits, spatiotemporal dependence, graph bandits, restless bandits, autoregressive rewards, confidence sequences

1 INTRODUCTION

Every day a short-video platform fills a trending slot, and its rewards are correlated in two ways. *Spatially*, videos that are close in a co-engagement graph tend to share long-run appeal, and a shock such as a holiday or a community event hits related videos together. *Temporally*, a video's engagement today predicts its engagement for days. Classical bandits assume neither. Graph bandits assume the first, as a static restriction on means [2, 28]. Restless and autoregressive bandits assume the second, usually with independent arms [5, 27]. This paper studies both together: what each kind of correlation does to the information in an observation, to the validity of confidence sets, and to regret.

Relevance to the Web. Spatiotemporal dependence is the normal state of Web rewards. The graphs are by-products of logging (co-engagement, embeddings, hyperlinks), not priors designed for the decision. Attention persists and spreads along those graphs. Exposure is bursty, because the same items fill a slate day after day. An online learner on a Web platform must therefore decide which correlation it can trust and how much each observation is worth. We answer with theory, and test it on KuaiRec short video [9], Wikipedia attention, and the Open Bandit Dataset [25].

Two ways to go wrong. A learner can trust spatial correlation that is not there: pooling along a graph whose neighbourhoods do not share appeal biases estimates and can cause linear regret. Or it can ignore temporal correlation: confidence sets built for independent rewards are too narrow when consecutive observations move together, so irrevocable decisions such as dropping an item go wrong. The theory below explains when each failure occurs and what repairs it.

Contributions.

(1) **A spatiotemporal reward model with two graph roles** (§2). A graph may restrict the long-run means or shape the innovation covariance. These are different assumptions, and only the first identifies unobserved arms. The node-time covariance factors into spatial and temporal parts, and it is separable only under homogeneous dynamics (Proposition 2.1).
(2) **Information under spatiotemporal dependence** (§3). An exact innovation regression gives graph-regularized confidence valid at all times under any adaptive restless schedule. A spectral sandwich bounds its information using the shock spectrum and the AR frequency response, and yields sublinear mean regret. Long-run information decomposes by graph Fourier mode. Two exact results show the interaction between space and time. Contrasts gain from correlated shocks even under staggered sampling. In an AR(2) example, block schedules beat alternation because spatial correlation is reachable only at informative lags.
(3) **Certified pooling across space under persistence in time** (§4). We prove a component-rejection condition in realized information and an iid pooling regret bound. A normalized path–clique example shows that diameter alone misses information geometry. General partial schedules require their conditional information, rather than a scalar long-run-variance substitution.
(4) **Tests with explicit controls and uncertainty** (§5). KuaiRec, Wikipedia, and the Open Bandit Dataset separate graph alignment from generic shrinkage, persistence from graph-specific transfer, and confidence validity from useful elimination. Estimated-dynamics and actual-log

evidence are evaluated separately from known-model guarantees.

2 A SPATIOTEMPORAL REWARD MODEL

There are N arms. Arm i's reward field is

$$X_{i,t} = \mu_i + z_{i,t}, \qquad z_{i,t} = \sum_{r=1}^{p_i} a_{i,r} z_{i,t-r} + \eta_{i,t}, \qquad \eta_t \overset{\text{iid}}{\sim} N(0, Q_G). \tag{1}$$

In round t the learner chooses a_t before seeing the field and observes $Y_t = X_{a_t,t} + \xi_t$, with independent sensor noise $\xi_t \sim N(0, r)$. Slates are vector observations chosen before any same-round feedback. Every arm evolves every round (restless), but only chosen arms are observed. The means μ are fixed and unknown; $Q_G \succ 0$, and the field starts in stationarity. The AR polynomials $A_i(s) = 1 - \sum_r a_{i,r} s^r$ are stable, and $c_i = A_i(1)$, so the raw AR intercept is $c_i \mu_i$. For the theory, the orders, coefficients, Q_G and r are known; §5 tests estimated dynamics.

Spatial correlation: two roles for a graph. A graph with Laplacian L_μ may restrict the *means*: $\mu^\top L_\mu \mu \le S^2$ and $\|\mu\| \le B$. This is deterministic side information, and through effective resistance it implies component widths, $|\mu_i - \mu_j| \le S\sqrt{(e_i - e_j)^\top L_\mu^\dagger (e_i - e_j)}$. A graph with Laplacian L_η may instead shape the *shocks*, for example $Q_G \propto (\alpha_\eta I + \lambda_\eta L_\eta)^{-1}$ rescaled to given variances. One graph may serve both roles, but that is an additional assumption. The roles also differ in identification. Correlated shocks improve prediction and comparisons, but they cannot identify the mean of an arm that is never observed: its column of the design is zero, so μ_i does not enter the likelihood. Only a mean restriction links an unobserved arm to observed ones.

Temporal correlation and its interaction with space. Stack each arm's current deviation and lags into s_t. Then $s_{t+1} = Fs_t + E\eta_{t+1}$ and $z_t = Cs_t$, where F is block-diagonal with the AR companion blocks, E inserts innovations, and $C = E^\top$. The stationary state covariance solves $\Gamma = F\Gamma F^\top + EQ_G E^\top$. Although F is block-diagonal, $EQ_G E^\top$ couples the arms.

Proposition 2.1 (Node-time covariance). *Let $G_h = \mathrm{Cov}(z_{t+h}, z_t) = CF^h \Gamma C^\top$, and write*

$$z_{i,t} = \textstyle\sum_{k \ge 0} \psi_i(k) \eta_{i,t-k}$$

with impulse response ψ_i. Then

$$(G_h)_{ij} = (Q_G)_{ij} \sum_{k \ge 0} \psi_i(k+h)\psi_j(k),$$

and the spectral density matrix is

$$\mathcal{S}_z(\omega) = \Lambda(\omega)\, Q_G\, \Lambda(\omega)^*, \qquad \Lambda(\omega) = \mathrm{diag}\left(A_i(e^{-\mathrm{i}\omega})^{-1}\right).$$

The covariance is a fixed spatial matrix times a scalar temporal kernel if and only if all arms have the same impulse response. Otherwise G_h is generally asymmetric for $h > 0$.

The innovation covariance supplies the spatial coupling, and each pair of filters sets its lag profile. Consequences follow directly. An AR(20) arm can have no lag-1 correlation but strong lag-20 correlation. Two arms can be uncorrelated at lag 1 and correlated at lag 2. A lag-1 summary, such as a single persistence parameter, therefore misstates the information in a schedule (Proposition 3.8).

Regret. *Mean regret* $R_\mu(T) = \sum_t (\mu^\star - \mu_{a_t})$ measures learning of persistent appeal. *Dynamic regret* $\sum_t (\max_i X_{i,t} - X_{a_t,t})$ measures tracking against an oracle that sees the current field. Actual-reward regret against the best fixed arm can be negative, because adaptive policies exploit predictable positive deviations: $\mathbb{E}R_{\text{fixed}} = \mathbb{E}R_\mu - \sum_t \mathbb{E}z_{a_t,t}$. Several familiar models are special cases. iid bandits have $p_i = 0$ and diagonal Q_G. Graph bandits add only the mean restriction. Restless AR bandits have no mean restriction.

3 INFORMATION UNDER SPATIOTEMPORAL DEPENDENCE

The innovation regression. Conditional on a candidate μ, a Kalman filter [17] tracks $s_t \mid \mu, \mathcal{H}_t \sim N(g_t + D_t\mu, P_t)$, where g_t, D_t and P_t do not depend on μ. For arm a, let $\ell_a = C^\top e_a$, $d_{t,a} = \ell_a^\top P_t \ell_a + r$ and $u_{t,a} = (e_a + D_t^\top \ell_a)/\sqrt{d_{t,a}}$.

Theorem 3.1 (Predictable innovation experiments). *The chosen observation satisfies $R_t := (Y_t - \ell_{a_t}^\top g_t)/\sqrt{d_{t,a_t}} = u_t^\top \mu + \epsilon_t$, where $u_t = u_{t,a_t}$ is predictable and $\epsilon_t \mid \mathcal{H}_t, a_t \sim N(0,1)$. On every recorded path, $\mathcal{I}_T = \sum_t u_t u_t^\top = M^\top \Xi^{-1} M$ and $q_T = \sum_t u_t R_t = M^\top \Xi^{-1} Y$. Here M selects observed means and Ξ is assembled from G_h. These are likelihood identities; conditioning on an adaptively chosen schedule does not generally leave Y Gaussian.*

Spatial correlation enters u_t through D_t. Removing the predictable shared noise from a reading of arm j also subtracts part of the mean of every recently observed arm, so a reading measures a weighted *contrast*, not μ_j alone. Temporal correlation enters through the propagation by F. The mean restriction enters as a penalty, $H = \alpha I + \lambda L_\mu$, $J_T = H + \mathcal{I}_T$ and $\hat{\mu}_T = J_T^{-1} q_T$.

Theorem 3.2 (Graph-regularized confidence, valid at all times). *Suppose $\mu^\top L_\mu \mu \le S^2$, $\|\mu\| \le B$, and the graph is fixed before measurement. Let*

$$\beta_T = \sqrt{\log \tfrac{\det J_T}{\det H} + 2 \log \tfrac{1}{\delta}} + \sqrt{\alpha B^2 + \lambda S^2}.$$

Then, with probability at least $1-\delta$, $|v^\top(\hat{\mu}_T - \mu)| \le \beta_T \|v\|_{J_T^{-1}}$ for all T and all contrasts v simultaneously. Stopping when every comparison with the leader clears its width returns the best arm with probability at least $1 - \delta$.

The first term of β_T prices the stochastic error after whitening in space and time [1]. The second prices the spatial restriction. If the graph is only approximately right, $(1-\zeta)L_\mu \le \hat{L} \le (1+\zeta)L_\mu$, replacing S^2 by $(1+\zeta)S^2$ keeps the guarantee. That repair applies only to the mean role. A shock covariance fitted from the wrong graph changes the likelihood itself.

Proposition 3.3 (Spectral information sandwich). *Let $a_{\min}$ and $a_{\max}$ be the extremes of $|A_i(e^{-\mathrm{i}\omega})|$ over arms and frequencies, and set $v_\pm = \lambda_{\max/\min}(Q_G)/a_{\min/\max}^2 + r$. For every realized schedule, $v_+^{-1}\,\mathrm{diag}(N_i(T)) \le \mathcal{I}_T \le v_-^{-1}\,\mathrm{diag}(N_i(T))$, where $N_i(T)$ is the number of observations of arm i.*

The worst-case information per observation is $1/v_+$, which combines the largest spatial eigenvalue of the shocks with the most

persistent temporal frequency. For AR(1), $a_{\min} = 1 - \varphi$, which recovers the $(1-\varphi)^{-2}$ cost of persistence that appears in B1 below.

Corollary 3.4 (Sublinear mean regret). *Mean-UCB on $\hat{\mu}_i + \beta_{t-1}\sqrt{(J^{-1})_{ii}}$, after observing each arm once, has, with probability at least $1-\delta$,*

$$R_\mu(T) \le 2BN + 4\beta_T\sqrt{v_+ NT},$$

$$\beta_T \le \sqrt{N\log\left(1+\tfrac{T}{\alpha v_-}\right) + 2\log\tfrac{1}{\delta}} + \sqrt{\alpha B^2 + \lambda S^2}.$$

This bound is conservative. Its value is that it holds under arbitrary spatial and temporal correlation. Sharper constants require the long-run structure below.

Proposition 3.5 (Long-run information and graph modes). *For full-field observations with $r = 0$ and $n \ge p := \max_i p_i$, $\mathcal{I}_n = \mathcal{I}_p + (n-p)D_c Q_G^{-1} D_c$, where $D_c = \mathrm{diag}(c_i)$. The long-run covariance of the sample-mean field is*

$$\Omega = D_c^{-1} Q_G D_c^{-1} + rI.$$

For common coefficients ($D_c = cI$) and simultaneous eigenvectors ϕ_k of Q_G and L, with eigenvalues q_k and ℓ_k, asymptotic information per field in mode $\phi_k^\top \mu$ is $(q_k/c^2 + r)^{-1}$. A penalty λL adds $\lambda\ell_k$; c^2/q_k is the noiseless case.

This is the spectral form of the interaction between space and time. Persistence ($c \to 0$) scales every mode's information by c^2. Graph-smooth shocks, such as $Q_G = (\alpha_\eta I + \lambda_\eta L)^{-1}$ with $q_k^{-1} = \alpha_\eta + \lambda_\eta \ell_k$, cancel in rough contrasts. High-frequency differences between neighbours are therefore cheap to learn. The global level ($\ell_1 = 0$), which no contrast reveals, is the most expensive. The mean penalty also acts on high frequencies, so the two graph roles reinforce each other only on rough modes.

Proposition 3.6 (Temporal inflation of iid confidence, B2). *For a predetermined consecutive block of b noiseless observations, $\mathrm{Var}(\bar{X}_i) = (G_0)_{ii} f_i(b)/b$, where*

$$f_i(b) = 1 + 2\sum_{h=1}^{b-1}(1 - h/b)\rho_i(h), \quad \rho_i(h) = (G_h)_{ii}/(G_0)_{ii}.$$

For AR(1), $f_i(b) = \frac{1+\varphi}{1-\varphi} - \frac{2\varphi(1-\varphi^b)}{b(1-\varphi)^2}$. A two-sided iid radius $\sqrt{2(G_0)_{ii}\ell/b}$ has per-check failure probability $2\Phi(-\sqrt{2\ell/f_i(b)})$. Sensor noise adds r/b. At arbitrary fixed observation times $\tau_1, \dots, \tau_n$, the exact variance is $n^{-2}\sum_{s,u}(G_{|\tau_s - \tau_u|})_{ii} + r/n$; separate blocks need not be independent.

By Proposition 2.1, ρ_i depends only on arm i's own filter. Within-arm inflation is purely temporal, while every contrast between arms is spatiotemporal:

Proposition 3.7 (Contrasts, B3(2)). *Two arms observed together on n consecutive dates have $n\mathrm{Var}(\bar{Y}_i - \bar{Y}_j) \to \Omega_{ii} + \Omega_{jj} - 2\Omega_{ij}$. With common dynamics and $r = 0$, the observed subset has long-run covariance Q_{SS}/c^2, with precision $(Q_{SS})^{-1}c^2$; the submatrix $(Q_G^{-1})_{SS}$ conditions on unobserved contemporaneous innovations. Equal variances give the ideal contrast factor $1-\rho$ only for common dynamics and $r = 0$. For staggered schedules, use the cross-covariances at every selected lag. Persistence can preserve much of the gain; it does not make all schedules equivalent.*

Proposition 3.8 (Space meets lag: an exact schedule comparison). *Let two arms follow $z_{i,t} = az_{i,t-2} + \eta_{i,t}$ with $0 < a < 1$, equal stationary variance V, and innovation correlation $0 \le \rho < 1$. For four observations with noise r, the GLS contrast variance is $V + r - a\rho V$ under AABB and $V + r + aV$ under ABAB. AABB has strictly higher fixed-mean probability of correct selection for every positive gap.*

Alternation looks natural for comparing two arms, but here it is wrong. Under AABB, each arm's consecutive readings are independent (lag 1), while readings of different arms two rounds apart share the correlated shock (lag 2). ABAB does the reverse: it reaches within-arm redundancy and misses the cross-arm correlation. At $V = 1$, $r = 0.1$, $a = 0.8$, $\rho = 0.6$ and gap 0.4, the variances are 0.62 and 1.90, and the probabilities of correct selection are 0.694 and 0.614. No single persistence number can rank these schedules. The ranking requires the spatial and temporal structure together, as in Proposition 2.1.

4 CERTIFIED POOLING ACROSS SPACE UNDER PERSISTENCE IN TIME

Spatial pooling with iid noise. SP-UCB partitions the arms into components C_c with certified widths ε_c. It keeps arm bounds $u_i = \bar{Y}_i + b(n_i)$ and pooled bounds $\hat{p}_c + b(N_c) + \varepsilon_c$, selects the component that maximizes the minimum of its two bounds, U_c, and pulls that component's best arm. SP-KLUCB uses KL radii [10]. Let $v_c = \max_{i \in C_c} \mu_i$, let $\Gamma_c = \mu^\star - v_c$ be the component gap, and let $\ell = \log(2(N+M)T/\delta)$.

Theorem 4.1 (A1: alignment-sensitive regret). *With valid widths, with probability at least $1-\delta$,*

$$\mathcal{R}_T \le \textstyle\sum_{c \in O} A_c + \sum_{c \notin O} \min\{A_c, H_c\}.$$

Here O is the set of components containing an optimal arm, $A_c = \sum_{i \in C_c : \Delta_i > 0}(\Delta_i + 8\sigma^2\ell/\Delta_i)$ is the cost of arm-by-arm exploration, and $H_c = (\Gamma_c + \varepsilon_c)(1 + 8\sigma^2\ell/(\Gamma_c - \varepsilon_c)^2)$ is the cost of rejecting the whole component. H_c is finite only when the component is rejectable, *that is, when $\varepsilon_c < \Gamma_c$.*

Geometry beyond widths. Consider an isolated homogeneous suboptimal component with m arms, gap Δ, Gaussian observation variance σ^2, and energy budget S. Define

$$F_L^*(s) = \max_{p \in \Delta_m} \min_{i \le m} \min_{\substack{z \in [0,1]^m,\ z_i = 1 \\ z^\top L z \le s^2}} \sum_j p_j z_j^2.$$

The structured change-of-measure program [6] gives component regret constant $2\sigma^2/(\Delta F_L^*(S/\Delta))$. This is a lower-bound information program, rather than an attained finite-budget constant. Normalize both graphs to effective-resistance diameter two. At $S = \Delta$, the clique has $F_L^* = 1/m$, while the path has $F_L^* \ge (1 - 1/\sqrt{2})^2$ (Appendix A). Thus equal diameters can conceal a growing information separation. Without a valid mean restriction, smoothing can reverse rankings: for means $(1, 0.9, 0)$ and a strong edge between arms 1 and 3, arm 2 becomes the smoothed leader. A particular random graph can also reverse a ranking; rewiring is an empirical control, not a safety guarantee.

Adding temporal dependence. Let $\Delta(C_c)$ denote probability weights supported on component C_c, and define

$$U_i = \hat{\mu}_i + \beta_t \|e_i\|_{J_t^{-1}},$$

$$U_c = \min\left\{\max_{i \in C_c} U_i,\ \min_{w \in \Delta(C_c)} (w^\top \hat{\mu} + \beta_t \|w\|_{J_t^{-1}}) + \varepsilon_c\right\}.$$

A pooling policy selects a component maximizing U_c and then an arm maximizing U_i within it.

Theorem 4.2 (B1: valid pooling and realized-information rejection). *With valid widths, a valid mean norm/energy bound, and correctly specified dynamics, all U_i and U_c are upper bounds with probability at least $1-\delta$, simultaneously at every round. If a suboptimal component c with $\Gamma_c > \varepsilon_c$ is selected, then*

$$\min_{w \in \Delta(C_c)} w^\top J_t^{-1} w \geq \frac{(\Gamma_c - \varepsilon_c)^2}{4\beta_t^2}.$$

Thus it cannot be selected after its realized variance falls below this threshold on the confidence event.

This proves the validity bridge under arbitrary adaptive restless histories. Converting rejection to a count-based bound needs information growth for that schedule. With independent AR(1) arms, $0 \leq \varphi < 1$, one scalar pull contributes at least $(1-\varphi)^2/(V+r)$ to that arm's information. Pooling sums information across arms; it supplies no extra factor $|C_c|$ per scalar reading. The spectral sandwich supplies a conservative count bound in the general model, but a full-field precision cannot substitute for partial-history information.

The vector confidence set pays through its log determinant. A scalar nuisance construction, denoted B1″ in the experiments, initializes valid mean intervals and recursively bounds the other arms' mean contributions (Appendix A). Its broad intervals can protect validity while preventing elimination. Estimated coefficients, covariance inflation, and empirical mean-width calibration are additional working approximations; their empirical coverage is not Theorem 3.2.

5 EVIDENCE

We test four implications: (i) supplied widths govern safe component rejection; (ii) bursts of persistent feedback undermine iid confidence; (iii) shared shocks can improve contrasts, with schedule-dependent gains; (iv) predictive persistence can help immediate reward without establishing graph-specific transfer. Static tests measure R_μ in Bernoulli simulators whose means are estimated from logs. Temporal panels measure retrospective current-oracle loss on transformed, partially observed reward fields. These are different objectives. All intervals below are 95%; Appendix B specifies their units and dependence assumptions.

5.1 Mean-channel pooling on KuaiRec

Protocol. KuaiRec [9] provides a nearly complete user–video matrix and a larger disjoint logging matrix. Graphs use non-evaluation users for item construction and non-evaluation videos for user construction. Collaborative graphs have stronger double-centered taste alignment than content and profile graphs (Appendix Table 4). The main comparison has 120 held-out users, three 300-video subsets per user, a 20-component partition, and $T = 20{,}000$ per instance: 360 instances and 10,440 main policy trajectories. A separate 1,440-trajectory experiment tests user-calibrated widths. All policies pay any noisy warm-up cost. Repeated subsets are clustered within users, not treated as 360 independent users.

I-mf policy / width	/ fixed KL	/ Beta TS	Valid widths
Oracle pooling	0.640	1.456	100%
Energy pooling	0.960	2.184	100%
Population q90	0.986	2.244	89.7%
Population q50	0.695	1.580	47.3%
User q90	0.947	2.155	89.3%†
User q75	0.819	1.863	73.6%†
Zero-width pooling	0.366	0.833	0%
Spectral TS, real	0.349	0.794	–
Spectral TS, rewired	0.348	0.792	–
Graph-free shrinkage TS	**0.302**	**0.688**	–

Table 1: KuaiRec: ratios of aggregate mean regrets. Fixed KL is conservative fixed-confidence KL-UCB, not standard log-time KL-UCB. Width validity is a diagnostic fraction of true component ranges covered, not joint coverage. †User diagnostics evaluate the true user level, rather than the realized noisy warm-up used by the policy.

Certificate usefulness. Oracle I-mf pooling has 0.640× matched fixed-KL regret, versus 0.802 for the mean of instance-wise ratios; the ratio estimator matters. It rejects 59.4% of suboptimal components, compared with 20.9% for truth-derived energy widths and 14.6% for q90 calibration. Energy and population-q90 widths leave only 4.0% and 1.4% aggregate gains. The 16 graph–certificate cells exhibit a descriptive negative association between rejectability and loss (Spearman −0.87), but the within-instance association is weak (−0.09). This supports the rejection mechanism, not a causal dose-response law or practical joint validity. Oracle and energy widths use the true simulated means and serve as controlled side information.

Graph against shrinkage. Oracle pooling on real I-mf has 8.45% lower regret than its degree-preserving rewiring, with user-cluster bootstrap interval [7.38%, 9.46%]. Spectral TS on real versus rewired I-mf differs by +0.29% [−4.13%, +4.64%], an inconclusive comparison. Graph-free shrinkage TS has 0.688× Beta-TS regret [0.644, 0.734] and beats real-I-mf spectral TS by 13.4% [4.5%, 22.1%]. Oracle pooling remains 1.456× Beta TS. Strong co-engagement spectral TS puts 26.7% of users above twice Beta-TS regret, with a 90th-percentile user ratio of 4.70. Consequently, a favorable graph-alignment statistic is insufficient evidence of a safe or superior learning policy.

5.2 Mean-channel checks on the Open Bandit Dataset

Simulator evidence. Uniform-random ZOZOTOWN logs [25] contain 2.69M impressions over three campaigns and seven days. The All and Women tests use prefix days 1–3 to construct attribute or audience clusters, and held-out days 4–7 click-rate estimates

Regret / matched fixed KL-UCB	All	Women
Standard log-time KL-UCB	0.684	0.746
Beta TS	0.353	0.382
Graph-free empirical-Bayes TS	**0.206**	**0.290**
Oracle pooling, attributes	0.837	0.982
Oracle pooling, audience	0.702	0.965
Prefix widths, attributes	0.862	1.011
Prefix widths, audience	0.775	0.809

Table 2: OBD simulator: aggregate loss ratios to a matched conservative baseline. Oracle gains do not establish superiority to ordinary TS.

as stationary Bernoulli means. There are 20 seeds per policy–campaign, 640 trajectories, and two million simulated impressions per trajectory, updated in batches of 100. This is a semi-synthetic fixed-mean test, not online deployment or off-policy value identification.

Oracle audience pooling gains 29.8% in All but only 3.5% in Women against fixed KL-UCB. Empirical-Bayes TS has the lowest point-estimate loss. Prefix widths cover only 25–70% of held-out component ranges. Uncertified audience pooling in All has no optimal-arm selections in the final 10% of the recorded horizon; finite trajectories do not prove its asymptotic slope. A 12-split sensitivity analysis, using 5,000 held-out Jeffreys draws per split, puts the empirical three-day best item's probability of being truly best at 0.627 in All and 0.553 in Women. These draws quantify ranking uncertainty under a working binomial model; they are not independent policy runs or a guarantee under future drift.

Actual-log pilot. A separate Men, position-1 pilot preserves logged hours, selects before feedback, and observes only matching random exposures, with propensity 1/34. Across 142 policy trajectories and 72 held-out hours, each trajectory obtains only 10–16 clicks; 91.7% of prefix arm–hour bins contain none. The IPS ranking is therefore underpowered. Its graph-transfer rule uses uncertified pseudo-observations, not the Gaussian innovation certificate. We report this negative result rather than treat simulator gains as real-log performance.

5.3 Temporal confidence: coverage and cost

Fresh model check. A 400-world AR(20) confirmation uses six arms, $T = 800$, bursts of 25, and a 365-round fitting prefix. Known dynamics produce 1/100 anytime violations [0.18%, 5.45%]; fitted dynamics 5/100 [2.15%, 11.18%]; fitted covariance inflated by 1.5 gives 3/100 [1.03%, 8.45%]. Jointly replacing AR(20) by AR(1) and removing cross-arm covariance gives 40/100 [30.94%, 49.80%]. This combined misspecification does not isolate lag order from covariance. Earlier lag-specific and heavy-tail stresses give additional failures. None of the fitted-model results establishes a nuisance-estimation theorem.

Wikipedia-calibrated worlds. Thirty articles determine six components, stable AR(7) dynamics, and correlated Gaussian innovations. Across 730 days and 100 worlds per cell, iid pooling certificates violate an arm or component upper bound in 56/100 runs




Figure 1: Centered Gaussian Wikipedia-calibrated worlds: coverage and mean-regret cost of SP-UCB, 100 worlds per cell. Error bars on failures are 95% Wilson intervals. Correct confidence is substantially more expensive at this finite horizon.

for slate size five and 94/100 for size ten. Known-model and fitted-model B1″ pooling certificates each have 0/100 observed violations in these centered Gaussian cells. For 0/100, the Wilson upper endpoint is 3.7%, not zero risk. Figure 1 shows the corresponding reward cost.

Known-model pooling incurs mean regret 441 versus 37.8 for iid confidence at size five, and 466.6 versus 44.6 at size ten. Known and fitted successive elimination keep all 30 arms; iid elimination violates bounds in 78/100 and 99/100 runs but never drops the best arm in these cells. Thus miscoverage need not imply catastrophic reward loss, while correctness need not imply useful rejection. Separate high-persistence AR(1) elimination tests do drop the best arm in 28–89% of selected burst configurations. Valid elimination retains it but often eliminates nothing through 20,000 rounds.

Median terminal width is 1.74 for the scalar nuisance construction and 0.70 for the all-direction ellipsoid, against a best–second gap of 0.135. A pointwise posterior width of 0.07 is not an adaptive, simultaneous certificate. A tighter time-uniform contrast construction [15] is a research direction, not an established replacement. Empirical residual-resampling cells are excluded from clean coverage conclusions: the saved residuals were not recentered, inducing a maximum stationary level shift of 0.0194 and invalidating one of six oracle component widths. Weekly block resampling is also a temporal-misspecification stress, rather than a test of iid Gaussian innovations.

Measured attention. Retrospective panels of 150 articles each, fit on 2022–2023 and evaluated on 2024–2025, exhibit weekday-adjusted block-mean inflation of 5.0–5.3 for seven days and 17.1–17.8 for 28 days. Full AR(20) autocovariance predictions are closer than a lag-one shortcut (Appendix Table 5). Cohorts and hyperlinks use a later snapshot, so these results describe historical covariance rather than prospective graph transfer. The controlled consecutive-block formula explains the direction and scale; it is not a formula for adaptive policy-wide failure probabilities.

5.4 Contrasts, prediction, and chronological decisions

Mechanism checks. Exact two-arm information calculations with 365 observations per arm and sensor standard deviation 0.1 give contrast-variance ratios 0.100 under common AR(1) coefficient 0.9 and innovation correlation 0.9, 0.280 with unequal innovation scales, and 0.383 with unequal persistence. Corresponding staggered ratios are 0.106, 0.284, and 0.406. The iid case gives 0.109 simultaneously and 1.000 when staggered. The staggered design spans a different calendar length; these ratios do not rank policies at equal total time. Eight independent Monte Carlo cells agree with their exact finite-sample values within 1.8%.

A paired 16-arm factorial screen crosses persistence, innovation correlation, and gap spread (18 cells, 20 worlds per cell, seven policies). In the high-persistence/high-correlation small-spread cell, joint UCB improves on temporal UCB by 0.0390 loss per round [0.0084, 0.0696]. The corresponding large-spread interval crosses zero. This is a mechanism screen, not the planned larger confirmation. A separate 100-arm AR(20) benchmark also distinguishes objectives: current-field joint UCB loses 1.248 per round versus 1.397 for iid UCB, while mean regret favors iid UCB (0.668 versus 0.686). Practical UCB coefficients in these policy tests are tuned, not the theorem's confidence radius.

Chronological KuaiRec. Three disjoint 11-day test windows and five video panels per window give 15 panel–window units, 49–50 videos per panel, budgets one and five, 13 policies, and five seeds (1,950 trajectories). The graph uses pre-cutoff interactions from non-evaluation users. The daily reward is logit completion rate. An empty chosen cell provides no observation; retrospective scoring uses the same-day median of available videos, with 17 missing test cells and 201 empty selections. This imputation defines the reported benchmark loss, not a deployable reward model. Development-panel eligibility conditions tuning on its cutoff cohort; the test windows remain later and disjoint.

Joint UCB lowers loss by 49.3% [13.4%, 84.8%] at budget one and 54.1% [42.6%, 67.0%] at budget five relative to iid TS. Against last value it differs by +3.2% [−12.9%, +44.3%] and +6.6% [−9.1%, +61.8%], respectively. At budget five it improves on temporal UCB by 11.3% [5.3%, 20.4%], but comparisons with rewired covariance (−1.4% [−6.5%, +3.5%]) and a common-factor model (−3.5% [−6.7%, +1.3%]) are inconclusive. Intervals resample windows and then panels; with only three time windows they are sensitivity summaries conditional on shared fitted inputs, not population guarantees.

Historical 2025 Wikipedia panels extend the check. At budget five, joint UCB has 0.749× iid-TS loss on astronomy and 0.661× on football, but EWMA nearly matches it on astronomy and temporal greedy is better on football (Appendix Table 6). Five policy seeds share each reward field and are not five independent historical replicates. Persistence is useful; the evidence does not establish a universal advantage from a detailed graph.

Loss / iid TS	$k = 1$	$k = 5$
Joint filter, greedy	**0.470**	0.440
Last observed value	0.491	**0.430**
EWMA	0.485	0.729
Temporal filter, greedy	0.496	0.456
Joint filter, UCB	0.507	0.459
Temporal filter, UCB	0.510	0.517
Joint UCB, rewired	0.500	0.465
Joint UCB, common factor	0.502	0.475
Sliding-window UCB	0.613	0.744
Discounted TS	0.768	0.897

Table 3: Chronological KuaiRec: aggregate current-oracle loss per selected slot per day, relative to iid TS. Paired uncertainty is reported for the specified comparisons in Figure 2.




Figure 2: Paired effects on chronological KuaiRec at budget five: joint UCB against each baseline. Negative values favor joint UCB. The iid comparison is favorable; last-value and graph-specific comparisons remain inconclusive.

What can be explored? Current innovations are independent of the pre-action history, imposing a one-step forecasting floor even for a learner that knows the means. They can influence future AR states and become learnable from later observations. Removing Q_G from a current forecast covariance is therefore a working exploration choice, not a proof that observing a fresh shock has no future value. Known-mean AR(1) controls give predictive sampling the best tested loss at $\varphi = 0.99$ (0.1495), but two-step lookahead the best at $\varphi = 0.9$ (0.4334). Mean learning, current tracking, and future information value require distinct comparisons.

6 RELATED WORK

Spatial dependence. Spectral bandits assume means smooth on a graph and bound regret by an effective dimension [19, 28]. Graph pure exploration prices similarity in samples [26]. Clustered and

collaborative bandits pool across users or arms [2, 4, 12, 31], and Web systems use social, knowledge and key-term graphs [23, 33, 35, 36]. Correlated-arm UCB pulls non-competitive arms $O(1)$ times when correlations are known [14], and network spillover adds dependence across users [7]. These works primarily exploit structural restrictions for transfer. Their assumptions and objectives differ from the two-role model here. We separate its role for the means from its role for the shocks, certify the first, and price the second in the spectral domain.

Temporal dependence. Switching and drifting bandits forget old data [3, 11, 32]. AR rewards [5], latent AR states [27] and linear Gaussian systems with Kalman prediction [13] model persistence. Predictive sampling targets information that persists [24], and the knowledge gradient handles correlated beliefs [8]. TV-GP-UCB combines spatial and temporal kernels, but they are separable [3]. We credit these works for filtering and for the policies. Our contribution is the non-separable node-time structure, the information and confidence it implies, and its interaction with certified spatial pooling.

Confidence and evaluation on Web logs. Self-normalized bounds [1] and time-uniform confidence sequences [15] underlie our certificates. Work on OBD questions the reliability of IPS rankings [20]. Our sparse actual-log pilot is evaluated separately from semi-synthetic mean learning; daily click residuals do not establish the positive persistence of the Gaussian attention model. Related uses of logged Web data include offline-online learning [22], slate evaluation [18], empirical-Bayes ranking [30, 34], and audits of feed exploration [16, 21, 29].

7 CONCLUSION AND LIMITATIONS

A graph restriction on means and a graph model for shocks supply different information. Exact innovation regression yields valid adaptive confidence under known spatiotemporal dynamics, and certified rejection remains sound when it uses that information. Full autocovariance, partial observation, and sampling times determine how much feedback is worth. The experiments support the mechanisms but expose a gap between correctness and usefulness: practical widths are often uninformative, and generic shrinkage or last value captures much of the observed benefit. Unknown dynamics, future drift, context-dependent clicks, three chronological test windows, and retrospective missing-cell scoring limit the empirical conclusions. We do not establish fitted-model coverage or prospective deployment gains. Improving per-contrast confidence while retaining validity is the next algorithmic challenge.

Data use. Experiments use existing public research logs and aggregate public attention records. They introduce no new user interaction, targeted intervention, or released user-level profile. Reported outcomes are simulated or retrospective; the work does not claim participant consent or institutional approval beyond the source datasets' documented arrangements.

REFERENCES

[1] Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. 2011. Improved Algorithms for Linear Stochastic Bandits. In *Advances in Neural Information Processing Systems (NeurIPS)*, Vol. 24.

[2] Yikun Ban and Jingrui He. 2021. Local Clustering in Contextual Multi-Armed Bandits. In *Proceedings of the Web Conference (WWW)*. https://doi.org/10.1145/3442381.3450058

[3] Ilija Bogunovic, Jonathan Scarlett, and Volkan Cevher. 2016. Time-Varying Gaussian Process Bandit Optimization. In *Proceedings of the 19th International Conference on Artificial Intelligence and Statistics (AISTATS) (PMLR, Vol. 51)*. 314–323.

[4] Emil Carlsson, Devdatt Dubhashi, and Fredrik D. Johansson. 2021. Thompson Sampling for Bandits with Clustered Arms. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence (IJCAI)*. 2212–2218. https://doi.org/10.24963/ijcai.2021/305

[5] Qinyi Chen, Negin Golrezaei, and Djallel Bouneffouf. 2023. Non-Stationary Bandits with Auto-Regressive Temporal Dependency. In *Advances in Neural Information Processing Systems (NeurIPS)*, Vol. 36.

[6] Richard Combes, Stefan Magureanu, and Alexandre Proutiere. 2017. Minimal Exploration in Structured Stochastic Bandits. In *Advances in Neural Information Processing Systems (NeurIPS)*. 1763–1771.

[7] Ahmed Sayeed Faruk and Elena Zheleva. 2025. Leveraging Heterogeneous Spillover in Maximizing Contextual Bandit Rewards. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3696410.3714706

[8] Peter Frazier, Warren Powell, and Savas Dayanik. 2009. The Knowledge-Gradient Policy for Correlated Normal Beliefs. *INFORMS Journal on Computing* 21, 4 (2009), 599–613. https://doi.org/10.1287/ijoc.1080.0314

[9] Chongming Gao, Shijun Li, Wenqiang Lei, Jiawei Chen, Biao Li, Peng Jiang, Xiangnan He, Jiaxin Mao, and Tat-Seng Chua. 2022. KuaiRec: A Fully-observed Dataset and Insights for Evaluating Recommender Systems. In *Proceedings of the 31st ACM International Conference on Information and Knowledge Management (CIKM)*.

[10] Aurélien Garivier and Olivier Cappé. 2011. The KL-UCB Algorithm for Bounded Stochastic Bandits and Beyond. In *Proceedings of the 24th Annual Conference on Learning Theory (COLT) (PMLR, Vol. 19)*. 359–376.

[11] Aurélien Garivier and Eric Moulines. 2011. On Upper-Confidence Bound Policies for Switching Bandit Problems. In *Algorithmic Learning Theory (ALT) (LNCS, Vol. 6925)*. https://doi.org/10.1007/978-3-642-24412-4_16

[12] Claudio Gentile, Shuai Li, and Giovanni Zappella. 2014. Online Clustering of Bandits. In *Proceedings of the 31st International Conference on Machine Learning (ICML) (PMLR, Vol. 32)*.

[13] Jonathan Gornet and Bruno Sinopoli. 2024. Restless Bandits with Rewards Generated by a Linear Gaussian Dynamical System. In *Proceedings of the 6th Annual Learning for Dynamics and Control Conference (L4DC) (PMLR, Vol. 242)*. 1791–1802.

[14] Samarth Gupta, Shreyas Chaudhari, Gauri Joshi, and Osman Yağan. 2021. Multi-Armed Bandits With Correlated Arms. *IEEE Transactions on Information Theory* (2021). https://doi.org/10.1109/TIT.2021.3081508

[15] Steven R. Howard, Aaditya Ramdas, Jon McAuliffe, and Jasjeet Sekhon. 2021. Time-uniform, Nonparametric, Nonasymptotic Confidence Sequences. *The Annals of Statistics* 49, 2 (2021). https://doi.org/10.1214/20-AOS1991

[16] Yiling Jia, Huazheng Wang, Stephen Guo, and Hongning Wang. 2021. PairRank: Online Pairwise Learning to Rank by Divide-and-Conquer. In *Proceedings of the Web Conference (WWW)*. https://doi.org/10.1145/3442381.3449972

[17] Rudolf E. Kalman. 1960. A New Approach to Linear Filtering and Prediction Problems. *Journal of Basic Engineering* 82, 1 (1960), 35–45. https://doi.org/10.1115/1.3662552

[18] Haruka Kiyohara, Masahiro Nomura, and Yuta Saito. 2024. Off-Policy Evaluation of Slate Bandit Policies via Optimizing Abstraction. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3589334.3645343

[19] Tomáš Kocák, Rémi Munos, Branislav Kveton, Shipra Agrawal, and Michal Valko. 2020. Spectral Bandits. *Journal of Machine Learning Research* 21, 218 (2020), 1–44.

[20] Daria Korovaitceva, Marina Sheshukova, Evgeny Frolov, and Sergey Samsonov. 2026. Revisiting IPS-based Algorithms for Off-Policy Evaluation of Contextual Bandits. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3774904.3792928

[21] Lihong Li, Wei Chu, John Langford, and Robert E. Schapire. 2010. A Contextual-Bandit Approach to Personalized News Article Recommendation. In *Proceedings of the 19th International Conference on World Wide Web (WWW)*. 661–670. https://doi.org/10.1145/1772690.1772758

[22] Ye Li, Hong Xie, Yishi Lin, and John C. S. Lui. 2021. Unifying Offline Causal Inference and Online Bandit Learning for Data Driven Decision. In *Proceedings of the Web Conference (WWW)*. https://doi.org/10.1145/3442381.3449982

[23] Zhuohua Li, Maoli Liu, Xiangxiang Dai, and John C. S. Lui. 2025. Towards Efficient Conversational Recommendations: Expected Value of Information Meets Bandit Learning. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3696410.3714773

[24] Yueyang Liu, Benjamin Van Roy, and Kuang Xu. 2023. Nonstationary Bandit Learning via Predictive Sampling. In *Proceedings of the 26th International Conference on Artificial Intelligence and Statistics (AISTATS) (PMLR, Vol. 206)*. 6215–6244.

[25] Yuta Saito, Shunsuke Aihara, Megumi Matsutani, and Yusuke Narita. 2021. Open Bandit Dataset and Pipeline: Towards Realistic and Reproducible Off-Policy Evaluation. In *NeurIPS Datasets and Benchmarks Track*.
[26] Parth K. Thaker, Mohit Malu, Nikhil Rao, and Gautam Dasarathy. 2022. Maximizing and Satisficing in Multi-armed Bandits with Graph Information. In *Advances in Neural Information Processing Systems (NeurIPS)*, Vol. 35.
[27] Anna L. Trella, Walter H. Dempsey, Asim H. Gazi, Ziping Xu, Finale Doshi-Velez, and Susan A. Murphy. 2025. Non-Stationary Latent Auto-Regressive Bandits. *Reinforcement Learning Journal* 6 (2025), 765–789.
[28] Michal Valko, Rémi Munos, Branislav Kveton, and Tomáš Kocák. 2014. Spectral Bandits for Smooth Graph Functions. In *Proceedings of the 31st International Conference on Machine Learning (ICML) (PMLR, Vol. 32)*. 46–54.
[29] Karan Vombatkere, Sepehr Mousavi, Savvas Zannettou, Franziska Roesner, and Krishna P. Gummadi. 2024. TikTok and the Art of Personalization: Investigating Exploration and Exploitation on Social Media Feeds. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3589334.3645600
[30] Shiyao Wang, Qi Liu, Tiezheng Ge, Defu Lian, and Zhiqiang Zhang. 2021. A Hybrid Bandit Model with Visual Priors for Creative Ranking in Display Advertising. In *Proceedings of the Web Conference (WWW)*. https://doi.org/10.1145/3442381.3449910
[31] Qingyun Wu, Huazheng Wang, Quanquan Gu, and Hongning Wang. 2016. Contextual Bandits in a Collaborative Environment. In *Proceedings of the 39th International ACM SIGIR Conference*. https://doi.org/10.1145/2911451.2911528
[32] Qingyun Wu, Huazheng Wang, Yanen Li, and Hongning Wang. 2019. Dynamic Ensemble of Contextual Bandits to Satisfy Users' Changing Interests. In *The World Wide Web Conference (WWW)*. https://doi.org/10.1145/3308558.3313727
[33] Xian Wu, Suleyman Cetintas, Deguang Kong, Miao Lu, Jian Yang, and Nitesh Chawla. 2020. Learning from Cross-Modal Behavior Dynamics with Graph-Regularized Neural Contextual Bandit. In *Proceedings of The Web Conference (WWW)*. https://doi.org/10.1145/3366423.3380178
[34] Tao Yang, Cuize Han, Chen Luo, Parth Gupta, Jeff M. Phillips, and Qingyao Ai. 2024. Mitigating Exploitation Bias in Learning to Rank with an Uncertainty-aware Empirical Bayes Approach. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3589334.3645487
[35] Xiaoying Zhang, Hong Xie, Hang Li, and John C. S. Lui. 2020. Conversational Contextual Bandit: Algorithm and Application. In *Proceedings of The Web Conference (WWW)*. https://doi.org/10.1145/3366423.3380148
[36] Canzhe Zhao, Tong Yu, Zhihui Xie, and Shuai Li. 2022. Knowledge-aware Conversational Preference Elicitation with Bandit Feedback. In *Proceedings of the ACM Web Conference (WWW)*. https://doi.org/10.1145/3485447.3512152

A PROOFS

Node-time covariance (Proposition 2.1). Stationarity and causal stability give $z_{i,t} = \sum_{k\ge 0} \psi_i(k)\eta_{i,t-k}$. Independence across innovation dates leaves only equal-date terms in the covariance, giving the stated sum for $h \ge 0$, with $G_{-h} = G_h^\top$. Fourier transformation gives $\Lambda Q_G \Lambda^*$. If every filter is identical, $G_h = \gamma(h) Q_G$ for all h. Conversely, separability implies identical normalized diagonal autocovariances because $Q_G \succ 0$. A stable causal AR transfer with numerator one is the unique normalized minimum-phase spectral factor of that autocorrelation spectrum. Hence the AR filters, and their impulse responses, agree (orders may differ only through zero coefficients). Heterogeneous filters generally yield nonsymmetric positive-lag cross-covariances.

Innovation regression (Theorem 3.1). Initialize $g_1 = D_1 = 0$ and $P_1 = \Gamma$. Given the history and a candidate mean, the selected conditional mean is $\ell_a^\top g_t + v_{t,a}^\top \mu$, where $v_{t,a} = e_a + D_t^\top \ell_a$, and variance is $d_{t,a}$. Standardization gives the unit conditional Gaussian error. Set $k_t = P_t \ell_a / d_{t,a}$. The update and prediction are

$$g_t^+ = g_t + k_t(Y_t - \ell_a^\top g_t), \qquad D_t^+ = D_t - k_t v_{t,a}^\top,$$
$$P_t^+ = P_t - k_t \ell_a^\top P_t, \qquad (g_{t+1}, D_{t+1}, P_{t+1}) = (F g_t^+, F D_t^+, F P_t^+ F^\top + E Q_G E^\top).$$

Thus the affine representation is preserved. On a recorded schedule the standardized residual transform is triangular and whitens Ξ, proving the two information identities. Adaptive policy factors do not depend on the candidate mean. For a slate, replace $\ell_a^\top$ by its selected observation matrix and whiten the conditional innovation vector; the action is fixed before same-round readings.

Simultaneous confidence (Theorem 3.2). For fixed θ, $\exp(\theta^\top W_T - \theta^\top \mathcal{I}_T \theta/2)$ is a nonnegative martingale, with $W_T = \sum_t u_t \epsilon_t$. Mixing over $\theta \sim N(0, H^{-1})$, for $\alpha > 0$ and $\lambda \ge 0$, yields

$$\sqrt{\det H / \det J_T}\, \exp(\|W_T\|^2_{J_T^{-1}}/2).$$

Ville's inequality bounds this by $1/\delta$ simultaneously in T. Since $\hat{\mu}_T - \mu = J_T^{-1}(W_T - H\mu)$ and $H \preceq J_T$, the regularization term has J_T-norm at most $\sqrt{\mu^\top H \mu} \le \sqrt{\alpha B^2 + \lambda S^2}$. Triangle and Cauchy–Schwarz inequalities give the all-direction statement. When a leader's lower contrast bounds against every other arm are positive, they are positive at the truth. With approximate mean graph $\hat{L} \preceq (1+\zeta) L_\mu$, its energy is at most $(1+\zeta)S^2$. This argument does not repair an incorrect innovation covariance.

Information sandwich and regret. The eigenvalues of $\mathcal{S}_z(\omega)$ lie between $\lambda_{\min}(Q_G)/a^2_{\max}$ and $\lambda_{\max}(Q_G)/a^2_{\min}$. Parseval's identity transfers these bounds to every finite field covariance. Selecting readings and adding sensor noise bounds Ξ between $v_- I$ and $v_+ I$. Inversion and congruence by M give Proposition 3.3, since $M^\top M = \mathrm{diag}(N_i)$. This pathwise matrix statement remains valid when the realized schedule is adaptive. After the first pull of every arm, $J_T \succeq v_+^{-1}\,\mathrm{diag}(N_i)$, so optimism bounds an ordinary selected gap by $2\beta_{t-1}\sqrt{v_+/N_{a_t}}$. Summing reciprocal square roots gives at most $2\sqrt{NT}$; initialization costs at most $2BN$. Finally $J_T \preceq H + (T/v_-)I$ and $H \succeq \alpha I$ yield the determinant bound in Corollary 3.4. For fixed N and model parameters, it is $O(\sqrt{T}\log^{1/2} T)$. Expected regret adds $2BT\delta$.

Long-run information (Proposition 3.5). With exact full-field readings and $t > p$, the residual

$$X_t - \sum_{k=1}^{p} \mathrm{diag}(a_{\cdot,k}) X_{t-k} = D_c \mu + \eta_t$$

is independent of earlier innovations and adds $D_c Q_G^{-1} D_c$ information. The first p stationary fields supply $\mathcal{I}_p$. At zero frequency, the observed process has spectral density $\Omega = D_c^{-1} Q_G D_c^{-1} + rI$. Stability gives summable covariances; consequently $n\mathrm{Cov}(\bar{Y}_n) \to \Omega$. For the full stationary Gaussian location experiment, boundary contributions are $o(n)$ and $\mathcal{I}_n/n \to \Omega^{-1}$. One way to see this is to apply the inverse covariance operator to a constant mean sequence: its interior response is the zero-frequency inverse, while stable-filter boundary terms are summable. Diagonalization in common graph modes gives the stated rates. Sensor noise requires this asymptotic argument and is not part of the exact noiseless increment identity.

Inflation and contrasts. Expand the variance of a block mean as $b^{-2}\sum_{s,u}(G_{s-u})_{ii}$. There are $b-h$ pairs at each positive lag, giving $f_i(b)$. Summing the AR(1) geometric series gives its closed form. The standardized Gaussian tail gives the fixed-block failure probability. For arbitrary dates, retain their actual lag differences; adaptively selected sample means need not have this unconditional Gaussian law. Expanding a simultaneous contrast mean similarly

gives

$$\frac{1}{n^2}\sum_{s,u=1}^{n}\left((G_{s-u})_{ii}+(G_{s-u})_{jj}-(G_{s-u})_{ij}-(G_{s-u})_{ji}\right)+\frac{2r}{n}.$$

Covariance summability yields Proposition 3.7. Restricting observations marginalizes the unobserved field, so the contemporaneous covariance is Q_{SS}. Conditioning on all its coordinates would instead use the restricted full precision. Staggered dates require the same sum with their selected cross lags.

The exact AR(2) schedules. Odd-lag covariances vanish and $G_{2h} = a^h V \left(\begin{smallmatrix} 1 & \rho \\ \rho & 1 \end{smallmatrix}\right)$. Under AABB the two within-arm readings have zero covariance; the only nonzero cross-arm covariances are the two lag-two pairs, each $a\rho V$. The symmetric GLS estimates are the per-arm averages, giving contrast variance $V + r - a\rho V$. Under ABAB each arm's readings have covariance aV and all cross-arm lags are odd, giving $V + r + aV$. The two-arm correct-selection probability is $\Phi(\Delta/\sqrt{\mathrm{Var}(\hat{\mu}_A - \hat{\mu}_B)})$ for $\Delta > 0$.

Iid pooling (Theorem 4.1). Assume centered conditionally σ^2-sub-Gaussian independent observation noise. Use $b(n) = \sqrt{2\sigma^2\ell/n}$, initialize each arm once, and use infinite bounds when a count is zero. Arm and pooled noise sums are martingales at their predictable selection times. A tail bound and union over at most $N+M$ processes and T counts gives the advertised event. A component's average sampled mean lies in $[v_c - \varepsilon_c, v_c]$, so the pooled upper bound is optimistic. If arm i is pulled, its gap obeys $\Delta_i \le 2b(n_i)$, giving at most $1 + 8\sigma^2\ell/\Delta_i^2$ pulls. If component c is selected and $\Gamma_c > \varepsilon_c$, then $\Gamma_c \le \varepsilon_c + 2b(N_c)$, giving at most $1 + 8\sigma^2\ell/(\Gamma_c - \varepsilon_c)^2$ component pulls. Each costs at most $\Gamma_c + \varepsilon_c$. Taking the smaller of the arm and component regret bounds proves A1. Bernoulli KL versions in the simulations use their own radii; A1 is the Gaussian/sub-Gaussian statement.

Path–clique information program. Take the homogeneous component mean to be zero and the unchanged outside optimum to be Δ. An alternative raises some component coordinate to Δ while satisfying its energy budget. Its Gaussian KL cost is $\sum_j n_j v_j^2/(2\sigma^2)$. Clipping an alternative to $[0, \Delta]$ cannot increase Dirichlet energy or this cost; division by Δ gives F_L^*. The change-of-measure constraints imply total component sampling at least $2\sigma^2 \log T/(\Delta^2 F_L^*)$ for a uniformly efficient policy on this restricted class.

For the normalized clique, $L = I - \mathbf{1}\mathbf{1}^\top/m$. Every e_i has energy $1 - 1/m \le 1$, so $F_L^* \le \max_p \min_i p_i = 1/m$; uniform weights give the reverse bound since $z_i = 1$. For the path, give every edge conductance $(m-1)/2$. Both graphs have resistance diameter two. Set half the design weight at each endpoint. For an interior i with $z_i = 1$, let d_1, d_m be the resistances from i to the endpoints, so $d_1 + d_m = 2$. Cauchy–Schwarz on each path segment gives

$$z^\top L z \ge \frac{(1-z_1)^2}{d_1} + \frac{(1-z_m)^2}{d_m} \ge \frac{(2-z_1-z_m)^2}{2}.$$

At energy at most one, $(z_1 + z_m)/2 \ge 1 - 1/\sqrt{2}$, and $(z_1^2 + z_m^2)/2 \ge (1 - 1/\sqrt{2})^2$. An endpoint choice of i gives an even stronger bound. This completes the claimed separation without an external supplement.

Dependent pooling (Theorem 4.2). On Theorem 3.2's event, $w^\top \mu \ge v_c - \varepsilon_c$ for every component weight. Both terms in U_c therefore upper-bound v_c. If c is selected, its optimized weighted term is at least $\mu^\star$, yet at most $v_c + \varepsilon_c + 2\beta_t \|w\|_{J_t^{-1}}$ for every w. Rearranging gives the rejection condition. For independent AR(1) arms, the scalar filter's affine mean coefficient after a reading stays in $[-1, 0]$. Across a gap $h \ge 1$, prediction multiplies it by φ^h; the next observation's mean coefficient is at least $1 - \varphi$. Its conditional variance is at most $V + r$, proving the stated scalar information increment. This argument does not extend unchanged to correlated arms.

Scalar nuisance intervals. For $\lambda = 0$, let $G = \mathcal{I}_t$, $J = \alpha I + G$, $q = G\mu + W$. A coordinate Gaussian-mixture bound and union with $\delta_i = \delta/N$ give, simultaneously in t, i,

$$|W_i| \le h_i := \sqrt{2J_{ii}\log\left(\sqrt{J_{ii}/\alpha}/\delta_i\right)}.$$

If valid intervals have centers m_j and half-widths ρ_j, set

$$\widetilde{m}_i = \frac{q_i - \sum_{j\neq i} G_{ij} m_j}{J_{ii}}, \qquad \widetilde{\rho}_i = \frac{h_i + \alpha B + \sum_{j\neq i} |G_{ij}|\rho_j}{J_{ii}}.$$

The score identity bounds $|\widetilde{m}_i - \mu_i|$ by $\widetilde{\rho}_i$ when $|\mu_i| \le B$. Intersect with current intervals, initialized at $[-B, B]$ or a supplied valid mean range. Repetition preserves truth on the same event. Cross-coordinate nuisance terms explain the possible conservatism; fitted likelihoods are outside this proof.

B PROTOCOLS AND REPRODUCIBILITY

KuaiRec static. The small matrix has 1,411 users and 3,327 videos; the larger matrix has 7,176 users and 10,728 videos. Simulator means are $\min(\text{watch ratio}, 5)/5$. Graphs are union k-nearest-neighbor graphs, $k \in \{5, 10, 20\}$, with Laplacians scaled to mean degree one. Main item policies use $k = 10$, a 20-way spectral partition, and degree-preserving nulls. Oracle widths equal true component ranges. Energy widths use a truth-derived energy radius and effective resistance. Population quantiles are fit on separate tuning users. User quantiles additionally use 300 paid noisy warm-up readings. Diagnostic width coverage is component-marginal, and the user diagnostic conditions on the true level, so neither is a joint $1-\delta$ certificate. All main paired intervals average three subsets within each of 120 users before 2,000 bootstrap resamples; they condition on the shared source matrix, graph fit, and tuning population. Earlier 30-user/60-instance results are nested exploratory evidence, not independent replication.

Chronological KuaiRec. The panel spans 63 days. Cutoffs 30, 41, and 52 each precede an 11-day test window; five disjoint panels per cutoff use prefix eligibility, requiring at least ten plays per fit day. Prefix co-engagement uses non-evaluation users. Development uses days 20–30 after fitting days 1–19, but its panel eligibility and graph are conditioned on the day-30 cutoff; it is a development-cohort approximation, not an online eligibility simulation. Policy rewards are transformed daily aggregates, with synthetic sensor standard deviation 0.05. Policies select before that

day's feedback and receive only selected nonempty cells. Missing-cell scoring is the available-video same-day median. Loss is oracle logit completion-rate difference per day per selected slot. Bootstrap sensitivity resamples the three windows, then panels within windows, 4,000 times, after averaging five policy seeds. Shared shocks and fitting data remain dependencies. Saved trajectories determine the reported outputs; a source implementation's process-dependent hashed policy seed means regenerated trajectories can differ across processes.

Wikipedia. Exploratory inflation panels contain one 150-article domain and six communities of 25 articles, with weekday adjustment, 2022–2023 fitting, and 2024–2025 testing. Article selection and hyperlinks from a later snapshot make their graph conclusions retrospective. Coverage worlds use 30 articles, six components, AR(7), $T = 730$, slate sizes five/ten, and 100 worlds per learner–policy–noise cell: 4,800 trajectories in total. Clean theory comparisons here use centered Gaussian innovations; empirical and weekly block residual resampling are separately audited stresses. Historical policy panels each have 24 astronomy or football articles. They use pre-2024 hyperlinks, 2024 fitting/development and full-year refitting, and 365 masked days in 2025 at budgets one/five; no full-field refresh occurs after testing begins. Five stochastic policy seeds share the same field. Date-block intervals at lengths 7, 14, and 28 are descriptive sensitivities. Earlier half-year runs are nested in these dates.

OBD.. Uniform-random logs cover 24–30 November 2019: All, Men, and Women, with 80, 34, and 46 items. Static simulations use All/Women, all logged positions pooled, days 1–3 construction, and days 4–7 estimated rates. Four-dimensional audience summaries and attribute metadata are retrospective features. Means ignore contextual and position heterogeneity. The real-log Men position-1 pilot uses three fit days, day four development, and the final 72 test hours. It retains the calendar and propensity 1/34, rather than compressing to matching events. Stochastic policy seeds measure algorithm variation on one log, not uncertainty over independent platforms. Empirical prefix widths cannot certify future levels under drift. Daily click residual lag-one correlations are negative (approximately −0.14 to −0.22); finer bins are near zero, so OBD does not verify persistent Gaussian click shocks at this resolution.

Reproducibility scope. The experiment snapshot comprises the completed trajectories and exact-information outputs reported above. Confidence rates use Wilson intervals over independent simulated worlds; static comparisons use user clusters; historical comparisons condition on their recorded panels. Figure data and generation code accompany the manuscript source, with checksums linking the numeric snapshot to saved experiment tables. No claim relies on an unrun larger factorial confirmation. Public raw datasets retain their source terms; reconstructing logs is separate from rebuilding manuscript figures.

C ADDITIONAL RESULTS

Geometry at finite budgets. In a controlled two-component experiment, graph-design elimination on the normalized path has mean regret 46.08 versus 191.83 for ordinary UCB at component size 256. At size 16 it has 40.32 versus 10.81. On the size-256 clique its regret is 216.65. The information separation does not remove finite-budget pilot overhead or guarantee dominance for every graph. The experiment uses homogeneous component means, a supplied energy allowance, and a capped design policy with fallback.

Graph	Energy quotient	Taste corr.	Smoothing loss
Item factorization	0.76 / 0.96	0.046	0.117 / 0.019
Item co-engagement	1.10 / 1.30	0.034	0.131 / 0.037
Item category/tag	0.91 / 0.99	0.010	0.099 / 0.079
User co-engagement	0.65 / 0.79	0.020	0.284 / 0.291
User profile/location	0.95–0.99	0.002–0.007	0.31–0.35

Table 4: KuaiRec alignment, $k = 10$. Slash entries are real / rewired. Energy quotients normalize by a random-pair expectation; taste correlations use double-centered means. Smoothing loss is best-choice value lost under $(I + 10L)^{-1}$. Small global energy need not preserve the best item.

Panel	Days	Observed	Lag-one	Full AR(20)
One domain	7	5.0	3.4	4.5
One domain	28	17.1	4.6	13.2
Six communities	7	5.3	4.4	5.0
Six communities	28	17.8	7.4	15.3

Table 5: Retrospective Wikipedia block-mean inflation: weekday-adjusted medians over 150 articles per panel. Fits use 2022–2023; observations use 2024–2025.

2025 Wikipedia, loss per slot ($k = 5$)	Astronomy	Football
Iid TS	0.05395	0.22025
Joint UCB	**0.04039**	0.14552
EWMA	0.04143	0.23209
Temporal greedy	0.05438	**0.13017**
Static	0.05345	0.22154

Table 6: Full-year historical attention: current-oracle $\log(1+\text{views})$ **loss per selected slot. Astronomy is competitive with EWMA; football favors temporal greedy.**

Objective and exploration controls. The fixed 100-arm AR(20) truth benchmark has 32 paired worlds per tested configuration. Full-state joint UCB leads iid UCB in current-oracle loss (1.248 versus 1.397), while iid UCB leads in mean regret (0.668 versus 0.686). Known-mean AR(1) controls run 40 worlds through 30,000 rounds with 5,000 burn-in. At persistence 0.99, predictive sampling loses 0.1495 per round, lifetime knowledge gradient 0.1659, and two-step lookahead 0.1997. At persistence 0.9, two-step lookahead loses 0.4334, lifetime knowledge gradient 0.4574, and predictive sampling 0.5669. These controls reject a universal ordering of the exploration rules; they do not prove optimality of any tested policy.