

# Pandas Visualization

```
In [1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt

%matplotlib notebook
```

```
In [2]: # see the pre-defined styles provided.
plt.style.available
```

```
Out[2]: ['seaborn-dark',
'seaborn-colorblind',
'bmh',
'dark_background',
'seaborn-ticks',
'seaborn-paper',
'seaborn',
'seaborn-poster',
'seaborn-notebook',
'fivethirtyeight',
'seaborn-pastel',
'seaborn-dark-palette',
'grayscale',
'seaborn-talk',
'seaborn-deep',
'seaborn-bright',
'ggplot',
'seaborn-whitegrid',
'seaborn-white',
'seaborn-muted',
'seaborn-darkgrid',
'classic']
```

```
In [3]: # use the 'seaborn-colorblind' style
plt.style.use('seaborn-colorblind')
```

## DataFrame.plot

```
In [4]: np.random.seed(123)

df = pd.DataFrame({'A': np.random.randn(365).cumsum(0),
                   'B': np.random.randn(365).cumsum(0) + 20,
                   'C': np.random.randn(365).cumsum(0) - 20},
                  index=pd.date_range('1/1/2017', periods=365))


df.head()
```

Out[4]:

	A	B	C
2017-01-01	-1.085631	20.059291	-20.230904
2017-01-02	-0.088285	21.803332	-16.659325
2017-01-03	0.194693	20.835588	-17.055481
2017-01-04	-1.311601	21.255156	-17.093802
2017-01-05	-1.890202	21.462083	-19.518638

```
In [27]: df.plot(); # add a semi-colon to the end of the plotting call to suppress unwanted output
```


Figure 10

[Back to previous view](#)

We can select which plot we want to use by passing it into the 'kind' parameter.

```
In [28]: df.plot('A', 'B', kind = 'scatter');
```

Figure 11




You can also choose the plot kind by using the `DataFrame.plot.kind` methods instead of providing the `kind` keyword argument.

kind :

- 'line' : line plot (default)
- 'bar' : vertical bar plot
- 'barh' : horizontal bar plot
- 'hist' : histogram
- 'box' : boxplot
- 'kde' : Kernel Density Estimation plot
- 'density' : same as 'kde'
- 'area' : area plot
- 'pie' : pie plot
- 'scatter' : scatter plot
- 'hexbin' : hexbin plot

```
In [29]: # create a scatter plot of columns 'A' and 'C', with changing color (c) and size (s) based on column 'B'  
df.plot.scatter('A', 'C', c='B', s=df['B'], colormap='viridis')
```


Figure 12

[Forward to next view](#)


Out[29]: <matplotlib.axes.\_subplots.AxesSubplot at 0x7fcb3f180438>

```
In [30]: ax = df.plot.scatter('A', 'C', c='B', s=df['B'], colormap='viridis')  
ax.set_aspect('equal')
```

Figure 13




```
In [31]: df.plot.box();
```

**Figure 14**



```
In [32]: df.plot.hist(alpha=0.7);
```

Figure 15


[Back to previous view](#)

Kernel density estimation plots ([https://en.wikipedia.org/wiki/Kernel\\_density\\_estimation](https://en.wikipedia.org/wiki/Kernel_density_estimation)) are useful for deriving a smooth continuous function from a

given sample.

```
In [33]: df.plot.kde();
```

Figure 16



## pandas.tools.plotting

[Iris flower data set \(https://en.wikipedia.org/wiki/Iris\\_flower\\_data\\_set\)](https://en.wikipedia.org/wiki/Iris_flower_data_set)


```
In [12]: iris = pd.read_csv('iris.csv')  
iris.head()
```

Out[12]:

	SepalLength	SepalWidth	PetalLength	PetalWidth	Name
0	5.1	3.5	1.4	0.2	Iris-setosa
1	4.9	3.0	1.4	0.2	Iris-setosa
2	4.7	3.2	1.3	0.2	Iris-setosa
3	4.6	3.1	1.5	0.2	Iris-setosa
4	5.0	3.6	1.4	0.2	Iris-setosa


```
In [34]: pd.tools.plotting.scatter_matrix(iris);
```

Figure 17

[Reset original view](#)

```
In [35]: plt.figure()  
pd.tools.plotting.parallel_coordinates(iris, 'Name');
```

Figure 18



# Seaborn

```
In [15]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns


%matplotlib notebook
```

```
In [16]: np.random.seed(1234)

v1 = pd.Series(np.random.normal(0,10,1000), name='v1')
v2 = pd.Series(2*v1 + np.random.normal(60,15,1000), name='v2')
```

```
In [17]: plt.figure()  
plt.hist(v1, alpha=0.7, bins=np.arange(-50,150,5), label='v1');  
plt.hist(v2, alpha=0.7, bins=np.arange(-50,150,5), label='v2');  
plt.legend();
```

Figure 1









```
In [18]: # plot a kernel density estimation over a stacked barchart
plt.figure()
plt.hist([v1, v2], histtype='barstacked', normed=True);
v3 = np.concatenate((v1,v2))
sns.kdeplot(v3);
```

Figure 2



```
In [19]: plt.figure()  
# we can pass keyword arguments for each individual component of the plot  
sns.distplot(v3, hist_kws={'color': 'Teal'}, kde_kws={'color': 'Navy'});
```


Figure 3



x=92.3085 y=0.00658793

```
In [20]: sns.jointplot(v1, v2, alpha=0.4);
```


Figure 4






```
In [21]: grid = sns.jointplot(v1, v2, alpha=0.4);  
         grid.ax_joint.set_aspect('equal')
```

Figure 5



```
In [22]: sns.jointplot(v1, v2, kind='hex');
```

Figure 6








```
In [23]: # set the seaborn style for all the following plots
sns.set_style('white')

sns.jointplot(v1, v2, kind='kde', space=0);
```

Figure 7




```
In [24]: iris = pd.read_csv('iris.csv')
iris.head()
```


Out[24]:

	SepalLength	SepalWidth	PetalLength	PetalWidth	Name
0	5.1	3.5	1.4	0.2	Iris-setosa
1	4.9	3.0	1.4	0.2	Iris-setosa
2	4.7	3.2	1.3	0.2	Iris-setosa
3	4.6	3.1	1.5	0.2	Iris-setosa
4	5.0	3.6	1.4	0.2	Iris-setosa

```
In [25]: sns.pairplot(iris, hue='Name', diag_kind='kde', size=2);
```

Figure 8





```
In [26]: plt.figure(figsize=(8,6))
plt.subplot(121)
sns.swarmplot('Name', 'PetalLength', data=iris);
plt.subplot(122)
sns.violinplot('Name', 'PetalLength', data=iris);
```

Figure 9



