🌟 What are Pseudo-classes?

A **pseudo-class** is a keyword added to a selector that specifies a **special state** of an element.

◇ Syntax:

```
selector:pseudo-class {
    property: value;
}
```

🎯 Common Pseudo-classes

1. 🔗 Link-related

Used for styling links based on interaction:

```
a:link {
    color: blue;
}

a:visited {
    color: purple;
}

a:hover {
    color: red;
}

a:active {
    color: green;
}
```

👉 Think of it like a lifecycle:

- `:link` → untouched

- `:visited` → already explored
- `:hover` → cursor is flirting with it
- `:active` → being clicked

2. 🧠 User Interaction

Reacts to user actions:

```
button:hover {
    background-color: yellow;
}

input:focus {
    border: 2px solid blue;
}
```

- `:hover` → mouse over
- `:focus` → clicked or typing inside

3. 📍 Structural (Position-based)

Select elements based on their position:

```
li:first-child {
    color: red;
}

li:last-child {
    color: blue;
}

li:nth-child(2) {
    color: green;
}
```

🧩 Examples:

- `:first-child` → first element

- `:last-child` → last element
- `:nth-child(n)` → specific position

4. ☑ Form States

Used for form validation and states:

```
input:checked {
    background-color: green;
}

input:disabled {
    background-color: gray;
}

input:required {
    border: 2px solid red;
}
```

5. 🚫 Negation

Select elements that **do NOT match** something:

```
p:not(.special) {
    color: black;
}
```

🧪 Mini Example

```
<ul>
  <li>Apple</li>
  <li>Banana</li>
  <li>Mango</li>
</ul>
li:hover {
    color: orange;
```

```
}

li:nth-child(2) {
    font-weight: bold;
}
```

👉 Result:

- Hover → turns orange 🍊
- 2nd item → bold

⚡ Pro Tips

- Combine pseudo-classes:

```
a:hover:first-child {
    color: red;
}
```

- Order matters for links:
  👉 `link → visited → hover → active` (LVHA rule)