🌟 What are Pseudo-elements?

A **pseudo-element** lets you style a **part of an element** (not its state like pseudo-classes).

◇ Syntax:

```
selector::pseudo-element {
    property: value;
}
```

👉 Notice the **double colon `::`** (modern syntax)

🎯 Common Pseudo-elements

1. ✍️ `::first-letter`

Styles the first letter

```
p::first-letter {
    font-size: 30px;
    color: red;
}
```

📖 Like those fancy newspaper paragraphs with big first letters.

2. 📝 `::first-line`

Styles the first line

```
p::first-line {
    font-weight: bold;
    color: blue;
}
```

3. ✨ `::before`

Inserts content **before** an element

```
h1::before {
    content: "🔥 ";
}
```

👉 Adds fire before heading without HTML changes.

4. 🚀 `::after`

Inserts content **after** an element

```
h1::after {
    content: " 🚀";
}
```

5. 🎨 `::selection`

Styles selected text

```
::selection {
    background-color: yellow;
    color: black;
}
```

👉 When you drag your mouse over text.

6. 🔢 `::marker`

Styles list bullets/numbers

```
li::marker {
    color: red;
```

```
    font-size: 20px;
}
```

7. 📦 `::placeholder`

Styles input placeholder text

```
input::placeholder {
    color: gray;
}
```

🧪 Mini Example

```
<p>Hello world, welcome to CSS!</p>
p::first-letter {
    font-size: 40px;
    color: green;
}

p::after {
    content: " 🌿";
}
```

👉 Output:

- First letter becomes big 🌱
- Leaf emoji added at end