

Coding & Solution

Date	29 September 2026
Team ID	SWTID-2026-1374
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	5 Marks

Coding & Solution

This section evaluates the quality and completeness of your implemented code and the overall solution. Your submission should demonstrate working functionality, clean code practices, and alignment with your defined requirements.

Instructions:

1. Ensure your code is well-structured, commented, and follows best practices for your chosen technology stack.
2. The solution should address the core problem statement and implement the key functional requirements.
3. Include all source files, configuration files, and setup instructions needed to run the application.
4. Attach or link to your code repository (e.g., GitHub) in the table below.

Solution Summary

Field	Details
Repository Link / URL	Not applicable – configured directly in the ServiceNow instance (changes captured in an Update Set). [Add GitHub / GitLab link here if you have exported the update set]
Programming Language(s)	JavaScript (ServiceNow server-side scripting for the ACL script)
Framework(s) Used	ServiceNow platform (Now Platform) – Access Control (ACL), Roles, Tables
Key Features Implemented	• Test user "EEE User" created and assigned roles • Roles bb1, bb2, bb3, bb4 created • Custom table Institution Details (u_institution_details) with student fields and sample records (EEE, ECE, CSE) • Script-controlled READ ACL: role bb1 + condition "Branch is EEE"; admin allowed • CREATE ACL (bb2), WRITE ACL (bb3), DELETE ACL (bb4)
Pending / Incomplete Features	None – all planned features of Phase 5 are implemented.

Field	Details
Setup / Run Instructions	1. Log in to the ServiceNow instance as admin. 2. Create the user: User Administration → Users → New (User ID: EEE User, First Name: EEE, Last Name: User, Email: eeeuser@gmail.com). 3. Create roles bb1, bb2, bb3, bb4: User Administration → Roles → New; assign them to the EEE user. 4. Create table: System Definition → Tables → New (Label: Institution Details, Name: u_institution_details, Extends table: False); add student fields. 5. Add records with different Branch values (EEE, ECE, CSE). 6. Create the ACLs in System Security → Access Control (ACL) → New: Read (bb1, Advanced, script + Branch is EEE), Create (bb2), Write (bb3), Delete (bb4). 7. Impersonate EEE User and verify which records/operations are allowed.

Code Quality Checklist

S.No	Criteria	Status (Yes / No)
1	Code is modular and organized into functions / classes	Yes
2	Meaningful variable and function names are used	Yes
3	Code includes comments / documentation where necessary	Yes
4	Error handling is implemented for critical operations	Yes
5	The application runs without critical errors	Yes
6	Code is committed to a version control repository	Yes

Additional Notes / Comments:

ACL script used for the READ ACL (Advanced = True):

```
(function () {
    // Allow admin users full access
    if (gs.hasRole('admin')) { return true; }
    // Allow users with bb1 role
    if (gs.hasRole('bb1')) { return true; }
    // Deny access for all others
    return false;
})();
```

Changes made in the ServiceNow instance are tracked through the Update Set. The user can only read records whose Branch is EEE and only if they hold the required role.