

Rajalakshmi Engineering College

Name: Gurucharan Chandramohan
Email: 240801092@rajalakshmi.edu.in
Roll no: 2116240801092
Phone: 6379544451
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is building a basic hash table to manage student roll numbers for quick lookup. He decides to use Linear Probing to handle collisions.

Implement a hash table using linear probing where:

The hash function is: $\text{index} = \text{roll_number} \% \text{table_size}$ On collision, check subsequent indexes (i+1, i+2, ...) until an empty slot is found.

You need to:

Insert a list of n student roll numbers into the hash table. Print the final state of the hash table. If a slot is empty, print -1.

Input Format

The first line of the input contains two integers n and table_size, where n is the

number of roll numbers to be inserted, and table_size is the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert into the hash table.

Output Format

The output should print a single line with table_size space-separated integers representing the final state of the hash table after all insertions.

If any slot remains unoccupied, it should be represented as -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4 7

50 700 76 85

Output: 700 50 85 -1 -1 -1 76

Answer

```
#include <stdio.h>
```

```
#define MAX 100
```

```
// You are using GCC
```

```
void initializeTable(int table[], int size) {
```

```
    for(int i=0;i<size;i++) table[i]=-1;
```

```
    //Type your code here
```

```
}
```

```
void linearProbe(int table[], int size, int num) {
```

```
    int index=num%size;
```

```
    int start=index;
```

```
    while(table[index]!=-1) {
```

```
        index=(index+1)%size;
```

```
        if(index==start) return;
```

```
    }
```

```
    table[index]=num;
```

```
    //Type your code here
```

```
}
```

```
void insertIntoHashTable(int table[], int size, int arr[], int n) {  
    //Type your code here  
    if(n>MAX||size>MAX) return;  
    for(int i=0;i<n;i++) linearProbe(table,size,arr[i]);  
}
```

```
void printTable(int table[], int size) {  
    //Type your code here  
    for(int i=0;i<size;i++) printf("%d ",table[i]);  
    printf("\n");  
}
```

```
int main() {  
    int n, table_size;  
    scanf("%d %d", &n, &table_size);  
  
    int arr[MAX];  
    int table[MAX];  
  
    for (int i = 0; i < n; i++)  
        scanf("%d", &arr[i]);  
  
    initializeTable(table, table_size);  
    insertIntoHashTable(table, table_size, arr, n);  
    printTable(table, table_size);  
  
    return 0;  
}
```

Status : Correct

Marks : 10/10