Rajalakshmi Engineering College

Name: Gurucharan Chandramohan Email: 240801092@rajalakshmi.edu.in

Roll no: 2116240801092 Phone: 6379544451

Branch: REC

Department: I ECE FA

Batch: 2028

Degree: B.E - ECE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1 Total Mark : 10

Marks Obtained: 7.5

Section 1: Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n, representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string k, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

- 1. The first line prints "The given key is removed!" after removing it.
- 2. The next n 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

- 1. The first line prints "The given key is not found!".
- 2. The next n lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

```
Input: 3
Alice 1234567890
Bob 9876543210
Charlie 4567890123
Bob
Output: The given key is removed!
```

Key: Alice; Value: 1234567890 Key: Charlie; Value: 4567890123

Answer

```
// You are using GCC
int hash(const char *key,int capacity){
  int h=0;
  for(int i=0;key[i]!='\0';i++) h=(h*31+key[i])%capacity;
  return h;
}
```

```
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {
//Type your code here
int index=hash(key,dict->capacity):
int originalise
   int originalIndex=index;
  while(dict->pairs[index].key[0]!='\0' &&
  strcmp(dict->pairs[index].key,"__DELETED__")!=0
   &&strcmp(dict->pairs[index].key,key)!=0){
     index=(index+1)%dict->capacity;
     if(index==originalIndex) return;
   if(dict->pairs[index].key[0]=='\0'\
   ||strcmp(dict->pairs[index].key,"__DELETED__")==0){
     insertionOrder[orderSize++]=index;
     dict->size++;
  strcpy(dict->pairs[index].key,key);
   strcpy(dict->pairs[index].value,value);
}
void removeKeyValuePair(Dictionary *dict, const char *key) {
   //Type your code here
   int index=hash(key,dict->capacity);
   int originalIndex=index;
   while(dict->pairs[index].key[0]!='\0'){
     if(strcmp(dict->pairs[index].key,key)==0)
       strcpy(dict->pairs[index].key,"__DELETED__");
        dict->size--:
       return;
     index=(index+1)%dict->capacity;
     if(index==originalIndex) break;
int doesKeyExist(Dictionary *dict, const char *key) {
   //Type your code here
   int index=hash(key,dict->capacity);
   int originalIndex=index;
  while(dict->pairs[index].key[0]!='\0'){
     if(strcmp(dict->pairs[index].key,key)==0)
```

```
return 1;
}
index=(index+1)%dict->capacity;
if(index==originalIndex) break;
}
return 0;
}
void printDictionary(Dictionary *dict) {
    //Type your code here
    for(int i=0;i<orderSize;i++){
        int idx=insertionOrder[i];
        if(dict->pairs[idx].key[0]!='\0'&&
            strcmp(dict->pairs[idx].key,"__DELETED__")!=0){
            printf("Key: %s; Value: %s\n",dict->pairs[idx].key,dict->pairs[idx].value);
        }
}
}
```

Status: Partially correct Marks: 7.5/10