Exp: 11

Examine network Address Translation Using cisco packet tracker

Aim: Implement network address Translation using cisco packet tracker we'll configure static, dynamic & port addresses Translation on a router

Procedure:

Step 1: Setup network Topology launch cisco packet tracker software

Step 2: add devices

Step 3: connect devices

Step 4: Verify connections

Step 5: Assign IP addresses

Step 6: Verify IP co

code:

```
#Enable configure Terminal
interface Gigabit Ethernet 0/0 i|p
 address 192.168.1.1 255.255.255.0
```

4.1 configure Inside & outside Interfaces for NAT

```
configure terminal interface
Gigabit Ethernet 0/0 ip hat
inside exit Interface
Gigabit Ethernet 0/1 ip hat
Outside exit
```

4.2 Static NAT Configuration (Example)

inside source static 192.168.1.10 200.1.1.10

ip nat pool My.pool 200.1.1.2 0 200.1.1.25
natmask 255.255.255.0

access_list 1 permit 192.168. 1.0.0.00.255

ipnat inside source list (pool My.pool)

TO SET DEFAULT GATEWAY:

1. click on PC1 in the workspace
2. Goto the desktop tab
3. click on IP configuration
4. In the default gateway Fieldstype
   192.168.1.1
5. make sure the IP address & subnet mask are already set
6. close the window.

Result: The Router succesfully translated Private IPs to public one Using static, dynamic & PAT configurations.