

Practical-5 Replication

Aim - Implementation of Replicas in MongoDB.

Summary:

Replication is the process of synchronizing data across multiple servers.

Replication is referred to the process of ensuring that the same data is available on more than one Mongo DB Server. This is sometimes required for the purpose of increasing data availability. Replication provides redundancy and increases data availability with multiple copies of data on different database servers. Replication protects a database from the loss of a single server. Replication also allows you to recover from hardware failure and service interruptions. Because if your main MongoDB Server goes down for any reason, there will be no access to the data. But if you had the data replicated to another server at regular intervals, you will be able to access the data from another server even if the primary server fails. MongoDB achieves replication by the use of replica set. A replica set is a group of mongod instances that host the same data set. Replica set can have only one primary node. Replica set is a group of two or more nodes (generally minimum 3 nodes are required).


Example how to Set Up a Replica Set

Step 1:

Shutdown already running MongoDB server.


Step 2:

Create 3 folders with name data1,data2,data3 at any location.



Step 3: (Creating Primary instance)

First change the cmd path.



Start MongoDB server and write the following query with proper file path.

```
mongod --port "PORT" --dbpath "YOUR_DB_DATA_PATH" --replSet  
"REPLICA SET INSTANCE NAME"6
```

```
mongod --port 27018 --dbpath "C:\data1" --replSet testrep
```

```
C:\>mongo --port 27018
```

```
C:\Windows\System32\cmd.exe -port 27088
Microsoft Windows [version 6.0.6002.18005]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Wendavon>cd c:\port 27088
Hadoop shell version v4.4.2
Connecting to: msagdb://227.8.8.1:27088/?compress=zlib&path=/usr/share/hadoop-
/bin/cy session=mscslw { "id": "00000000-0000-0000-0000-000000000000" }
Hadoop server version: 4.4.2

The Server generated these startup settings when booting:
2012-05-24T22:01:49.560+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted.
2012-05-24T22:01:49.560+05:30: This server is bound to localhost. Remote systems will be unable to connect to this server. Start the server with --bind_ip address(es) to specify which IP addresses it shall
to serve responses from, or with --bind_ip all to bind to all interfaces. If this behavior is desired, start the server with --bind_ip 227.8.8.1 to disable this warning

Enable Hadoop's free cloud-based monitoring service, which will then receive and display
metrics about your deployment (disk utilization, CPU, memory statistics, etc).

The monitoring data will be available as a Hadoop website with a unique URL accessible to you
and anyone you share the URL with. Hadoop may use this information to make product
improvements and to suggest Hadoop products and deployment solutions to you.

To enable free monitoring, run the following command: $h.enableFreeMonitoring()
To permanently disable this reminder, run the following command: $h.disableFreeMonitoring()

test@ip:~$
```

Step-4

Open another cmd and in that write the following query.

First change the cmd path.

```

C:\Windows\system32\cmd /c cd C:\Program Files\Pangolin\Server& .\bin
C:\Program Files\Pangolin\Server>.6.4bin\mongo --port 27018
MongoDB shell version v4.4.2
connecting to mongo://27.0.4.1:27018/?compressor=disabled&sslServiceName=mongodb
Implicit Session: session { "id" : "600079c3b6b03044c4399-6071-67169570e602" }
MongoDB server version: 4.4.2

The server generated these startup warnings when booting:
2022-06-13T14:01:25.096049300: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted.
2022-06-13T14:01:25.096049300: This server is bound to localhost. Remote systems will be unable to connect to this server. Start the server with --bind_ip addresses to specify which IP addresses it should
accept responses from, or with --bind_ip all to bind to all interfaces. If this behavior is desired, start the server with --bind_ip 27.0.4.1 to disable this warning.

Enable Pangolin's free cloud-based monitoring service, which will then receive and display
metrics about your deployment (disk utilization, CPU, operation statistics, etc.).

The monitoring data will be available on a Pangolin website with a unique URL, accessible to you
and anyone you share the URL with. Pangolin may use this information to make product
improvements and to suggest Pangolin products and deployment options to you.

To enable free monitoring, run the following command: db.enableFreeMonitoring()
To permanently disable this reminder, run the following command: db.disableFreeMonitoring()

config { _id: "testrep", members: [1,3], _type: "localhost:27018" }
  "id" : "testrep",
  "members" : [
    {
      "id" : 1,
      "host" : "localhost:27018"
    }
  ]
}

rs.initiate(config)

{
  "ok" : 1,
  "electionTime" : {
    "electionTime" : Timestamp(1608087700, 1),
    "signature" : 1,
    "id" : ObjectId("AAAAAAAAAAAAAAAAAAAA"),
    "key" : NumberLong(0)
  },
  "operationTime" : Timestamp(1608087700, 1)
}

```

```
mongo --port 27018
```

```
Microsoft Windows [version 10.0.17045.10]
(c) Microsoft Corporation. All rights reserved.

C:\Users\20012011130> cd /Program Files/MongoDB/Server/4.4/bin

C:\Program Files\MongoDB\Server/4.4/bin> mongod --port 27018

Starting MongoDB 4.4 on localhost
connecting to: mongodb://127.0.0.1:27018/?compressor=snappy&ssl=false&serverSelectionTimeoutMS=30000
Implicit session: session {"id":"10001","info":{"start-time":"2021-07-17T05:00:04Z"}}
MongoDB server version: 4.4.3

The server generated these startup warnings when booting:
2021-07-17T05:00:04.000+05:00: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
2021-07-17T05:00:04.000+05:00: This server is bound to localhost. Remote systems will be unable to connect to this server. Start the server with --bind_ip address to specify which IP addresses it should serve responses from, or with --bind_ip_all to bind to all interfaces. If this behavior is desired, start the server with --bind_ip 127.0.0.1 to disable this warning

Enable MongoDB's free cloud-based monitoring service, which will then monitor and diagnose
errors about your deployment (disk utilization, CPU, operation statistics, etc).

The monitoring data will be available on a MongoDB website with a unique URL accessible to you
and anyone you share the URL with. MongoDB may use this information to make product
improvements and to suggest MongoDB products and deployment options to you.

To enable free monitoring, run the following command: db.setProfilingLevel(1)
To permanently disable this reminder, run the following command: db.disableMonitoring()

config: {
  "_id": "config",
  "members": [
    {
      "_id": 0,
      "host": "localhost:27018"
    }
  ]
}

rs.initiate(config)

{
  "ok": 1,
  "errmsg": "initiating",
  "code": 0,
  "codeName": null,
  "details": {
    "clusterTime": Timestamp(146000000, 1),
    "signature": {
      "key": "AAAAAAAAAAAAAAAAAAAAAAAA",
      "keyId": "AAAAAAAAAAAAAAAAAAAAAAAA"
    },
    "operationTime": Timestamp(146000000, 1)
  }
}

config: {
  "_id": "config",
  "members": [
    {
      "_id": 0,
      "host": "localhost:27018"
    }
  ]
}
```

Now our primary server is running on port 27018.

- Now repeat step on 3 for starting secondary server but this time we have to give file path of folder data2/data3 we made earlier

And in other terminal write following query mongo -port 27019.

First change the cmd path.

```
Microsoft Windows [version 10.0.17045.10]
(c) Microsoft Corporation. All rights reserved.

C:\Users\20012011130> cd /Program Files/MongoDB/Server/4.4/bin

C:\Program Files\MongoDB/Server/4.4/bin> mongod --port 27019 --dbpath "D:\Sem 4\No Sql\No-Sql Practical 5\data 2" --replSet testrep

Starting MongoDB 4.4 on localhost
connecting to: mongodb://127.0.0.1:27019/?compressor=snappy&ssl=false&serverSelectionTimeoutMS=30000
Implicit session: session {"id":"10002","info":{"start-time":"2021-07-17T05:00:05Z"}}
MongoDB server version: 4.4.3

The server generated these startup warnings when booting:
2021-07-17T05:00:05.000+05:00: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
2021-07-17T05:00:05.000+05:00: This server is bound to localhost. Remote systems will be unable to connect to this server. Start the server with --bind_ip address to specify which IP addresses it should serve responses from, or with --bind_ip_all to bind to all interfaces. If this behavior is desired, start the server with --bind_ip 127.0.0.1 to disable this warning

Enable MongoDB's free cloud-based monitoring service, which will then monitor and diagnose
errors about your deployment (disk utilization, CPU, operation statistics, etc).

The monitoring data will be available on a MongoDB website with a unique URL accessible to you
and anyone you share the URL with. MongoDB may use this information to make product
improvements and to suggest MongoDB products and deployment options to you.

To enable free monitoring, run the following command: db.setProfilingLevel(1)
To permanently disable this reminder, run the following command: db.disableMonitoring()

config: {
  "_id": "config",
  "members": [
    {
      "_id": 0,
      "host": "localhost:27018"
    },
    {
      "_id": 1,
      "host": "localhost:27019"
    }
  ]
}

rs.initiate(config)

{
  "ok": 1,
  "errmsg": "initiating",
  "code": 0,
  "codeName": null,
  "details": {
    "clusterTime": Timestamp(146000000, 1),
    "signature": {
      "key": "AAAAAAAAAAAAAAAAAAAAAAAA",
      "keyId": "AAAAAAAAAAAAAAAAAAAAAAAA"
    },
    "operationTime": Timestamp(146000000, 1)
  }
}

config: {
  "_id": "config",
  "members": [
    {
      "_id": 0,
      "host": "localhost:27018"
    },
    {
      "_id": 1,
      "host": "localhost:27019"
    }
  ]
}
```

mongod --port 27019 --dbpath "D:\Sem 4\No Sql\No-Sql Practical 5\data 2" --replSet testrep

[illegible]

Now Open another command prompt for client. We will use this window to query our second server instance

First change the cmd path.

```
Administrator: Windows [Version 10.0.19044.1415]
C:\> Microsoft Corporation. All rights reserved.

C:\Users\joshua> cd C:\Program Files\MongoDB\Server\4.4\bin
C:\Program Files\MongoDB\Server\4.4\bin> mongod --port 27018
MongoDB shell version v4.4.2
connecting to: mongodb://127.0.0.1:27018/?compressors=disabled&gssapiServiceName=mongodb
Implicit session: session ("id" : 00000000-0000-0000-b605-b6054370117)
MongoDB server version: 4.4.2

The server generated these startup warnings when booting:
2022-04-11T14:56:54.106+09:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
2022-04-11T14:56:54.106+09:30: Remote system will be unable to connect to this server. Start the server with --bind_ip address to specify which IP addresses it should
accept requests from, or with --bind_ip_all to bind to all interfaces. If this behavior is desired, start the server with --bind_ip 127.0.0.1 to disable this warning

...

Enable MongoDB's free cloud-based monitoring service, which will then receive and display
metrics about your deployment (disk utilization, CPU, operation statistics, etc).

The monitoring data will be available on a MongoDB website with a unique URL, accessible to you
and anyone you share the URL with. MongoDB may use this information to make product
improvements and to suggest MongoDB products and deployment options to you.


To enable free monitoring, run the following command: sh.enableFreeMonitoring()
To permanently disable this reminder, run the following command: sh.disableFreeMonitoring()

...

> show sh
Caught exception: Error: MongoClient failed: {
  "name": "MongoServerError",
  "message": "MongoServerError: {
    \"operationTime\" : Timestamp(1489678011, 1),
    \"ok\" : 0,
    \"errmsg\" : \"not master and slaveNotPrimary\",
    \"code\" : 1043,
    \"codeName\" : \"NotPrimaryNoSecondary\",
    \"clusterTime\" : {
      \"clusterTime\" : Timestamp(1489678011, 1),
      \"signature\" : {
        \"hash\" : 810data[0,\"aaaaaaaaaaaaaaaaaaaaaaaa\"],
        \"keyId\" : NumberLong(0)
      }
    }
  }\",
  \"stack\": \"MongoServerError: {
    \"operationTime\" : Timestamp(1489678011, 1),
    \"ok\" : 0,
    \"errmsg\" : \"not master and slaveNotPrimary\",
    \"code\" : 1043,
    \"codeName\" : \"NotPrimaryNoSecondary\",
    \"clusterTime\" : {
      \"clusterTime\" : Timestamp(1489678011, 1),
      \"signature\" : {
        \"hash\" : 810data[0,\"aaaaaaaaaaaaaaaaaaaaaaaa\"],
        \"keyId\" : NumberLong(0)
      }
    }
  }\",
  \"name\": \"MongoServerError\",
  \"code\": 1043,
  \"codeName\": \"NotPrimaryNoSecondary\",
  \"operationTime\": \"Timestamp(1489678011, 1)\"
}
```


```
mongo --port 27019
```



Now Open another command prompt for client. We will use this window to query our second server instance

First change the cmd path.



```

Microsoft Windows [Version 10.0.19044.1215]
(c) Microsoft Corporation. All rights reserved.

C:\Windows\system32\cmd.exe /c mongo --port 27018

MongoDB shell version 4.4.2
connecting to: mongodb://127.0.0.1:27018/?compressor=disabled&gssapiServiceName=mongodb
Implicit session: session { "id" : 14027, "remoteAddr" : "127.0.0.1", "localAddr" : "127.0.0.1" }
MongoDB server version: 4.4.2

The server generated these startup warnings when booting:
2022-04-23T15:01:31.546+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
2022-04-23T15:01:31.547+05:30: This server is bound to localhost. Remote systems will be unable to connect to this server. Start the server with --bind_ip address to specify which IP addresses it should serve requests from, or with --bind_ip_all to bind to all interfaces. If this behavior is desired, start the server with --bind_ip 127.0.0.1 to disable this warning

...

Enable MongoDB's free cloud-based monitoring service, which will then receive and display
metrics about your deployment (disk utilization, CPU, operation statistics, etc).

The monitoring data will be available on a MongoDB website with a unique URL accessible to you
and anyone you share the URL with. MongoDB may use this information to make product
improvements and to suggest MongoDB products and deployment options to you.

To enable free monitoring, run the following command: db.enableFreeMonitoring()
To permanently disable this reminder, run the following command: db.disableFreeMonitoring()

...

> show dbs
admin 0.000MB
config 0.000MB
local 0.000MB
test 0.000MB
totalSize 167584KB

```

Now we have in total 6 CMDs among them 2 for primary and other pairs for secondary.

Step 5:

Now go to the command prompt of Primary server's Client instance. Now type the following code

```
config = { _id : "testrep" , members : [ { _id : 0, host : "localhost:27018" } ] }
```

Above code set id=0 to the first replica instance which is on port 27018.(PRIMARY INSTANCE)

```

Enable MongoDB's free cloud-based monitoring service, which will then receive and display
metrics about your deployment (disk utilization, CPU, operation statistics, etc).

The monitoring data will be available on a MongoDB website with a unique URL accessible to you
and anyone you share the URL with. MongoDB may use this information to make product
improvements and to suggest MongoDB products and deployment options to you.

To enable free monitoring, run the following command: db.enableFreeMonitoring()
To permanently disable this reminder, run the following command: db.disableFreeMonitoring()

> config = { _id : "testrep" , members : [ { _id : 0, host : "localhost:27018" } ] }
> rs.initiate(config)
{ "ok" : 1,
  "members" : [
    { "name" : "testrep",
      "host" : "localhost:27018",
      "state" : 1,
      "syncSourceId" : 0,
      "electionTime" : Timestamp(1650667786, 1),
      "signature" : [
        "test" : ObjectId("AAAAAAAAAAAAAAAAAAAAAAAA"),
        "key1" : ObjectId("00000000000000000000000000000000")
      ]
    }
  ],
  "operationTime" : Timestamp(1650667786, 1) }

> rs.status()
{ "set" : "testrep",
  "date" : ISODate("2022-04-23T15:01:30.428Z"),
  "members" : [
    { "name" : "testrep",
      "state" : 1,
      "syncSourceId" : 0,
      "electionTime" : Timestamp(1650667786, 1),
      "signature" : [
        "test" : ObjectId("AAAAAAAAAAAAAAAAAAAAAAAA"),
        "key1" : ObjectId("00000000000000000000000000000000")
      ]
    }
  ],
  "operationTime" : Timestamp(1650667786, 1) }

```

After this write command `rs.initiate(config)`

This is confirmed by the output, which should resemble the following:

```

config = { "id" : "testapp", members : [{ id : 0, host : "localhost:27000" }]
          "id" : "testapp",
          "members" : {
            {
              "id" : 0,
              "host" : "localhost:27000"
            }
          }
}

rs.initialize(config)

{ "id" : 0,
  "clusterTime" : Timestamp(160666700, 0),
  "signature" : {
    "key" : BinData(0,"AAAAAAAAAAAAAAAAAAAAAAAA"),
    "keyId" : NumberLong(0)
  },
  "expirationTime" : Timestamp(160666700, 0)
}

testapp.close()

testapp.shutdown(rs.state())

{ "set" : "testapp",
  "date" : ISODate("2020-06-11T00:00:00Z"),
  "write" : 1,
  "term" : NumberLong(1),
  "syncSourceSet" : "",
  "syncSourceId" : 0,
  "writePriorityWallTime" : NumberLong(2000),
  "writePriorityCount" : 1,
  "writePriorityCount" : 1,
  "writePriorityCount" : 1,
  "writePriorityCount" : 1,
  "writePriorityCount" : 1,
  "term" : {
    "lastWriteWallTime" : {
      "ts" : Timestamp(160666700, 0),
      "s" : NumberLong(0)
    },
    "lastWriteWallTime" : ISODate("2020-06-11T00:00:00Z"),
    "readConcernMajorityTime" : {
      "ts" : Timestamp(160666700, 0),
      "s" : NumberLong(0)
    },
    "readConcernMajorityTime" : ISODate("2020-06-11T00:00:00Z"),
    "writeTime" : {
      "ts" : Timestamp(160666700, 0),

```

```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040

```

[illegible]

Step 6:

In primary server's cmd we have to execute `rs.add()` query.

[illegible]

```

shell(1,1)
strncpy(PK20000, "1.0001localhost(1700)",
"sk" : 1,
"clusterfile" : "spectrap(14001010, 1),
"signature" : {
"task" : $Data(0, "AAAAAAAAAAAAAAAAAAAA"),
"keyid" : $Header(0)
}
},
"signaturefile" : "spectrap(14001010, 1)
strncpy(PK20000, "1.0001localhost(1700)",
"sk" : 1,
"clusterfile" : "spectrap(14001010, 1),
"signature" : {
"task" : $Data(0, "AAAAAAAAAAAAAAAAAAAA"),
"keyid" : $Header(0)
}
},
"signaturefile" : "spectrap(14001010, 1)
strncpy(PK20000, "1.0001localhost(1700)",
"task" : "spectrap",
"date" : ($Data("2002-04-11T01:40:12-0600"),
"style" : 1,
"year" : $Header(1),
"epochseconds" : "",
"epochseconds" : 1,
"epochsecondsInterval" : $Header(1000),
"majorityofNodes" : 1,
"setofmajorityNodes" : 1,
"setofmajorityNodes" : 1,
"setofmajorityNodes" : 1,
"setofmajorityNodes" : 1,
"options" : {
"setofmajorityNodes" : {
"to" : "spectrap(14001010, 1),
"to" : $Header(1)
}
},
"setofmajorityNodes" : ($Data("2002-04-11T01:40:12-0600"),
"setofmajorityNodes" : {
"to" : "spectrap(14001010, 1),
"to" : $Header(1)
}
},
"setofmajorityNodes" : ($Data("2002-04-11T01:40:12-0600"),
"setofmajorityNodes" : ($Data("2002-04-11T01:40:12-0600"),

```

Now to check whether everything is working fine or not we'll create one collection and check for it in secondary servers.

Step 7:

Create a database named demo1 and collection inside named demo1. On CMD client window of Primary client (port 27018).

```
"operationName": "SignIn",  
    "lastHeartbeat": 290Date("2022-06-17T09:48:10"),  
    "lastHeartbeats": [290Date("2022-06-17T09:48:12.13Z")],  
    "pubid": Random(10),  
    "lastHeartbeatMessage": "",  
    "specSourceHost": "localhost:37010",  
    "specSourceId": 1,  
    "infoMessage": "",  
    "configVersion": 1,  
    "configType": 1  
},  
  
{  
    "is": 1,  
    "clusterTime": {  
        "clusterTime": Timestamp(144907370, 1),  
        "signature": {}  
    },  
    "hash": $ifData($,"AAAAAAAAAAAAAAAAAAAAAA"),  
    "keyid": RandomLong(1)  
}  
  
},  
    "operationTime": Timestamp(144907370, 1)  
},  
    "logop.FB2WACv": one done!  
    attached to db done!  
    "secretKeyHash":"0x1f4d6c01e457da6..."  
},  
  
{  
    "is": 1,  
    "clusterTime": {  
        "clusterTime": Timestamp(144907395, 1),  
        "signature": {}  
    },  
    "hash": $ifData($,"AAAAAAAAAAAAAAAAAAAAAA"),  
    "keyid": RandomLong(1)  
}  
  
},  
    "operationTime": Timestamp(144907395, 1)  
},  
    "logop.FB2WACv":
```

Step 8:

Now goto client window of port 27019(To check whether we can see the database replica over there or not).

First try to execute show dbs directly, it will show error or operation failed!

[illegible]

Then to get perfect output we need to execute `rs.secondaryOk()` method.

[illegible]

We can also use `rs.status()` to check status of our servers whether its primary or secondary.


```

Administrator: C:\Windows\System32\cmd.exe - mongo --port 27018
)
testrep:PRIMARY> rs.status();
{
  "set" : "testrep",
  "date" : ISODate("2022-04-11T09:43:02.485Z"),
  "myState" : 1,
  "term" : NumberLong(1),
  "syncSourceHost" : "",
  "syncSourceId" : -1,
  "heartbeatIntervalMillis" : NumberLong(2000),
  "majorityVoteCount" : 2,
  "writeMajorityCount" : 2,
  "votingMembersCount" : 3,
  "writableVotingMembersCount" : 3,
  "optimes" : {
    "lastCommittedOpTime" : {
      "ts" : Timestamp(1649670171, 1),
      "t" : NumberLong(1)
    },
    "lastCommittedWallTime" : ISODate("2022-04-11T09:42:51.248Z"),
    "readConcernMajorityOpTime" : {
      "ts" : Timestamp(1649670171, 1),
      "t" : NumberLong(1)
    },
    "readConcernMajorityWallTime" : ISODate("2022-04-11T09:42:51.248Z"),
    "appliedOpTime" : {
      "ts" : Timestamp(1649670171, 1),
      "t" : NumberLong(1)
    },
    "durableOpTime" : {
      "ts" : Timestamp(1649670171, 1),
      "t" : NumberLong(1)
    },
    "lastAppliedWallTime" : ISODate("2022-04-11T09:42:51.248Z"),
    "lastDurableWallTime" : ISODate("2022-04-11T09:42:51.248Z")
  },
  "lastStableRecoveryTimestamp" : Timestamp(1649670159, 1),
  "electionCandidateMetrics" : {
    "lastElectionReason" : "electionTimeout",
    "lastElectionDate" : ISODate("2022-04-11T09:31:39.720Z"),
    "electionTerm" : NumberLong(1),
    "lastCommittedOpTimeAtElection" : {
      "ts" : Timestamp(0, 0),
      "t" : NumberLong(-1)
    },
    "lastSeenOpTimeAtElection" : {
      "ts" : Timestamp(1649669499, 1),
      "t" : NumberLong(-1)
    },
    "numVotesNeeded" : 1,

```

```

Administrator: C:\Windows\System32\cmd.exe - mongo --port 27018

{
  "_id" : 0,
  "name" : "localhost:27018",
  "health" : 1,
  "state" : 1,
  "stateStr" : "PRIMARY",
  "uptime" : 2196,
  "optime" : {
    "ts" : Timestamp(1649670171, 1),
    "t" : NumberLong(1)
  },
  "optimeDate" : ISODate("2022-04-11T09:42:51Z"),
  "syncSourceHost" : "",
  "syncSourceId" : -1,
  "infoMessage" : "",
  "electionTime" : Timestamp(1649669499, 2),
  "electionDate" : ISODate("2022-04-11T09:31:39Z"),
  "configVersion" : 3,
  "configTerm" : 1,
  "self" : true,
  "lastHeartbeatMessage" : ""
},
{
  "_id" : 1,
  "name" : "localhost:27019",
  "health" : 1,
  "state" : 2,
  "stateStr" : "SECONDARY",
  "uptime" : 44,
  "optime" : {
    "ts" : Timestamp(1649670171, 1),
    "t" : NumberLong(1)
  },
  "optimeDurable" : {
    "ts" : Timestamp(1649670171, 1),
    "t" : NumberLong(1)
  },
  "optimeDate" : ISODate("2022-04-11T09:42:51Z"),
  "optimeDurableDate" : ISODate("2022-04-11T09:42:51Z"),
  "lastHeartbeat" : ISODate("2022-04-11T09:43:00.638Z"),
  "lastHeartbeatRecv" : ISODate("2022-04-11T09:43:00.663Z"),
  "pingMs" : NumberLong(0),
  "lastHeartbeatMessage" : "",
  "syncSourceHost" : "localhost:27018",
  "syncSourceId" : 0,
  "infoMessage" : "",
  "configVersion" : 3,
  "configTerm" : 1
},
{

```

```

Select Administrator: C:\Windows\System32\cmd.exe - mongo --port 27018

    "configTerm" : 1
  },
  {
    "_id" : 2,
    "name" : "localhost:27020",
    "health" : 1,
    "state" : 2,
    "stateStr" : "SECONDARY",
    "uptime" : 17,
    "optime" : {
      "ts" : Timestamp(1649670171, 1),
      "t" : NumberLong(1)
    },
    "optimeDurable" : {
      "ts" : Timestamp(1649670171, 1),
      "t" : NumberLong(1)
    },
    "optimeDate" : ISODate("2022-04-11T09:42:51Z"),
    "optimeDurableDate" : ISODate("2022-04-11T09:42:51Z"),
    "lastHeartbeat" : ISODate("2022-04-11T09:43:00.639Z"),
    "lastHeartbeatRecv" : ISODate("2022-04-11T09:43:01.939Z"),
    "pingMs" : NumberLong(0),
    "lastHeartbeatMessage" : "",
    "syncSourceHost" : "localhost:27019",
    "syncSourceId" : 1,
    "infoMessage" : "",
    "configVersion" : 3,
    "configTerm" : 1
  }
],
"ok" : 1,
"$clusterTime" : {
  "clusterTime" : Timestamp(1649670171, 1),
  "signature" : {
    "hash" : BinData(0,"AAAAAAAAAAAAAAAAAAAAAAAAAAAA="),
    "keyId" : NumberLong(0)
  }
},
"operationTime" : Timestamp(1649670171, 1)
}

```