

CSE 486/586 Distributed Systems Reliable Multicast --- 1

Steve Ko
Computer Sciences and Engineering
University at Buffalo

CSE 486/586, Spring 2013

Last Time

- Global states
 - A union of all process states
 - Consistent global state vs. inconsistent global state
- The "snapshot" algorithm
 - Take a snapshot of the local state
 - Broadcast a "marker" msg to tell other processes to record
 - Start recording all msgs coming in for each channel until receiving a "marker"
 - Outcome: a consistent global state

CSE 486/586, Spring 2013

2

Today's Question

- How do a group of processes communicate?
- Unicast (best effort or reliable)
 - One-to-one: Message from process p to process q .
 - Best effort: message *may* be delivered, but will be intact
 - Reliable: message *will* be delivered
- Broadcast
 - One-to-all: Message from process p to *all* processes
 - Impractical for large networks
- Multicast
 - One-to-many: "Local" broadcast within a group g of processes
- What are the issues?
 - Processes crash (we assume crash-stop)
 - Messages get delayed

CSE 486/586, Spring 2013

3

Examples



CSE 486/586, Spring 2013

4


Examples

- Akamai's Configuration Management System (called ACMS)
 - A core group of 3-5 servers.
 - Continuously multicast to each other the latest updates.
 - After an update is reliably multicast within this group, it is then sent out to all the (1000s of) servers Akamai has all over the world.
- Air Traffic Control System
 - Commands by one ATC need to be ordered (and reliable) multicast out to other ATC's.
- Newsgroup servers
 - Multicast to each other in a reliable and ordered manner.

CSE 486/586, Spring 2013

5

The Interface



CSE 486/586, Spring 2013

6

Properties to Consider

- **Liveness**: guarantee that something good will happen eventually
 - For the initial state, there is a reachable state where the predicate becomes true.
 - “Guarantee of termination” is a liveness property
- **Safety**: guarantee that something bad will never happen
 - For any state reachable from the initial state, the predicate is false.
 - Deadlock avoidance algorithms provide safety
- Liveness and safety are used in many other CS contexts.

CSE 486/586, Spring 2013

7

Basic Multicast (B-multicast)

- A straightforward way to implement B-multicast is to use a reliable one-to-one send (unicast) operation:
 - B-multicast(g, m): for each process p in g , send(p, m).
 - receive(m): B-deliver(m) at p .
- Guarantees?
 - All processes in g eventually receive every multicast message...
 - ... as long as the sender doesn't crash

CSE 486/586, Spring 2013

8

Reliable Multicast Goals

- **Integrity**: A correct (i.e., non-faulty) process p delivers a message m at most once.
 - “Non-faulty”: doesn't deviate from the protocol & alive
- **Agreement**: If a correct process delivers message m , then all the other correct processes in group(m) will eventually deliver m .
 - Property of “all or nothing.”
- **Validity**: If a correct process multicasts (sends) message m , then it will eventually deliver m itself.
 - Guarantees liveness to the sender.
- Validity and agreement together ensure overall liveness: if some correct process multicasts a message m , then, all correct processes deliver m too.

CSE 486/586, Spring 2013

9

Reliable Multicast Overview

- Keep a history of messages for at-most-once delivery
- Everyone repeats multicast upon a receipt of a message for agreement & validity.

CSE 486/586, Spring 2013

10

Reliable R-Multicast Algorithm

On initialization

Received := {};

For process p to R-multicast message m to group g

B-multicast(g, m);

($p \in g$ is included as destination)

On B-deliver(m) at process q with $g = \text{group}(m)$


if ($m \notin \text{Received}$):

Received := Received \cup { m };

if ($q \neq p$):

B-multicast(g, m);

R-deliver(m)



CSE 486/586, Spring 2013

11

Reliable R-Multicast Algorithm

On initialization

Received := {};

For process p to R-multicast message m to group g

B-multicast(g, m);

($p \in g$ is included as destination)

On B-deliver(m) at process q with $g = \text{group}(m)$

if ($m \notin \text{Received}$): Integrity

Received := Received \cup { m };

if ($q \neq p$):

B-multicast(g, m); Agreement

R-deliver(m) Validity

CSE 486/586, Spring 2013

12


CSE 486/586 Administrivia

- Come talk to me!
- PA2 is out.
- Amazon EC2 is ready.

CSE 486/586, Spring 2013

13

Ordered Multicast Problem



CSE 486/586, Spring 2013

14

FIFO Ordering

- Preserving the process order
- The message delivery order at each process should preserve the message sending order from every process.
- For example,
 - P1: m0, m1, m2
 - P2: m3, m4, m5
 - P3: m6, m7, m8
- FIFO? (m0, m3, m6, m1, m4, m7, m2, m5, m8)
 - Yes!
- FIFO? (m0, m4, m6, m1, m3, m7, m2, m5, m8)
 - No!

CSE 486/586, Spring 2013

15

Causal Ordering

- Preserving the happened-before relations
- The message delivery order at each process should preserve the happened-before relations across all processes.
- For example,
 - P1: m0, m1, m2
 - P2: m3, m4, m5
 - P3: m6, m7, m8
 - Cross-process happened-before: m0 → m4, m5 → m8
- Causal? (m0, m3, m6, m1, m4, m7, m2, m5, m8)
 - Yes!
- Causal? (m0, m4, m1, m7, m3, m6, m2, m5, m8)
 - No!

CSE 486/586, Spring 2013

16

Total Ordering

- Every process delivers all messages in the same order.
- For example,
 - P1: m0, m1, m2
 - P2: m3, m4, m5
 - P3: m6, m7, m8
- Total?
 - P1: m7, m1, m2, m4, m5, m3, m6, m0, m8
 - P2: m7, m1, m2, m4, m5, m3, m6, m0, m8
 - P3: m7, m1, m2, m4, m5, m3, m6, m0, m8
- Total?
 - P1: m7, m1, m2, m4, m5, m3, m6, m0, m8
 - P2: m7, m2, m1, m4, m5, m3, m6, m0, m8
 - P3: m7, m1, m2, m4, m5, m3, m6, m8, m0

CSE 486/586, Spring 2013

17

Ordered Multicast


- **FIFO ordering:** If a correct process issues $\text{multicast}(g, m)$ and then $\text{multicast}(g, m')$, then every correct process that delivers m' will have already delivered m .
- **Causal ordering:** If $\text{multicast}(g, m) \rightarrow \text{multicast}(g, m')$ then any correct process that delivers m' will have already delivered m .
 - Typically, \rightarrow defined in terms of multicast communication only
- **Total ordering:** If a correct process delivers message m before m' (independent of the senders), then any other correct process that delivers m' will have already delivered m .

CSE 486/586, Spring 2013

18

Total, FIFO and Causal Ordering

- Totally ordered messages T_1 and T_2 .
- FIFO-related messages F_1 and F_2 .
- Causally related messages C_1 and C_2 .
- Total ordering does not imply causal ordering.
- Causal ordering implies FIFO ordering.
- Causal ordering does not imply total ordering.
- Hybrid mode: causal-total ordering, FIFO-total ordering.



CSE 486/586, Spring 2013

19

Display From Bulletin Board Program

Bulletin board: <i>os.interesting</i>		
Item	From	Subject
23	A.Hanlon	Mach
24	G.Joseph	Microkernels
25	A.Hanlon	Re: Microkernels
26	T.L.Heureux	RPC performance
27	M.Walker	Re: Mach
end		



What is the most appropriate ordering for this application?
(a) FIFO (b) causal (c) total

CSE 486/586, Spring 2013

20

Providing Ordering Guarantees (FIFO)

- Look at messages from each process in the order they were sent:
 - Each process keeps a sequence number for each of the other processes.
 - When a message is received, if message # is:
 - » as expected (next sequence), accept
 - » higher than expected, buffer in a queue
 - » lower than expected, reject

CSE 486/586, Spring 2013

21


Implementing FIFO Ordering

- S_g^p : the number of messages p has sent to g .
- R_g^q : the sequence number of the latest group- g message p has delivered from q .
- For p to FO-multicast m to g :
 - p increments S_g^p by 1.
 - p "piggy-backs" the value S_g^p onto the message.
 - p B-multicasts m to g .
- At process p , Upon receipt of m from q with sequence number S :
 - p checks whether $S = R_g^q + 1$. If so, p FO-delivers m and increments R_g^q .
 - If $S > R_g^q + 1$, p places the message in the hold-back queue until the intervening messages have been delivered and $S = R_g^q + 1$.

CSE 486/586, Spring 2013

22


Hold-back Queue for Arrived Multicast Messages



CSE 486/586, Spring 2013

23

Example: FIFO Multicast



CSE 486/586, Spring 2013

24

Summary

- **Reliable Multicast**
 - Reliability
 - Ordering
 - R-multicast
- **Ordered Multicast**
 - FIFO ordering
 - Total ordering
 - Causal ordering
- Next: continue on multicast

Acknowledgements

- These slides contain material developed and copyrighted by Indranil Gupta (UIUC).