

INT201 Decision, Computation and Language

Lecture 5 – Regular Languages (2)

Dr Yushi Li



Xi'an Jiaotong-Liverpool University

西交利物浦大学

Kleene's Theorem 克莱因定理

设 L 为一种语言。那么 L 是正则语言当且仅当存在描述 L 的正则表达式时， L 是正则的。

Let L be a language. Then L is **regular** if and only if there exists a regular expression that describes L .

- ① • If a language is described by a regular expression, then it is regular.
如果一种语言是用正则表达式描述的，那么它就是正则语言。
- ② • If a language is regular, then it has a regular expression.
如果一种语言是正则表达式，那么它就有正则表达式。



如果一种语言是用正则表达式描述的，那么它就是正则语言。

① The language described by a regular expression is a regular language

让正则表达式R转换为 NFA M

Proof Convert a regular expression R into a NFA M

1st case. If $R = \epsilon$, then $L(R) = \{\epsilon\}$. The NFA is $M = (\{q\}, \Sigma, \delta, q, \{q\})$ where:

$$\delta(q, a) = \emptyset \text{ for all } a \in \Sigma_\epsilon$$

2nd case. If $R = \emptyset$, then $L(R) = \emptyset$. The NFA is $M = (\{q\}, \Sigma, \delta, q, \emptyset)$ where:

$$\delta(q, a) = \emptyset \text{ for all } a \in \Sigma_\epsilon$$



The language described by a regular expression is a regular language

Proof

3rd case. If $R = a$ for $a \in \Sigma$, then $L(R) = \{a\}$. The NFA is $M = (\{q_1, q_2\}, \Sigma, \delta, q_1, \{q_2\})$

where:

$$\delta(q_1, a) = \{q_2\}$$

$$\delta(q_1, b) = \emptyset \text{ for all } b \in \Sigma_\epsilon \setminus \{a\} \quad \Sigma_\epsilon \text{ 不包括 } \{a\}$$

$$\delta(q_2, b) = \emptyset \text{ for all } b \in \Sigma_\epsilon$$




The language described by a regular expression is a regular language

Proof

4th case (union). If $R = (R_1 \cup R_2)$ and 当 regular expression 为 $R_1 \cup R_2$ 时, 用以下的图格式转换为 LLK)

- $L(R_1)$ has NFA M_1
- $L(R_2)$ has NFA M_2

Then $L(R) = L(R_1) \cup L(R_2)$ has NFA as:




The language described by a regular expression is a regular language

Proof

5th case (concatenation). If $R = R_1 R_2$ and 当 regular expression 为 $R = R_1 R_2$ 时,


- $L(R_1)$ has NFA M_1
- $L(R_2)$ has NFA M_2

Then $L(R) = L(R_1) L(R_2)$ has NFA as:



The language described by a regular expression is a regular language

Example



正则语言有正则表达式

A regular language has a regular expression $R \rightarrow RE$

Convert DFA into regular expression 将DFA转换成 regular Expression

Every DFA M can be converted to a regular expression that describes the language $L(M)$.

Generalized NFA (GNFA)

A GNFA can be defined as a 5-tuple, $(Q, \Sigma, \delta, \{s\}, \{t\})$, consisting of

- a finite set of states Q ; 有限的状态集合
- a finite set called the alphabet Σ ; 有限的可输入字符集
- a transition function $(\delta : (Q \setminus \{t\}) \times (Q \setminus \{s\}) \rightarrow R)$; 转换关系
- a start state ($s \in Q$); 起始态
- an accept state ($t \in Q$); 接受态

where R is the collection of all regular expressions over the alphabet Σ .



R 是所有基于字母集 Σ 的 regular expression 的集合




A regular language has a regular expression

Example

Convert the given DFA into regular expression



remove q_1 , only remain S and t




final . $(bva a^* b)(a/b)^*$ 2nd step: eliminate states



A regular language has a regular expression

Exercise


$M = (Q, \Sigma, \delta, q_0, F)$, where $Q = \{q_0, q_1, q_2\}$, $\Sigma = \{a, b\}$, $F = \{q_2\}$, and δ is given as:



Convert it to a regular expression.






Exercise



Convert it GNFA.



Exercise



Exercise

$$(a \cup (b \cup b(ab^*a))^*b$$



Pumping Lemma for Regular Languages

包含数学证明.

pumping lemma 只能验证
是不是 non-regular

可用于证明某些语言不规则的工具。该定理说明，所有正则表达式语言都有一个特殊属性。

A tool that can be used to prove that certain languages are not regular. This theorem states that all regular languages have a special property.

This property states that all strings in the language can be “pumped” if they are at least as long as a certain special value, called the **pumping length**.


- If a language L is regular, it always satisfies pumping lemma. If there exists at least one string made from pumping which is not in L , then L is surely not regular.
- The opposite may not be true. If pumping lemma holds, it does not mean that the language is regular.



Pumping Lemma for Regular Languages

Example

DFA with $\Sigma = \{0, 1\}$ for language A.




$$Q = \{q_1, q_2, q_3, q_4, q_5\}$$



Pumping Lemma for Regular Languages

For any string s with $|s| \geq 5$, guaranteed to visit some state twice by the **pigeonhole principle**. 鸽巢原理

String $s = 0011011$ is accepted by DFA, i.e., $s \in A$



q_2 is first state visited twice.

Using q_2 , divide string s into 3 parts x, y, z such that $s = xyz$.

- $x = 0$, the symbols read until first visit to q_2 .
- $y = 0110$, the symbols read from first to second visit to q_2 .
- $z = 11$, the symbols read after second visit to q_2 .



Pumping Lemma for Regular Languages

DFA accepts string

$$S = \underbrace{0}_x \underbrace{0110}_y \underbrace{11}_z$$

DFA also accepts string


$$xyyz = \underbrace{0}_x \underbrace{0110}_y \underbrace{0110}_y \underbrace{11}_z$$

$$xy^i z, i \geq 0 \quad (\text{可以接受多个或1个} y \text{ 部分})$$

String $xy^i z \in A$ for each $i \geq 0$.




Pumping Lemma for Regular Languages



- More generally, consider
 - ✓ language A with DFA M having p states (where p is number of states in DFA).
 - ✓ string $s \in A$ with $|s| \geq p$.
- When processing s on M , guaranteed to visit some state twice.
- Let r be first state visited twice.
- Using state r , can divide s as $s = xyz$.
 - ✓ x are symbols read until first visit to r .
 - ✓ y are symbols read from first to second visit to r .
 - ✓ z are symbols read from second visit to r to end of s .



Pumping Lemma for Regular Languages



- Because y corresponds to starting in r and returning to r ,

$$\underline{xy^iz \in A \text{ for each } i \geq 1.}$$


- Also, note $xy^0z = xz \in A$, so

$$\underline{xy^iz \in A \text{ for each } i \geq 0.}$$

- $|y| > 0$ because
 - ✓ y corresponds to starting in r and coming back;
 - ✓ this consumes at least one symbol (because DFA), so y can't be empty



Pumping Lemma for Regular Languages




- $|xy| \leq p$, where p is number of states in DFA, because
 - ✓ xy are symbols read up to second visit to r .
 - ✓ Because r is the first state visited twice, all states visited before second visit to r are unique.
 - ✓ So just before visiting r for second time, DFA visited at most p states, which corresponds to reading at most $p - 1$ symbols.
 - ✓ The second visit to r , which is after reading 1 more symbol, corresponds to reading at most p symbols.



Pumping Lemma for Regular Languages

Let A be a regular language. Then there exists an integer $p \geq 1$, called the pumping length, such that the following holds: Every string s in A , with $|s| \geq p$, can be written as $s = xyz$, such that

1. $y \neq \epsilon$ (i.e., $|y| \geq 1$),
2. $|xy| \leq p$, and
3. for all $i \geq 0$, $xy^iz \in A$.



Example

Language $A = \{ 0^n 1^n \mid n \geq 0 \}$ is Nonregular

Proof

- ① Define pumping length $-p$
- ② Consider string $s = 0^p 1^p \in A$
- ③ $|s| = 2p \geq p$, pumping lemma will hold
- ④ So split s into $s = xyz$, satisfying
 1. $|y| > 0$
 2. $|xy| \leq p$
 3. $xy^iz \in A$ for each $i \geq 0$
- ⑤ Became 1st p symbol of



Example

Language $A = \{0^n 1^n \mid n \geq 0\}$ is Nonregular

Proof $| \cdot s = \underbrace{00 \dots 0}_p \underbrace{11 \dots 1}_p$ are all $0s$

$\Rightarrow x$ and y consist of only $0s$.

$\Rightarrow z$ will hold all the rest $0s$ and all $1s$.

key: y has some $0s$ and z contains all $1s \Rightarrow$ pumping y only changes the number of $0s$, but not the numbers of $1s$.

⑥: so we have

$$x = 0^j \text{ for some } j \geq 0$$


$$y = 0^k \text{ for some } k \geq 0$$

$$z = 0^m 1^p \text{ for some } m \geq 0$$

⑦ $S = xyz \Rightarrow$


$$0^p 1^p = 0^j 0^k 0^m 1^p = 0^{j+k+m} 1^p \Rightarrow j+k+m = p$$

⑧ $|y| > 0 \Rightarrow k > 0$

⑨ $xyz \in A$ but $xyyz = 0^j 0^k 0^k 0^m 1^p = 0^{j+k+k+m} 1^p = 0^{p+k} 1^p \neq 0^p 1^p$ 

$\Rightarrow xyz \notin A$

\Rightarrow contradiction $\Rightarrow A$ is non-regular



THANK YOU



XJTLU | SCHOOL OF
FILM AND
TV ARTS