

INT 303 BIG DATA ANALYTICS

#Lecture12: Summary & Review Part 2

Jia Wang

Jia.wang02@xjtlu.edu.cn



Xi'an Jiaotong-Liverpool University

西交利物浦大學



FINAL EXAMINATION

Reading Time: *5 mins*

Writing Time: *120 mins*

INSTRUCTIONS TO CANDIDATES

1. This is a closed-book examination. NO notes or books are permitted.
2. Total marks available are 100. The number on the right indicates the mark for each question.
3. Attempt ALL questions. Write all the answers in the answer booklet provided.
4. Only solutions written in English will be accepted.
5. Correct answers do not guarantee a full score: mark penalties may be imposed for missing intermediate solution steps or illogical solution processes.




Questions:

5. Principal Components
Analysis





The Intuition Behind PCA

- Top PCA components capture the most of amount of variation (interesting features) of the data.
- Each component is a linear combination of the original predictors - we visualize them as vectors in the feature space.



EXERCISES

Solution:



Questions:

6. Large-scale Machine

Learning Linear Regression

Logistic Regression

Decision Tree

Nearest Neighbor Classifier

Support Vector Machines

Convolutional Neural

Network K-means

...

You should identify one model or technique that best addresses the practical problem and provide a justification for why it is the most suitable choice.



Questions:


7.
Clustering

...



HIERARCHICAL CLUSTERING

- **Key operation:**
Repeatedly combine two nearest clusters
- **Three important questions:**
 - **1)** How do you represent a cluster of more than one point?
 - **2)** How do you determine the “nearness” of clusters?
 - **3)** When to stop combining clusters?




EUCLIDEAN SPACE

- **Key operation:** Repeatedly combine two nearest clusters
- **(1) How to represent a cluster of many points?**
 - **Key problem:** As you merge clusters, how do you represent the “location” of each cluster, to tell which pair of clusters is closest?
- **Euclidean case:** each cluster has a **centroid** = average of its (data)points
- **(2) How to determine “nearness” of clusters?**
 - Measure cluster distances by distances of centroids



CENTROID AND CLUSTROID




Centroid is the avg. of all (data)points in the cluster. This means centroid is an “**artificial**” point.

Clustroid is an **existing** (data)point that is “closest” to all other points in the cluster.



Example: Assigning Clusters

$k = 2$




x ... data point
□ ... centroid

Clusters after round 1

Example: Assigning Clusters

$k = 2$




x ... data point
□ ... centroid

Clusters after round 2

Example: Assigning Clusters

$k = 2$




x ... data point
□ ... centroid

Clusters at the end

GETTING THE K RIGHT

- Average falls rapidly until right k , then changes little



Questions:

8. Recommendation
Systems Content-based
Systems Collaborative
Filtering
 User-user CF
 Item-item CF
...



FORMAL MODEL

- X = set of **Customers**
- S = set of **Items**
- **Utility function** $u: X \times S \rightarrow R$
 - R = set of ratings
 - R is a totally ordered set
 - e.g., **0-5** stars, real number in **$[0,1]$**



KEY PROBLEMS

- **(1) Gathering “known” ratings for matrix**
 - How to collect the data in the utility matrix
- **(2) Extrapolate unknown ratings from the known ones**
 - Mainly interested in high unknown ratings
 - We are not interested in knowing what you don't like
but what you like
- **(3) Evaluating extrapolation methods**
 - How to measure success/performance of recommendation methods



CONTENT-BASED RECOMMENDATIONS


- **Main idea:** Recommend items to customer x similar to previous items rated highly by x

Example:

- **Movie recommendations**
 - Recommend movies with same actor(s), director, genre, ...
- **Websites, blogs, news**
 - Recommend other sites with “similar” content



PLAN OF ACTION



ITEM PROFILES

- For each item, create an **item profile**
- **Profile is a set (vector) of features**
 - **Movies:** author, title, actor, director,...
 - **Text:** Set of “important” words in document




USER PROFILES

- **User profile possibilities:**
 - Weighted average of rated item profiles
 - **Variation:** Normalize weights using average rating of user
 - More sophisticated aggregations possible...



COSINE SIMILARITY

- Estimate $u(\mathbf{x}, i) = \cos(\mathbf{x}, i) = \frac{\mathbf{x} \cdot i}{\|\mathbf{x}\| \cdot \|i\|}$



For convenience, we use $\cos(\theta)$ as our similarity measure and call it the "cosine similarity" in this context.



PROS: CONTENT-BASED APPROACH

- **+: No need for data on other users**
 - No (item) cold-start or sparsity problems
- **+: Able to recommend to users with unique tastes**
- **+: Able to recommend new & unpopular items**
 - No first-rater problem
- **+: Able to provide explanations**
 - Can provide explanations of recommended items by listing content-features that caused an item to be recommended




CONS: CONTENT-BASED APPROACH

- **–: Finding the appropriate features is hard**
 - E.g., images, movies, music
- **–: Overspecialization**
 - Never recommends items outside user's content profile
 - People might have multiple interests
 - **Unable to exploit quality judgments of other users**
- **–: Recommendations for new users**
 - **How to build a user profile? (User) cold-start problem**



COLLABORATIVE FILTERING

- Consider user x
- Find set N of other users whose ratings are “similar” to x ’s ratings
- Estimate x ’s ratings based on ratings of users in N



ITEM-ITEM CF ($|N|=2$)

	users											
	1	2	3	4	5	6	7	8	9	10	11	12
movies	1	1		3	?	5			5		4	
	2			5	4			4		2	1	3
	3	2	4		1	2		3		4	3	5
	4		2	4		5			4		2	
	5			4	3	4	2				2	5
	6	1		3		3			2		4	



- estimate rating of movie 1 by user 5



ITEM-ITEM CF ($|N|=2$)

	users												
	1	2	3	4	5	6	7	8	9	10	11	12	$\text{sim}(1,m)$
movies	1	1	3		?	5			5		4		1.00
	2		5	4			4			2	1	3	-0.18
	<u>3</u>	2	4	1	2		3		4	3	5		<u>0.41</u>
	4		2	4	5			4			2		-0.10
	5		4	3	4	2					2	5	-0.31
	<u>6</u>	1	3		3			2			4		<u>0.59</u>

Neighbor selection:

Identify movies similar to
movie 1, rated by user 5

Here we use mean-adjusted cosine similarity:

1) Subtract mean rating m_i from each movie i

$$m_1 = (1+3+5+5+4)/5 = 3.6$$

row 1: $[-2.6, 0, -0.6, 0, 0, 1.4, 0, 0, 1.4, 0, 0.4, 0]$

2) Compute cosine similarities between rows

3) Predict by taking weighted average



ITEM-ITEM CF ($|N|=2$)

		users												
		1	2	3	4	5	6	7	8	9	10	11	12	
movies	1	1		3		?	5			5		4		$\text{sim}(1,m)$ 1.00
	2			5	4			4			2	1	3	-0.18
	<u>3</u>	2	4		1	2		3		4	3	5		<u>0.41</u>
	4		2	4		5			4			2		-0.10
	5			4	3	4	2					2	5	-0.31
	<u>6</u>	1		3		3			2			4		<u>0.59</u>

Compute similarity weights:

$s_{1,3}=0.41$, $s_{1,6}=0.59$



ITEM-ITEM CF (|N|=2)

		users											
		1	2	3	4	5	6	7	8	9	10	11	12
movies	1	1		3		2.6	5			5		4	
	2			5	4			4			2	1	3
	<u>3</u>	2	4		1	2		3		4	3	5	
	4		2	4		5			4			2	
	5			4	3	4	2					2	5
	<u>6</u>	1		3		3			2			4	

Predict by taking weighted average:

$$r_{1.5} = (0.41 \cdot 2 + 0.59 \cdot 3) / (0.41 + 0.59) = 2.6$$

$$r_{ix} = \frac{\sum_{j \in N(i;x)} s_{ij} \cdot r_{jx}}{\sum s_{ij}}$$

