


FEATURES


- Epoxy meets UL-94 V-0 flammability rating
- Complementary to MMBT3906
- Power dissipation of 200mW
- High stability and high Reliability

SOT-23



MECHANICAL DATA

- Case: SOT-23(TO-236)
- Terminals: Plated solderable per MIL-STD-750, method 2026
- Mounting Position: Any
- Marking: 1AM



MAXIMUM RATINGS($T_A=25^{\circ}\text{C}$ Unless otherwise specified)

Parameter	Symbol	Unit	Value
Collector-Emitter Voltage	V_{CEO}	V	40
Collector-Base Voltage	V_{CBO}	V	60
Emitter-Base Voltage	V_{EBO}	V	6
Collector Current, Continuous	I_C	mA	200
Collector Power Dissipation	P_D	mW	200
Operation Junction Temperature	T_J	$^{\circ}\text{C}$	-55 to +150
Storage Temperature	T_{STG}	$^{\circ}\text{C}$	-55 to +150
Thermal resistance From junction to ambient	$R_{\theta JA}$	$^{\circ}\text{C/W}$	625

MMBT3904

ELECTRICAL CHARACTERISTICS(T_A=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	V	I _C = 1.0mA, I _B = 0	40	---
Collector-Base Breakdown Voltage	V _{(BR)CBO}	V	I _C = 10μA, I _E = 0	60	---
Emitter-Base Breakdown Voltage	V _{(BR)EBO}	V	I _E = 10μA, I _C = 0	6	---
Collector cut-off Current	I _{CBO}	nA	V _{CB} = 60V, I _E = 0	---	100
Collector cut-off Current	I _{CEO}	nA	V _{CE} = 20V, I _B = 0	---	---
Emitter cut-off Current	I _{EBO}	nA	V _{EB} = 5V, I _C = 0	---	100
DC Current Gain	h _{FE(1)}		I _C = 10mA, V _{CE} = 1V	100	300
	h _{FE(2)}		I _C = 50mA, V _{CE} = 1V	60	---
	h _{FE(3)}		I _C = 100mA, V _{CE} = 1V	30	---
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V	I _C = 10mA, I _B = 1mA	---	---
			I _C = 50mA, I _B = 5mA	---	0.3
Base-Emitter Saturation Voltage	V _{BE(sat)}	V	I _C = 10mA, I _B = 1mA	---	---
			I _C = 50mA, I _B = 5mA	---	0.95
Output Capacitance	C _{ob}	pF	V _{CB} = 6V, f = 1.0MHz, I _E = 0	---	---
Input Capacitance	C _{ib}	pF	V _{EB} = 0.5V, f = 1.0MHz, I _C = 0	---	---
Current Gain-Bandwidth Product	f _T	MHz	I _C = 10mA, V _{CE} = 20V f = 100MHz	300	---
Noise Figure	NF	dB	V _{CE} = 5.0V, f = 1.0kHz, I _C = 100μA, R _S = 1.0K	---	---







CLASSIFICATION OF h_{FE(1)}

h _{FE}	100-300	
Rank	L	H
Range	100-200	200-300


AVAILABLE PACK INFORMATION

Product code	Pack	Reel Size (mm)	Quantity (Pcs/reel)	Quantity (pcs/box)	Quantity (pcs/carton)
MMBT3904	T/R	Φ180	3K	30K	120K

Characteristics(Typical)




Outline Dimensions



Dimensions in inches and (millimeters)

Suggested pad layout



Dimensions in millimeters

Friendship Reminder

■ JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.

■ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

■ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

■ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

■ No license is granted by implication or otherwise under any intellectual property rights of JH.

■ JH is products are not authorized for use as critical components in life support devices or systems without express written approval of JH.