

Sprint 01

Assignment 04 : Inventory Part II

Part I

Step 01: Setup

- As we have setup a Pickup System in the previous assignment, in this one we will create a common descriptive system for each Pickup Item along with Projectiles for each type of Ammo & Weapons.
- In total, we complete this assignment in 4 steps:
 - Common Descriptive System (IEquipable & IEquipableMain)
 - Weapon Scripts
 - Projectiles
 - Inventory Menu Screen
- So, start by creating two common descriptive script called “*IEquipable*” & “*IEquipableMain*”.
- Then we attach these to the weapons(Gun & Mele) scripts by creating their instances in other scripts.
- Then for the Gun item we setup a Projectile System which detects the “Ammo Type” and fires the projectile.
- Finally, after all that, we create the Inventory Menu i.e., the Visual representation of the Menu, from where we can Equip or Drop an item.
- So first, we create the IEquipable & IEquipableMain scripts.


Step 02: Script & Workflow

- The Scripts workflow for EquipmentController is like this:
 - LevelController > PlayerController > PlayerEquipmentController > IEquipable & IEquipableMain > All Pickups (Ammos, Supplies & Weapons).

- The “*PlayerEquipmentController*” acts as the Main Centre Script to which all the other scripts are attached.
- IEquipable & IEquipableMain Interfaces are used in every Pickup items.
 - PlayerEquipmentController > IEquipable & IEquipableMain > Gun & Sword.
 - Gun > IGun > DamageAmmo, ExplosiveAmmo, GuardAmmo, Supplies, PlayerObjectData & ProjectilePool.
 - Sword > SwordAttackAnimation, PlayerObjectData & CollisionCallbacks.
- Next, the Script Workflow for Projectiles:
 - LevelController > LevelDependencies > ProjectileLibrary > ProjectileType > ProjectileManager > IProjectile > ProjectileFactory > ProjectilePool.
- Only ProjectileLibrary is a MonoBehaviour script which is attached to the “*Dependencies*” GameObject in the scene.
- To this all Missiles or Ammos Prefabs are attached.
- All the ammos (DamageAmmo, ExplosiveAmmo, etc.) are generated in the equipment factory and fired using the other respective Projectile scripts.

❖ IEquipable.

- It is the first script which is also used by the IEquipableMain interface.
- It also acts as a descriptive class for Secondary Equipable item.
- It consists of some descriptive variables that need to be set when accessing or implementing this script in other scripts compulsorily.




The screenshot shows a Unity C# script editor with three tabs: `PlayerEquipmentController.cs`, `IEquipable.cs`, and `InventoryController.cs`. The `IEquipable.cs` tab is active, showing the `IEquipable` interface. The script is located at `Assets > Scripts > Equipment > IEquipable.cs`. The code defines the `IEquipable` interface with several methods and a property, each with reference counts shown in the left margin.

```
1  using System.Collections;
2  using System.Collections.Generic;
3  using UnityEngine;
4
5  30 references
6  public interface IEquipable
7  {
8      3 references
9      bool CanEquipAsMain();
10     //We pass in a Parameter bcoz we need the Ammo as a necessity for the Gun Equipment.
11     3 references
12     bool CanEquipAsSecondary(IEquipableMain requiredEquipment);
13
14     2 references
15     void Equip(IEquipable currentMainHandEquipment, Transform equipmentHolder);
16
17     1 reference
18     void Unequip(IEquipable currentMainHandEquipment);
19     2 references
20     void Destroy();
21
22     10 references
23     ItemType Type { get; }
```

❖ IEquipableMain.

- It is the second script which uses the IEquipable interface.
- It also has its own descriptive variables.
- It is used for the Primary or Main Equipment.



The screenshot shows a Visual Studio code editor with three tabs: `PlayerEquipmentController.cs`, `IEquipableMain.cs`, and `IEquipable.cs`. The `IEquipableMain.cs` tab is active, and the breadcrumb path is `Assets > Scripts > Equipment > IEquipableMain.cs > IEquipableMain`. The code defines the `IEquipableMain` interface, which inherits from `IEquipable`. It includes several methods and properties with their respective reference counts:

```
5  14 references
6  public interface IEquipableMain : IEquipable
7  {
8      1 reference
      bool CanUse();
9      1 reference
      void StartUse();
10     0 references
      void EndUse();
11     1 reference
      void Update();
12
13     2 references
      Action<ItemType> OnItemConsumed { get; set; }
14     3 references
      Action OnUsed { get; set; }
15
16 }
17
```

❖ Sword.

- This is a Main Weapon Equipment.
- This script simply is responsible for disabling the Sword GameObject when it is picked up, and enabling the actual Sword that is present on the Player GameObject.
- It also checks for Collisions and plays the Sword Animation.

```
PlayerEquipmentController.cs M  Sword.cs U X  IEquipableMain.cs U  IEquipable.cs U  InventoryController.cs M
Assets > Scripts > Player > Pickups > Sword > Sword.cs > ...
1  using System;
2  using System.Collections;
3  using System.Collections.Generic;
4  using UnityEngine;
5
6  2 references
7  public class Sword : IEquipableMain
8  {
9      2 references
10     public Action<ItemType> OnItemConsumed { get{ return toConsume; } set { toConsume = value; }}
11     3 references
12     public Action OnUsed { get{ return toUse; } set{ toUse = value; } }
13
14     10 references
15     public ItemType Type => ItemType.Melee; //Bcoz Sword is a Melee Item.
16
17     2 references
18     private Action<ItemType> toConsume;
19     2 references
20     private Action toUse;
21
22     4 references
23     private GameObject _gameObject;
24     1 reference
25     private PlayerObjectData playerObjectData;
26     6 references
27     private CollisionCallbacks collisionCallbacks;
28     6 references
29     private SwordAttackAnimation attackAnimation;
30
31     2 references
32     public Sword(GameObject gameObject, PlayerObjectData playerObjectData)
33     {
34         this._gameObject = gameObject;
35         this.playerObjectData = playerObjectData;
36
37         //We add <>(true) becoz it checks hidden GameObjects too. If we do not write the (true),
38         //it will not look through the hidden GameObjects
39         collisionCallbacks = gameObject.GetComponentInChildren<CollisionCallbacks>(true);
40         //collisionCallbacks.gameObject.SetActive(false); //DO NOT ENABLE - Turns the Sword Collison Off in the Scene.
41     }
42 }
```

```

32     3 references
33     public bool CanEquipAsMain()
34     {
35         return true;
36     }
37
38     3 references
39     public bool CanEquipAsSecondary(IEquipableMain requiredEquipment)
40     {
41         return false;
42     }
43
44     1 reference
45     public bool CanUse()    //Check Animation is Active
46     {
47         Debug.Log("Slash");
48         return true;
49     }
50
51     2 references
52     public void Equip(IEquipable currentMainHandEquipment, Transform equipmentHolder)
53     {
54         _gameObject.SetActive(true);
55         collisionCallbacks.OnTriggerEntered += SwrodCollision;
56     }
57
58     1 reference
59     public void Unequip(IEquipable currentMainHandEquipment)
60     {
61         _gameObject.SetActive(false);
62         collisionCallbacks.OnTriggerEntered -= SwrodCollision;
63     }

```

- We get the actual Sword GameObject from the PlayerObjectData, and enable it when we pick up the Sword that is present in the scene as a Pickable object.
- We then disable that picked up object and enable the Sword from PlayerObjectData.
- We also check for the its collisions with the environment, by accessing the respective Actions set in the “CollisionCallbacks” script.

```

61 private void SwrodCollision(Collider obj)
62 {
63     Debug.Log("Sword Collider with: " + obj.name);
64     //Guards guard = obj.GetComponent<Guards>();
65     //guard.TakeDamage(guard.generalData.attackDamage, playerObjectData.Sword);
66 }
67
68 1 reference
69 public void StartUse()
70 {
71     attackAnimation = new SwordAttackAnimation(_gameObject.transform);
72     attackAnimation.OnAttackStarted += () => EnableHitBox(); //Turn On Collison
73     attackAnimation.OnAttackStarted += () => DisableHitBox(); //Turn Off Collison
74     attackAnimation.Start();
75 }
76 0 references
77 public void OnAttackStart()
78 {
79     //Debug.Log("OnAttack - from Sword");
80     OnUsed();
81     EnableHitBox();
82 }
83 2 references
84 public void EnableHitBox()
85 {
86     //Debug.Log("EnableHitBox - from Sword");
87     collisionCallbacks.gameObject.SetActive(true);
88 }
89 1 reference
90 public void DisableHitBox()
91 {
92     //Debug.Log("DisableHitBox - from Sword");
93     collisionCallbacks.gameObject.SetActive(false);
94 }

```


```

94 public void EndUse()
95 {
96 }
97 }
98
99 1 reference
100 public void Update()
101 {
102     if(attackAnimation != null)
103     {
104         attackAnimation.Update();
105     }
106 }
107 2 references
108 public void Destroy()
109 {
110     collisionCallbacks.OnTriggerEntered -= SwrodCollision;
111 }

```


❖ SwordAttackAnimation.

- This script is responsible for the Sword Animation.
- The Sword Attack Animation is done, by moving the Sword a step forward along its Z-Axis, so as to give the feel of attacking.
- We do not use any AnimationController or AnimationClip for the animation.



The screenshot shows a Unity IDE with several open scripts: PlayerEquipmentController.cs, SwordAttackAnimation.cs, Sword.cs, IEquipable.cs, and InventoryCo. The active script is SwordAttackAnimation.cs, located at Assets > Scripts > Player > Pickups > Sword. The script content is as follows:

```
1 using System;
2 using System.Collections.Generic;
3 using System.Linq;
4 using System.Text;
5 using System.Threading.Tasks;
6 using UnityEngine;
7
8 public class SwordAttackAnimation
9 {
10     private const float ANIM_TIME = 0.3f;
11     public Action OnAttackStarted = delegate { };
12     public Action OnAttackEnded = delegate { };
13     private Vector3 returnPos;
14     private Vector3 lungePos;
15     private Transform sword;
16     private bool active; //Default: false
17     private float remainingAnimTime;
18
19     public SwordAttackAnimation(Transform sword)
20     {
21         this.sword = sword;
22
23         returnPos = sword.localPosition;
24         lungePos = returnPos + new Vector3(0, 0, 1f); //Moves Sword One Unit Forward (in Z-Axis).
25     }
26
27     public void Start()
28     {
29         active = true;
30         remainingAnimTime = ANIM_TIME;
31         OnAttackStarted();
32     }
```



```

33  //Reference
34  public void Update()
35  {
36      if(remainingAnimTime >= 0)
37      {
38          remainingAnimTime -= Time.deltaTime;
39
40          if(remainingAnimTime <= 0)
41          {
42              active = false;
43              sword.localPosition = returnPos;
44              OnAttackEnded();
45              return;
46          }
47
48          //This is the Value(in float, but which is taken as Percentage) to which the Lerp() will blend from "returnPos" & "lungePos" values.
49          float normalizedAnimTime = (ANIM_TIME - remainingAnimTime) / ANIM_TIME;
50          if(remainingAnimTime > (ANIM_TIME / 2f))
51          {
52              //We use "Lerp()" function bcoz we want to transition the movement of the Sword, from initial position to forward position.
53              //If we do not use Lerp(), then there will be direct or sudden displacement between the positions of the Sword.
54              sword.localPosition = Vector3.Lerp(returnPos, lungePos, normalizedAnimTime * 2f);
55          }
56          else
57          {
58              //Here, we switch the lungPos & returnPos as we are going back from "Forward Position" to "Original Position".
59              sword.localPosition = Vector3.Lerp(lungePos, returnPos, (normalizedAnimTime - 0.5f) * 2f);
60          }
61      }
62  }
63
64  //0 references
65  public bool IsActive
66  {
67      get { return active; }
68  }
69  }

```

❖ CollisionCallbacks.

- It basically consists of Action Events which are triggered when the respective GameObject enters a collision event or collides in the scene.



```
C# PlayerEquipmentController.cs M C# CollisionCallbacks.cs U X C# SwordAttackAnimation.cs
Assets > Scripts > Settings > Physics > C# CollisionCallbacks.cs > CollisionCallbacks
1 using System;
2 using UnityEngine;
3 
4 public class CollisionCallbacks : MonoBehaviour
5 {
6     public Action<Collider> OnTriggerEntered = delegate { };
7     public Action<Collision> OnCollisionEntered = delegate { };
8     public Action<Collider> OnTriggerStayed = delegate { };
9     public Action<Collider> OnTriggerExited = delegate { };
10 
11     private void OnTriggerEnter(Collider other)
12     {
13         OnTriggerEntered(other);
14     }
15 
16     private void OnCollisionEnter(Collision collision)
17     {
18         OnCollisionEntered(collision);
19     }
20 
21     private void OnTriggerStay(Collider other)
22     {
23         OnTriggerStayed(other);
24     }
25 
26     private void OnTriggerExit(Collider other)
27     {
28         OnTriggerExited(other);
29     }
30 }
31
```

❖ PlayerObjectData.

- It consists of all the Object that are attached to the Player.
- This script is attached to the Player GameObject in the scene.



The screenshot shows a code editor with two tabs: 'C# PlayerObjectData.cs' and 'C# PlayerEquipmentController.cs'. The 'PlayerObjectData.cs' tab is active, showing the following code:

```
1 using UnityEngine;
2
3 public class PlayerObjectData : MonoBehaviour
4 {
5     public Transform Blaster;
6     public Transform Sword;
7     public Transform Head;
8 }
9
```

Reference counts are shown next to some lines: '17 references' for line 2, '2 references' for line 5, '3 references' for line 6, and '1 reference' for line 7.

❖ Gun.

- It acts same as the Sword script, but the only difference in this is instead of playing some animation like Hitting, it actually fires bullets by accessing various scripts.
- It uses the IProjectile scripts to create projectiles and launch it.
- It first creates ProjectileType with the ItemType and then uses the other script to launch missiles and record its collisions with the Target and Environment.

```
Assets > Scripts > Player > Pickups > Gun > C# Gun.cs > ...
1 using System;
2 using System.Collections;
3 using System.Collections.Generic;
4 using UnityEngine;
5
6 6 references
7 public class Gun : IEquipableMain
8 {
9     2 references
10     public static float COOL_DOWN_PERIOD = 0.3f;
11     2 references
12     public Action<ItemType> OnItemConsumed { get { return toConsume; } set { toConsume = value; }}
13     3 references
14     public Action OnUsed { get { return toUse; } set { toUse = value; } }
15
16     10 references
17     public ItemType Type => ItemType.Gun;
18
19     2 references
20     private Action<ItemType> toConsume = delegate { };
21     2 references
22     private Action toUse = delegate { };
23     1 reference
24     public Action<Transform, ProjectileType> OnProjectileSpwaned = delegate { };
25
26     4 references
27     private float coolDown;
28     3 references
29     private GameObject _gameObject;
30     2 references
31     private PlayerObjectData playerObjectData;
32     2 references
33     private ProjectilePool projectilePool;
34     5 references
35     private IGunAmmo ammo;
36
37     2 references
38     public Gun(GameObject gameObject, PlayerObjectData playerObjectData, ProjectilePool projectilePool)
39     {
40         this._gameObject = gameObject;
41         this.playerObjectData = playerObjectData;
42         this.projectilePool = projectilePool;
43     }
44 }
```

```

31     public bool CanEquipAsMain()
32     {
33         return true;
34     }
35
36     3 references
37     public bool CanEquipAsSecondary(IEquipableMain requiredEquipment)
38     {
39         return false;
40     }
41
42     1 reference
43     public bool CanUse()
44     {
45         //Debug.Log("Shoot!");
46         //Have we left enough time left between Shots?
47         //Do we have ammo?
48         return (ammo != null && coolDown <= 0f);    // "(Equals to) Sign is VERY IMP //
49
50     2 references
51     public void Equip(IEquipable currentMainHandEquipment, Transform equipmentHolder)
52     {
53         _gameObject.SetActive(true);
54     }
55
56     1 reference
57     public void Unequip(IEquipable currentMainHandEquipment)
58     {
59         _gameObject.SetActive(false);
60     }

```

```

61     1 reference
62     public void StartUse()
63     {
64         //TODO Shoot Ammo
65         if(ammo == null)
66         {
67             return;
68         }
69
70         ItemType ammoType = ammo.Type; //ammo: ProjectileType & Type: ItemType
71         ProjectileType projectileType = ammo.projectileType;
72         IProjectile projectile = projectilePool.Get(projectileType);
73         projectile.OnSubProjectileSpawned += (subProjectile) => ProjectileSpawned(subProjectile, projectileType);
74         projectile.OnCollidedWithEnvironment += (collisionPoint) => CollidedWithEnvironment(collisionPoint);
75         projectile.OnCollidedWithTarget += (collider, collisionPoint) => CollidedWithTarget(collider, collisionPoint);
76         ProjectileSpawned(projectile.Transform, projectileType);
77         Transform blaster = playerObjectData.Blaster;
78         projectile.Fire(blaster, blaster.position, blaster.forward);
79
80         OnUsed();
81         OnItemConsumed(ammoType);    //ammo.Type
82
83         coolDown = COOL_DOWN_PERIOD;    //Decrementing
84     }
85
86     4 references
87     public void ChangeAmmo(IGunAmmo gunAmmo)
88     {
89         //Set Local Variable
90         this.ammo = gunAmmo;
91     }

```



```

92     private void CollidedWithTarget(Collider collider, Vector3 collisionPoint)
93     {
94         Debug.Log("Collided with Target.");
95     }
96
97     1 reference
98     private void CollidedWithEnvironment(Vector3 collisionPoint)
99     {
100         Debug.Log("Collided with Environment.");
101     }
102
103     2 references
104     private void ProjectileSpawned(Transform projectile, ProjectileType projectileType)
105     {
106         OnProjectileSpawned(projectile, projectileType);
107         Debug.Log("Projectile Spawned! ");
108     }
109
110     1 reference
111     public void Update()
112     {
113         coolDown -= Time.deltaTime;
114         Mathf.Clamp(coolDown, 0.0f, COOL_DOWN_PERIOD); //Bcoz the coolDown value can be Negative so it clamps it to Zero.
115     }
116
117     0 references
118     public void EndUse()
119     {
120     }
121
122     2 references
123     public void Destroy()
124     {
125     }
126 }

```

❖ IGunAmmo.

- It simply consists of ProjectileType.
- It also implements the IEquipable interface.


```

C# PlayerEquipmentController.cs M  C# IGunAmmo.cs U X  C# ProjectileType.cs U
Assets > Scripts > Player > Pickups > Gun > Ammo > C# IGunAmmo.cs > IGunAmmo >
1  using System.Collections;
2  using System.Collections.Generic;
3  using UnityEngine;
4
5  5 references
6  public interface IGunAmmo : IEquipable
7  {
8      1 reference
9      ProjectileType projectileType { get; }
10 }


```

❖ ProjectileType.

- It is an Enum which consists of the Types of Missiles or Ammos.
- It is similar to the ItemType, and is mainly used to check if the ItemType is equal to or matches with the ProjectileType.



The screenshot shows a code editor with two tabs: 'ProjectileType.cs' and 'IGunAmmo.cs'. The 'ProjectileType.cs' tab is active, displaying the following code:

```
Assets > Scripts > Player > Pickups > Gun > Ammo > P
1  using System;
2  using System.Collections.Generic;
3  using System.Linq;
4  using System.Text;
5  using System.Threading.Tasks;
6  
   32 references
7  public enum ProjectileType
8  {
   3 references
9      Damage,
   3 references
10     Explosive,
   3 references
11     SubExplosion,
   2 references
12     Guard
13 }
14
```



❖ DamageAmmo.

- It implements the “*IGunAmmo*” interface.
- And because the *IGunAmmo* script uses the “*IEquipable*” interface, it also gets implemented in this script.
- This script basically creates ammo of the Type defined. (In this case it is DamageAmmo type)
- It first matches the ProjectileType with the ItemType, and then check whether it can be Equipped as Secondary, by passing a check statement that checks if the Main Required Equipment is equal to the Gun type.
- If it is, then it can be equipped, otherwise it cannot be equipped if it does not match the Gun type.
- That is, if we are holding a Sword or any other Weapon, other than Gun, we should be able to grab any type of Ammo as a Secondary Equipment.
- After checking the above statement, we pass this data into the Main or Primary Equipment class (Gun), under the function “*ChangeAmmo*” of the “*Gun*” script.
- This function basically sets current ammo that we are pass to the Gun script’s ammo, which is “*IGunAmmo*” class.
- Then we use the Ammo.
- The amount of Ammo is set in the Inspector, with the “*Pickup*” script.
- And the ammo is decremented by decrementing its Count, from the “*InventoryController*” script.
- It is also displayed in the Inventory Menu UI.

```
C# IGunAmmo.cs U C# DamageAmmo.cs U X C# Gun.cs U C# PlayerEquipmentController.cs M C# Pi
Assets > Scripts > Player > Pickups > Gun > Ammo > Damage > C# DamageAmmo.cs > DamageAmmo
1 using System.Collections;
2 using System.Collections.Generic;
3 using UnityEngine;
4
5 1 reference
6 public class DamageAmmo : IGunAmmo
7
8     1 reference
9     public ProjectileType projectileType => ProjectileType.Damage;
10
11     10 references
12     public ItemType Type { get { return ItemType.DamageAmmo; } }
13
14     3 references
15     public bool CanEquipAsMain()
16     {
17         return false;
18     }
19
20     3 references
21     public bool CanEquipAsSecondary(IEquipableMain requiredEquipment)
22     {
23         //Return True, only if the the requiredEquipment is Gun.
24         return requiredEquipment.Type == ItemType.Gun;
25     }
26
27     2 references
28     public void Equip(IEquipable currentMainHandEquipment, Transform equipmentHolder)
29     {
30         (currentMainHandEquipment as Gun).ChangeAmmo(this);
31     }
32
33     1 reference
34     public void Unequip(IEquipable currentMainHandEquipment)
35     {
36         (currentMainHandEquipment as Gun).ChangeAmmo(null);
37         Debug.Log("Ammo --- UnEquipping!");
38     }
39
40     2 references
41     public void Destroy()
42     {
43     }
44 }
```


❖ ExplosiveAmmo & GuardAmmo.

- It is just same as DamageAmmo.
- Its functionality is same.
- Just the difference or change in these scripts is the “*ProjectileType*” and “*ItemType*” would be ExplosiveAmmo & GuardAmmo respectively.



The screenshot shows the Visual Studio code editor with the `ExplosiveAmmo.cs` script open. The breadcrumb path is `Assets > Scripts > Player > Pickups > Gun > Ammo > Damage > ExplosiveAmmo.cs`. The script content is as follows:

```
1 using System.Collections;
2 using System.Collections.Generic;
3 using UnityEngine;
4
5 1 reference
6 public class ExplosiveAmmo : IGunAmmo
7 {
8     1 reference
9     public ProjectileType projectileType => ProjectileType.Explosive;
10
11     10 references
12     public ItemType Type { get { return ItemType.ExplosiveAmmo; } }
13 }
```




The screenshot shows the Visual Studio code editor with the `GuardAmmo.cs` script open. The breadcrumb path is `Assets > Scripts > Player > Pickups > BowAndArrow > Ammo > GuardAmmo.cs`. The script content is as follows:

```
1 using System;
2 using System.Collections;
3 using System.Collections.Generic;
4 using UnityEngine;
5
6 0 references
7 public class GuardAmmo : IGunAmmo
8 {
9     10 references
10     public ItemType Type { get { return ItemType.GuardAmmo; } }
11
12     1 reference
13     public ProjectileType projectileType => ProjectileType.Guard;
14 }
```

❖ Supplies.


- It is created to get rid of the “*DebugError*” that pops up when we picked up supplies.
- It simply prints a “*Debug.Log*” message when we pickup supplies.



```
Assets > Scripts > Player > Pickups > Gun > Ammo > Damage > C# Supplies.cs > Supplies
1  using System.Collections;
2  using System.Collections.Generic;
3  using UnityEngine;
4
5  1 reference
   public class Supplies : IEquipable
6  {
7      10 references
       public ItemType Type => throw new System.NotImplementedException();
8
9      3 references
       public bool CanEquipAsMain()
10     {
11         return false;
12     }
13
14     3 references
       public bool CanEquipAsSecondary(IEquipableMain requiredEquipment)
15     {
16         return false;
17     }
18
19     2 references
       public void Destroy()
20     {
21     }
22
23     2 references
       public void Equip(IEquipable currentMainHandEquipment, Transform equipmentHolder)
24     {
25         Debug.Log("You collected Supplies.");
26     }
27
28     1 reference
       public void UnEquip(IEquipable currentMainHandEquipment)
29     {
30     }
31
32 }
33
```

❖ PlayerEquipmentController.

- It is the Main Parent Script which controls all the other scripts.
- It consists of Functions , which examine the picked-up item, and then check whether it can be used as a Main Equipment or Secondary Equipment, and assign it, to the respective slots.
- It also has function that perform the Weapon Switch action as well as UnEquip item(s).



```
Assets > Scripts > Player > Equipment > PlayerEquipmentController.cs > PlayerEquipmentController
1  using System;
2  using System.Collections;
3  using System.Collections.Generic;
4  using UnityEngine;
5
6  8 references
7  public class PlayerEquipmentController
8  {
9      //The below 2 Capital variables are used to access only in other script.
10     //They are not used in this script. They return the Primary & Secondary Weapons
11     2 references
12     public IEquipableMain PrimaryEquipment { get { return main; } }
13     3 references
14     public IEquipable SecondaryEquipment { get { return secondary; } }
15
16     8 references
17     private InventoryController inventory;
18     5 references
19     private PlayerObjectData playerObjectData;
20     0 references
21     private Transform equipmentHolder;
22     17 references
23     private IEquipableMain main;
24     9 references
25     private IEquipable secondary;
26     2 references
27     private ProjectilePool projectilePool;
28     7 references
29     private EquipmentFactory equipmentFactory; //Creates ItemType (Melee, Sword, etc..)
30     1 reference
31     public Action OnMainUnequiped = delegate { };
32     1 reference
33     public Action OnSecondaryUnequiped = delegate { };
34     2 references
35     public Action OnNewItemEquiped = delegate { };
36
37 }
```



```

24 1 reference
25 public PlayerEquipmentController(
26     InventoryController inventoryController, PlayerObjectData playerObjectData,
27     ProjectilePool projectilePool, EquipmentFactory equipmentFactory)
28 {
29     this.inventory = inventoryController;
30     this.playerObjectData = playerObjectData;
31     this.projectilePool = projectilePool;
32
33     this.equipmentFactory = new EquipmentFactory
34     (
35         playerObjectData, projectilePool,
36         playerObjectData.Sword.gameObject,
37         playerObjectData.Blaster.gameObject
38     );
39
40     inventory.OnItemCountUpdated += (item, count) =>
41     {
42         if(secondary != null && item == secondary.Type && count <= 0)
43         {
44             UnequipSecondary();
45         }
46     };
47
48 1 reference
49 public void OnPlayerPickedUp(Pickup pickup)
50 {
51     inventory.Add(pickup.itemType, pickup.quantity); //We access the 2nd Add function which takes 2 arguments.
52
53     if(pickup.requiredForLevelCompletion)
54     {
55         inventory.SetAsUndroppable(pickup.itemType);
56     }
57     pickup.gameObject.SetActive(false);
58
59     EquipItemIfEmptyHanded(pickup.itemType);
60
61 private void EquipItemIfEmptyHanded(ItemType itemType)
62 {
63     IEquipable equipablePickup = equipmentFactory.Create(itemType);
64
65     bool isEquipable = equipablePickup != null; //Same way of writing if(!= null) then true, else(== null) then false.
66
67     if(!isEquipable) //If it returns a Null Value, then execute below code.
68     {
69         Debug.LogError("Tried to Equip Object type of : " + itemType + " wich is invalid!");
70         return;
71     }
72
73     if( (main == null && equipablePickup.CanEquipAsMain()) ||
74         (secondary == null && equipablePickup.CanEquipAsSecondary(main)) )
75     {
76         Equip(equipablePickup);
77     }
78     else
79     {
80         //To DO Cleanup bcoz we'll have constructed a class.
81         equipablePickup.Destroy();
82     }
83
84 1 reference
85 public bool CanEquip(ItemType type) //for Equip Button
86 {
87     IEquipable equipable = equipmentFactory.Create(type);
88     bool isEquipable = equipable != null; //True if Not Equals to Null.
89
90     if(isEquipable == false)
91     {
92         return false;
93     }
94
95     //Here we check wether it can be equipped as Primary or Secondary.
96     //If it can be equipped as any one of those, then return True, else return False.
97     isEquipable = equipable.CanEquipAsMain() ||
98         equipable.CanEquipAsSecondary(main);
99
100     return isEquipable; //return the above bool.
101 }
102

```

```

120
121 //This function is used to get the (IEquipable) equipable for the Equip Button - (if statement)
122 //It is also an "Overload" (with same function name, but different parameters)
1 reference
123 public void Equip(ItemType type)
124 {
125     IEquipable equipable = equipmentFactory.Create(type);
126     bool isEquipable = equipable != null; //True if Not Equals to Null.
127
128     if(isEquipable) //if true,
129     {
130         Equip(equipable);
131     }
132     else
133     {
134         Debug.LogError("Tried to Equip Non-Equipable item!");
135     }
136 }
137

```

```

2 references
187 private void Equip(IEquipable equipablePickup)
188 {
189     if(equipablePickup.CanEquipAsMain())
190     {
191         //We create these 2 Functions bcoz when the Player equips any Pickup Item as Main Item,
192         //we want to Unequip all the Primary & Secondary items that are currently present in Player's Hand.
193         //Also if the Player is already holding a Gun and suddenly picks up Sword or assigns Sword to Primary Slot,
194         //then the Gun should go back to the Inventory i.e., Unequip along with its Bulletes(Secondary)
195         UnequipSecondary();
196         UnequipMain();
197
198         //Casting: One Class from Another, to basically use its variables & functions
199         //Here "equipablePickup" belong to "IEquipable" Class, and we want to access the "IEquipableMain" Class to.
200         //So we Cast the "equipablePickup" as "IEquipableMain" class.
201         main = equipablePickup as IEquipableMain;
202
203         main.OnItemConsumed += (item) =>
204         {
205             inventory.Remove(item);
206         };
207
208         main.OnUsed += () =>
209         {
210         };
211
212         inventory.EquipPrimary(equipablePickup.Type); //Boolean: from IEquipable. It is set as ItemType.Melee(Sword) in Sword Script.
213         equipablePickup.Equip(main, playerObjectData.Sword); //Function: from IEquipable
214         OnNewItemEquiped();
215     }
216
217     else if(equipablePickup.CanEquipAsSecondary(main))
218     {
219         UnequipSecondary();
220         secondary = equipablePickup;
221         inventory.EquipSecondary(equipablePickup.Type);
222         equipablePickup.Equip(main, playerObjectData.Sword);
223         OnNewItemEquiped();
224     }
225 }
226
227

```




```

228     3 references
    private void UnequipSecondary()
229     {
230         if(secondary != null)
231         {
232             inventory.UnEquipSecondary();
233             secondary.UnEquip(main);
234             secondary.Destroy();
235             secondary = null;
236             OnSecondaryUnequiped();
237         }
238     }
239
240     1 reference
    private void UnequipMain()
241     {
242         main = null;
243         OnMainUnequiped();
244     }
245
246     1 reference
    internal void StartUse()
247     {
248         if(main != null && main.CanUse())
249         {
250             main.StartUse();
251         }
252     }
253
254     1 reference
    public void Update()
255     {
256         if(main != null)
257         {
258             main.Update();
259         }
260     }
261 }
262

```

❖ PlayerController.

- We just pass a reference of the “ProjectilePool” script in here, so that it can be accessed in the LevelController.



```
26 | private PlayerInputBroadcaster inputBroadcaster;
27 | private PlayerViewRelativeMovement viewRelativeMovement;
28 | private float playerMaxHP = 100f;
29 | private PlayerInputCallbacks callbacks;
30 | private PlayerEquipmentController equipmentController; //Assignment 04 - Part I
31 | private InventoryController inventory; //Assignment 04 - Part II
32 | public ProjectilePool projectilePool; //Assignment 04 - Part II
33 |
34 | public PlayerController(Transform transform,
35 |     NavMeshAgent navMeshAgent, PlayerInteractionController interactionController,
36 |     PlayerCollision collision, PlayerInputBroadcaster inputBroadcaster,
37 |     InventoryController inventory, PlayerEquipmentController equipmentController, ProjectilePool projectilePool) //Assignment 04 - Part I & II
38 | {
39 |     this.transform = transform;
40 |     this.navMeshAgent = navMeshAgent;
41 |     this.interactionController = interactionController;
42 |     this.collision = collision;
43 |     this.inputBroadcaster = inputBroadcaster;
44 |     this.equipmentController = equipmentController; //Assignment 04 - Part I
45 |     this.inventory = inventory; //Assignment 04 - Part I
46 |     this.projectilePool = projectilePool; //Assignment 04 - Part II
47 |
48 |     playerHealth = new PlayerHealth(playerMaxHP);
49 |
50 |     playerHealth.OnDamageTaken += (currentHealth) =>
51 |     {
52 |         OnPlayerDamageTaken(currentHealth);
53 |     };
54 |
55 |     playerHealth.OnKilled += () =>
56 |     {
57 |         OnDeathSequenceStarted();
58 |         HandlePlayerDeath();
59 |     };
60 |
61 |     rigidbody = transform.GetComponent<Rigidbody>();
62 |
63 |     playerObjectData = transform.GetComponent<PlayerObjectData>();
64 | }
```

❖ LevelController.

- We create some instances of the Projectile classes.
- We create an instance of “ProjectilePool” here, because we need to pass the data to the “Dependencies” components.
- We pass in the “ProjectileLibrary” and a new “ProjectileFactory” which gets created.
- Also, we pass in the “ProjectileManager” which controls the projectiles and pass it the “projectilePool” variable.

- Then we pass in the “*PlayerEquipmentController*” in the “*return Player()*” function and also in the “*Player*” Class.

```

C# PlayerEquipmentController.cs M  C# LevelController.cs M X  C# UIController.cs M  C# PickupController.cs M  C# Pickup.cs  C# ProjectilePool.cs U  C# IE
Assets > Scripts > Level > C# LevelController.cs > ...
3 references
18 private GuardManager guardManager; //Assignment - 03
3 references
19 private TimeController timecontroller; //Assignment - 01
4 references
20 private LevelStatsController levelStatsController;
21 //private PlayerEquipmentController equipmentController; //Assignment 04 - Part I
1 reference
22 private PickupController pickupController; //Assignment 04 - Part I
4 references
23 private InventoryController inventory; //Assignment 04 - Part I
24 //private PickupEvents pickupEvents; //Assignment 04 - Part I
2 references
25 private ProjectilePool projectilePool; //Assignment 04 - Part II
1 reference
26 private ProjectileManager projectileManager; //Assignment 04 - Part II
1 reference
27 private EquipmentFactory projectileFactory; //Assignment 04 - Part II
28
0 references
29 public void Start()
30 {
31     LevelDependencies dependencies = GetComponentInChildren<LevelDependencies>();
32     if(dependencies == null)
33     {
34         Debug.LogError("Unable to find LevelDependencies. Cannot play level.");
35     }
36
37     GameObject playerObj = CreatePlayerObject(dependencies.player);
38
39     projectilePool = new ProjectilePool(dependencies.projectileLibrary, new ProjectileFactory()); //Assignment 04 - Part II
40     projectileManager = new ProjectileManager(projectilePool); //Assignment 04 - Part II
41
42     PickupEvents pickupEvents = new PickupEvents(); //Assignment - 04 Part I
43
44     //Part II - Added projectilePool
45     player = CreatePlayer(playerObj, projectilePool); //Assignment - 04 Part I
46
47     pickupController = new PickupController(transform, player.Controller, pickupEvents); //Assignment 04 - Part I
48
49     pickupEvents.OnPickupEventCollected += (pickup) => //Assignment 04 - Part I
50     {
51         player.Controller.OnPickupCollected(pickup); //Inside Player Controller
52     };
53
54     player.Controller.OnDeathSequenceCompleted += () =>
55     {
56         FailLevel();
57     };

```

```

73
74 HUDController hudController = cameraController.MainCameraTransform.Find("HUDCanvas/HUD").GetComponent<HUDController>();
75 player.Controller.OnPlayerDamageTaken += (currentHealth) => hudController.UpdatePlayerHealth(currentHealth);
76
77 uiController = new UIController(player, cameraController.MainCameraTransform,
78     levelID, timecontroller, levelStatsController, dependencies.inventoryUI, inventory); //Assignment - 04 - Part II
79
80 uiController.OnLevelLoad += (level) => //Assignment - 02 (to 'GameController')
81 {
82     OnLevelLoadRequest(level);
83 };
84
85 uiController.OnExit += () => //Assignment - 02 (to 'GameController')
86 {
87     OnExitRequest();
88 };

```

```

155
156     broadcaster.Callbacks.OnPlayerStartUseFired += () => controller.StartUse();
157
158     return new Player(controller, broadcaster,
159         objectData, interaction, equipmentController); //Assignment 04 - Part II
160 }
161
162 1 reference
163 private void FailLevel()
164 {
165     player.Broadcaster.EnableActions(ControlType.None);
166     uiController.OnLevelFailed("You were killed!");
167 }

```

```


13 references
176 public class Player
177 {
178     9 references
179     public PlayerController Controller { get; }
180     14 references
181     public PlayerInputBroadcaster Broadcaster { get; }
182     0 references
183     public Animator Animator { get; }
184     4 references
185     public PlayerObjectData ObjectData { get; }
186     3 references
187     public PlayerInteractionController Interaction { get; }
188     2 references
189     public PlayerEquipmentController playerEquipment { get; } //Assignment 04 - Part II
190
191     1 reference
192     public Player(PlayerController controller, PlayerInputBroadcaster broadcaster,
193         PlayerObjectData objectData, PlayerInteractionController interaction,
194         PlayerEquipmentController playerEquipment) //Assignment 04 - Part II
195     {
196         this.Controller = controller;
197         this.Broadcaster = broadcaster;
198         this.ObjectData = objectData;
199         this.Interaction = interaction;
200         this.playerEquipment = playerEquipment; //Assignment 04 - Part II
201     }
202 }


```

Part II – Inventory Menu UI


Step 01: Setup

- There is already an “*InventoryUI*” created in the Prefabs > UI > InventoryMenu.
- Open the prefab, and set the “Alpha” value to 1, to make it visible.
- Then, we create scripts and attach them to the components.
- The Main Parent Script is the “*InventoryMenu*” script.
- After creating all the scripts, we assign them as follow:





(For each Item in Row1, Row2 and Row3)



Step 02: Script & Workflow

- The Script Workflow for Inventory Menu:
 - UIController > InventoryMenuController > InventorySubMenuController, InventoryMenu, InventoryItem, InventoryController, PlayerEquipmentController.
 - InventorySubMenuController > Entry (Sub Class within it) > InventorySubMenuItem.
 - InventoryMenu > ItemIcons (ItemIcon Sub Class).
- InventoryMenu is the Main Script attached to the Main Parent Inventory UI GameObject.
- InventoryItem, InventoryMenu, InventorySubMenuItem, ItemIcons are all MonoBehaviour scripts and are attached to respective elements of the Main Parent Inventory UI GameObject.

❖ ItemIcons.

- This class simply consists of all the Pickup Item's Icons.
- It contains a List and also has functions: "*GetIcons*" which is used to get the Normal Icons, and "*GetDesaturatedIcons*" which is used to get the Desaturated form of the Icons.
- It also has a Sub Class which contains the basic elements, and these elements are later called in the above functions to set their images and make them access in other scripts respectively.


C# ItemIcons.cs U X C# UIController.cs M

Assets > Scripts > UI > InventoryScreen > C# ItemIcons.cs > ...

```
1 using System.Collections;
2 using System.Collections.Generic;
3 using UnityEngine;
4
5 1 reference
6 public class ItemIcons : MonoBehaviour
7 {
8     2 references
9     public List<ItemIcon> icons;
10
11     3 references
12     public Sprite GetIcons(ItemType type)
13     {
14         foreach (ItemIcon icon in icons)
15         {
16             if (icon.type == type)
17             {
18                 return icon.icon;
19             }
20         }
21         return null;
22     }
23
24     0 references
25     public Sprite GetDesaturatedIcons(ItemType type)
26     {
27         foreach (ItemIcon icon in icons)
28         {
29             if (icon.type == type)
30             {
31                 return icon.iconDesat;
32             }
33         }
34         return null;
35     }
36 }
37
38 [System.Serializable] // Add This Line To make Visible in the Hierarchy Prefab //
39 3 references
40 public class ItemIcon
41 {
42     2 references
43     public ItemType type;
44     1 reference
45     public Sprite icon;
46     1 reference
47     public Sprite iconDesat; //Desturation: turns the icon grey after it is used.
48 }
49
50
```

❖ InventoryMenu.

- It is the Main Script which is attached to the Main Parent Object of the “Inventory Menu UI”
- It consists of all the UI Sprites, which are then further accessed by other scripts.




The screenshot shows a code editor with three tabs: 'C# ItemIcons.cs U', 'C# InventoryMenu.cs U X', and 'C# UIController.cs M'. The 'InventoryMenu.cs' tab is active, showing the following code:

```
Assets > Scripts > UI > InventoryScreen > C# InventoryMenu.cs > ...
1  using System.Collections;
2  using System.Collections.Generic;
3  using UnityEngine;
4  using UnityEngine.UI;
5  using TMPro;
6
7  2 references
   public class InventoryMenu : MonoBehaviour
8  {
9      0 references
       public RectTransform itemGrid;
       1 reference
10     public Button closeButton;
       3 references
11     public Image mainEquipmentIcon;
       3 references
12     public Image secondaryEquipmentIcon;
       3 references
13     public TextMeshProUGUI secondaryCount;
       1 reference
14     public GameObject subMenu;
       1 reference
15     public GameObject subMenuButton;
       3 references
16     public ItemIcons icons;
17 }
18
```

❖ InventorySubMenuItem.

- This script consists of a String and Button which is used and accessed by other scripts.
- It is used to create a button with a label or name in the Inventory Menu UI.



```
Assets > Scripts > UI > InventoryScreen > C# InventorySubMenuItem.cs > ...  
1 using System.Collections;  
2 using System.Collections.Generic;  
3 using UnityEngine;  
4 using UnityEngine.UI;  
5 using TMPro;  
6  
7 2 references  
8 public class InventorySubMenuItem : MonoBehaviour  
9 {  
10     1 reference  
11     public Button button;  
12     1 reference  
13     public TextMeshProUGUI label;  
14 }  
15
```

❖ InventorySubMenuController.

- This script takes the Button & String values of the “InventorySubMenuItem” Script and make the Instantiate in the Inventory Menu UI.
- Its “Show()” function is responsible for creating or generating the Button(s) and “Hide()” function which is used to hide the buttons once clicked.

- It also has a Sub Class called “Entry” which contains a String and an Action event called “OnClicked” which is then accessed in further scripts.

```

C# ItemIcons.cs U C# InventorySubMenuController.cs U X C# InventorySubMenuItem.cs U C# InventoryMenu.cs U C# Inve
Assets > Scripts > UI > InventoryScreen > C# InventorySubMenuController.cs > ...
1 using System;
2 using System.Collections;
3 using System.Collections.Generic;
4 using UnityEngine;
5
6 references
7 public class InventorySubMenuController
8 {
9     2 references
10     private GameObject subMenuPrefab;
11     2 references
12     private GameObject subMenuItem;
13     5 references
14     private GameObject subMenu;
15
16     1 reference
17     public InventorySubMenuController(GameObject subMenuPrefab, GameObject subMenuItem)
18     {
19         this.subMenuPrefab = subMenuPrefab;
20         this.subMenuItem = subMenuItem;
21     }
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50

```

```

47
48 //Below function, we Destroy & Create(Instantiate) a "subMenu" GameObject for the Equip Button Option.
49 1 reference
50 public void Show(Transform parent, List<Entry> entries)
51 {
52     21
53     if(subMenu != null)
54     {
55         22
56         GameObject.Destroy(subMenu);
57     }
58
59     23
60     subMenu = GameObject.Instantiate(subMenuPrefab, parent);
61
62     24
63     foreach(Entry entry in entries)
64     {
65         25
66         GameObject buttonObj = GameObject.Instantiate(subMenuItem, subMenu.transform);
67         InventorySubMenuItem item = buttonObj.GetComponent<InventorySubMenuItem>();
68
69         26
70         item.label.text = entry.label;
71
72         27
73         item.button.onClick.AddListener(() =>
74         {
75             28
76             Hide();
77             29
78             entry.onClicked();
79         });
80     }
81
82     30
83     // UThen we Destroy it here, bcoz when clicked "Equiped" it will go to Primary of Secondary,
84     //and it should not generate button again, after its use.
85     31
86     1 reference
87     public void Hide()
88     {
89         32
90         GameObject.Destroy(subMenu);
91     }
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150

```

```

51 //-----New Class-----//
   6 references
52 public class Entry
53 {
   2 references
54     public string label;
   2 references
55     public Action onClicked;
56
   2 references
57     public Entry(string label, Action onClick)
58     {
59         this.label = label;
60         this.onClicked = onClick;
61     }
62 }
63
64 }
65

```

❖ InventoryItem.

- This script contains all the UI Sprites.
- It is attached to a Prefab called “*ItemIcons*” which is further attached to the main Inventory Menu UI parent object.
- It displays the Image of the Equipment and is attached to each Item in each and every row.

```
C# ItemIcons.cs U C# InventoryItem.cs U X C# InventoryS
Assets > Scripts > UI > InventoryScreen > C# InventoryItem.cs >
1 using System.Collections;
2 using System.Collections.Generic;
3 using TMPro;
4 using UnityEngine;
5 using UnityEngine.UI;
6
7 9 references
8 public class InventoryItem : MonoBehaviour
9 {
10     3 references
11     public Image icon;
12     3 references
13     public TextMeshProUGUI count;
14     1 reference
15     public Button button;
16     0 references
17     public GameObject subMenuIcon;
18     1 reference
19     public Transform menuContainer;
20 }
```

❖ InventoryMenuController.

- It is the main parent script which gathers all the other scripts & components and make them work.
- It has a Lists of two "*InventoryItem*"; "*inventoryItems*" – those items which are present in the Inventory, and "*itemsInUse*" – items that are currently in use.
- It consists of "*Show()*" and "*Hide()*" functions which simply make the InventoryUI Hide & UnHide.
- It has "*Refresh()*" function which refreshes the items present in the Inventory, each time a there is a change in the Inventory, i.e., when an item is Added, Dropped or Equipped as Primary or Secondary in the inventory.
- Also, it has "*Clears()*" function which disables the item when Dropped or been used in the Primary or Secondary slots.

- Then it has the “*UpdateItems()*” and “*UpdateEquipment()*” functions which simply update items & equipments in the inventory.
- The “*UpdateItems()*” function consists the “*Equip*” & “*Drop*” button code as it can be accessed when clicked on each item.

```

Assets > Scripts > UI > InventoryScreen > InventoryMenuController.cs > ...
1 using System;
2 using System.Collections;
3 using System.Collections.Generic;
4 using UnityEngine;
5
6 public class InventoryMenuController
7 {
8     2 references
9     public Action OnClose = delegate { };
10    1 reference
11    private Transform hudTransfrom;
12    4 references
13    private InventoryController inventoryController;
14    8 references
15    private PlayerEquipmentController equipmentController;
16    2 references
17    private InventorySubMenuController inventorySubMenuController;
18    5 references
19    private CanvasGroup canvasGroup;
20    16 references
21    private InventoryMenu menu; //Main ineventoryUI Prefab
22    3 references
23    private List<InventoryItem> inventoryItems; //Each Small Boxes (Rows & Clomuns)
24    4 references
25    private List<InventoryItem> itemsInUse;
26
27    1 reference
28    public InventoryMenuController(Transform hudTransfrom, InventoryController inventoryController,
29    GameObject inventoryUI, PlayerEquipmentController equipmentController)
30    {
31        this.hudTransfrom = hudTransfrom;
32        this.inventoryController = inventoryController;
33        this.equipmentController = equipmentController;
34
35        //gameObject = Inventory Inertface or UI.
36        GameObject gameObject = GameObject.Instantiate(inventoryUI, hudTransfrom);
37
38        menu = gameObject.GetComponent<InventoryMenu>(); //Main Parent Object.
39        canvasGroup = gameObject.GetComponent<CanvasGroup>(); //CanvasGroup of InventoryMenu.
40
41        inventoryItems = new List<InventoryItem>(gameObject.GetComponentsInChildren<InventoryItem>(true)); //Use "s" in GetComponents bcoz its a List.
42        //We do not use GetComponents here bcoz, thses are simply the items that are being used.
43        //Bascially 2 items can be used, out of 'n' number of Items in the Inventory.
44        itemsInUse = new List<InventoryItem>();
45    }
46

```



```

36
37 //The "X" icon on the Upper-Right Corner.
38 menu.closeButton.onClick.AddListener( () => Hide());
39
40 inventorySubMenuController = new InventorySubMenuController(menu.subMenu, menu.subMenuButton);
41
42 Refresh();
43
44 }
45
46 1 reference
47 public void Hide()
48 {
49     //We use the "alpha" valuse to Hide-Unhide instead of SetActive(True & False)
50     //bcz it gives Blend in Animation by default (from 0.0 to 1.0 values).
51     canvasGroup.alpha = 0;
52     canvasGroup.blocksRaycasts = false;
53     OnClose();
54 }
55
56 1 reference
57 public void Show()
58 {
59     canvasGroup.alpha = 1;
60     canvasGroup.blocksRaycasts = true;
61     Refresh();
62 }
63
64 //This function is used to Refresh the Inventory, to check wether there is any Update in the Inventory.
65 //Like if any item(s) is used/consumed (deleted) or some new items(s) added.
66 4 references
67 public void Refresh()
68 {
69     Clear(); //Simply clears items in the Inevntory.
70
71     UpdateItems();
72     UpdateEquipment();
73 }

```

```

74 private void UpdateItems()
75 {
76     //Here we check whats in the Inventory.
77     //Content: conatins all the items in the Inventory. It is from here we will be accessing the items.
78     //Contents: Actual item representation (like DamageAmmo, Missiles, Gun, Sword, etc...).
79     //InventoryItems: Graphical representation of these items in the Inventory UI Menu (each item on seperate slots).
80     foreach(KeyValuePair<ItemType, ItemData> item in inventoryController.Contents)
81     {
82         InventoryItem slot = GetNextAvailableSlot();
83
84         slot.gameObject.SetActive(true);
85         slot.icon.gameObject.SetActive(true);
86         slot.count.text = item.Value.count.ToString(); //Bcoz item.Value is an int which is converted to a String.
87         slot.count.gameObject.SetActive(true);
88         //slot.subMenuIcon.gameObject.SetActive(true);
89         slot.icon.sprite = menu.icons.GetIcons(item.Key); //Key: "ItemType" from KeyValuePair.
90
91         //Create Button (Equip & Drop)
92         slot.button.onClick.AddListener(() =>
93         {
94             List<InventorySubMenuController.Entry> entries = new List<InventorySubMenuController.Entry>();
95
96             //Equip
97             if(equipmentController.CanEquip(item.Key)) //Key: ItemType
98             {
99                 entries.Add(new InventorySubMenuController.Entry("Equip", () =>
100                 {
101                     equipmentController.Equip(item.Key);
102                     Debug.Log(item.Key);
103                     Refresh();
104                 }));
105             }
106
107             //Drop
108             if(item.Value.canDrop)
109             {
110                 entries.Add(new InventorySubMenuController.Entry("Drop", () =>
111                 {
112                     inventoryController.RemoveAll(item.Key); //Key: ItemType
113                     //TODO Implement a nice drop here
114                     Refresh();
115                 }));
116             }
117
118             inventorySubMenuController.Show(slot.menuContainer, entries);
119         });
120     }
121 }

```

```

124 private void Clear()
125 {
126     foreach(InventoryItem item in inventoryItems)
127     {
128         item.gameObject.SetActive(false);
129         item.icon.gameObject.SetActive(false);
130         item.count.gameObject.SetActive(false);
131         //item.subMenuIcon.gameObject.SetActive(false);
132         //Debug.Log("Enetred Clear!");
133     }
134
135     itemsInUse.Clear();
136 }
137
138 //Below function sets the Primary & Secondary slots with the Weapons & Ammos Icons.
139 //reference
140 private void UpdateEquipment()
141 {
142     if(equipmentController.PrimaryEquipment == null)
143     {
144         menu.mainEquipmentIcon.gameObject.SetActive(false);
145     }
146     else
147     {
148         menu.mainEquipmentIcon.sprite = menu.icons.GetIcons(equipmentController.PrimaryEquipment.Type);
149         menu.mainEquipmentIcon.gameObject.SetActive(true);
150     }
151
152     if(equipmentController.SecondaryEquipment == null)
153     {
154         menu.secondaryEquipmentIcon.gameObject.SetActive(false);
155         menu.secondaryCount.gameObject.SetActive(false);
156     }
157     else
158     {
159         //Enables
160         menu.secondaryEquipmentIcon.sprite = menu.icons.GetIcons(equipmentController.SecondaryEquipment.Type);
161         menu.secondaryEquipmentIcon.gameObject.SetActive(true);
162
163         //Gets Ammo Count (amount)
164         menu.secondaryCount.text = inventoryController.GetCount(equipmentController.SecondaryEquipment.Type).ToString();
165         menu.secondaryCount.gameObject.SetActive(true);
166     }
167 }

```


```

//reference
168 private InventoryItem GetNextAvailableSlot()
169 {
170     //Here we visually assign each item in seperate next slots.
171     foreach(InventoryItem nextSlotItem in inventoryItems)
172     {
173         if(!itemsInUse.Contains(nextSlotItem))
174         {
175             itemsInUse.Add(nextSlotItem);
176             return nextSlotItem;
177         }
178     }
179     Debug.Log("Enetred GetNextAvailableSlot!");
180
181     return null;
182 }
183 }
184

```

❖ UIController.

- We simply create an instance of the “*LevelMenuController*” here.
- Then we create function to Show the Inventory Menu UI, as well as to close it..
- We also create an Action delegate in the “*PlayerInputCallbacks*” script called “*OnInventoryRequested*”, and pass it in the “*ShowInventory()*” function.



```
Assets > Scripts > Player > Input > C# PlayerInputCallbacks.cs > PlayerInputCallbacks
1  using System;
2  using UnityEngine;
3
4  14 references
5  public class PlayerInputCallbacks
6  {
7      5 references
8      | public Action<Vector2> OnPlayerMoveFired = delegate { };
9      | 3 references
10     | public Action<Vector2> OnPlayerLookFired = delegate { };
11     |
12     | 1 reference
13     | public Action OnPlayerTapFired = delegate { };
14     | 1 reference
15     | public Action OnPlayerTapReleased = delegate { };
16     |
17     | 2 references
18     | public Action OnPlayerStartUseFired = delegate { };
19     | 1 reference
20     | public Action OnPlayerEndUseFired = delegate { };
21     |
22     | 2 references
23     | public Action OnPlayerPauseRequested = delegate { }; //Assignment - 01
24     | 2 references
25     | public Action OnPlayerResumeRequested = delegate { }; //Assignment - 01
26     | 1 reference
27     | public Action OnPlayerRequestedJump = delegate { Debug.Log("Jump!"); }; //Assignment - 01
28     |
29     | 2 references
30     | public Action OnInventoryRequested = delegate { }; //Assignment 04 - Part II
31 }
32
```

```

PlayerEquipmentController.cs M  UIController.cs M X  LevelController.cs M  PickupController.cs M  Pickup.cs  ProjectilePool.cs U  IEquipable.cs U
Assets > Scripts > UI > UIController.cs > ...
1  using System;
2  using System.Collections;
3  using System.Collections.Generic;
4  using UnityEngine;
5
6  2 references
7  public class UIController
8  {
9      11 references
10     private HUDController hudController;
11     6 references
12     private LevelEndMenuController levelEndMenu;
13     4 references
14     private Player player;
15     3 references
16     private TimeController timeController; //Assignment - 01
17     2 references
18     private LevelIntroUIController levelIntroController;
19     3 references
20     private InventoryMenuController inventoryMenuController; //Assignment - 04 - Part II
21     //private InventoryController inventoryController; //Assignment - 04 - Part II
22     2 references
23     private int currentLevelID;
24     6 references
25     private PauseMenuController pauseMenuController; //Assignment - 01
26     4 references
27     public Action<Levels.Data> OnLevelLoad = delegate { }; //Assignment - 02 (Conatins <Levels.Data> bcoz to load level)
28     2 references
29     public Action OnExit = delegate { }; //Assignment - 02
30
31     1 reference
32     public UIController(Player player, //Constructor
33         Transform cameraTransform, int currentLevelID, TimeController timeControl, LevelStatsController levelStatsController, //Assignment - 01
34         GameObject inventoryUI, InventoryController inventoryController) //Assignment - 04 - Part II
35     {
36         this.player = player;
37         this.currentLevelID = currentLevelID;
38         this.timeController = timeControl; //Assignment - 01
39         //this.inventoryController = inventoryController;
40     }

```

```

58     levelEndMenu.OnExitRequested += () => //Assignment - 02 (to 'LevelController')
59     {
60         OnExit();
61         ResumeGame();
62     };
63
64     levelEndMenu.OnRetryRequested += () => //Assignment - 02 (to 'LevelController')
65     {
66         OnLevelLoad(GetCurrentLevel());
67         ResumeGame();
68     };
69
70     InventoryMenuController = new InventoryMenuController(hudController.transform, inventoryController, inventoryUI, player.playerEquipment); //Assignment 04 - Part II
71
72     player.Broadcaster.Callbacks.OnInventoryRequested += () => ShowInventory();
73     hudController.OnInventoryRequested += ShowInventory; //Also could be written as: += () => ShowInventory();
74
75     InventoryMenuController.OnClose += () =>
76     {
77         //InventoryMenuController.Hide(); No need for this bcoz we have added "OnClose()" delegate in Hide().
78         player.Broadcaster.EnableActions(ControlType.Gameplay);
79         hudController.ShowHUD();
80     };
81
82     }
83

```




```


2 references
107 private void ShowPause() //Assignment - 01
108 {
109     PauseGame(); //Timescale = 0;
110
111     //GameIsPaused = true;
112     hudController.HideHUD();
113     pauseMenuController.Show();
114 }

2 references
115 private void ShowInventory() //Assignment 04 - Part II
116 {
117     inventoryMenuController.Show();
118     player.Broadcaster.EnableActions(ControlType.None);
119     hudController.HideHUD();
120 }
121
122
1 reference
123 public void OnLevelFailed(string message)
124 {
125     levelEndMenu.Show(message, false);
126     PauseGame(); //Assignment - 01 (Stops Time & Disables Inputs)
127 }
128

```

❖ Final Output.







Step 03: What have I learnt

- **What is the factory pattern? Explain how it can be used in Unity. Give one non-inventory scenario where it could be useful.**
 - Factory patterns is a design pattern used for creating new instances or copies of the predetermined object.
 - It is a way to create object but the client or calling class will not know about how the objects were created.
 - In factory pattern subclass decides about instantiation of a class.

- We can Implement Factory Pattern to describe the basic functionality of guards and then apply these actions for various Guards.
- **Are there any further improvements we could make to this inventory system? Choose 1 suggestion, explain what it is and give a rough run down of how you would implement it.**
 - We can create a rotation animation for the items.
 - We simply create an “AnimationClip” that moves the Pickup Item Up and Down.
 - For this select the main prefab “PickupBase” and in the “Animation” clip, add property of Transform type.
 - Then, on the First Frame set the object on position 0 and then on Second 1 in timeline, set its Y-Position to 1 and on second 2, again set it to 0.
 - Hence we have a Loop Animation.
 - And its “AnimationController” automatically gets created.
 - Now simply attach this AnimationClip to each and every Pickup Item Prefab-variant.





-----THE END-----