

ITW202: Mobile Application

Unit IV: Developing for Android

Ms. Sonam Wangmo

Gyalpozhing College of Information Technology
Royal University of Bhutan


May 26, 2021

Mobile Application Development

Internet connection



Steps to connect to the Internet

- 
- 1 Add permissions to Android Manifest
 - 2 Check Network Connection
 - 3 Create Worker Thread
 - 4 Implement background task
 - Create URI
 - Make HTTP Connection
 - Connect and GET Data
 - 5 Process results
 - Parse Results

Mobile Application Development

Permissions



Permissions in AndroidManifest

Mobile Application Development

Internet

```
<uses-permission android:name="android.permission.INTERNET"/>
```

Check Network State

```
<uses-permission  
    android:name="android.permission.ACCESS_NETWORK_STATE"/>
```

Mobile Application Development

Manage Network Connection



Check if network is available

Mobile Application

```
ConnectivityManager connMgr = (ConnectivityManager)
    getSystemService(Context.CONNECTIVITY_SERVICE);

NetworkInfo networkInfo = connMgr.getActiveNetworkInfo();

if (networkInfo != null && networkInfo.isConnected()) {
    // Create background thread to connect and get data
    new DownloadWebpageTask().execute(stringUrl);
} else {
    textView.setText("No network connection available.");
}
```

Mobile Application Development

Worker Thread



Use Worker Thread

Mobile Application Development

- AsyncTask—very short task, or no result returned to UI
- AsyncTaskLoader—for longer tasks, returns result to UI



Background work

Mobile Application Development

In the background task (for example in `doInBackground()`)

- 1 Create URI
- 2 Make HTTP Connection
- 3 Download Data

Mobile Application Development

Create URI



URI = Uniform Resource Identifier

Mobile Application Development

String that names or locates a particular resource

- file://
- http:// and https://
- content://



Sample URL for Google Books API

[https://www.googleapis.com/books/v1/volumes?
q=pride+prejudice&maxResults=5&printType=books](https://www.googleapis.com/books/v1/volumes?q=pride+prejudice&maxResults=5&printType=books)

Constants for Parameters

```
final String BASE_URL =  
    "https://www.googleapis.com/books/v1/volumes?";  
  
final String QUERY_PARAM = "q";  
  
final String MAX_RESULTS = "maxResults";  
  
final String PRINT_TYPE = "printType";
```

Build a URI for the request

Mobile Application Development

```
Uri builtURI = Uri.parse(BOOK_BASE_URL).buildUpon()  
    .appendQueryParameter(QUERY_PARAM, queryString)  
    .appendQueryParameter(MAX_RESULTS, "10")  
    .appendQueryParameter(PRINT_TYPE, "books")  
    .build();  
URL requestURL = new URL(builtURI.toString());
```

Mobile Application Development

HTTP Client Connection



Make a connection from scratch

- Use `HttpURLConnection`
- Must be done on a separate thread
- Requires `InputStreams` and `try/catch` blocks

Note: If you run network operations on the main thread instead of on a worker thread, your code will throw a `NetworkOnMainThreadException` and your app will close.

Create a HttpURLConnection

Mobile Application Development

```
HttpURLConnection conn = (HttpURLConnection)  
requestURL.openConnection();
```



Connect and get response

Mobile Application Development

```
InputStream inputStream =  
urlConnection.getInputStream();  
reader = new BufferedReader(new  
InputStreamReader(inputStream));
```



Close connection and stream

```
} finally {  
    conn.disconnect();  
    if (is != null) {  
        is.close();  
    }  
}
```

Mobile Application Development

Convert Response to String



BufferedReader is more efficient

Mobile Application

```
StringBuilder builder = new StringBuilder();
BufferedReader reader =
    new BufferedReader(new InputStreamReader(inputStream));
String line;
while ((line = reader.readLine()) != null) {
    builder.append(line + "\n");
}
if (builder.length() == 0) {
    return null;
}
resultString = builder.toString();
```

Mobile Application Development

Parse Results



Parsing the results

- Implement method to receive and handle results (`onPostExecute()`)
- Response is often JSON or XML
- Parse results using helper classes
JSONObject, JSONArray,
XMLPullParser—parses XML

Note: When you make web API queries, the results are often in JSON format.

JSON Example

Mobile Application Development

```
{
  "kind": "books#volumes",
  "totalItems": 1589,
  "items": [
    {
      "kind": "books#volume",
      "id": "tQPECgAAQBAJ",
      "etag": "yq+HQmssIHs",
      "selfLink": "https://www.googleapis.com/books/v1/volumes/tQPECgAAQBAJ",
      "volumeInfo": {
        "title": "Classics Reimagined, Pride and Prejudice",
        "authors": [
          "Jane Austen"
        ],
        "publisher": "Classics Reimagined",
        "publishedDate": "2015-10",
        "description": "More amazing and inspiring than your tired, old bedtime story."
      }
    }
  ]
}
```


Mobile Application Development

THANK YOU

