

SQL INSERT

Ing. Ladislav Körösi, PhD.
ÚRK, FEI STU

ladislav.korosi@stuba.sk

INSERT

The INSERT INTO statement is used to insert new records in a table. It is possible to write the INSERT INTO statement in two forms.

The first form does not specify the column names where the data will be inserted, only their values:

```
INSERT INTO table_name  
VALUES (value1,value2,value3,...);
```

The second form specifies both the column names and the values to be inserted:

```
INSERT INTO table_name (column1,column2,column3,...)  
VALUES (value1,value2,value3,...);
```

INSERT

Example:

```
INSERT INTO Customers
```

```
(CustomerName, ContactName, Address, City, PostalCode,  
Country)
```

```
VALUES
```

```
('Cardinal','Tom B. Erichsen','Skagen 21', 'Stavanger', '4006',  
'Norway');
```

INSERT

Example:

```
INSERT INTO Customers (CustomerName, City, Country)  
VALUES ('Cardinal', 'Stavanger', 'Norway');
```

INSERT

id_predmet	nazov	semester	id_garant
1	Predmet1	ZS	3
2	Predmet2	LS	2
3	Predmet3	LS	1
4	Predmet4	ZS	3

Example:

```
INSERT INTO Predmety (nazov, semester)  
VALUES ('Predmet5', 'ZS');
```

?

INSERT

Chyba

SQL dotaz:

```
INSERT INTO Predmety (nazov, semester)
VALUES ('Predmet5', 'ZS')
```

MySQL hlási: 

```
#1364 - Field 'id_garant' doesn't have a default value
```

- id_predmet OK -> auto increment
- Id_garant NOK -> missing default value. set not null?

INSERT

Chyba

SQL dotaz:

```
INSERT INTO Predmety (nazov, semester)
VALUES ('Predmet5', 'ZS')
```

MySQL hlási: 

```
#1364 - Field 'id_garant' doesn't have a default value
```

- id_predmet OK -> auto increment
- Id_garant NOK -> missing default value. set not null?

NO !

 Chyba dopytu:

#1171 - All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead

INSERT

id_zapis	id_studenta	id_predmetu	rok
1	1	1	2015
2	1	2	2015
3	1	3	2015
4	2	1	2015
5	2	3	2015
6	3	1	2016

Example:

Insert new row with default/actual year.

INSERT

Example:

```
INSERT into zapis  
(id_studenta, id_predmetu, rok)  
VALUES  
(3, 2, year(now()))
```

id_zapis	id_studenta	id_predmetu	rok
1	1	1	2015
2	1	2	2015
3	1	3	2015
4	2	1	2015
5	2	3	2015
6	3	1	2016
7	3	2	2016