

CS ADOForm ver3 소스

//ver3

===== form1 =====

```
using System;
using System.Collections.Generic;
using System.ComponentModel;
using System.Data;
using System.Drawing;
using System.Linq;
using System.Text;
using System.Windows.Forms;
using Oracle.DataAccess.Client;
namespace ADOForm
{
    public partial class Form1 : Form
    {
        //수정하거나 삭제하기 위해 선택된 행의 인덱스를 저장한다.
        private int SelectedRowIndex;

        // Data Provider인 DBAdapter 입니다.
        OracleDataAdapter DBAdapter;

        // DataSet 객체입니다.
        DataSet DS;

        // 추가, 수정, 삭제시에 필요한 명령문을
        // 자동으로 작성해주는 객체입니다.
        OracleCommandBuilder myCommandBuilder;

        // ataTable 객체입니다.
        DataTable phoneTable;

        // 수정, 삭제할 때 필요한 레코드의 키값을 보관할 필드
        private int SelectedKeyValue;

        private void ClearTextboxes()
        {
            txtid.Clear();
            txtName.Clear();
            txtPhone.Clear();
            txtMail.Clear();
        }

        private void DB_Open()
        {
            try
            {
                string connectionString = "User Id=hong1;
                Password=1111; Data Source=(DESCRIPTION = (ADDRESS =
                (PROTOCOL = TCP)(HOST = localhost)(PORT = 1521))
                (CONNECT_DATA = (SERVER = DEDICATED)
                (SERVICE_NAME = xe) ) );";

                string commandString = "select * from Phone";

                DBAdapter = new
                OracleDataAdapter(commandString, connectionString);
                myCommandBuilder = new
                OracleCommandBuilder(DBAdapter);

                DS = new DataSet();
            }
            catch (DataException DE)
            {
                MessageBox.Show(DE.Message);
            }
        }

        public Form1()
        {
            InitializeComponent();
            DB_Open();/*
        }

        private void DAOpenBtn_Click(object sender, EventArgs
        e)
        {
            //전체 보기
            try
            {
                DS.Clear();
                DBAdapter.Fill(DS, "phone");
                // phoneTable = DS.Tables["Phone"];/*
                DBGrid.DataSource =
                DS.Tables["phone"].DefaultView;
            }
            catch (DataException DE)
            {
                MessageBox.Show(DE.Message);
            }
            catch (Exception DE)
            {
            }
        }
    }
}
```

```
        MessageBox.Show(DE.Message);
    }
}

private void AppendBtn_Click(object sender, EventArgs e)
{
    try
    {
        MessageBox.Show("텍스트 상자에 모든 데이터 입력
        하셨으면 추가합니다!");
        // DS.Clear();/*

        // DBAdapter.Fill(DS, "Phone");/*

        phoneTable = DS.Tables["Phone"];/*
        DataRow newRow = phoneTable.NewRow();
        newRow["id"] = Convert.ToInt32(txtid.Text);
        newRow["PName"] = txtName.Text;
        newRow["Phone"] = txtPhone.Text;
        newRow["Email"] = txtMail.Text;

        phoneTable.Rows.Add(newRow);
        DBAdapter.Update(DS, "Phone");
        DS.AcceptChanges();/*
        ClearTextboxes(); /*
        DBGrid.DataSource =
        DS.Tables["Phone"].DefaultView;
    }
    catch (DataException DE)
    {
        MessageBox.Show(DE.Message);
    }
    catch (Exception DE)
    {
        MessageBox.Show(DE.Message);
    }
}

private void dataGridview1_CellClick(object sender,
DataGridViewCellEventArgs e)
{
    try
    {
        // DataSet DS = new DataSet();/*
        //DBAdapter.Fill(DS, "Phone");

        DataTable phoneTable = DS.Tables["Phone"];

        if (e.RowIndex < 0)
        {
            // DBGrid의 컬럼 헤더를 클릭하면 컬럼을 정렬하므
            로
            // 아무 메시지도 띄우지 않습니다.
            return;
        }
        else if (e.RowIndex > phoneTable.Rows.Count - 1)
        {
            MessageBox.Show("해당하는 데이터가 존재하지 않
            습니다.");
            return;
        }

        DataRow currRow = phoneTable.Rows[e.RowIndex];
        txtid.Text = currRow["id"].ToString();
        txtName.Text = currRow["PName"].ToString();
        txtPhone.Text = currRow["Phone"].ToString();
        txtMail.Text = currRow["EMail"].ToString();

        SelectedRowIndex = Convert.ToInt32(currRow["id"]);
    }
    catch (DataException DE)
    {
        MessageBox.Show(DE.Message);
    }
    catch (Exception DE)
    {
        MessageBox.Show(DE.Message);
    }
}
}
```

```

private void UpdateBtn_Click(object sender, EventArgs e)
{
    try
    {
        //DS.Clear();
        //DBAdapter.Fill(DS, "Phone");

        phoneTable = DS.Tables["Phone"];/*
        DataColumn[] PrimaryKey = new DataColumn[1];
        PrimaryKey[0] = phoneTable.Columns["id"];
        phoneTable.PrimaryKey = PrimaryKey;

        DataRow currRow =
phoneTable.Rows.Find(SelectedRowIndex);

        currRow.BeginEdit();
        currRow["id"] = txtid.Text;
        currRow["PName"] = txtName.Text;
        currRow["Phone"] = txtPhone.Text;
        currRow["EMail"] = txtMail.Text;
        currRow.EndEdit();

        DataSet UpdatedSet =
DS.GetChanges(DataRowState.Modified);
        if (UpdatedSet.HasErrors)
        {
            MessageBox.Show("변경된 데이터에 문제가 있
습니다.");
        }
        else
        {
            DBAdapter.Update(UpdatedSet, "Phone");
            DS.AcceptChanges();
        }

        DBGrid.DataSource =
DS.Tables["Phone"].DefaultView;
    }
    catch (DataException DE)
    {
        MessageBox.Show(DE.Message);
    }
    catch (Exception DE)
    {
        MessageBox.Show(DE.Message);
    }
}

private void DeleteBtn_Click(object sender, EventArgs e)
{
    try
    {
        // DS.Clear();
        // DBAdapter.Fill(DS, "Phone");

        phoneTable = DS.Tables["Phone"];/*
        DataColumn[] PrimaryKey = new DataColumn[1];
        PrimaryKey[0] = phoneTable.Columns["id"];
        phoneTable.PrimaryKey = PrimaryKey;

        DataRow currRow =
phoneTable.Rows.Find(SelectedRowIndex);
        currRow.Delete();

        DBAdapter.Update(DS.GetChanges(DataRowState.Deleted),
"Phone");

        DBGrid.DataSource =
DS.Tables["Phone"].DefaultView;
    }
    catch (DataException DE)
    {
        MessageBox.Show(DE.Message);
    }
    catch (Exception DE)
    {
        MessageBox.Show(DE.Message);
    }
}

private void DBGrid_CellContentClick(object sender,
DataGridViewCellEventArgs e)
{
}

```

```

private void SearchBtn_Click(object sender, EventArgs e)
{
    Form2 frm2 = new Form2();
    frm2.Owner = this;
    frm2.ShowDialog();
    frm2.Dispose();
}

public String TxtS //속성 설정
{
    get { return txtSearch.Text; }
    set { txtSearch.Text = value.ToString(); }
}

```

```

}
}

```

====form2=====

```
using System;
using System.Collections.Generic;
using System.ComponentModel;
using System.Data;
using System.Drawing;
using System.Linq;
using System.Text;
using System.Windows.Forms;
using Oracle.DataAccess.Client;

namespace ADOForm
{
    public partial class Form2 : Form
    {
        new Form1 Parent;

        //수정하거나 삭제하기 위해 선택된 행의 인덱스를 저장한다.
        private int SelectedRowIndex;

        // Data Provider인 DBAdapter 입니다.
        OracleDataAdapter DBAdapter;

        // DataSet 객체입니다.
        DataSet DS;

        // 추가, 수정, 삭제시에 필요한 명령문을
        // 자동으로 작성해주는 객체입니다.
        OracleCommandBuilder myCommandBuilder;

        // ataTable 객체입니다.
        DataTable phoneTable;

        // 수정, 삭제할 때 필요한 레코드의 키값을 보관할 필드
        private int SelectedKeyValue;

        private void ClearTextBoxes()
        {
            txtid.Clear();
            txtName.Clear();
            txtPhone.Clear();
            txtMail.Clear();
        }

        private void DB_Open()
        {
            try
            {
                string connectionString = "User Id=hong1;
                Password=1111; Data Source=(DESCRIPTION = (ADDRESS =
                (PROTOCOL = TCP)(HOST = localhost)(PORT = 1521))
                (CONNECT_DATA = (SERVER = DEDICATED)
                (SERVICE_NAME = xe) ) );";

                string commandString = "select * from Phone";

                DBAdapter = new
                OracleDataAdapter(commandString, connectionString);
                myCommandBuilder = new
                OracleCommandBuilder(DBAdapter);

                DS = new DataSet();
            }
            catch (DataException DE)
            {
                MessageBox.Show(DE.Message);
            }
        }

        public Form2()
        {
            InitializeComponent();
            DB_Open();
        }

        private void UpBtn_Click(object sender, EventArgs e)
        {
            {
                if (NameList.SelectedIndex != 0)
                {
                    NameList.SelectedIndex = NameList.SelectedIndex - 1;
                }
                else
                {
                    MessageBox.Show("이곳은 레코드의 처음입니다.");
                }
            }
        }

        private void DownBtn_Click(object sender, EventArgs e)
        {
            {
                if (NameList.SelectedIndex != NameList.Items.Count - 1)
                {
                    NameList.SelectedIndex = NameList.SelectedIndex + 1;
                }
                else
                {

```

```

                {
                    MessageBox.Show("이곳은 레코드의 마지막입니
                    다.");
                }
            }
        }

        private void NameList_SelectedIndexChanged(object
        sender, EventArgs e)
        {
            //DS.Clear();
            //DBAdapter.Fill(DS, "Phone");
            Parent = (Form1)Owner;
            phoneTable = DS.Tables["Phone"];

            DataRow[] ResultRows = phoneTable.Select("PName
            like '%" + Parent.TxtS + "%'");

            DataColumn[] PrimaryKey = new DataColumn[1];
            PrimaryKey[0] = phoneTable.Columns["id"];
            phoneTable.PrimaryKey = PrimaryKey;

            DataRow currRow =
            phoneTable.Rows.Find(NameList.Text.Substring(0, 2));

            SelectedKeyValue =
            Convert.ToInt32(currRow["id"].ToString());
            txtid.Text = currRow["id"].ToString();
            txtName.Text = currRow["PName"].ToString();
            txtMail.Text = currRow["Email"].ToString();
            txtPhone.Text = currRow["Phone"].ToString();
        }

        private void Form2_Load(object sender, EventArgs e)
        {
            DS.Clear();
            DBAdapter.Fill(DS, "Phone");
            Parent = (Form1)Owner;
            phoneTable = DS.Tables["Phone"];

            DataRow[] ResultRows
            = phoneTable.Select("PName like '%" +
            Parent.TxtS + "%'");

            NameList.Items.Clear();

            foreach (DataRow currRow in ResultRows)
            {
                NameList.Items.Add(currRow["Id"].ToString()
                + " " + currRow["PName"].ToString());
            }
        }
    }
}
```