



温州肯恩大学
WENZHOUCHEAN UNIVERSITY

CPS 2231 Computer Programming (Java)

Review Questions on Arrays in Java

Dr. Hamza Djigal

Assistant Professor,

Department of Computer Science, Wenzhou-Kean University

dhamza@kean.edu

Semester: Fall 2025

September 24, 2025

Questions

1. What symbol is used for a varargs method parameter?
 - A. ..
 - B. ...
 - C. —
 - D. —
2. Fill in the blank in the following code to get the first element from the varargs parameter.

```
1 public void toss(Frisbee... f) {  
2     Frisbee first = _____ ;  
3 }
```

- A. f
- B. f[0]
- C. f[1]
- D. None of the above

3. How many of the following are legal declarations?

```
1 [] double lion;  
2 double[] tiger;  
3 double bear[];
```

- A. None
- B. One
- C. Two
- D. Three

4. How do you determine the number of elements in an array?

- A. buses.length
- B. buses.length()
- C. buses.size
- D. buses.size()

5. Which of the following create an empty two-dimensional array with dimensions 2×2 ?

- A. `int[][] blue = new int[2, 2];`
- B. `int[][] blue = new int[2], [2];`
- C. `int[][] blue = new int[2][2];`
- D. `int[][] blue = new int[2 x 2];`

6. What are the names of the methods to do searching and sorting respectively on arrays?

- A. `Arrays.binarySearch()` and `Arrays.linearSort()`
- B. `Arrays.binarySearch()` and `Arrays.sort()`
- C. `Arrays.search()` and `Arrays.linearSort()`
- D. `Arrays.search()` and `Arrays.sort()`

7. What does this code output?

```
1 String[] nums = new String[] { "1", "9", "10" };  
2 Arrays.sort(nums);  
3 System.out.println(Arrays.toString(nums));
```

- 1, 9, 10
- 1, 10, 9
- 10, 1, 9

A. None of the above

8. How many of the following are legal declarations?

```
1 String lion[] = new String[] {"lion"};
2 String tiger[] = new String[1] {"tiger"};
3 String bear[] = new String[] {};
4 String ohMy[] = new String[0] {};
```

A. None

B. One

C. Two

D. Three

9. Which is not a true statement about an array?

A. An array expands automatically when it is full.

B. An array is allowed to contain duplicate values.

C. An array understands the concept of ordered elements.

D. An array uses a zero index to reference the first element.

10. What does the following output?

```
1 String[] os = new String[] { "Mac", "Linux", "Windows" };
2 Arrays.sort(os);
3 System.out.println(Arrays.binarySearch(os, "Mac"));
```

A. 0

B. 1

C. 2

D. The output is not defined.

11. Which is the first line to prevent this code from compiling and running without error?

```
1 char[][] ticTacToe = new char[3,3]; // r1
2 ticTacToe[1][3] = 'X'; // r2
3 ticTacToe[2][2] = 'X';
4 ticTacToe[3][1] = 'X';
5 System.out.println(ticTacToe.length + " in a row!"); // r3
```

A. Line r1 B. Line r2 C. Line r3 D. None of the above

12. How many of the following are legal declarations?

```

1 [][] String alpha;
2 [] String beta;
3 String[][] gamma;
4 String[] delta[];
5 String epsilon[][];

```

A. Two B. Three C. Four D. Five

13. What happens when calling the following method with a non-null and non-empty array?

```

1 public static void addStationName(String[] names) {
2     names[names.length] = "Times Square";
3 }

```

A. It adds an element to the array. B. It replaces the last element. C. It does not compile. D. It throws an exception.

14. What is a possible output of the following code?

```

1 String[] strings = new String[2];
2 System.out.println(strings);

```

// Output:

```

1 [Ljava.lang.String;@74a14482

```

A. [null, null] B. [,] C. [Ljava.lang.String;@74a14482 D. None of the above

15. What is the output of the following when run as 'java FirstName Wolfie'?

```

1 public class FirstName {
2     public static void main(String... names) {
3         System.out.println(names[0]);
4     }
5 }

```

A. FirstName B. Wolfie C. ArrayIndexOutOfBoundsException D. NullPointerException

16. What is the output of the following when run as 'java Count 1 2'?

```

1 public class Count {
2     public static void main(String target[]) {
3         System.out.println(target.length);
4     }
5 }

```

A. 0 B. 1 C. 2 D. The code does not compile.

17. What is the output of the following when run as 'java Count 1 2'?

```

1 public class Count {
2     public static void main(String target[]) {
3         System.out.println(target.length());
4     }
5 }

```

A. 0 B. 1 C. 2 D. The code does not compile.

18. How many dimensions does the array reference 'moreBools' allow?

```

1 boolean[][] bools[], moreBools;

```

A. One dimension B. Two dimensions C. Three dimensions D. None of the above

19. What is the result of running the following program?

```

1 package fun;
2 public class Sudoku {
3     static int[][] game;
4
5     public static void main(String[] args) {
6         game[3][3] = 6;
7         Object[] obj = game;
8         game[3][3] = "X";
9         System.out.println(game[3][3]);
10    }
11 }

```

A. X B. The code does not compile. C. NullPointerException at runtime. D. Compiles but throws a different exception at runtime.

20. What is the output of the following when run as 'java unix.EchoFirst seed flower'?

```

1 package unix;
2 import java.util.*;
3 public class EchoFirst {
4     public static void main(String[] args) {
5         Arrays.sort(args);
6         String result = Arrays.binarySearch(args, args[0]);
7         System.out.println(result);
8     }
9 }

```

A. 0 B. 1 C. The code does not compile. D. Compiles but throws an exception at runtime.