FLASK API



In programming more generally, the term API, short for Application Programming Interface, refers to a part of a computer program designed to be used or manipulated by another program.

What is an API?

Estimated Time: 60 minutes

Learn what an API is and when you should use one.

Learn how to build a web API that returns data to its users.

Computer programs frequently need to communicate amongst themselves or with the underlying operating system, and APIs are one way they do it.

Objective

A web API allows for information or functionality to be manipulated by other programs via the internet. For example, with Twitter's web API, you can write a program in a language like Python or Javascript that can perform tasks such as favoriting tweets or collecting tweet metadata.

When to Create an API

In general, consider an API if:

• Your data set is large, making download via FTP unwieldy or resource-intensive. • Your users will need to access your data in real time, such as for display on another website or as part of an application. Your data changes or is updated frequently.

• Your users only need access to a part of the data at any one time.

• Your users will need to perform actions other than retrieve data, such as contributing, updating, or deleting data. **API Terminology**

- When using or building APIs, you will encounter these terms frequently: • HTTP (Hypertext Transfer Protocol) is the primary means of communicating data on the web. HTTP implements a number of "methods," which tell which direction data is moving and what
- should happen to it. The two most common are GET, which pulls data from a server, and POST, which pushes new data to a server. • URL (Uniform Resource Locator) - An address for a resource on the web, such as https://programminghistorian.org/about. A URL consists of a protocol (http://), domain (programminghistorian.org), and optional path (/about). A URL describes the location of a specific resource, such as a web page. When reading about APIs, you may see the terms URL, request, URI, or endpoint used to describe adjacent ideas.

(i) localhost:8889/notebooks/Untitled6.ipynb?kernel_name=python3

Insert

In [*]: import flask

def home():

* Debug mode: off

Follow the link above, http://127.0.0.1:5000/, using your web browser to see the running application:

Cell

app = flask.Flask(__name__) #app.config["DEBUG"] = True

@app.route('/', methods=['GET'])

Use a production WSGI server instead.

* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit) 127.0.0.1 - - [23/Dec/2021 14:01:54] "GET / HTTP/1.1" 200 -

127.0.0.1 - - [23/Dec/2021 14:01:54] "GET /favicon.ico HTTP/1.1" 404 -

Kernel

► Run ■ C

import flask

app.run()

app = flask.Flask(__name___)

C

Implementation of web API using Flask Flask is a web framework for Python, meaning that it provides functionality for building web applications, including managing HTTP requests and rendering templates

Flask maps HTTP requests to Python functions.

- JSON (JavaScript Object Notation) is a text-based data storage format that is designed to be easy to read for both humans and machines. JSON is generally the most common format for
- returning data through an API, XML being the second most common.
- Let us understand this with a small example If you have installed jupyter notebook. Create a new notebook and paste these lines of code

@app.route('/', methods=['GET']) def home():

return "<h1>Distant Reading Archive</h1>This site is a prototype API for distant reading of science fiction novels."

Help

~

return "<h1>Distant Reading Archive</h1>This site is a prototype API for distant reading of science fiction novels."

Widgets

દ\≡

Logout

Python 3

Trusted

jupyter Untitled6 Last Checkpoint: 08/13/2021 (unsaved changes) View

app.run() * Serving Flask app "__main__" (lazy loading) * Environment: production WARNING: This is a development server. Do not use it in a production deployment.

In []:

i 127.0.0.1:5000 **Distant Reading Archive** This site is a prototype API for distant reading of science fiction novels.

In this case, we've mapped one URL path ('/') to one function, home. When we connect to the Flask server at http://127.0.0.1:5000/, Flask checks if there is a match between the path provided

and a defined function. Since /, or no additional provided path, has been mapped to the home function, Flask runs the code in the function and displays the returned result in the browser. In this case, the returned result is HTML markup for a home page welcoming visitors to the site hosting our API.

@app.route('/', methods=['GET'])

what kind of HTTP requests are allowed.

Creating the API

'key': 'value',

The process of mapping URLs to functions is called routing.

The last line, app.run(), is one such method.

• app.run() — A method that runs the application server.

'name': 'Alexander Graham Bell',

'number': '1-333-444-5555'

'name': 'Thomas A. Watson',

'number': '1-444-555-6666'

• We will add 3 route methods

Below are brief explanations of the other components of the application:

as Bad Gateway in the browser when there's a problem with your code.

• import flask — Imports the Flask library, making the code available to the rest of the application.

We'll be adding our data as a list of Python dictionaries. Dictionaries in Python group pairs of keys and values, like this:

• @app.route('/', methods=['GET']) which will map to method home which will return a html response

Create some test data for our catalog in the form of a list of dictionaries.

'first_sentence': 'The coldsleep itself was dreamless.',

'title': 'The Ones Who Walk Away From Omelas',

'first_sentence': 'to wound the autumnal city.',

Check if an ID was provided as part of the URL.

If no ID is provided, display an error in the browser.

Use the jsonify function from Flask to convert our list of

127.0.0.1:5000/books/all

Delany","first_sentence":"to wound the autumnal city.","id":2,"published":"1975","title":"Dhalgren"}]

Python dictionaries to the JSON format.

you will be able to view the response showing all books.

If ID is provided, assign it to a variable.

A prototype API for distant reading of science fiction novels.'''

'key': 'value' The key identifies the type of information represented, such as title or id. The value is the actual data. For example, a short telephone book might take this format:

The above phone book is a list of two dictionaries. Each dictionary is a phone book entry consisting of two keys, name and number, each paired with a value that provides the actual information.

'first_sentence': 'With a clamor of bells that set the swallows soaring, the Festival of Summer came to the city Omelas, bright-towered by the sea.',

• Here we are creating a list of dictionaries. Each dictionary will contain ID number, title, author, first sentence, and year of publication for each book.

• @app.route('/books', methods=['GET']) which will map to method api_id() filterning and returning book information with respect to an id.

• @app.route('/books/all', methods=['GET']) which will map to method api_all returning all book information as a json response.

Now that we have a running Flask application and know a little about what Flask does, we're finally ready to implement a small API with data that we'll define right in our application.

syntax is the part of the program that lets Flask know that this function, home, should be mapped to the path /. The methods list (methods=['GET']) is a keyword argument that lets Flask know

• app = flask.Flask(name) — Creates the Flask application object, which contains data about the application and also methods (object functions) that tell the application to do certain actions.

• app.config["DEBUG"] = True — Starts the debugger. With this line, if your code is malformed, you'll see an error when you visit your app. Otherwise you'll only see a generic message such

import flask from flask import request, jsonify app = flask.Flask(__name___)

books = [

{'id': 0,

{'id': 1,

{'id': 2,

def api_id():

results = []

Here when you give the url

http://127.0.0.1:5000/books/all

C G

 \mathbb{C}

'title': 'A Fire Upon the Deep',

'author': 'Vernor Vinge',

'year_published': '1992'},

'published': '1973'},

'title': 'Dhalgren',

'published': '1975'}

'author': 'Ursula K. Le Guin',

'author': 'Samuel R. Delany',

@app.route('/books', methods=['GET'])

if 'id' in request.args:

- @app.route('/', methods=['GET']) def home(): return '''<h1>Distant Reading Archive</h1>
- @app.route('/books/all', methods=['GET']) def api_all(): return jsonify(books)
 - id = int(request.args['id']) else: return "Error: No id field provided. Please specify an id." # Create an empty list for our results
 - # Loop through the data and match results that fit the requested ID. # IDs are unique, but other fields might return many results for book in books:
 - if book['id'] == id: results.append(book)
- return jsonify(results) app.run()

[{"author":"Vernor Vinge","first_sentence":"The coldsleep itself was dreamless.","id":0,"title":"A Fire Upon the Deep","year_published":"1992"},{"author":"Ursula K. Le Guin","first_sentence":"With a clamor of bells that set the swallows soaring, the Festival of Summer came to the city Omelas, bright-towered by the sea.","id":1,"published":"1973","title":"The Ones Who Walk Away From Omelas"},{"author":"Samuel R.

Further if you want to make a specific request, you need to add the filtering criteria like for example in this case id

(i) 127.0.0.1:5000/books?id=0

the url will be as follows http://127.0.0.1:5000/books?id=0 you will be able to view results with respect to id =0 as follows

[{"author":"Vernor Vinge","first_sentence":"The coldsleep itself was dreamless.","id":0,"title":"A Fire Upon the Deep","year_published":"1992"}]

Change Description

Note: Here the response is a json response. Here you have learnt how to build a web API that returns data to its users using python web framewok Flask. **Author**

Changelog **Date**

Lakshmi Holla

Malika Singla

2021-12-23

0.1 Lakshmi Holla, Malika Singla **Initial Version** © IBM Corporation 2021. All rights reserved.

Changed by

Version