



Hands-on Lab: Committing and Rolling back a Transaction using a Stored Procedure

Estimated time needed: 10 minutes

A transaction is simply a sequence of operations performed using one or more SQL statements as a single logical unit of work. A database transaction must be ACID (Atomic, Consistent, Isolated and Durable). The effects of all the SQL statements in a transaction can either be applied to the database using the COMMIT command or undone from the database using the ROLLBACK command.

In this lab, you will learn some commonly used TCL (Transaction Control Language) commands of SQL through the creation of a stored procedure routine. You will learn about COMMIT, which is used to permanently save the changes done in the transactions in a table, and about ROLLBACK, which is used to undo the transactions that have not been saved in a table. ROLLBACK can only be used to undo the changes in the current unit of work.

Software Used in this Lab

In this lab, you will use an [IBM Db2 Database](#). Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow the lab below first:

- [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Data Used in this Lab

The data used in this lab is internal data. You will be working on the **BankAccounts** and **ShoeShop** tables.

| ACCOUNTNUMBER | ACCOUNTNAME | BALANCE |
|---------------|-------------|-----------|
| B001 | Rose | 300.00 |
| B002 | James | 1345.00 |
| B003 | Shoe Shop | 124200.00 |
| B004 | Corner Shop | 76000.00 |

| PRODUCT | STOCK | PRICE |
|------------|-------|--------|
| Boots | 11 | 200.00 |
| High heels | 8 | 600.00 |
| Brogues | 10 | 150.00 |
| Trainers | 14 | 300.00 |

This lab requires you to have the **BankAccounts** and **ShoeShop** tables populated with sample data on Db2. Download the [BankAccounts--CREATE.sql](#) and [ShoeShop--CREATE.sql](#) scripts below, upload them to the Db2 console and run them. The scripts will create new tables called BankAccounts and ShoeShop while dropping any previous BankAccounts and ShoeShop tables if they exist, and will populate them with the sample data required for this lab.

- [BankAccounts-CREATE.sql](#)
- [ShoeShop-CREATE.sql](#)

Please go through the lab below to learn how to upload and run a script on Db2 console (for this case, you need don't need to know anything else other than how to upload and run a script):

- [Hands-on Lab : Create tables using SQL scripts and load data into tables](#)

Objectives

After completing this lab, you will be able to:

- Permanently save the changes done in a transaction
- Undo the transaction that has not been saved

Instructions

When you approach the exercises in this lab, follow the instructions to run the queries on Db2:

- Go to the [Resource List](#) of IBM Cloud by logging in where you can find the Db2 service instance that you created in a previous lab under **Services** section. Click on the **Db2-xx service**. Next, open the Db2 Console by clicking on **Open Console** button. Click on the 3-bar menu icon in the top left corner and go to the **Run SQL** page. The Run SQL tool enables you to run SQL statements.

- If needed, follow [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Exercise

Task A: Example exercise

Let us go through an example on committing and rolling back a transaction

- Make sure you have created and populated the **BankAccounts** and **ShoeShop** tables by following the "**Data Used in this Lab**" section of this lab.

| ACCOUNTNUMBER | ACCOUNTNAME | BALANCE |
|---------------|-------------|-----------|
| B001 | Rose | 300.00 |
| B002 | James | 1345.00 |
| B003 | Shoe Shop | 124200.00 |
| B004 | Corner Shop | 76000.00 |

| PRODUCT | STOCK | PRICE |
|------------|-------|--------|
| Boots | 11 | 200.00 |
| High heels | 8 | 600.00 |
| Brogues | 10 | 150.00 |
| Trainers | 14 | 300.00 |

- You will create a stored procedure routine named **TRANSACTION_ROSE** which will include TCL commands like COMMIT and ROLLBACK.
 - Now develop the routine based on the given scenario to execute a transaction.
 - Scenario:** Let's buy Rose a pair of Boots from ShoeShop. So we have to update the Rose balance as well as the ShoeShop balance in the BankAccounts table. Then we also have to update Boots stock in the ShoeShop table. After Boots, let's also attempt to buy Rose a pair of Trainers.
 - To create the stored procedure routine on Db2, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
--#SET TERMINATOR @
CREATE PROCEDURE TRANSACTION_ROSE                                -- Name of this stored procedure routine

LANGUAGE SQL                                                    -- Language used in this routine
MODIFIES SQL DATA                                              -- This routine will only write/modify data in the table

BEGIN

    DECLARE SQLCODE INTEGER DEFAULT 0;                          -- Host variable SQLCODE declared and assigned 0
    DECLARE retcode INTEGER DEFAULT 0;                          -- Local variable retcode with declared and assigned 0
    DECLARE CONTINUE HANDLER FOR SQLEXCEPTION                  -- Handler tell the routine what to do when an error or warning occurs
    SET retcode = SQLCODE;                                     -- Value of SQLCODE assigned to local variable retcode

    UPDATE BankAccounts
    SET Balance = Balance-200
    WHERE AccountName = 'Rose';

    UPDATE BankAccounts
    SET Balance = Balance+200
    WHERE AccountName = 'Shoe Shop';

    UPDATE ShoeShop
    SET Stock = Stock-1
    WHERE Product = 'Boots';

    UPDATE BankAccounts
    SET Balance = Balance-300
    WHERE AccountName = 'Rose';

    IF retcode < 0 THEN                                          -- SQLCODE returns negative value for error, zero for success, positive value for war

        ROLLBACK WORK;

    ELSE

        COMMIT WORK;

    END IF;

END
@
```

1--SET TERMINATOR @
2CREATE PROCEDURE TRANSACTION_ROSE
3
4LANGUAGE SQL
5MODIFIES SQL DATA
6
7BEGIN
8
9DECLARE SQLCODE INTEGER DEFAULT 0;
10DECLARE retcode INTEGER DEFAULT 0;
11DECLARE CONTINUE HANDLER FOR SQLEXCEPTION
12
13SET retcode = SQLCODE;
14
15UPDATE BankAccounts
16SET Balance = Balance-200
17WHERE AccountName = 'Rose';
18
19UPDATE BankAccounts
20SET Balance = Balance+200
21WHERE AccountName = 'Shoe Shop';
22
23UPDATE ShoeShop
24SET Stock = Stock-1
25WHERE Product = 'Boots';
26
27UPDATE BankAccounts
28SET Balance = Balance-300
29WHERE AccountName = 'Rose';
30
31
32IF retcode < 0 THEN
33ROLLBACK WORK;
34
35ELSE
36COMMIT WORK;
37
38END IF;
39
40END
41@
42

✓CREATE PROCEDURE TRANSACTION_ROSE LANGUAGE SQL MODIFIES SQL DATA BEGIN DEC...Run time: 0.076 s

Status: Success | Affected Rows: 0

Result set 1

| ACCOUNTNUMBER | ACCOUNTNAME | BALANCE |
|---------------|-------------|-----------|
| B001 | Rose | 300.00 |
| B002 | James | 1345.00 |
| B003 | Shoe Shop | 124200.00 |
| B004 | Corner Shop | 76000.00 |

Result set 1

| PRODUCT | STOCK | PRICE |
|------------|-------|--------|
| Boots | 11 | 200.00 |
| High heels | 8 | 600.00 |
| Brogues | 10 | 150.00 |
| Trainers | 14 | 300.00 |

- Let's now check if the transaction can successfully be committed or not. Copy the code below in a **new blank script** and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
CALL TRANSACTION_ROSE; -- Caller query

SELECT * FROM BankAccounts;

SELECT * FROM ShoeShop;
```

- We can observe that the transaction has been executed. But when we observe the tables, no changes have permanently been saved through COMMIT. All the possible changes happened might have been undone through ROLLBACK since the whole transaction fails due to the failure of a SQL statement or more. Let's go through the possible reason behind the failure of the transaction and how COMMIT - ROLLBACK works on a stored procedure:

- The first three UPDATES should run successfully. Both the balance of Rose and ShoeShop should have been updated in the BankAccounts table. The current balance of Rose should stand at 300 - 200 (Price of a pair of Boots) = 100. The current balance of ShoeShop should stand at 124200 + 200 = 124400. The stock of Boots should also be updated in the ShoeShop table after the successful purchase for Rose, 11 - 1 = 10.
- The last UPDATE statement tries to buy Rose a pair of Trainers, but her balance becomes insufficient (Current balance of Rose: 100 < Price of Trainers: 300) after buying a pair of Boots. So, the last UPDATE statement fails. Since the whole transaction fails if any of the SQL statements fail, the transaction won't be committed.
- The **SQLCODE** which is a stand-alone host variable contains success/failure/warning information of each SQL statement execution. Now since **SQLCODE** variable gets reset back as the next SQL statement runs, **retcode** is our local variable to catch the return value of this **SQLCODE**. **SQLCODE** returns negative value for each SQL statement if not executed successfully. So, on any error occurrence, all the changes are rolled back. Commit only takes place after the transaction gets executed successfully without any error.

1SELECT * FROM BankAccounts;

2

3

4SELECT * FROM ShoeShop;

5

6

✓CALL TRANSACTION_ROSE

Run time: 0.183 s

Status: Success | Affected Rows: 0

✓SELECT * FROM BankAccounts

Run time: 0.013 s

Result set 1

Search

Q

⬆

⬆

⬆

| ACCOUNTNUMBER | ACCOUNTNAME | BALANCE |
|---------------|-------------|-----------|
| B001 | Rose | 300.00 |
| B002 | James | 1345.00 |
| B003 | Shoe Shop | 124200.00 |
| B004 | Corner Shop | 76000.00 |

✓SELECT * FROM ShoeShop

Run time: 0.004 s

Result set 1

Search

Q

⬆

⬆

⬆

| PRODUCT | STOCK | PRICE |
|------------|-------|--------|
| Boots | 11 | 200.00 |
| High heels | 8 | 600.00 |
| Brogues | 10 | 150.00 |
| Trainers | 14 | 300.00 |

Task B: Practice exercise

Now let's practice an exercise on committing and rolling back a transaction.

- Problem:

Create a stored procedure **TRANSACTION_JAMES** to execute a transaction based on the following scenario: First buy James 4 pairs of Trainers from ShoeShop. Update his balance as well as the balance of ShoeShop. Also, update the stock of Trainers at ShoeShop. Then attempt to buy James a pair of Brogues from ShoeShop. If any of the UPDATE statements fail, the whole transaction fails. You will roll back the transaction. Commit the transaction only if the whole transaction is successful.

- Hint
- Solution

Congratulations! You have completed this lab, and you are ready for the next topic.

Author(s)

- [Sandip Saha Joy](#)

Other Contributor(s)

- [Lin Joyner](#)

Changelog

| Date | Version | Changed by | Change Description |
|------------|---------|-----------------|-------------------------|
| 2020-12-24 | 1.1 | Steve Ryan | ID Reviewed |
| 2020-12-20 | 1.0 | Sandip Saha Joy | Created initial version |